INFRASTRUCTURE OF SERBIAN RAILWAYS JSC

NETWORK STATEMENT 2025

Adopted by the Shareholders' Meeting of "Infrastructure of Serbian Railways" JSC No: 5/2023-525-204 dated December 12th, 2023

Effective as of December 15th, 2024 Applicable to 2024/2025 Timetable На основу члана 20. став 6. Закона о железници ("Службени гласник РС", бр. 41/18 и 62/23) и члана 17. став 1. и члана 43. став 2. Закона о Влади ("Службени гласник РС", бр. 55/05, 71/05 - исправка, 101/07, 65/08, 16/11, 68/12 - УС, 72/12, 7/14 - УС, 44/14 и 30/18 - др. закон),

Влада доноси

РЕШЕЊЕ

О ДАВАЊУ САГЛАСНОСТИ НА ОДЛУКУ О ВИСИНИ ЦЕНА ПРИСТУПА И ЦЕНА ПРИСТУПА ДЕЛУ ЈАВНЕ ЖЕЛЕЗНИЧКЕ ИНФРАСТРУКТУРЕ КОЈИ ПОВЕЗУЈЕ СА УСЛУЖНИМ ОБЈЕКТИМА ЗА РЕД ВОЖЊЕ 2024/2025

I

Даје се сагласност на Одлуку о висини цена приступа и цена приступа делу јавне железничке инфраструктуре који повезује са услужним објектима за Ред вожње 2024/2025, коју је донела Скупштина Акционарског друштва за управљање јавном железничком инфраструктуром "Инфраструктура железнице Србије", Београд, на седници од 21. септембра 2023. године.

II

Ово решење објавити у "Службеном гласнику Републике Србије".

05 Број: 338-11265/2023 У Београду, 20. новембра 2023. године

ВЛАДА



ПРЕДСЕДНИК

Ана Брнабић, с.р.



No	Subject	Determined by the Decision No.	Valid as of
1.	7.3.5, Appendices 3.11 and 6	Infrastructure of Serbian Railways JSC Shareholders' Meeting Decision 5/2024-535- 212 dated Aprl 2 nd 2024	April 2 nd , 2024
2.	1.1; 4.2; Appendices 1, 3.10 and 4.1.b	Infrastructure of Serbian Railways JSC Shareholders' Meeting Decision 5/2024-542- 215 dated May 29 th 2024	May 29 th , 2024
3.	1.1; 2.2; 2.3.1; 2.3.13; 7.3.3; Appendices 1, 3.6a and 3.10	Infrastructure of Serbian Railways JSC Shareholders' Meeting Decision No 5/2024- 554-221 dated September 26 th 2024	September 26 th , 2024
4.	2.3.10; 2.3.11; 2.3.12; 2.3.13; 2.4.7; 2.4.8; Appendices 3.5, 3.11, 4.2, 6, 8 and 10	Infrastructure of Serbian Railways JSC Shareholders' Meeting Decision No 5/2024- 557-222 dated October 23 th , 2024	October 23 th , 2024
5.	5.9	Infrastructure of Serbian Railways JSC Shareholders' Meeting Decision No 5/2024- 579-224 dated November 14 th , 2024	November 14 th , 2024
6.	1.1; 2.2.2; 2.4.7; 5.4; Appendices 3.4, 3.11 and 6	Infrastructure of Serbian Railways JSC Shareholders' Meeting Decision No 5/2024 - 583-227 dated December 12 th , 2024	December 12 th , 2024
7.	1.1; 2.4.8; 4.6;7.3.4; Appendices 1, 3.11 and 6	Infrastructure of Serbian Railways JSC Shareholders' Meeting Decision No 5/2025- 591-233 dated March 17 th , 2025	March 17 th , 2025
8.	1.1; 2.3.1 Appendices 3.11 and 6	Infrastructure of Serbian Railways JSC Shareholders' Meeting Decision No 5/2025- 601-237 dated June 6 th , 2025	June 6 th , 2025

Amendments, corrections, and interpretations



TABLE OF CONTENTS

		AND ABBREVIATIONS	
1. 0	GENE	RAL INFORMATION	10
	1.1	Introduction	
	1.2	Purpose of the Network Statement	13
	1.3	Legal Aspects	13
	1.3.	1 Legal Framework	14
	1.3.	2 Legal Status and Liability	15
	1.3.	3 Appeals Procedure	15
	.4	Structure of the Network Statement	16
	1.5	Validity Period, Updating and Publishing	16
	1.5.	1 Validity Period of the Network Statement	
		2 Updating Process	
		3 Publishing, Distribution and Availability of the Network Statement	
	.6	Contacts	
-	.7	Cooperation Between European IMs/ABs	
-	1.7.	1 Rail Freight Corridors	
		2 RailNetEurope	
21		ASTRUCTURE	
	2.1	Introduction	
_	2.2	Extent of Network	
4		1 Limits	
		2 Connecting Railway Networks	
~	2.2. 2.3		
4		1 Geographic data and types of railway lines	
		2 Track Gauges	
		3 Stations and Nodes	
		4 Loading Gauge	
		5 Weight Limits	
		6 Line Gradients	
		7 Maximum Line Speeds	
		*	
		8 Maximum Train Lengths	
		9 Power Supply	
		10 Signalling Systems	
		11 Traffic Control Systems	
		12 Communication Systems	
		13 Train Control Systems	
4	2.4	Traffic Restrictions	
		1 Specialised Infrastructure	
		2 Environmental Restrictions	
		3 Dangerous Goods	
		4 Tunnel Restrictions	
		5 Bridge Restrictions	
	2.5	Availability of the Infrastructure	
	2.6	Infrastructure Development	
		ESS CONDITIONS	
	3.1	Introduction	
	3.2	General Access Requirements	
		1 Conditions for Applying for Capacity	
	3.2.	2 Conditions for Access to the Railway Infrastructure	35
	3.2.	3 Licenses	36
		4 Safety Certificate	
	3.2.	5 Coverage for Civil Liability (Insurance)	37
	3.3	Contractual Arrangements	37
	3.3.	1 Framework Agreement	37



3.3.	2 Contracts with RUs	
3.4 Sp	ecific Access Requirements	
3. 4 .	1 Rolling Stock Acceptance	
3.4.	2 Staff Acceptance	
3.4.	3 Exceptional Transport	
3.4.4	4 Transport of Dangerous Goods	
4. CAPA	CITY ALLOCATION	
4.1	Introduction	
4.2.	Description of infrastructure capacity allocation procedure	
4.3	Allocation of capacity for maintenance, including the allocation process	
4.4.	Impact of Framework Agreements	
4.5	Schedule for Path Requests and Allocation Process	
	1 Schedule of requests submission for new annual timetabling process	
	2 Schedule of requests submission for train path allocation during annual Timetable validity	
	ugh regular and special amendments of and supplements to the Timetable	
	3 Allocation of capacities during annual Timetable validity period on ad hoc request	
	4 Path Allocation and Coordination Process	
	5 Dispute Resolution Process	
4.6	Congested Infrastructure	
4.7.	Exceptional Transports and Dangerous Goods	
4.8	Rules After Path Allocation	
	1 Non-usage of allocated train path	
	2. Rules of Cancellation	
4.9.	International Timetabling Process Redesign (TTR)	
	1. Objectives of TTR	
	VICES AND CHARGES	
5.1	Introduction	
5.1 5.2	Charging Principles	
5.2 5.3	Minimum Access Package and Charges	
5.3 5.4	Additional Services and Charges	
5.4 5.5	Ancillary Services and Charges	
5.5 5.6	Discounts	
5.0 5.7	Performance Scheme	
5.7 5.8	Changes to Charges	
5.8 5.9	Billing Arrangements	
5.9 5.10	Tariff system	
	ATIONS	
6.1	Introduction	
6.1 6.2	Operational Rules	
6.2 6.3		
	Operational Measures	
	1. Principles	
	2. Operation regulation	
	3. Foreseen and Unforeseen problems	
7. SEK V. 7.1.	ICE FACILITIES Introduction	
7.1. 7.2.		
7.2.	Service Facility Overview Service Facilities Managed by IŽS	
	1. Common Provisions 2 Use of station buildings in the function of passenger traffic	
	3 Freight Terminals	
	4 Marshalling Yards and Train Formation Facilities, including Shunting Facilities	
	5 Storage Sidings	
	6 Maintenance facilities	
	7 Other Technical Facilities, including Cleaning and Washing Facilities	
	8 Maritime and Inland Port Facilities	
	9 Relief Facilities	
1.3.	10 Refuelling Facilities	



APPENDICES	79
Appendix 1: Organizational chart of "Infrastructure of Serbian Railways" JSC	. 80
Appendix 2: Internal regulations (documents) and technological procedures	
Appendix 3.1. Loading Gauge ŽS I	. 82
Appendix 3.2. Loading Gauge UIC-GA	
Appendix 3.3. Loading Gauge UIC-GB	
Appendix 3.3a Loading Gauge UIC-GC	. 85
Appendix 3.4. Electrified lines	
Appendix 3.5 Power supply facilities	
Appendix 3.6 Overview of signaling & safety devices equipping level	. 90
Appendix 3.6a Request for issuance of encryption keys for communication in the ETCS system	
Appendix 3.7 Overview of telecommunication devices equipping level	
Appendix 3.8. List of service points where it is possible to perform the transshipment of dangerous goods	
Appendix 3.9. Alternative transport routes	
Appendix 3.10. Facilities for rolling stock maintenance	
Appendix 3.10a. Information on the service facility managed by Nelt Co	
Appendix 3.11. Railway infrastructure development projects	
Appendix 4.1. Request for train path allocation (form)	
Appendix 4.1a. Request for train path allocation (e-papir)	124
Appendix 4.1b Template for submission of traction vehicle technical data	
Appendix 4.2. Instruction for completion of the Request for train path allocation	128
Appendix 4.3. Deadlines for annual 2024/2025 timetable preparation	
Appendix 4.4. Deadlines for amendments to annual 2024/2025 Timetable	
Appendix 5.1. Overview of railway lines on which train running is possible when they are manned only w	
engine driver	
Appendix 5.2. Overview of the lines that do not meet the conditions for train running with an engine dr	
only	
Appendix 5.3. Geometry of pantograph (current collector) TIP POS - 254/III used on IŽS network	134
Appendix 6. Register of infrastructure data	
Appendix 7. Overview of primary train delay causes	
Appendix 8. Overview of platforms and arranged surfaces in service points	
Appendix 9. Method for calculation of electricity consumption for train traction	
Appendix 10. Railway node boundaries	176



TERMS AND ABBREVIATIONS

Terms:

	means the entire railway infrastructure constituting a network operated by the
Public railway	infrastructure manager, but not including the railway lines and secondary
infrastructure	tracks (industrial railway lines and industrial tracks) connected to the network;
Infrastructure	is a public enterprise or a company responsible for construction, exploitation, maintenance, and rehabilitation of railway infrastructure on the network, as
Manager	well as for participation in its development within the general policy of
0	infrastructure development and financing;
	is a company or other legal entity, registered for the prevailing activity of
	provision of freight and/or passenger railway transport services, to whom the license was issued, with an obligation to provide train traction or that provides
Railway Undertaking	train traction only. In terms of access to railway infrastructure, service facilities
	and services in connection to performing of railway transport, a railway
	undertaking is also a company or other legal entity that performs railway transport for its own purposes and to whom the license for transport for its own
	purposes was issued;
	is a facility along the railway lines with freight transport, specifically arranged
	in order to enable loading of goods onto the freight trains and/or unloading of goods from such trains, as well as integration of services of railway freight
Freight Terminal	transport with the services of road, maritime, inland waterway and air
	transport, i.e. forming or changing the composition of freight trains, and, if necessary, it is used to implement the border procedures at the borders with
	other countries;
	is a document by which a relevant licensing authority confirms the capacity of a company or other legal entity, registered for provision of the activity of
Transport License	public transport of goods and/or passengers, to provide railway transport
	services as a railway undertaking, which can be limited to the provision of certain types of services or the provision of railway transport for own purposes;
	certain types of services of the provision of farway transport for own purposes,
	means a railway undertaking or an international grouping of railway
Applicant	undertakings, or other persons or legal entities, such as competent authorities, consignors, forwarding agents or combined transport operators, having the
11	commercial interest for provision of public service or commercial interest for
	allocation of railway infrastructure capacity; is a request for individual train paths submitted during the validity of the
Ad hoc request	established timetable;
	is a network of railway lines, including the connecting lines and secondary
	tracks, with elements of railway infrastructure, operated by the Infrastructure Manager; intended for railway transport of goods and/or passengers, as well as
Network	for transport for own purposes, which can be performed by railway
	undertakings according to the principle of transparent and non-discriminatory
	access to the network; is the capacity of railway infrastructure necessary for train movement between
Path	two service points, within the envisaged period of time and under the precisely
	determined technical and technological conditions on the public railway infrastructure;
	is a formal document of the public railway infrastructure manager setting out
Timetable	the schedule of operation for passenger and freight trains as well as for trains
	operated for own purposes on the public railway infrastructure of the infrastructure manager;
Infrastructure conscitu	is a possible number of train paths for timetabling on the particular part of
Infrastructure capacity	public railway infrastructure over a given period of time;
Congested	is a section of railway infrastructure for which infrastructure capacity demand



infrastructure	cannot be completely satisfied during certain time periods, even after different infrastructure capacity requests have been coordinated;
Path allocation	is the allocation of public railway infrastructure capacities by the infrastructure manager;
Access right	is the right of a railway undertaking to use the railway infrastructure;
Coordination	is a process whereby the infrastructure manager and applicants make an adjustment of individual requests for path allocation;
Safety Certificate	means evidence that a railway undertaking has established the safety management system and that it meets the requirements set out in the technical specifications of interoperability, national safety regulations and other relevant regulations in order to control the risks and perform safe railway traffic operations on the network;
Competent institution, Relevant authority (body)	is an authority entitled to adopt various decisions relating to particular fields;
Relevant Railway Authority	is an authority authorised to act regarding the administrative issues in the railway sector of the Republic of Serbia (Directorate for Railways or the Ministry of Construction, Transport and Infrastructure, as the case may be).
Service Facility Operator	is an entity responsible for operating one or more service facilities or for providing one or more services to railway undertakings (basic, additional and/or accompanying), including operating of railway infrastructure which forms a part of a service facility.
Information about service facility	is a document containing detailed information necessary for access to a service facility and services (basic, additional and accompanying) with reference to performing of railway transport provided by the operator in that service facility.



The abbreviations used in the Network Statement have the following meanings:

ATC	Automatic Train Control
AGC	European Agreement on Main International Railway Lines
AGTC	European Agreement on Important International Combined Transport Lines and Related
	Installations
EU	European Union
FTE	Forum Train Europe
IM	Infrastructure Manager
MCTI	Ministry of Construction, Transport and Infrastructure of the Republic of Serbia
MF	Ministry of Finance of the Republic of Serbia
NS	Network Statement
DG	Dangerous goods
OSS	One-Stop-Shop
RID (2017)	Regulations concerning the international carriage of dangerous goods by rail
RNE	RailNetEurope (European Infrastructure Managers Association)
UIC	International Union of Railways
DR	Directorate for Railways – Regulatory Body in the Republic of Serbia
IŽS	"Infrastructure of Serbian Railways" JSC
EMU	Electric multiple-unit set
DMU	Diesel multiple-unit set
TOR	Top of rail
RS	Republic of Serbia
LTDG	Law on Transport of Dangerous Goods ("Official Gazette of the RS" no. 106/2016,
	83/2018, 95/2018 (other law), 10/2019 (other law))
GSM-R	Global System for Mobile Communications – Railway
ERTMS	European Rail Traffic Management System
ETCS	European Train Control System



1. GENERAL INFORMATION

1.1 Introduction

"Infrastructure of Serbian Railways" JSC (hereinafter IŽS) is a joint stock company for the management of public railway infrastructure (hereinafter: railway infrastructure), founded by the Republic of Serbia.

Railway infrastructure represents goods in general use, owned by the Republic of Serbia, that can be used by railway undertakings, on equal terms, in accordance with the Law on Railways.

Management of railway infrastructure is an activity of general interest.

Railway infrastructure includes permanent way and substructure, tunnels, bridges and other track structures, station tracks, level crossings including devices for securing of level crossings; safety, signaling and telecommunication installations on open lines, in stations and marshalling yards, including the plants for generating, transforming and distribution of electric energy for signaling and telecommunications; buildings for such installations or plants; track brakes; plants for transformation and transmission of electric energy for train traction: 110 kV two-phase transmission lines, sub-stations except for 110 kV distribution switchgear in such substation, supply cables between substations and contact wire, catenary and girders, third rail with beams, lighting installation for traffic and safety needs, service points' buildings and other facilities on trackside land used for regulation of railway traffic including the part of the equipment for calculation and charging of transport charges and buildings for railway infrastructure maintenance, accesses for passengers and goods, including road access and access to passengers for arrival and departure of pedestrians, track-side land and the airspace above the track, 12 m high, i.e. 14m high at over 220kV overhead power lines, measured from the top of rail.

The Network Statement is a document that contains all the information in accordance with the Law on Railways of the Republic of Serbia ("Official Gazette of the RS" No. 41/18 and 62/23).

The document is compliant to all the norms set forth under the guidelines provided by the association RailNetEurope (hereinafter RNE) and shall be used as informative material for the interested railway undertakings. Moreover, the Network Statement has been harmonized with relevant EU Directives.

Network Statement provides general information on railway network, terms and conditions for access to railway infrastructure, principles and criteria for allocation of capacities, principles for charge calculation and their amounts, procedures for dispute resolution and other important details for usage of services provided to railway undertakings.

Infrastructure Manager Basic Information

Joint Stock Company for Public Railway Infrastructure Management "Infrastructure of Serbian Railways", Belgrade (hereinafter: Company) was founded with the Decision on founding of Joint Stock Company for Public Railway Infrastructure Management ("Official Gazette of the RS", no.60/15 and 73/15) and registered in the registry of Serbian Business Registers Agency, under the number BD 69692/2015 from August 10, 2015.

The founder of the Company is the Republic of Serbia, as the sole stakeholder of the Company, of behalf of which the founder's right is enforced by the Government of the Republic of Serbia, Belgrade, Nemanjina 11, company number 07020171. The Company is under the jurisdiction of the Ministry of Construction, Transport and Infrastructure.

Business company name: Joint Stock Company for Public Railway Infrastructure Management "Infrastructure of Serbian Railways", Belgrade

Abbreviated Company Name: "Infrastructure of Serbian Railways" JSC



Company Headquarters is in Belgrade, and the address of company's headquarters is 6 Nemanjina, Belgrade.

The main activity of company is "Service activities in land transport", activity code is 5221.

Company Reg. No is 21127094, TIN 109108420.

Company Business Accounts are 205-222959-26 and 160-438771-53.

The main activity of the Company includes: Service activities in land transport. The activity includes the management of public railway infrastructure in the segment of maintenance of public railway infrastructure, organization and control of railway traffic, provision of access and use of public railway infrastructure to all interested railway undertakings and protection of public railway infrastructure. The company performs the activity of general interest in accordance with the law. The company may also perform other activities in accordance with the law. The company performs the activities and services in domestic and international trade in accordance with the law.

Responsible persons: Acting General Manager Zoran Jevtić Tel.: +381 11 3618 330 kabinet.infrastruktura@srbrail.rs

Infrastructure Manager Organisational Chart

The organizational structure of Joint Stock Company for Public Railway Infrastructure Management "Infrastructure of Serbian Railways", Belgrade is based on the Rulebook on organization and systematization of operations of Joint Stock Company for Public Railway Infrastructure Management "Infrastructure of Serbian Railways", Belgrade.

Joint Stock Company for Public Railway Infrastructure Management "Infrastructure of Serbian Railways", Belgrade, (hereinafter: the Company), in order to perform the activities of management of public railway infrastructure, is organized according to the groups of operations, as follows:

- organization and control of railway traffic,
- maintenance of railway infrastructure,
- economic affairs,
- investments,
- human resources and common affairs, and
- operations that are organizationally related to the General Manager's Office.

The Company operations are performed within its departments, divisions, sections, units, technical-technological divisions, stations and operational sections and other lower organizational forms.

The management of public railway infrastructure includes the maintenance of public railway infrastructure, the organization and control of railway traffic, the provision of access and use of public railway infrastructure to all interested railway undertakings, the protection of public railway infrastructure, as well as the performing of investor function in construction and reconstruction of public railway infrastructure.

The following operations are also performed within the Company: traffic engineering, civil engineering and electrical engineering operations, development, investment and project management operations, as well as common affairs: financial, planning and analysis operations, restructuring and cooperation with international financial institutions, accounting, public procurement and warehousing operations, human resources management, occupational health and safety, operations related to property and inventory-taking, information technologies implementation and development operations, internal safety, international affairs and ethic's operations. Furthermore, in order to implement the operative, professional and administrative functions within the Company, the operations which are organizationally related to the General Manager's Office are also performed.



The operations referred to in the previous paragraph are performed within:

- 1. Traffic Department,
- 2. Railway Infrastructure Access Department,
- 3. Centre for Relief Train Operations,
- 4. Centre for Infrastructure Technical Monitoring,
- 5. Civil Engineering Department,
- 6. Electrical Engineering Department,
- 7. Centre for Railway Infrastructure Testing and Diagnostics,
- 8. Centre for Infrastructure Rail Vehicles Maintenance System Management,
- 9. Warehousing Department,
- 10. Finance Department,
- 11. Accounting Department,
- 12. Centre for Planning, Analysis and Restructuring,
- 13. Inventory Department,
- 14. Development Department,
- 15. Investment Department,
- 16. Department for EU-Funded Projects Management (PIU),
- 17. Human Resources and General Affairs Department,
- 18. IT Department,
- 19. Centre for Security,
- 20. Real Estate Department,
- 21. Centre for International Affairs,
- 22. Department for Maintenance of Railway Station Buildings and Other Service Facilities,
- 23. Procurement Department,
- 24. Company's Management Secretariat,
- 25. Legal Department,
- 26. Centre for Safety Management System,
- 27. Media Centre,
- 28. Ethic's Office,
- 29. Centre for Internal Audit,
- 30. Centre for Internal Control.

The Organizational Chart of "Infrastructure of Serbian Railways" JSC is provided in Appendix 1.

Contact details

"Infrastructure of Serbian Railways" JSC contact details are the following:

Acting General Manager Zoran Jevtić Tel.: +381 11 3618 330 kabinet.infrastruktura@srbrail.rs

Traffic Department Nemanjina 6 11000 Belgrade, Serbia Serbia Tel.: +381 11 3618 214 Fax: +381 11 3616 814 sektor.sp@srbrail.rs

Railway Infrastructure Access Department Nemanjina 6 11000 Belgrade, Serbia Serbia Tel.: +381 11 3618 214/ Fax: +381 11 3616 814 <u>sektor.pzi@srbrail.rs</u>



Civil Engineering Department Nemanjina 6 11000 Belgrade, Serbia Tel: +381 11 3618 248 Fax: +381 11 3616 874 infr.sektorzagp@srbrail.rs

Electrical Engineering Department Nemanjina 6 11000 Belgrade, Serbia Tel: +381 11 3618 241 Fax: +381 11 3618 130 etp@infrazs.rs

Centre for Relief Train Operations Nemanjina 6 11000 Belgrade, Serbia Tel.: +381 11 3620 899 Fax: +381 11 3620 899 radomir.brkic@infrazs.rs

Warehousing Department Nemanjina 6 11 000 Belgrade, Serbia stovarista.infra@srbrail.rs

Finance Department Nemanjina 6 11 000 Belgrade, Serbia Tel.: +381 11 3618 465 Fax: +381 11 3618 465 finansijeizs@srbrail.rs

1.2 Purpose of the Network Statement

The purpose of this Network Statement is provision of single source basic information to the users of services provided to railway undertakings on the railway infrastructure operated by IŽS.

The Network Statement is a document which sets out the detailed general rules, deadlines, procedures and criteria related to the manner of calculation of charges and allocation of infrastructure capacities, including other relevant information necessary for submitting the request for infrastructure capacity allocation.

The Network Statement will be published on the web site of "Infrastructure of Serbian Railways" JSC, <u>www.infrazs.rs</u>, and the decision on its adoption will be published in the "Official Gazette of ŽS".

1.3 Legal Aspects

The functioning of infrastructure and traffic on the network operated by "Infrastructure of Serbian Railways" JSC is regulated by:

- legislation of the Republic of Serbia,
- formal documents of the Infrastructure Manager "Infrastructure of Serbian Railways" JSC,
- formal documents and technological procedures of the railway undertakings falling within the scope indicated in the above legislation.



1.3.1 Legal Framework

Regulations of the Republic of Serbia

Regulations of the Republic of Serbia of particular importance to this Network Statement include the following documents:

- Law on Railways ("Official Gazette of the RS", No. 41/18 and 62/23);
- Law on Interoperability of Railway System ("Official Gazette of the RS", No. 62/23);
- Law on Safety in Railway Traffic ("Official Gazette of the RS", No. 41/18")
- Regulation on Categorization of Railway Lines that belong to Public Railway Infrastructure ("Official Gazette of the RS", No. 92/20, 6/21, 33/22 and 63/23);
- Rules on Railway Infrastructure Elements ("Official Gazette of the RS", No.30/19);
- Rules on the Timetable ("Official Gazette of the RS", No. 58/19 and 1/2020);
- Regulation on Methodology for Valuation of the Elements for Determining the Level of Charge for the Use of Railway Infrastructure ("Official Gazette of the RS", No. 122/14);
- Rules on the Manner of Transport and Mandatory Operational Monitoring of Dangerous Goods Carried by Rail, as well as on the Obligations of the Participants in the Transport of Dangerous Goods by Rail and Emergencies ("Official Gazette of the RS", No. 81/15);
- Rules on training programme and method of knowledge checking of employees and of participants of dangerous goods transport in the railway transport, as well the manner in which the documentation is processed and their training ("Official Gazette of the RS", No. 81/15);
- Law on Transport of Dangerous Goods, passed by the National Assembly of the Republic of Serbia ("Official Gazette of the RS", No. 104/2016-34, 83/2018-57, 95/2018-389 (other law), 10/2019-13 (other law));
- Rules on Mandatory Elements of the Contract on the Use of Railway Infrastructure ("Official Gazette of the RS", No. 8/2019);
- Rules on Special Loads Transport ("Official Gazette of the RS", No. 74/19);
- Regulation on the Manner of Conclusion and Content of Framework Agreements for Allocation of Railway Infrastructure Capacity ("Official Gazette of the RS" No. 74/19);
- Regulation on Particularities of Procedures and Criteria Applicable to Access to the Services Provided in Service Facilities ("Official Gazette of the RS" No. 57/19 and 13/20);
- Rules on the Elements of Service Facility Information ("Official Gazette of the RS" No. 66/19).

International Regulations

When using the allocated train path, the railway undertaking must abide by all legal norms contained in the sources of international law (Convention concerning International Carriage by Rail (COTIF), its annexes, agreements and protocols governing the cross-border railway traffic and border control, UIC standards and any other relevant international regulations) as well as in the national laws and bylaws.

Formal documents of the Infrastructure Manager

Internal regulations (formal documents) and technological procedures of the Infrastructure Manager are listed in Appendix 2.



1.3.2 Legal Status and Liability

The Network Statement is based on the legal framework defined in section 1.3.1. In case of any ambiguities or legal proceedings, the relevant provisions of the legislation of the Republic of Serbia will apply.

The present Network Statement has been developed on the basis of the information available at the moment of drafting thereof. IŽS is liable for accuracy of the information given in the present Network Statement. All regulations and technical documentation which become effective upon publishing of this Network Statement shall apply and shall be taken into consideration on the occasion of construing this Network Statement.

IŽS is not liable for the accuracy of data published herein, which are submitted by the service facility operators.

1.3.3 Appeals Procedure

Appeals procedure in respect of the Network Statement, and in respect of other formal documents of the Infrastructure Manager relating to the path allocation procedure and use of railway infrastructure, is governed by the Law on Railways.

The function of the regulatory body for the railway sector is performed by the Directorate for Railways (hereinafter: the Directorate), as a separate organization which runs the railway-specific state administration affairs as set forth in the Law on Railways.

The scope of the Directorate for Railways has been set out in Articles 118-129 of the Law on Railways ("Official Gazette of the RS" No. 41/2018 and 62/23) and by the provisions of the Law on Safety of Railway Transport ("Official Gazette of the RS" No.41/2018).

Article 120 of the Law on Railways provides that the Directorate is in charge of the following:

- regulation of railway services market;
- licensing of railway undertakings;
- passenger rights;
- safety in railway traffic and interoperability of railway system;
- cableway;
- realization of international cooperation within its scope of competence;
- other tasks in accordance with this law and other laws governing the area of safety in railway transport, interoperability of railway system and cableways for transport.

The applicant for train path allocation may lodge a complaint with the Directorate for Railways against the decision made by the Infrastructure Manager to reject its application for path allocation or against the established conditions for supply of infrastructure capacity, and also when it is not satisfied with the train path allocation procedure and its outcome, subject to payment of a fee in the amount of administrative fee charged for the appeals to the authority.

As a regulatory body, the Directorate deliberates, in the segment of regulation of railway services market, on the complaints lodged by applicants for train path allocation, especially taking into account any potential unfair treatment or discrimination by the Infrastructure Manager or railway undertakings, in connection with:

- (1) the Network Statement,
- (2) the criteria set out in the Network Statement,
- (3) the train path allocation procedure and its outcome,
- (4) the method for determining the charge for the use of train path;
- (5) the level or structure of charges for the use of train path which it is or may be obliged to pay,
- (6) information about service facilities;



(7) the application of provisions of article 13 of the Law on Railways and particularly of access and charges.

The decision of the Directorate is final. The appeal against it may be lodged with the Administrative Court within 30 days of its receipt.

1.4 Structure of the Network Statement

The structure of 2025 Network Statement is in accordance with the general structure for network statements of the European Railway Association (RailNetEurope association) which is applied by most infrastructure managers in Europe in the process of network statement preparation.

The general structure of Network Statement is reviewed as necessary and the latest version is available on the RNE's web-site. The objective of general structure is that all applicants and interested parties may find the same information at the same place in the Network Statement.

The Network Statement consists of 7 chapters that make up the basic document and a series of attachments that contain additional information.

No	Chapter	Description			
1.	General information	Contains the general information about Network Statement and contacts			
2.	Infrastructure	Contains the description of the network operated by JSC "Infrastructure of Serbian Railways" (IŽS)			
3.	Access conditions	Provides a specification of conditions, which will be met by the railway undertaking, prior to gaining the track access			
4.	Capacity allocation	Provides the principles and criteria for infrastructure capacities allocation			
5.	Services and charges	Provides an overview of services provided by "Infrastructure of Serbian Railways" JSC and charges			
6.	Operations	Contains operational rules			
7.	Service facilities	Provides an overview of service facilities connected to rail network operated by IŽS			

Table No 1. Network Statement Structure

1.5 Validity Period, Updating and Publishing

1.5.1 Validity Period of the Network Statement

This Network Statement shall be valid during the timetable validity period, from December 15th, 2024 to December 13th, 2025.

The Network Statement shall be published not later than two months prior to the commencement of the final deadline for submission of applications for path allocation and shall remain valid during the entire timetable validity period.

1.5.2 Updating Process

The Network Statement will be updated in case of change of important pieces of information published in the Network Statement. Any amendment to the Network Statement will be published separately in the "Official



Gazette of Serbian Railways", whereas the updated (amended) Network Statement will be published on the "Infrastructure of Serbian Railways" JSC website.

1.5.3 Publishing, Distribution and Availability of the Network Statement

The Network Statement will be published on the "Infrastructure of Serbian Railways" JSC website (<u>www.infrazs.rs</u>), both in Serbian and English languages.

If so requested by a railway undertaking, "Infrastructure of Serbian Railways" JSC may provide the Network Statement or a part of it, free of charge, in electronic format.

1.6 Contacts

Contacts relevant for information contained in the Network Statement:

"Infrastructure of Serbian Railways" JSC Railway Infrastructure Access Department 6, Nemanjina St. 11000 Belgrade Serbia Tel.: +381 11 3618 214 Fax: +381 11 3616 814 sektor.pzi@srbrail.rs

1.7 Cooperation Between European IMs/ABs

1.7.1 Rail Freight Corridors

The Pan-European Corridor X from Salzburg in Austria to Thessaloniki in Greece stretches via the infrastructure network of "Infrastructure of Serbian Railways" JSC. On the territory of the Republic of Serbia, on the network of "Infrastructure of Serbian Railways" JSC, Corridor X includes the following railway lines from Šid to Preševo:

- Belgrade Šid State border,
- Belgrade Mladenovac Niš,
- (Belgrade) Rakovica Jajinci Mala Krsna Velika Plana,
- Niš Preševo State border.

The following branches connect to the primary route of the Corridor:

- Xb, (Budapest) Novi Sad Belgrade (railway line (Belgrade) Stara Pazova Subotica), and
- Xc, Niš Dimitrovgrad (Sofia Istanbul) (railway line Niš Dimitrovgrad State border).

Infrastructure of Serbian Railways is a member of Railway Freight Corridor Alpine-Western Balkans (RFC 10). The corridor connects five countries: Austria, Slovenia, Croatia, Serbia and Bulgaria. The corridor route goes from Svilengrad in Bulgaria, via Sofia, Belgrade, Zagreb to Zidani Most in Slovenia, where the route branches off to two routes via Maribor, Gratz to Wels and via Ljubljana, Villach to Salzburg. The corridor covers 2,114 km of main lines and 31 km of connecting lines. There are 21 intermodal terminals and 12 marshalling yards on the corridor.

More details on the corridor are available on its website https://www.rfc-awb.eu/.

1.7.2 RailNetEurope

RailNetEurope association (hereinafter RNE) was established in January 2004 by virtue of an agreement between 12 Infrastructure Managers from the entire Europe, and their number is constantly rising.



Through its members, RNE operates over 230,000 km long railway lines, including the important ferry lines, and cooperates with more than 120 railway undertakings in international traffic and with more than 300 railway undertakings that, for the time being, operate only in the domestic traffic of the members.

The main efforts are put towards enhancing the access conditions and performance of international railway transport, particularly with respect to operability. To achieve this, RNE is focused on the overall process of international transport operations. It starts with harmonization of mid-term and long-term planning of particular members, joint marketing and sales approach, appropriate planning and operation, and ends with provision of services after transport has been performed, such as monitoring, control and assessment of performed transport.

One of the first steps towards progressive harmonization was creation of a structure model for the preparation of Network Statement, applied by all RNE members.

One of the most important RNE steps was creation of an international network of One Stop Shop offices.

The list of all RNE members and further information on this association may be found at <u>www.railneteurope.com</u>.

"Infrastructure of Serbian Railways" JSC is a full member of the association from April 21, 2016.

One Stop Shop - OSS

Infrastructure Managers have opened national One Stop Shop (OSS) offices that jointly make up a network of contact points for the users within the RNE. As regards the international path allocation applications, the users only need to contact one of these OSSs that will initiate the entire process of international path allocation.

In close cooperation with other IMs, the contacted OSS will:

- offer support and information to undertakings on the entire range of Infrastructure Managers' products and services along the whole route;
- provide all information on the conditions for access to the infrastructure of any Infrastructure Manager within the RNE;
- process the applications for international path allocation within the RNE;
- make sure that all the applications for the next year's Timetable are timely taken into account during
 preparation of the annual Timetable;
- provide offers for railway paths on the entire route in international traffic.

In accordance with its motto "one face to the customer", the OSS provides professional and efficient assistance via all border crossings, underpinned by transparent procedures based on trust and non-discrimination. The list of contacts by member countries is available at <u>www.railneteurope.com</u>.

"Infrastructure of Serbian Railways" JSC, as a RNE member, conducts intensive activities on defining the procedures so as to implement the OSS in the near future in the railway sector of the Republic of Serbia.

RNE tools

Since 2005, the RNE has taken over the full responsibility for preparation of the international timetable and the support to its activities; it operates the following information systems: for path coordination - PCS (Path Coordination System), for charging - CIS (Charging Information System) and for train information - TIS (Train Information System).



PCS

PCS (Path Coordination System) – is an international path request coordination system for path applicants i.e. railway undertakings, infrastructure managers and allocation bodies. This web-based application optimises international path coordination by ensuring that path requests and offers are harmonised by all involved parties. The input for international path requests needs to be entered only once into the system – either via the domestic application or directly into the PCS. More information is available on: http://pcs.RNE.eu/.

CIS

CIS (Charging Information System) – is an infrastructure charging information system for railway undertakings, infrastructure managers and allocation bodies. This web-based application provides fast information on charges related to the use of the European rail infrastructure and estimates the charge for the use of international train paths within minutes. This is an umbrella application for various national rail infrastructure charging systems. More information is available on: <u>http://cis.RNE.eu/.</u>

TIS

TIS (Train Information System) – is a web-based application which manages the operation of international trains by delivering information on movements of international passenger and freight trains in real time. These data are obtained directly from the system. More information is available on: http://tis.RNE.eu/.



2. INFRASTRUCTURE

2.1 Introduction

The purpose of this section is to provide the information on the railway infrastructure owned by the Republic of Serbia and managed by IŽS, to provide the description and overview of the characteristics of the railway lines and appertaining facilities and equipment that can be used by all those to whom the access to and use of infrastructure have been granted in accordance with the provisions of the Law on Railways. Other information on the IŽS network can be found on the website <u>www.infrass.rs</u>.

Information on the railway infrastructure published in this document is based on the facts that were familiar at the time of its preparation. All changes occurring after publishing of this document will be updated on the website <u>www.infrazs.rs</u>.

2.2 Extent of Network

The total structural length of standard-gauge lines on the territory of "Infrastructure of Serbian Railways" JSC network amounts to 3 357.341 km, out of which 3 012.201 km of single-track and 345.140 km of double-track lines. The above-mentioned line length includes 1 758.971 km of main lines and 1 598.37 km of other lines. The total of 1 313.257 km of open tracks have been electrified, together with main running tracks (968.117 km of single-track and 345.140 km of double-track lines).

The total length of electrified lines - open tracks and main running tracks is 1 659.525 km. All the above data relate to standard-gauge 1435 mm tracks. More detailed information is available in Appendix 6.

In addition, "Infrastructure of Serbian Railways" JSC also operates the museum-tourist railway line - "Shargan Eight" - which is 22.471 km long and whereof track gauge is 760 mm.

2.2.1 Limits

In terms of ownership and management of public railway infrastructure, there is only one railway network in the Republic of Serbia and this is a state-owned network, managed by IŽS. Therefore, the term "limit" also means state borders which at the same time represent borders with the neighbouring railway networks.

The IŽS railway network borders with the neighbouring railway networks are the following border stations: Subotica, Horgoš, Kikinda, Vršac, Bogojevo, Šid, Brasina, Preševo, Đeneral Janković, Vrbnica and Dimitrovgrad.

Upon crossing of state borders, the track gauge remains unchanged.

The type of traction is changed only at the border crossing with the Republic of Bulgaria, at Dimitrovgrad station on the railway line Niš-Dimitrovgrad- State Border.

2.2.2 Connecting Railway Networks

The railway network of the Republic of Serbia is connected with the railway networks of the following seven countries: Croatia, Hungary, Romania, Bulgaria, North Macedonia, Montenegro and Bosnia and Herzegovina. Traffic can be organized via ten border crossings, while one border-crossing is under the control of UNMIK.

For more detailed information please refer to Table No 2. The names of neighbouring countries' stations in the table are given in authentic form, as registered in the official timetables.

The term joint border station means a border station in which border control is jointly performed by the competent state authorities, as well as traffic handover between the railway undertakings. Joint border stations are governed by bilateral state agreements. Performing of traffic handover in other border stations is within decision –making domain and agreement between the railway undertakings.



	Neighbouring country	country Border ranway lines		Neighbouring infrastructure manager	Note	
1 Croatia -		Šid-State Border -Tovarnik	Šid Tovarnik	HŽI		
1	Cround	Bogojevo-State Border- Erdut	Bogojevo Erdut	HŽI		
		Subotica-State Border- Kelebia	Subotica Kelebia	MAV Zrt		
2	Hungary	Horgoš-State Border- Roszke	Subotica Roszke	MAV Zrt	In case of freight trains, each country conducts the border police and customs' inspections on its own territory, wheras for passenger trains, joint border control is performed in Roszke station.	
3	Romania	Vršac- State Border - Stamora Moravita	Vršac Stamora Moravita	CFR SA		
		Kikinda-State Border- Jimbolia	Kikinda Jimbolia	CFR SA		
4	Bulgaria	Dimitrovgrad-State Border Dragoman	Dimitrovgrad Dragoman	NKŽI		
		Preševo- State Border Tabanovci	Preševo/ Ristovac Tabanovci	IŽRSM	Joint border station Tabanovci	
5	North Macedonia	North Macedonia	Đeneral Janković - State Border -Volkovo	Đeneral Janković	IŽRSM	Temporary under the supervision of UNMIK Railways
6	Montenegro	Vrbnica - State Border – Bijelo Polje	Vrbnica / Bijelo Polje	ŽICG	Joint border station Bijelo Polje	
7	Bosnia and Herzegovina	Brasina - State Border – Zvornik Novi	Brasina Zvornik Novi	ŽRS		

Table No 2. Border crossings, border railway lines and border stations

Within the national network, the public railway infrastructure operated by IŽS is connected with other railway infrastructures in the Republic of Serbia. The sidings of Elektroprivreda Srbije and HBIS Group Serbia Iron & Steel" d.o.o. are connected to IŽS national railway network.



These sidings are used for transport of goods for own needs (industrial railways) and they do not belong to the national railway network.

Railway infrastructure operated by IŽS is also connected with a number of railway industrial sidings owned by the business entities.

For other information on railway infrastructure operated by IŽS, which are not contained and presented herein, please contact IŽS at the following address:

"Infrastructure of Serbian Railways" JSC Railway Infrastructure Access Department 6 Nemanjina St., 11000 Belgrade, Serbia Phone.: +381 11 3618 214 Fax: +381 11 3616 814 sektor.pzi@srbrail.rs

2.3 Network Description

2.3.1 Geographic data and types of railway lines

General network information is given in Table No. 3.

Table No 3. Structural length of the lines within the network

Total network length	3 357.341 km
Single-track lines	3 012.201 km
Double track lines	345.140 km
Narrow-gauge lines	22.471 km*
Non-electrified lines	2 044.084 km
Electrified lines	1 313.257 km

* Narrow-gauge line Šargan Vitasi – Mokra Gora – State Border (Višegrad)

Types of railway lines

Pursuant to the Regulation on categorization of railway lines that belong to public railway infrastructure ("Official Gazette of the RS", No. 92/20, 6/21, 33/22 and 63/23) applied by the "Infrastructure of Serbian Railways" JCS, railway lines are classified as main lines, regional lines, local lines, shunting lines and museum-tourist lines.

Pursuant to the law governing the railways, railway lines are classified as follows:

- 1. main lines- of importance to international and domestic service;
- 2. regional lines of importance to regional and local service;
- 3. local lines of importance to local service;
- 4. shunting lines of importance to business entities,
- 5. museum-tourist railway lines.

Main lines with associated line number are:

- 101 Belgrade Centre-S. Pazova-Šid-State border-(Tovarnik);
- 102 Belgrade Centre Junction "G"- Rakovica-Mladenovac-Lapovo-Niš-Preševo-State border-(Tabanovce);
- 103 (Belgrade Centre)- Rakovica-Jajinci-M.Krsna-V.Plana;
- 104 (Jagodina) Ćuprija Junction Ćuprija-Paraćin;
- 105 (Belgrade Centre)-S.Pazova-N.Sad-Subotica-State border-(Kelebia);
- 106 Niš-Dimitrovgrad-State border-(Dragoman);
- 107 Belgrade Centre-Pančevo Main St.-Vršac- State border-(Stamora Moravita);
- 108 (Belgrade Centre)-Resnik-Požega-Vrbnica- State border-(Bijelo Polje);
- 109 Lapovo-Kraljevo-Lešak-Kosovo Polje-Djeneral Janković- State border-(Volkovo);



- 110 Subotica-Bogojevo-State border-(Erdut);
- 111 Belgrade Marshalling Yard "A"-Ostružnica-Batajnica;
- 112 Belgrade Marshalling Yard "B"-Ostružnica;
- 113 Belgrade Marshalling Yard "A"-Junction, "B"- Junction "K/K1"-Resnik;
- 114 Ostružnica-Junction "B"-(Junction "K/K1");
- 115 Belgrade Marshalling Yard "B"-Junction "R"- Junction "A"-(Resnik);
- 116 (Belgrade Marshalling Yard "B")-Junction "R"-Rakovica;
- 117 Belgrade Marshalling Yard "A"-Junction "T"-Rakovica;
- 118 Belgrade Marshalling Yard "B"-Junction "T"-(Rakovica);
- 119 Connecting track in the area of Junction "K/K1": (Junction "B")--Points "K"-Points "K1"-(Jajinci);
- 120 (Junction Pančevo Most)-Junction Karadjordjev park-Junction Dedinje-(Junction "G");
- 121 Indjija-Golubinci;
- 122 Novi Sad-Novi Sad Marshalling Yard-Junction Sajlovo;
- 123 By-pass track at the station Mala Krsna: (Kolari)-Junction points 1-Junction points 28-(Osipaonica);
- 124 Junction Lapovo Varoš-Lapovo Marshalling Yard-Lapovo;
- 125 Trupale-Niš Marshalling Yard-Medjurovo;
- 126 Crveni Krst-Niš Marshalling Yard;
- 127 Niš-Junction Most-(Niš Marshalling Yard);

128 Connecting track at the station Niš: (Crveni Krst)-Junction points 3-Junction points 4-(Ćele Kula).

Regional lines with associated line number are:

- 201 Subotica-Horgos-State border-(Roszke);
- 202 Pančevo Main St.-Zrenjanin-Kikinda-State Border-(Jimbolia);
- 203 Belgrade Donji Grad (km 7 + 041) Belgrade Danube Junction Pančevo most¹;
- 204 Topčider Passenger Station (km 4 + 195) Junction "G" (Rakovica)²;
- 205 Banatsko Miloševo-Senta-Subotica;
- 206 Pančevo Varoš-Junction "2a"-(Jabuka);
- 207 Novi Sad-Odžaci-Bogojevo;
- 208 (Novi Sad)-Junction Sajlovo-Rimski Šančevi-Orlovat stop;
- 209 Novi Sad Marshalling Yard Junction points 7-Novi Sad Lokoteretna-Sajlovo Junction;
- 210 Orlovat- Junction "1a"-(Lukićevo);
- 211 Ruma-Šabac-Junction Donja Borina-State border-(Zvornik Novi);
- 212 (Platičevo)-Junction "1"-Junction "3"-(Štitar);
- 213 Stalać-Kraljevo-Požega;

214 Connecting track at the station Kraljevo: (Mataruška Banja)-Junction points 72-Junction points 73-(Adrani)

215 Connecting track at the station Požega: (Uzići)-Junction points 53-Junction points 54-(Dragačevo);

216 Smederevo - Junction Jezava - Radinac - Mala Krsna;

- 217 Junction Jezava Smederevo Port;
- 218 Mala Krsna-Bor-Junction "2"-(Vražogrnac);
- 219 (Nis) Crveni krst-Zaječar-Prahovo Port;
- 220 (Rgotina)-Junction "3"-Junction "1"-(Trnavac);
- 221 (Barlovo)-Junction "1"-Kuršumlija;
- 222 Kuršumlija-Kastrat;
- 223 Doljevac-Kastrat-Merdare Kosovo Polje;
- 224 Kosovo Polje-Metohija-Peć;
- 225 Kosovo Polje Freight St.-Junc. "1"-(Drenica);

² By virtue of the Conclusion adopted by the Government of the Republic of Serbia No 340-2989/2022 dated April 7th, 2022, the Decision of the Shareholders' Meeting of Infrastructure of Serbian Railways JSC on termination of public railway service, dismounting and reconstruction of infrastructure capacities on railway line Topčider Putnička (km 4 + 195 – Junction "G" – (Rakovica) has been approved.



¹ By virtue of the Conclusion adopted by the Government of the Republic of Serbia No 340-2986/2022 dated April 7th, 2022, the Decision of the Shareholders' Meeting of Infrastructure of Serbian Railways JSC on termination of railway line Belgrade Donji Grad (km 7+041) – Belgrade Danube – Junction Pančevo Most has been approved.

226 Vrbas - Sombor.

Local lines with associated line number are:

301 Subotica-Subotica Factory;
302 Subotica-Subotica Hospital;
303 Novi Sad (km 1+042)-Novi Sad Ložionica;
304 (Podbara)-Junction "3"-Junction "2"-(Kać);
305 (Rimski Šančevi)-Junction "1"-Junction "3"-(Podbara);
306 Rimski Šančevi-Žabalj;
308 (Brasina)-Junction Donja Borina-Zvornik Grad;
309 Pančevo Varoš-Pančevo Vojlovica;
310 Connecting track at the station Senta: (Čoka)-Junction points 22-Junction points 23-(Orom);
311 Markovac-Svilajnac-Despotovac- (Resavica);
312 Metohija-Prizren;
313 Vršac – Bela Crkva.

Shunting lines with associated line number are:

- 401 Vršac-Vršac Vašarište;
 402 Kikinda-Metanolsko sirćetni kompleks(km 6+413);
 403 Bogojevo-Dunavska Obala;
 404 Paraćin-Stari Popovac;
 405 Surčin-Jakovo-Bečmen;
 406 Šid-Sr.Rača Nova-State Border-(Bijeljina);
 407 Ovča-Padinska Skela;
 408 Sonta Apatin factory;
- 409 Bačka Palanka Gajdobra

Museum-tourist line with its associated number is:

501 Šargan Vitasi – Mokra Gora – State Border (Višegrad).

Due to the technical condition of particular local and shunting lines, traffic is no longer possible on such lines and is currently completely or partially suspended. More details can be found in Appendix 6.

The following IŽS lines belong to main international railway lines according to AGC (European Agreement on Main International Railway Lines):

<u>Direction North – South</u> E 771 Subotica-Bogojevo E 79 Belgrade - Vrbnica E 85 Subotica-Belgrade-Niš-Preševo -Kraljevo-Djeneral Janković <u>Direction West – East</u> E 66 Belgrade-Vršac E 70 Šid-Belgrade-Niš-Dimitrovgrad

2.3.2 Track Gauges

Track gauge along the network is 1435 mm, except for the museum-tourist line the "Shargan Eight", whose gauge is 760 mm.

2.3.3 Stations and Nodes

Names, km-points and distances in km between particular service points and railway nodes are given in Appendix 6 and Appendix 10.



2.3.4 Loading Gauge

Loading gauge is a limited space viewed as a cross section vertical to the track axis that may not be exceeded by any part of the rail vehicle, whether loaded or empty. The loading gauge registered for all IŽS lines for international traffic is UIC GB, except for parts of the railway lines Valjevo – Kalenić and Grlica - Djeneral Janković, where the registered loading gauge is UIC GA. These loading gauges are in line with the UIC Leaflet 506.

The loading gauge that applies to domestic traffic on IŽS lines is ŽS I. The ŽS I gauge is slightly larger than the UIC GA loading gauge and slightly smaller than UIC GB. The summary of loading gauges is presented in Appendices 3.1.-3.3.

IŽS lines have not been coded for the combined transport gauges in accordance with UIC Leaflet 596-6. However, the measurements that were performed have shown that movements of wagons carrying combined transport load units - such as high cube containers (HCC), semi-trailers and entire road vehicles - are possible. Movements of such consignments are possible under special safety conditions in the exceptional transport regime.

For further information, please contact IŽS:

"Infrastructure of Serbian Railways" JSC Traffic Department 6 Nemanjina St. 11000 Belgrade Serbia Tel.: +381 11 3618 214 Fax: +381 11 3616 814 E-mail: <u>sp@infrazs.rs</u>

2.3.5 Weight Limits

In accordance with UIC Leaflet 700, depending on track capacity to bear loads by vehicles on the railway network, various weight limits are applicable and expressed in tonnes per axle and tonnes per linear metre.

The load by a railway vehicle per linear metre is the load of an unloaded or loaded railway vehicle divided by the length of the railway vehicle expressed in metres and measured between tops of uncompressed buffers.

Axle load of a railway vehicle is the load of an unloaded or loaded railway vehicle divided by the number of axles of the railway vehicle.

Based on the above-stated, railway lines were classified into categories (Regulations on classification of railway lines No. 325, published in the Official Gazette of the Community of Yugoslav Railways (ZJŽ) Nos. 7/89 and 9/90). The classification of IŽS railway lines is shown in Table No. 4.

A dura in a i la la	laada		Admissible loads per axle			
Admissible loads per linear metre		per	А	В	С	D
			16 t	18 t	20 t	22,5 t
1	5.0 t/m		А	B1		
2	6.4 t/m			B2	C2	D2
3	7.2 t/m				C3	D3
4	8.0 t/m					D4

Table No 4: Categories of admissible loads on IŽS network



The overview of admissible loads in tonnes per axle and in tonnes per linear metre is presented in Appendix 6.

2.3.6 Line Gradients

In order to determine required train braked weight, the ruling gradients for braking must be determined for each line or track section. The ruling line gradient for braking means the value of its longitudinal gradient, on the basis of which braked weight percentages are determined, i.e. the required train braked weight on a certain line or track section. The longest longitudinal gradient (rising or falling) on a specific line (or section), over the length of 1000 metres or more, is considered to be the ruling gradient of that specific line or section. In determining the ruling gradient for braking, the curve and tunnel related resistances are not taken into consideration.

The ruling resistance of a line or one of its sections means the value of its specific resistance due to gradient, curve and tunnel, on the basis of which train weight i.e. locomotive hauled load is determined.

The overview of ruling gradients and ruling resistances of particular lines is presented in Appendix 6.

2.3.7 Maximum Line Speeds

The maximum permissible speed with respect to line capacity is the maximum speed permitted on a line or line section with respect to the railway line superstructure and its structures (carrying capacity of the track, its lining and levelling, curve radius, points design, etc.), fixed electric traction installations and signalling and interlocking devices on the line, and it may not exceed the lowest one of such speeds.

Restricted speeds are permanently prescribed speeds that are lower than the maximum permissible speed on the railway line and that are applied on a certain section of the railway line due to its technical condition or that are applied while running in the points area.

For further information on maximum permissible speeds and restricted speeds with respect to line capacity, please refer to Appendix 6.

2.3.8 Maximum Train Lengths

The length of each train is determined during the capacity allocation procedure and it is expressed in rounded metres. The maximum permissible length of a train operating on a line, for the purposes of its smooth acceptance and forming in railway stations, at passing points and other service points, is determined on the basis of the maximum permissible train length in certain stations, passing points and other service points along the given line and with respect to usable length of main lines.

Maximum permissible length of a train for station tracks is obtained by subtracting the length of 25 m to be taken up by the locomotive and spare 10 m to be taken up by the train, from the usable track length expressed in metres and determined under the Instructions (Instructions on the technical standards and data for the preparation of timetable implementation, "Official Gazette of ZJŽ Nos. 9/89, 6/91, 8-9/91, 4/92, and 9/92).

Actual length of a train is obtained by totalling the lengths over uncompressed buffers of all vehicles included in the train, except for the locomotive hauling the train, whose length has been taken into account during determination of maximum permissible train length at a station. If a train has double heading, banking locomotive or intermediate-haul locomotive, their lengths must be taken into account when determining the train length.

The overview of distances between the service points and maximum permissible train lengths relative to usable track lengths is presented in Appendix 6.

The provisions of paragraph 2 of this article shall also apply to the length of the passenger train. The passenger train may be longer than the length of the platforms and arranged areas in service points, and if the



railway undertaking requires their dwelling in such service points, it must set and ensure the necessary safety measures for passengers in accordance with local and/or other specific circumstances. The overview of platforms and arranged areas in service points is given in Appendix 8 and for further details, please contact IŽS:

"Infrastructure of Serbian Railways" JSC Railway Infrastructure Access Department 6 Nemanjina St. 11000 Belgrade Serbia Tel.: +381 11 3618 214 Fax: +381 11 3616 814 sektor.pzi@srbrail.rs

2.3.9 Power Supply

IŽS ensures the transmission of required electric energy from the public power supply network of the Republic of Serbia via the fixed electric traction installations (substations) and the catenary for electric train traction. All electrified railway lines have the basic power supply system, which is single-phase AC 25 kV 50 Hz system. The overview of electrified railway lines is presented in Appendix 3.4. The overview of power supply installations is presented in Appendix 3.5.

The power supply system voltage is U=25 kV, and its frequency is f=50Hz. The height of the contact wire are Hkpmin=5000 mm, Hkpnom=5500 mm and Hkpmax=6000 mm. The staggering of the OCL is $p=\pm200$ mm along the straight track, and p=300 mm in curves.

In the 25kV, 50 Hz power supply system, the use of pantograph (current collector) for electric motive power is permitted according to the General Contact Line Catalogue (type POS-III/E). The design of pantograph is shown in Figure No 1.

The basic parameters for the asymmetric pantograph used on IŽS network, with double contact strip and pneumatic actuator, are in accordance with the provisions of UIC Leaflet 608 and are shown in Table No 5.




Figure No 1. – Dimensions of pantograph



Table No. 5: Pantograph parameters

Permissible width of horned slipper holder (mm)	Width of metal horns (mm)	Rated current (A)	Height of contact line (mm)	Minimum length of contact strip (mm)	Static force Fa (N	Maximum aerodynamic force Fa (N)	Maximum speed (km/h)	Type of contact strip
1600	1400	400	6200 5500 5000	800	60-90	70	160	graphite

2.3.10 Signalling Systems

Railway signals provide signals by means of which railway staff can mutually communicate in a fast and reliable way about train operation, shunting, permitted and forbidden runnings via a certain location, the track condition, the need for speed restriction, etc. Some signals are used for preserving of personal safety of railway staff and other persons.

Regulations on types of signals, signal markings and track markings ("Official Gazette of the RS" No.50/20) are applicable to the use of signals and signal markings.

There are eleven types of station track interlocking on the network of "Infrastructure of Serbian Railways" JSC, and they are presented in Appendix 6.

On IŽS network, the main arterial routes are equipped with fully centralized electrical relay signalling & interlocking equipment, as follows:

- Belgrade Center-Niš-Preševo: Siemens SpDrS-64/JZ track circuit system,
- (Belgrade Center) Resnik-Vrbnica: Siemens SpDrS-64/JZ axle counter system,
- Stara Pazova Golubinci: Siemens SpDrS-64/JZ track circuit system,
- Golubinci-Ruma: Siemens SpDrS-64/JZ axle counter system,
- Ruma-Šid: Siemens SpDrS-64/JZ track circuit system,

In all stations on Belgrade Center – Stara Pazova – Novi Sad – Subotica line section, new electronic signalling and interlocking devices type "DS6-60" with "MMI" electronic control and monitoring system have been installed. Within the upgrade performed on trackside and station electronic signalling and interlocking devices, all service points on Belgrade Center – Stara Pazova – Novi Sad – Subotica line section have been included in the central traffic control and command system – remote control type "FZt – CTC".

The main arterial routes Šid- Golubinci – (Stara Pazova) – (Belgrade Center)-Niš-Preševo and Belgrade Center- Vrbnica are included in the system of remote traffic control and command – remote control centre (manufactured by Westinghouse). There are three remote control centres - in Belgrade, Požega and Niš. Based on this device, 3 remote control centres were set-up in Belgrade, Niš and Požega with the total of 133 controlled stations.

Dimitrovgrad Station (railway line Niš-Dimitrovgrad-State Border) is equipped with electronic signalling & interlocking device Simis-W with Iltis control & supervision system manufactured by Siemens.

In addition to the above-mentioned, Pančevo Main St. and Ćuprija stations are equipped with electronic signalling & interlocking devices.

Other railway lines are equipped with other above stated interlocking types, but there is no continuity as regards to one system of interlocking.

The overview of signalling and interlocking devices is presented in Appendix 3.6.



2.3.11 Traffic Control Systems

The movement of trains running in opposite directions and consecutive train movements are controlled by requesting and giving the permission i.e. announcement of arrival and departure.

Consecutive trains can follow one another only in particular space intervals. For the control of trains following one another in particular space intervals, railway lines can be divided into:

- Block sections between stations when two neighbouring stations control the sequence of trains in the station interspace,
- Train-recording sections when two neighbouring train-recording points or a station and a neighbouring train-recording point control the sequence of trains in announcement intervals,
- Block sections when the traffic of consecutive trains is controlled by automatic positioning of automatic block signals in the position of permitted or forbidden train ride.

In addition to space distance, in case of consecutive trains in train reporting and block intervals, there should be a time interval so as to avoid train stopping before automatic block signals due to different train journey times over block sections (time spacing).

On the railway lines of "Infrastructure of Serbian Railways" JSC there are also interstation interlocking devices (MZ) which regulate train traffic at distances between stations, where an interstation track occupation is reported by means of axle counters.

There can only be one train in one block section on the same track and at the same time.

Train operation is regulated by movements inspectors who uses the station signal boxes and along railway lines through remote control – by the remote control dispatcher from the central signal box, except at the stations that are not included in the remote control system. The traffic of trains running in opposite directions and consecutive trains is regulated by movements inspectors at manned stations and along the railway lines included in the remote control system it is regulated by remote control dispatchers.

"Infrastructure of Serbian Railways" JSC uses "Flexi code 560" remote control system on its territory, manufactured by Westinghouse. It uses semiconductor technology and a code system, and controls instruction completeness at the stages of forwarding and acceptance. It was developed as a standard format and it consists of a remote control centre, which can control 32 stations on one railway line and of one or more lines for data transfer, as well as the remote control equipment at stations (satellites).

Based on this device, 3 remote control centres were constructed in Belgrade, Nis and Pozega, with 140 controlled stations.

On Belgrade Center – Stara Pazova – Novi Sad – Subotica line section, all service points are included in the central traffic control and management system – remote control center type FZt-CTC.

The train control system is governed by the Traffic Regulations ("Official Gazette of RS" No 34/22 and 107/22) and Instructions on particular procedures in performing of traffic service on the territory of Infrastructure of Serbian Railways ("Official Gazette of Serbian Railways" No 43/22).

The train control methodology is presented in Appendix 6.

2.3.12 Communication Systems

In the course of traffic operations, communication is carried out via telecommunication devices – telephone and ground-train radio links. Communication via means that provide reliable and continuous registration of notifications (teleprinter, telephone or radio link with registration devices) is considered to be verifiable communication. The notifications related to the control of train movements (permissions and instructions given to train crew via telephone or ground-train radio links) are furnished exclusively via devices for verifiable communication.



The communication between movements inspectors, remote control centre dispatchers and drivers is carried out in Serbian language.

All notifications are given in the format and manner set forth in the Traffic Regulations ("Official Gazette of RS" No 34/22 and 107/22), Instructions on particular procedures in performing of traffic service on the territory of Infrastructure of Serbian Railways ("Official Gazette of Serbian Railways" No 43/22) and Regulation on records kept by the railway undertaking and the railway infrastructure manager ("Official Gazette of the RS" no.56/19, 154/20 and 159/20).

The overview of telecommunication links and installations is presented in Appendix 3.7.

IŽS network uses analogue ground-train radio system (RDV) for transmission of specially coded voice information in the frequency range of 460 MHz and by using frequencies belonging to quadrifrequency groups according to UIC Leaflet 751-3. The system operates in full duplex (modes A and B), with selective calling option including automatic identification and making special calls (group, intervention).

There is a possibility of integrating into local radio networks (mode C) and automatic telephone exchange. The devices were manufactured by AEG (now EADS telecom) in the '70s and the '90s.

On the lines with a dispatcher control system, the train operating staff is connected with the remote control centre dispatchers via mobile RDV units, which represent mandatory driver's cab equipment.

The GSM-R system enables voice communication and transmission of text messages within the ERTMS, i.e. for ETCS L2 and ETCS L3. The GSM-R system is installed on line section Belgrade Center – Stara Pazova–Novi Sad – Subotica.

2.3.13 Train Control Systems

For the time being, there is no automatic train control system on the railway lines of "Infrastructure of Serbian Railways" JSC.

Intermittent transmission AS device (automatic train control) with resonant frequencies of 1000Hz and 2000Hz, type Indusi (I 60), is used for the control of train movements. It is comprised of:

- track magnet (stationary trackside part of the device)
- transmission system (inductive link between the track magnet and locomotive auto-stop device), and
- locomotive part installed on the traction unit.

Track magnets are installed on the right-hand side of the track, in the direction of train movement.

Functioning and operating of AS devices have been stipulated under the Operator's Manual for inductive I-60 AS devices (Instructions No 425), Instructions for installation, testing and putting into operation and maintenance of the locomotive part of I-60 AS device (Instructions No 426), and Instructions for use, installation, testing and maintenance of trackside AS devices on the lines of Yugoslav Railways (Instructions No 427).

The overview of the lines equipped with AS device is presented in Appendix 3.6.

The ERTMS is the European Rail Traffic Management System. The ETCS is a part of ERTMS. On Belgrade Center – Stara Pazova – Novi Sad – Subotica line section the ETCS L2 is installed.

Functioning of the KMC (Key Management Center) system for the ETCS key management, enabling the railway carriers to use the GSM-R and ETCS, is prescribed in the *Instructions for creating the KMC keys for registering the new devices on the ETCS-2 system*. The instructions, in the format of Infrastructure Manager's act, is provided in Appendix 2.

In accordance with the instructions and aimed at using the GSM-R and ETCS, it is necessary for the railway carrier to submit a Request for issuance of encryption keys for communication in the ETCS system via the



Railway Infrastructure Access Department. The request is submitted in a prescribed format, in line with Appendix 3.6a.

2.4 Traffic Restrictions

2.4.1 Specialised Infrastructure

According to Article 40 of the Law on Railways ("Official Gazette of RS" No 41/18 and 62/23), if there are appropriate alternative routes, the Infrastructure Manager may, upon consulting interested parties, designate the specialised infrastructure for particular types of traffic.

In case that a specialized infrastructure is designated, the Infrastructure Manager may, when allocating the infrastructure capacity, give priority to such type of traffic, however prioritizing may not be in collision with the competition protection rules. Designating of specialized infrastructure will not exclude the use of such infrastructure for other types of traffic when capacities are available.

There is no specialised infrastructure on the network operated by IŽS in the above sense.

2.4.2 Environmental Restrictions

Environmental restrictions, such as noise levels, are not currently applied on the network managed by IŽS.

2.4.3 Dangerous Goods

The transport of dangerous goods on the railway infrastructure operated by IŽS is regulated by international and national regulations in the field of transport of dangerous goods in accordance with 3.4.4 - Dangerous Goods.

On the Niš – Dimitrovgrad – State Border – (Dragoman) railway line, the transport of tank wagons carrying ammonia is prohibited.

Locations for loading, unloading, transshipment of dangerous goods may be performed only in places that meet prescribed requirements. The stations (service points open to the acceptance and forwarding of goods) within the rail infrastructure do not meet this requirement, wherefore handling of dangerous goods in the station areas (service points) is not allowed.

Handling of certain types of dangerous goods () can be performed on special tracks under special conditions, i.e. on particular parts of the tracks in particular stations. The list of service points in which transshipment of dangerous goods can be performed is given in Appendix 3.8.

For further details, please contact IŽS:

"Infrastructure of Serbian Railways" Traffic Department Central Operational Department Main Dispatcher for Transport of Dangerous Goods 6 Nemanjina St 11000 Belgrade Serbia Tel.: +381 11 3619 288 e-mail: <u>rid1@srbrail.rs</u>.



2.4.4 Tunnel Restrictions

On the railway line Belgrade Centre –Pančevo Main St. - Vršac- State border, through the "Vračar" tunnel i.e. on the section junction Karađorđev park – junction and Pančevo Most stop and through the "connecting" ("vezni") tunnel i.e. on the route Karađorđev park junction - Dedinje junction, the trains with diesel traction vehicles, DMUs, diesel motor track vehicles, as well as vehicles with their own diesel generator set (power supply wagon, reefers with generator set station) cannot be regularly dispatched. Exceptions to this are DMUs series 711 and relief (auxiliary) trains with diesel traction of the infrastructure manager which are urgently dispatched to the accident/incident locations and diesel motor track vehicles used for urgent elimination of obstacles disrupting the traffic, while respecting the limitations that interval of sequence and the time between meeting of any two vehicles with diesel drive cannot be shorter than 30 minutes.

In other cases, the diesel motor vehicles of the infrastructure manager can run on the specified sections when the transport of trains for transport of passengers is not organized in the service point Vukov spomenik.

Along with the obligation to respect the restrictions regarding the vehicle drive, for the transport of freight trains containing wagons with a RID marking (loaded or empty vehicles for transport of dangerous goods), the following conditions apply:

- on the part of railway line Pančevo Most–Rakovica and Pančevo Most Belgrade Centre, trains can operate only in the period when traffic of passenger trains is not organized i.e. when the station is closed for passenger transport,
- on the part of railway line Pančevo Most –Rakovica and Pančevo Most Belgrade Centre, there can be only one train with RID marked wagons i.e. meeting of two freight trains if at least one is composed of RID marked wagons is not permitted;
- during the operation of trains composed of RID marked wagons, an additional technical inspection must be carried out, which includes checking of bearing temperature and enhanced visual control of loads (valve, clamps etc.)for the train which operaters in direction Pančevo Most – Rakovica and Pančevo Most – Belgrade Centre in Pančevo Main St., and for the trains operating in direction Rakovica –Pančevo Most either in Rakovica station or in Belgrade Marshalling Yard (if it is performed in Belgrade Marshalling Yard, there is no need for the inspection to be performed in Rakovica station);
- obligation of railway undertaking upon performed additional technical inspection of a train in stations Pančevo Main St., Rakovica and Belgrade Marshalling Yard, is to register a clause in the telegraph-telephone log "The additional technical inspection of train No ______ was performed on date ______ hours (signature of authorized representative of railway undertaking)", thereby to inform the train dispatcher in a proved way that technical inspection of train was completed before dispatching it on the part of railway line Pančevo Most-Rakovica. In the event that railway undertaking does not have an organized inspection service in stations Pančevo Main St., Rakovica and Belgrade Marshalling Yard, and that technical inspection of trains composed of loaded or empty RID marked wagons has not been performed, such train cannot operate on the part of railway line Pančevo Most-Rakovica.

Freight trains, which have loaded or empty RID marked wagons, must in no case operate in the direction Belgrade Center - Pančevo Most.

2.4.5 Bridge Restrictions

There are no bridge restrictions in terms of specifically defined requirements apart from those arising from the bridge structural parameters. Exceptionally, until the construction of the fifth longitudinal bridge girder into the construction of "Pančevo Most" across Danube river, on the railway line Belgrade Centre – Pančevo Main St. – Vršac – State Border, between location on junction Pančevo Most—Krnjača Most all assemblies of two freight trains are prohibited on "Pančevo Most".



2.4.6 Maximum Train Weight Restrictions

The maximum train weight for the trains running on the Niš – Dimitrovgrad – State Border – (Dragoman) is restricted to 1200 tonnes.

2.4.7 Train Traction Restrictions

On the Stara Pazova – Novi Sad – Subotica line section, trains with diesel traction must not be dispatched. The exception from this rule are the trains of railway undertakings performing construction, reconstruction or maintenance of railway infrastructure. In case of trains that, in addition to the train locomotive, also contain the additional work locomotives, i.e. double heading locomotives, such locomotives must run within the train composition along the entire Batajnica – Novi Sad – Subotica line section. Inclusion i.e. removal of the double heading locomotive from the train composition is allowed only in Novi Sad Marshalling Yard, if planned according to the Timetable documents.

2.4.8 Train Speed Restrictions

On the Batajnica – Stara Pazova – Novi Sad – Subotica line section, the speed of freight trains is 90 km/h. The exception from this rule are the trains of railway undertakings performing construction, reconstruction or maintenance of railway infrastructure. Trains operating between Batajnica and Stara Pazova, on the routes to/from Šid, do not have this speed restriction.

2.5 Availability of the Infrastructure

All railway lines operated by IŽS are open to railway traffic from 0.00 h to 24.00, except for the lines on which the traffic due to technical condition is temporary impossible/ or with the Decision of the Government of the Republic of Serbia the consent for the suspension of public transport of passengers and goods on the part on the railway infrastructure was given ("Official Gazette of the RS"no.80/2016), and they are listed in Appendix 6. Service points are open for railway traffic permanently, as some of them may have limited operating hours envisaged for the effective staff of the traffic service, as stated in Appendix 6. Details about mentioned working time are published in the timetable material, and for more datils please contact:

"Infrastructure of Serbian Railways"JSC Traffic Department 6 Nemanjina Street, 11 000 Belgrade, Serbia Tel/Fax: +381 11 3618 214 E mail: sektor.sp@infrazs.

Exceptionally, on the railway lines with limited hours of operation where mentioned staff is working in limited operating hours, train operations can take place outside the mentioned hours when trains have to operate via auxiliary routes due to the occurrence of an accident or incident. Appendix 3.9 contains an overview of auxiliary routes that may be used as alternative to regular ones. Certain lines that may be used as auxiliary routes can be of different class from the line class along the regular routes with respect to permitted loads per axle or m'.

A railway operator may also submit a request for train path allocation outside the operating hours of the line or railway service points, in which case such railway operator has to bear all the costs of entire traffic organization for longer operating hours of the line, i.e. service points.

If several railway operators are using longer operating hours, they will jointly bear the costs.

Infrastructure Manager is responsible for maintenance, overhaul and modernization of the infrastructure in order to provide appropriate service and safe performance of transport operations. In this respect, IŽS plans regular maintenance of the lines that affect the availability of infrastructure, in the sense of closure of specific line sections for a specific time period or introduction of temporary train speed restrictions.



The infrastructure use restrictions required for regular infrastructure maintenance are part of the capacity allocation process and are published within the timetable documents, in the timetable booklets (KRVs).

IŽS will issue for all railway operators a 3-months' prior notice of any planned longer works to be performed on the railway infrastructure and which could affect the transport operations and the timetable due to the speed restrictions, route changes, use of buses instead of trains for the carriage of passengers, etc.

For all freight trains running in the South-North and transit the part of railway infrastructure between station Velika Plana and node Belgrade, regular routing is across the railway line (Belgrade)-Rakovica-Jajinci-M. Krsna-V. Plana and the compiling of paths in done in this way. Exceptionally this rule cannot be applied during the planned works on reconstruction of above-mentioned railway line.

For all freight trains running in the south-north and transit the part of railway infrastructure between node Belgrade and station Velika Plana, regularly routing is across the railway line (Belgrade)-Resnik-Mladenovac-V. Plana and the compiling of paths in done in this way.

The railway lines on the territory of Kosovo and Metohija are under interim supervision of UNMIK, according to the Temporary Agreement between ZTP Beograd and UNMIK Railways of 31/05/2002 (ref. number 300/2002 - 153 of 31/05/2002), wherefore the path allocation requests for this territory will not be taken into consideration.

2.6 Infrastructure Development

Railway infrastructure, which is managed by IŽS, is constantly being renewed and modernized, in order to enable to the users the best possible service quality.

Development projects of the infrastructure are defined within Strategic plan of IŽS (Decision of the Assembly of Joint stock company for public railway infrastructure management "Infrastructure of Serbian Railways" JSC, Belgrade no. 5/2017-116-49 from June 29, 2017)", which is prepared on the base of the National program of the infrastructure ("The Official Gazette of RS", no. 53/17). Development of the railway infrastructure is directed towards the modernization of the lines which are part of the Pan-European corridor.

Possibility of the realization of the planned works depend upon the amount of the financial means, which are provided from the state budget of the Republic of Serbia and from the amount provided from the other sources of financing.

Appendix 3.11. contains a list of development projects.



3. ACCESS CONDITIONS

3.1 Introduction

This chapter of the Network Statement describes the conditions associated with access to the railway infrastructure managed by the IŽS. These conditions also apply to the part of freight corridors passing through the railway infrastructure managed by the IŽS.

3.2 General Access Requirements

A railway undertaking can provide transport services on IŽS railway infrastructure based on:

- valid license for carriage in railway transport over the infrastructure, issued by Directorate for Railways (hereinafter: DR),
- valid certificate on safety for carriage in railway transport,
- allocated capacity path and contract on provision of access to and use of public railway infrastructure concluded with the infrastructure manager.

Requirements for the submission of application for license, safety certificate and thereof contents are stipulated in the Law on Railways ("Official Gazette of RS" No 41/18 and 62/23), Law on Safety in Railway Traffic ("Official Gazette of RS" No 41/18), Rules on transport licenses in railway traffic ("Official Gazette of RS" No 53/19), Rules on joint safety methods for evaluation of compliance with the requirements for obtaining of safety certificates and safety management system elements ("Official Gazette of RS" No 32/21) and Rules on transport safety certificate forms ("Official Gazette of RS" No 63/19).

3.2.1 Conditions for Applying for Capacity

Request for train path allocation can be submitted by a railway undertaking or an international group of railway undertakings or other persons or legal entities, such as competent authorities, consignors and forwarding agents and operators in combined transport, having interest in provision of public service or having commercial interest in the allocation of railway infrastructure capacity.

Where a train path is allocated to an applicant other than a railway undertaking, the contract on the use of railway infrastructure shall be concluded between the infrastructure manager and the railway undertaking hired by such applicant.

If a request has been submitted after a specified deadline, train path in accordance with remaining capacities will be offered to the applicant, and if there are no capacity constraints, a new path will be subsequently created.

3.2.2 Conditions for Access to the Railway Infrastructure

Services of carriage in railway transport may be provided by a company, other legal entity or entrepreneur registered for provision of public transport services or transport for own purposes, incorporated in the Republic of Serbia, subject to the submission of evidence of fulfilment of the conditions related to good reputation, financial capability, and competence, and the cover for civil liability.

The license for carriage in railway transport and the certificate on safety is issued by DR or a competent authority of another country, based on reciprocity, with which country Serbia has signed an intergovernmental agreement on mutual recognition of certification.

Transport on railway infrastructure may be performed by railway undertakings meeting the requirements referred to in paragraph 1 hereof, who signed the Contract for use of public railway infrastructure. The Contract for use of public railway infrastructure regulates the mutual rights and obligations between the infrastructure manager and railway undertakings and they are concluded in line with article 19 of the Law on Railways.



3.2.3 Licenses

Directorate for railways issue transport license: for transport of goods/passengers and for transport for own purposes.

Transport License is issued to applicant, company, other legal entity whose main registered activity is for provision of railway transport of good and/or passengers, or to a company or other legal entity who performs or will perform transport for own purposes, incorporated in the Republic of Serbia, subject to the submission of evidence of fulfilment of the conditions related to:

- a) good reputation,
- b) financial capability,
- c) proficiency and
- d) cover for civil liability in line with the Law on Railways.

Details related to licensing of railway undertakings are set from article 81.to article 85. of the Law on Railways.

Contact of competent institution for issuance of license is:

Directorate for Railways 6 Nemanina St., 11000 Belgrade The Republic of Serbia Manager's Office tel. (011) 361 68 66 fax (011) 361 83 46 e-mail: kontakt@raildir.gov.rs

web page: www.raildir.gov.rs

3.2.4 Safety Certificate

The railway undertaking must have safety certificate for transport to be allowed to access infrastructure. The type and scope of operations of railway undertaking related to certificate are specified in the safety certificate.

The safety certificate may include the entire network or certain part thereof.

Safety certificate is consisting of:

1) part A confirming the acceptance of railway security management system of railway undertaking;

2) part B confirming the acceptance of provisions adopted by railway undertaking in order to meet the specific requirement set for transport safety on appropriate network; these requirement may include the application of technical specification, the national safety regulation and internal regulation of railway undertaking, the acceptance of employee's certificates and permissions for usage of rolling stock used by that railway undertaking.

Directorate for Railways is responsible for issuance of safety certificate for transport in set form and in the form of decision. The decision to issue or to refuse to issue safety certificate for transport is ultimately in the administrative procedure and a dispute can be brought against it at Administrative Court.

The validity period of the safety certificate for transport is five years and can be renewed at the request of the holder.

Directorate for Railways determine in more detail forms of safety certificate for transport, numbering of forms of safety certificate for transport in line with European identification number, the application form for



issuance of safety certificate for transport and instructions for its completion, as well as necessary documentation enclosed with the request for issuance of safety certificate for transport.

Provisions regarding safety certificate for transport are set in Law on Railway Transport Safety.

Contact of competent institution for issuing safety certificate is:

Directorate for Railways 6 Nemanjina St., 11000 Belgrade The Republic of Serbian Manager's Office tel. (011) 361 68 66 fax (011) 361 83 46 e-mail: kontakt@raildir.gov.rs

web page: www.raildir.gov.rs

3.2.5 Coverage for Civil Liability (Insurance)

One of the conditions for issuing a transport license is the fulfillment of the requirements related to civil liability coverage (Insurance).

The requirement relating to civil liability coverage for a company or other legal entity that is registered for the public transport of goods and / or passengers, or performs or will carry out transport for its own purposes, is fulfilled if it is adequately insured or has adequate guarantees under market conditions for coverage, in accordance with legal requirements and confirmed international treaties, for their liability in the event of an accident.

Civil liability coverage may not be required to take effect before the railway undertaking starts operating the service.

3.3 Contractual Arrangements

3.3.1 Framework Agreement

The Infrastructure Manager and an applicant may, by way of exception, draw up a framework agreement on the use of capacity on the relevant railway infrastructure for a period longer than the period of validity of the timetable.

The Framework Agreement between the infrastructure manager and the applicant shall contain the characteristics of the infrastructure capacity for which the applicant applied and which he was offered for a time period exceeding the period of validity of one timetable.

The Regulation on the Manner of Conclusion and Content of Framework Agreements for Allocation of Railway Infrastructure Capacity lays down the procedures, content and criteria relating to the framework agreements for the allocation of railway infrastructure capacity, as well as the obligations of the infrastructure manager regarding information regarding the framework capacity.

At present, the infrastructure manager does not offer the possibility of concluding a framework agreement with the applicant. However, it intensively conducts the activities aimed at defining the procedures so as to have this option open in the near future.

3.3.2 Contracts with RUs

The Law on Railway of the Republic of Serbia stipulates the obligation of concluding a contract on the use of infrastructure that allows railway undertakings to use railway infrastructure. Contracts for use of public



railway infrastructure regulate in more detail the mutual rights and obligations of infrastructure managers and railway undertakings related to guaranteeing the technical and other conditions for safe transport operation, the application of regulations governing the transport of dangerous goods, as well as payment of access charges and charges of services. Contracts for use of public railway infrastructure are concluded under non-discriminatory and transparent conditions.

Contracts on the use of infrastructure are concluded no later than 1 (one) month prior new timetable enter into force or immediately after the allocation of ad hoc train path.

If during the validity period of Contract for use of public railway infrastructure, the railway undertaking through an authorized person submit ad hoc request in approved way for allocation of train path, it is considered that addendum of that contract is concluded at the moment of allocation of requested train path by infrastructure manager.

For other services (basic, additional and accompanying) provided by infrastructure manager special contracts are concluded.

3.4 Specific Access Requirements

3.4.1 Rolling Stock Acceptance

Railway undertaking may use only the rolling stock that complies with the technical regulations and standards. Rolling stock shall, by virtue of their structure and technical condition, ensure safety of transport on the infrastructure, safety of transported persons and goods, safety of staff, and shall meet the health and environment protection requirements.

All requirements relating to rolling stock and thereof use on the railway infrastructure of IŽS are set forth in the Law on Railway Safety and Interoperability ("Official Gazette of the RS", no. 41/18) and Law on Railway Traffic Safety ("Official Gazette of the RS",no.41/18).Railway undertaking shall be responsible for the technical condition, maintenance and operation of the rolling stock.

3.4.2 Staff Acceptance

Railway undertaking shall be responsible for ensuring that his staff meets the requirements stipulated by the Law on Railway Safety ("Official Gazette of the RS", No. 41/8) and applicable by-laws.

The railway undertaking's train manning shall be familiar with the official language in the Republic of Serbia.

Railway undertaking shall be responsible for staff training, validity of periodical knowledge tests, knowledge of track condition and local conditions at stations/stops. Railway undertaking is obliged in that respect to abide by the applicable legislation of the Republic of Serbia.

3.4.3 Exceptional Transport

A load shall be considered special if due to its external dimensions, weight or properties, and with respect to the station installations or wagons in transport by one of the railways participating in transport, it causes particular difficulties, wherefore it is received for transport only under special technical or operating conditions. Carriage of special loads in domestic and international railway transport, as well as the conditions under which such carriage may take place, shall be approved by the Infrastructure Manager whose railway infrastructure will be used for transport. IŽS provides the special loads service (for vehicles or goods) in accordance with the provisions on transport of special loads set forth in the Rules on Transport of Special Loads ("Official Gazette of the RS", no. 6/17).

IŽS shall be responsible for the allocation of capacity and defining the conditions for transport of special loads.



In addition to what was stated above, the railway undertaking in international transport shall comply with the provisions of UIC 502.1 and 502.2, governing the process of approval of requests for transport of special loads. The railway undertaking shall submit a request for transport of loads to the relevant department of IŽS. Special loads will be accepted for transport only if special operating and technical conditions are met. For more details on transport of special loads please refer to Chapters 4 and 5 of this Network Statement.

For more details on transport of special loads please contact:

Infrastructure of Serbian Railways"JSC Traffic Department 6 Nemanjina Street 11000 Belgrade Serbia Tel.: +381 11 3618 214 Fax: +381 11 36<u>16 814</u> <u>sektor.sp@</u>srbrail.rs

3.4.4 Transport of Dangerous Goods

Transport of dangerous goods by rail in the Republic of Serbia shall be performed in accordance with: Annex C to Convention concerning international carriage by rail (–COTIF) - Regulations governing the international carriage of dangerous goods by rail (RID); the Law on the Transport of Dangerous Goods; the by-laws based on LTDG and other regulations in the Republic of Serbia.

The Ministry of Construction, Transport and Infrastructure is responsible for performance of administrative, inspection, technical and other expert activities in the field of transport of dangerous goods in the Republic of Serbia(www.utot.gov.rs).



4. CAPACITY ALLOCATION

4.1 Introduction

Pursuant to the Law on Railways and Decision of the Government of the Republic of Serbia on incorporation of Joint Stock Company for Public Railway Infrastructure Management and the Company's Articles of Incorporation, "Infrastructure of Serbian Railways" JSC performs the activities of public railway infrastructure management and is responsible for allocation of infrastructure capacities for the purposes of international and domestic transport in a transparent and non-discriminatory manner, provided that all legal provisions on the conditions for access and use of railway infrastructure set out in Chapter 3 of this Network Statement have been previously fulfilled.

4.2. Description of infrastructure capacity allocation procedure

The Infrastructure Manager normally allocates the train paths once a year, upon reconciling the train path allocation requests in the timetabling process, not exceeding the Timetable validity period.

Allocation of infrastructure capacities in the form of a train path is carried out in accordance with the procedures specified in this document for:

- infrastructure capacities allocation procedure for the new Timetable,
- infrastructure capacities allocation procedure during Timetable validity period (including train path allocation on ad hoc request).

A Railway Undertaking may not assign the allocated train path to another Railway Undertaking. Train path trading is prohibited. Train path user will pay a charge for the use of railway infrastructure and for railway traffic organization and control.

The Government of the Republic of Serbia sets out the Methodology for valuation of elements for determining the charges for the use of railway infrastructure. The Decree on methodology for valuation of elements for determining the charges for the use of railway infrastructure is published in the "Official Gazette" of RS" No 122/14. For additional services, a train path user will pay a charge in accordance with the Infrastructure Manager's formal decision.

How to apply?

Request for infrastructure capacity allocation can be submitted by railway undertakings using the train path request form, which is available in Appendix 4.1, and published on IŽS website: www.infrazs.rs.

When submitting the request, the RU is obliged to submit the following technical data for each traction vehicle series: series, description (axle layout), length (mm), weight (t), maximum speed (Vmax), inertia factor, resistance formula (coefficients a, b and c), traction diagram and braking diagram (tabular and graph presentation), traction type (diesel or electric), as per template provided in Appendix 4.1.b. The requested data are input data for capacity allocation, i.e. for software based timetabling. The data are submitted once for each traction vehicle as well as in case of change of data. If within the same series there are traction vehicles with different technical properties ("subseries") the data need to be provided for each "subseries".

Requests are submitted according to procedures defined under section 4.5.

The request should contain the following data:

- Full registered name of the Railway Undertaking (TIN, company identification number),
- Train type (for passenger transport, freight, empty, locomotive, and similar),
- The desired time of train departure from the departure station and the time of train arrival to the terminal station,
- Traffic route and transport route,



- Necessary stops with minimum lengths of delays,
- Traffic period and days (traffic calendar),
- Series and number of wagons/series and number of train units,
- Train length and mass (length in meters, mass in tons),
- Type and serial number of the traction vehicle (traction passport),
- Additional locomotives (type and serial number) and on which section,
- Maximum train speed,
- Braking type,
- Special notes, such as vehicle shunting, change in train composition, implementation of connections, crew change, type of intermodal transport unit, type of dangerous goods (UN number, number for marking of danger or, for Class 1 dangerous goods, the subclass and compatibility group for substances and items, *NHM* code with minimum 6 digits and the name of dangerous goods based on *RID*), exceptional consignments, handover procedures on border crossings, technical hold ups (inspection, water supply, removing of waste and similar) and the required time period, the need for additional track capacities (storing, preheating/cooling, train formation and similar), the need for access to other facilities for provision of additional services and similar.

Upon the request of IŽS, a Railway Undertaking will be required to provide all the missing data within five working days, otherwise the request for capacity allocation will not be considered as submitted.

A request for capacity allocation submitted to IŽS on time and containing all the necessary elements makes a basis for timetabling and train path allocation. If a Railway Undertaking changes the request completely or partially after the determined deadlines for request submission it assumes the risk of not having the request granted.

After the annual timetable drafting process has been completed, the remaining available capacities will be allocated according to the deadlines defined in Appendix 4.3 according to the sequence of request submission.

Manner of capacity allocation

IŽS decides on capacity allocation taking into account all legally valid requests and legal provisions in force. In accordance with the Law on Railways, the procedures and deadlines in capacity allocation have been determined under point 4.5 of the present Network Statement.

Defining of procedures and deadlines in capacity allocation is harmonized with Directive 2012/34/EU and its appendices, as well as the RNE recommendations from "Procedures for International Path Requests".

Relevant bodies involved in the capacity allocation process and their responsibility

Bodies participating in capacity allocation process:

- IŽS "Infrastructure of Serbian Railways" JSC as Infrastructure Manager and capacity allocation body
- Railway Undertakings railway undertakings submitting capacity allocation requests
- RNE RailNetEurope body coordinating the allocation of international train paths and determining processes and deadlines for submission of international train path requests
- FTE ForumTrainEurope European organization of railway undertakings representing the European Forum for technical planning of international passenger and freight transport.

IŽS, as Infrastructure Manager and capacity allocation body, is a member of RNE and is actively involved in the activities of FTE.



4.3 Allocation of capacity for maintenance, including the allocation process

Allocation of infrastructure capacities for maintenance, renewal and modernization of railway infrastructure is an integral part of capacity allocation process. Aiming at maintaining a certain level of quality, safety and reliability of railway infrastructure, $I\check{Z}S$ – Department for access to railway infrastructure will, during the timetabling process, reserve a part of infrastructure capacities for scheduled railway infrastructure maintenance, for specific time periods and specific line sections.

Periods reserved for scheduled railway infrastructure maintenance are published in the Timetable Booklet.

4.4. Impact of Framework Agreements

"Infrastructure of Serbian Railways" is currently not concluding framework agreements with interested applicants for allocation of infrastructure capacities.

4.5 Schedule for Path Requests and Allocation Process

Each year IŽS prepares a schedule for path request submission and capacity allocation which is applied in the annual timetabling process and in the capacity allocation process outside the annual timetabling process published in the Network Statement.

Railway Undertakings allocation requests for the new Timetable and during Timetable validity period should be submitted in the form defined in Appendix 4.1, to the following address:

By mail, to the following address: "Infrastructure of Serbian Railways" JSC Department for access to railway infrastructure 6, Nemanjina St 11000 Belgrade, Serbia By e-mail: <u>sektor.pzi@srbrail.rs</u>

4.5.1 Schedule of requests submission for new annual timetabling process

The Applicant submits a request for capacity allocation not earlier than 12 months and not later than 10 months before the new Timetable enters into force. Deadlines for requests submission regarding Timetable 2024/2025 which enters into force on December 15th,2024 with validity until December 13th 2025 are presented in Appendix 4.3.

For the needs of Railway Undertakings wishing to use additional capacities or to change parametres of already allocated train paths, the new capacity allocation during Timetable validity period is enabled by:

- Regular amendments of and supplements to the Timetable
- Special amendments of and supplements to the Timetable
- Train path allocation on ad hoc request

In the form defined by Articles 4.5.2 and 4.5.3 in this Network Statement.

4.5.2 Schedule of requests submission for train path allocation during annual Timetable validity period through regular and special amendments of and supplements to the Timetable

During the Timetable validity period, there are regular amendments of and supplements to the Timetable 5 times a year, in accordance with internationally determined terms which are presented in Appendix 4.4. Deadlines for submission of requests for capacity allocation are presented in the column 1, Appendix 4.4.

Requests for regular amendments of and supplements to the Timetable that are submitted after deadlines specified in the column 1, Appendix 4.4, will be considered as special requests and shall be included in



regular amendments of and supplements to only in case of existence of available infrastructure capacities and technical possibilities for their processing.

After the 5th regular amendments of and supplements to the 2024/2025 Timetable enter into force it will be only possible to submit ad hoc requests for capacity allocation.

Besides regular amendments of and supplements to the Timetable in accordance to the terms specified in the column 3, Appendix 4.4, Railway Undertakings may submit special request for infrastructure capacity allocation outside specified terms. If there is possibility for allocation of the requested capacities, consequent changes in the Timetable shall be considered as special amendments of and supplements to the Timetable.

4.5.3 Allocation of capacities during annual Timetable validity period on ad hoc request

Ad hoc requests for infrastructure capacity allocation are requests for allocation of single train path, which are submitted during annual Timetable validity period.

Infrastructure Manager is obliged to respond to ad hoc requests as soon as possible and not later than five working days upon receiving the request.

4.5.4 Path Allocation and Coordination Process

IŽS will allocate the infrastructure capacity if the applicant fulfils the conditions for capacity allocation set out in the Network Statement and if the infrastructure capacity allows such allocation. IŽS will act in such a manner so as not to favour any applicant.

The following criteria will be applied in the path allocation process:

- Volume of service;
- Utilization of railway infrastructure;
- Volume of additional services provided by the IM in connection with the transport provided on the path;
- Business reputation;
- Public service obligation; and
- Quality of performed transport service in the previous period.

After the final deadline for submission of requests for the annual timetabling has expired, IŽS will initiate the capacity allocation process in a transparent and non-discriminatory manner.

Requests for capacity allocation received after the annual timetable drafting cannot affect draft alteration, except with the consent of the Railway Undertaking to whom the capacity has been originally allocated.

Allocated capacity can be used upon conclusion of Access Contract between IŽS and the Railway Undertaking submitting a request for capacity allocation.

Allocated capacity cannot be transferred onto another Railway Undertaking in accordance with the Law on Railways.

Coordination process

Every year at the beginning of the new annual timetabling process, IZS will conduct consultations with railway undertakings on their plans for the timetable which will come into force in not less than 11 months (x-11). In the course of these consultations, IZS will inform railway undertakings on major maintenance works, overhaul and modernization of railway infrastructure.

The coordination process is run by IŽS – Department for access to railway infrastructure, which is preparing and publishing the annual Timetable and preparing of all required working materials.



Upon the expiry of the final deadline for submission of requests for capacity allocation for the annual Timetable, IZS – Department for access to railway infrastructure will start the coordination process, together with railway undertakings for the purposes of solving conflicting requests and their better harmonization, aiming to fulfil the needs of users as much as possible in a non-discriminatory and transparent way.

Timetable planning includes reviewing all received requests, including all restrictions imposed by IŽS and the scheduled infrastructure maintenance plans.

If the number of requests for allocation of the same infrastructure capacity exceeds the permitted capacity of the particular railway line, IŽS apply priority rules from 4.6.

Following the completion of the coordination procedure, IŽS will deliver the draft timetable to railway undertakings. Together with railway undertakings IŽS will perform the final consultations concerning the draft timetable. Railway undertakings must state, in written form, whether they accept, partially or completely, that is, do not accept, the Timetable.

Deadline for making the statement is one month from the day of the draft submission, at the latest.

After the expiry of the deadline for making the statement, IŽS will define the Timetable according to the requests submitted on time and it will be deemed that the train paths have been allocated.

IŽS will subsequently allocate the remaining available capacities according to requests received after the final deadline, in the order of their receipt.

4.5.5 Dispute Resolution Process

IŽS will initiate the dispute resolution process upon delivery of written complaints by railway undertakings, relating to complete or partial acceptance/non-acceptance of the proposed Timetable.

Complaints are to be addressed to IŽS:

By mail, to the following address:
"Infrastructure of Serbian Railways" JSC
Department for access to railway infrastructure
6, Nemanjina St
11000 Belgrade, Serbia
By e<u>-mail: sektor.pzi@</u>srbrail.rs

IŽS will evaluate all complaints and objections and conduct consultations with railway undertakings aiming to fulfil their requests.

If a mutual solution is not found, IŽS will determine the capacity and inform the railway undertakings of this. If after the request coordination it is still not possible to satisfy all the requests for capacity allocation, IŽS will be obliged to announce that the said line section is congested.

Railway undertakings can appeal to the Directorate for Railways with respect to IŽS decision.

A potential appeal of a Railway Undertaking cannot be the reason to delay the process of Timetable adoption and coming into force.

4.6 Congested Infrastructure

If in the coordination process IŽS is unable to adequately satisfy all railway undertaking requests due to capacity limitations, IŽS will declare the requested infrastructure capacity to be "congested".



In cases when IŽS declares infrastructure "congested", it will conduct an analysis of capacities on congested infrastructure and define limitations due to which it was not possible to satisfy capacity allocation requests as well as propose a plan to enhance the particular capacity.

Infrastructure capacity will not be considered congested if the infrastructure capacity cannot be allocated due to the execution of works on the infrastructure maintenance, modernization, construction and reconstruction.

If the number of requests for allocation of the same infrastructure capacity exceeds the permitted capacity of a specific railway line, and if congested infrastructure is declared regarding that line, i.e. the part of that line, IŽS will, in an effort to allocate the train paths, apply priority rules according to the following order:

- 1) passenger trains in international traffic
- 2) passenger trains in domestic traffic
- 3) international freight trains
- 4) other freight trains

Considering the above mentioned priorities, the train path allocation process will be carried out according to the following rules:

- Requests for train paths of regular trains have the priority over the requests for train paths of special trains and trains transporting exceptional consignments;
- Requests for train paths according to framework agreements have the priority over new requests;
- Requests for train paths for a longer time period of service have the priority over requests for train paths for a shorter time period;
- Requests for train paths for a longer route have the priority over train paths for a shorter route.

If a Railway Undertaking considers that its rights were withheld, it can appeal to the Directorate for Railways.

4.7. Exceptional Transports and Dangerous Goods

Exceptional Transports

Transport of exceptional consignments is transport in the course of which there is a deviation from at least one technical standard applied on the given infrastructure, such as for example, axle load, railway vehicle gauge, loading gauge and similar. Taking into account all the elements required for the transport of an exceptional consignment, IŽS will decide whether the requested infrastructure capacity will be allocated and under what conditions.

Deadline for submission of request for transport of exceptional consignments is not later than 20 days in domestic and 30 days in international traffic prior to service provision. Decision on the request for transport of exceptional consignments shall be made as soon as possible and not later than 15 days upon submission of the request.

Detailed information can be obtained at the below address. Deadline for capacity allocation will be as soon as possible. IŽS will decide whether it is possible to accept a certain transport and under which conditions.

Requests are submitted to:

"Infrastructure of Serbian Railways" JSC Traffic Department 6, Nemanjina St 11000 Belgrade, Serbia Tel.: +381 11 3618 214 Fax: +381 11 3616 814 E-mail: sektor.sp@srbrail.rs



In their request for capacity allocation, railway undertakings are required to list all the necessary information on the exceptional consignment which is being transported, regardless of whether it is a capacity allocation process for the annual Timetable or an ad hoc capacity allocation.

Dangerous Goods Transport

Dangerous goods transport on railway infrastructure operated by IŽS is regulated by international and national regulations in the field of dangerous goods transport, in accordance with point 3.4.4 of the Network Statement.

Based on clauses 1.4.2.2.5 and 1.4.3.6 of *RID* and Article 23, para 4, item 2) and Article 29 para 2 of the Law on Transport of Dangerous Goods, a Railway Undertaking is obliged to report every consignment of dangerous goods to railway Infrastructure Manager.

Reporting of dangerous goods transport can be done by phone: +381 11 3618 288 and in writing to the below address. The below address can be also used for more detailed information:

"Infrastructure of Serbian Railways" JSC 6, Nemanjina St, 11000 Belgrade Central Operations Unit Main dispatcher for dangerous goods transport Tel.: +381 11 3618 288 E-mail: <u>rid1@srbrail.rs</u>; <u>glavni.riddisp@srbrail.rs</u>

For the purposes of safe transport of dangerous goods on IŽS network, a Railway Undertaking is obliged to:

- Report each transport of dangerous goods consignment in real time i.e. immediately before the commencement of transport or at acceptance from the successive carrier.
- Report completion of transport of dangerous goods consignment in real time i.e. at the moment of completion of transport after the completed handover of consignment to the consignee at the destination station or upon handover of consignment to successive carrier.

Railway Undertakings are responsible for obtaining appropriate consents regarding the safety of dangerous goods transport.

Pursuant to clauses 1.4.2.3.1 of *RID* and Article 24 para 2 item 1) of the Law on Transport of Dangerous Goods, the consignee of dangerous goods in railway transport is obliged not to postpone the acceptance of dangerous goods consignment which is resulting in the railway undertaking's obligation not to postpone the handover of dangerous goods consignment after having performed the transport service.

Railway Undertaking is obliged to, after having accepted the dangerous goods consignment for transport at the forwarding station, immediately start the process of transporting the said consignment without any additional delays at the station, except for traffic reasons, accident or incident etc. Phased collecting of wagons loaded with dangerous goods (and non-cleaned empty wagons which were previously loaded with dangerous goods) in the forwarding station for the purposes of subsequent dispatching is prohibited due to the safety in transport of dangerous goods. The process of transport of dangerous goods (acceptance of consignment for transport from the consignor, dispatching, transport and handover of consignment to the consignee) must be performed in accordance with the technologically specified time in order to avoid the potential safety risks in transport.

After the customs clearing of consignment, it is exceptionally permitted for the consignment to remain on station sidings but only for a time period which is necessary to organize the dispatching and continuing of planned transport route, or handover to the consignee in accordance with the specified technological process for station operation i.e. Station Regulations, Part II.



Obligation to announce the transport of dangerous goods Class 1 and Class 7

Exceptionally in transport of dangerous goods Class 1 and Class 7, a Railway Undertaking is obliged to submit to the Infrastructure Manager, in writing (Central Operational Unit – Main dispatcher for transport of dangerous goods) an announcement for the said transport in the time period which is not less than 24 hours prior to the moment of acceptance for transport (entry onto IŽS network). Railway Undertaking may send the announcement of transport also in the form of an email with scanned documents to the following address: rid1@srbrail.rs.

The announcement should contain the following data and attachments:

- 1. Consignor
- 2. Forwarding station and country
- 3. Consignee
- 4. Destination station and country
- 5. Entry border station
- 6. Exit border station
- 7. Net quantity of dangerous goods and wagon number in the train loaded with dangerous goods
- 8. Name of goods (official name of the goods)
- 9. UN number, number for marking of danger (all, if there are several)
- 10. Data on persons hired according to the Decision of the Ministry of the Interior of the Republic of Serbia in the capacity of armed company (first and last name, ID document number, etc., from the Decision issued by the Ministry of the Interior of RS)
- 11. Buffer wagon
- 12. Number of the decision on transport and name of issuing state authority.

The announcement should also contain two appendices:

- Photocopy of the Decision on transport issued by a relevant state authority, and
- For Class 1 dangerous goods: Instructions on special safety measures (MSDS lists) from the manufacturer of Class 1 dangerous goods;
- For Class 7: instructions on measures that the Railway Undertaking should take in transport, restrictions and required data on planned transport route as well as measures in case of danger that are adequate in relation to the consignment in accordance with RID 5.4.1.2.5.2.

Permit for transport of Class 1 dangerous goods is issued by the ministry responsible for the interior affairs, and permit for transport of Class 7 dangerous goods is issued by the authority responsible for protection against ionizing radiation and nuclear safety in the Republic of Serbia (Article 7 of the Law on Transport of Dangerous Goods). The announcement of transport should also contain the basic data on the Railway Undertaking and the transport organizer if case of irregularities or emergency events in transport of dangerous goods. In terms of data it is mandatory to specify the first name, last name and mobile phone number of the person (employed with the Railway Undertaking and/or transport organizer) who is always available during the transport.

4.8 Rules After Path Allocation

4.8.1 Non-usage of allocated train path

In cases when a Railway Undertaking is not using the allocated train path envisaged by the Timetable, IŽS will, depending upon the non-usage percentage, charge the reservation of train path, that is, IŽS will cancel the allocated train path.

IŽS is monitoring the realization of allocated train paths, in such a way that IŽS is calculating the train path utilization degree for all the allocated train paths.

The utilization degree is calculated by dividing the realized train path number of one train with the allocated train path number of the same train, and the result is shown in percentages.



The degree of utilization of allocated train paths is calculated monthly, for the calendar month.

IŽS reserves the right to cancel the allocated train path if a train path is utilized less than 25% of the monthly quota, that is, less than 50% of the monthly quota in case of congested infrastructure.

For the allocated train paths where the degree of utilization is less than the borderline degree of utilization, IŽS will charge the non-usage of the capacity.

The borderline degree of utilization, according to the type of the trains, is given in the below table 6.

Table No 6. Borderline degree of utilization

Train type	Borderline degree of utilization [%]
Passenger trains	80
Freight trains	40
Facultative trains	10

Facultative train is a train which has set timetable but operates with special announcement (if needed).

Requests for train paths for all other trains will have priority over the request for train paths for facultative trains.

Infrastructure Manager will not grant facultative train paths on congested infrastructure.

In cases when the degree of utilization of the train path is below the borderline degree of utilization, the Infrastructure Manger will charge the full price of the train path for the used train paths, and for the non-used train paths, which represent the difference between the borderline degree of utilization and the degree of utilization of one train path, IM will charge for the reservation of the train path.

The charge for the reservation is 20% of the agreed train path price.

If the train path is not used in its entirety, as agreed in contract, the full price of the train path will be charged, according to the required elements.

4.8.2. Rules of Cancellation

A Railway Undertaking may cancel the allocated train path as part of changes and amendments of the Timetable. If a Railway Undertaking cancels the allocated route or requires modifications of parameters for the already allocated train paths outside the deadlines set forth in Appendix 4.4 and if they are such that their implementation will result in freeing of infrastructure capacities, such as:

- Cancellation of a part of already allocated train path i.e. shortening of the train path while all other parameters of the allocated train path remain the same,
- Change in traffic regularity, such that the train is transferred from the regular train status into the facultative train status, or the prescribed number of train operating days is reduced,
- Reduction of train length,

IŽS will not charge the costs prescribed under the tariff system under item 5.10.



Cancellation of allocated train path is done in writing, to the following address:

By mail:
"Infrastructure of Serbian Railways" JSC Railway Infrastructure Access Department 6, Nemanjina St 11000 Belgrade, Serbia
By e-mail: sektor.pzi@srbrail.rs

Cancelled train paths can be allocated to other railway undertakings by IŽS.

4.9. International Timetabling Process Redesign (TTR)

4.9.1. Objectives of TTR

RailNetEurope (RNE) and Forum Train Europe (FTE), supported by the European Rail Freight Association (ERFA) are currently working on a Redesign of the International Timetabling Process (TTR). The objective of TTR is to harmonise and improve the European rail timetabling system to significantly increase the competitiveness of railway transports.

TTR consists of different components, including in particular an improved planning of the distribution of infrastructure capacity (including temporary capacity restrictions) and the introduction of new capacity allocation processes.

The purpose is to better serve all market needs and achieve an optimised use of existing infrastructure capacity. In particular for passenger traffic it will mean earlier availability of the final timetable allowing earlier and more reliable ticket purchasing for passengers. For the majority of freight traffic, it will mean more possibilities for short-term path requests and thus more flexibility to better meet customers' needs.

Detailed information can be found on ttr.rne.eu and http://www.forumtraineurope.eu/services/ttr/.

TTR is planned to be fully implemented for the timetable 2025 provided that it is supported by the European and national legal framework.



5. SERVICES AND CHARGES

5.1 Introduction

Serbian legislation defined four types of services which railway undertakings can use with the aim of performing of transport operations on the allocated infrastructure capacity.

Categories of services offered by "Infrastructure of Serbian Railways" JSC to railway undertakings on the network are in line with the provisions of the Law on Railways and defined by the following documents:

- Decision on establishing of Joint Stock Company for Public Railway Infrastructure Management ("Official Gazette of RS" No 60/2015);
- Rulebook on organization and systematization of jobs at Joint Stock Company for Public Railway Infrastructure Management "Infrastructure of Serbian Railways";
- Methodology for valuation of elements for determining the charges for the use of railway infrastructure ("Official Gazette of RS" No 122/14).

The services that can be provided to railway undertakings are the following ones:

- 1. Minimum access package of services (hereinafter: the minimum package of services);
- 2. Basic services in services facilities including the access tracks to such facilities;
- 3. Additional services; and
- 4. Ancillary services.

Until the Government determines the Methodology for determining the price for access and the price for services and, based on it, the specific rules for calculation of the price for access and the price for services provided by the Infrastructure Manager, "Infrastructure of Serbian Railways" will apply the valid Methodology for valuation of elements for determining the charges for the use of railway infrastructure ("Official Gazette of RS" No 122/14), and according to this Methodology, where necessary, classification to the following service categories:

- Category I: Minimum package of services;
- Category IIa: Package for track access to service facilities;
- Category IIb: Package for provision of services in service facilities;
- Category III: Package for additional services;
- Category IV: Package for ancillary services.

IM – "Infrastructure of Serbian Railways" JSC will enable all interested railway undertakings to use the minimum access package of services and track access to services facilities, in a non-discriminatory manner, provided that railway undertakings have fulfilled the requirements for rail transport service in accordance with the provisions of the Law on Railways and the signed Contract for the use of railway infrastructure. Railway Undertaking's requests for the use of facilities and services provided in such facilities may be rejected only if there are feasible alternatives enabling the railway undertakings to perform the transport of goods and passengers on the same or alternative transport routes under the economically acceptable conditions. According to the nature of distinction and type of activity, the former notion of service facility can be aligned with the notion of services facility in the entire text, and the notion "level of charge for the use of public railway infrastructure" can be aligned with the notion "level of access charges and charges for access to the part of public railway infrastructure connecting the services facilities".

The use of all services facilities, additional and ancillary services provided by the IM – "Infrastructure of Serbian Railways" JSC - will be enabled to all railway undertakings in a non-discriminatory manner and upon their request, and will be defined in a separate contract.

The use of services facilities not owned by the IM – "Infrastructure of Serbian Railways" JSC, as well as additional and ancillary services not provided by the IM – "Infrastructure of Serbian Railways" JSC, is subject to separate contracts with managers of the said facilities and service providers.



Based on the volume of services provided, as defined in items 5.2 to 5.10, Railway Undertaking pays a charge for access and a charge for the provided service to:

- "Infrastructure of Serbian Railways" JSC based on the Contract for the use of railway infrastructure and separate contracts;
- Other service providers based on separate contracts.

5.2 Charging Principles

The basic principles underpinning the charging regime for the use of infrastructure are set forth in the Methodology for valuation of elements for determining the charges for the use of railway infrastructure ("Official Gazette of RS" No 122/14, dated November 11, 2014). The Methodology is defining, in more detail, valuation of elements for determining the level of charge for minimum package of services and package for track access to service facilities and provision of services in service facilities.

The methodology is based on the principle that railway undertakings should only bear the justified cost of IM operations and the costs arising from the efficient provision of services requested by the users.

This methodology is based on the economic principle of valuation of elements for determining of charge level known as marginal cost plus (MC+). It is a charge setting principle based on marginal costs increased by the mark-up. The selected principle enables covering of justified costs arising in provision of requested services and is favourable for the so called "network systems" (systems that require major capital investments such as telecommunications, energy, natural gas transportation, road transport and other means of transport).

Marginal costs are estimated based on the variable costs which, within the Methodology, include short-term marginal costs: track wearing, train movement control and signalling, consumption of energy sources and overheads.

The charge is set based on the following elements: line category (main, regional or local) used by train, use of railway nodes, train category (passenger or freight) and traction type (electrical or diesel).

The components of the total charge include charge for the minimum package of services (category I), charge for track access to service facilities (category IIa), charge for providing the services in service facilities (category IIb), charge for providing the additional services in service facilities (category III) and charge for providing the ancillary services in service facilities (category IV).

5.3 Minimum Access Package and Charges

Minimum access package

Within the minimum package of services for the use of railway infrastructure, IŽS provides the following services:

- Handling of requests for capacity allocation;
- Right to use the allocated capacity;
- Use of infrastructure on the main running track (turnouts, tracks, railway nodes and lines),
- Train control including signalling, regulation of train movements, acceptance and dispatching of trains and communication regarding the train operations and provision of information on train movements;
- Use of electrical supply equipment, where available;
- Provision of all other information to implement or operate the service for which the capacity has been granted.

The access price includes the minimum access package of services. Railway Undertaking will pay the access charge to "Infrastructure of Serbian Railways" JSC based on the Contract for the use of public railway infrastructure.



- Handling of requests for infrastructure capacity

Handling of requests for infrastructure capacity allocation is a part of the capacity allocation process described in Chapter 4. Principles, priorities and criteria for allocation of infrastructure capacity. Requests for infrastructure capacity allocation which have been submitted by railway undertakings are processed in mutual cooperation with railway undertakings, implementation possibilities are examined, contradictions resolved and the train path offer is prepared, which ultimately results in a Timetable.

- Right to use the allocated capacity

Provided that all necessary prerequisites for the train operation are in line with valid legal provisions on conditions for access to and use of railway infrastructure specified in Chapter 3 of the present Network Statement, the applicable legislation and the signed Contract for the use of railway infrastructure, Railway Undertaking is entitled to use the allocated capacity in the form of a train path.

- Use of infrastructure on main running track (turnouts, tracks, railway nodes and lines)

Use of infrastructure on main running track (turnouts, tracks, railway nodes and lines) on the allocated capacity enables the Railway Undertaking to perform train operations.

- Train control including signalling, regulation of train movements, acceptance and dispatching of trains and communication regarding the train operations and provision of information on train movements

Overall train traffic management, including signalling, train movement regulation, acceptance and dispatching of trains, communication regarding the train operations and provision of information on train movements using the telecommunication devices enables railway undertakings to perform train operations on the allocated train path.

- Use of electrical supply equipment

On its electrified railway lines IŽS enables a Railway Undertaking to use the electrical supply equipment for traction (without electricity).

- All other information to implement or operate the service for which the capacity has been granted

After the Timetable has been adopted and published, railway undertakings will be provided with all additional information required for the train operations within the minimum access package of services.

Charge for the minimum package of services (category I)

Charges for the minimum package of services for infrastructure access are defined based on the costs of railway traffic management and infrastructure capacities maintenance.

The level of unit charges is determined in relation to line category (main, regional, local), train category (passenger trains, freight trains) and traction type (diesel, electrical).

The charging units are:

- 1) Train km;
- 2) Gross tonne km.

Charge for minimum package of services (NKI) is determined according to the following formula:

$$NKI = (\sum VKM_{ijk} \cdot C_{VKM_{ijk}}) + F \cdot (\sum BRTKM_{ij} \cdot C_{BRTKM_{ij}})$$

Key:

i – Line category (main, regional, local)



j – Train category (passenger trains, freight trains)

k – Traction type (diesel, electrical)

 $(\sum_{VKM_{ijk}} C_{VKM_{ijk}})$ - charge for the use of infrastructure capacities for the minimum package of services in relation to line category (i), train category (j) and traction type (k)

 VKM_{ijk} - number of train km on the network in relation to line category (i), train category (j) and traction type (k)

 $C_{VKM_{ijk}}$ - charge per one train km in relation to line category (i), train category (j) and traction type (k)

F - factor depending on the train category (factor level depends on the train category impact on the level of infrastructure maintenance costs or the applied strategy for development of a particular segment of railway market)

 $(\sum BRTKM_{ij} \cdot C_{BRTKM_{ij}})$ - charge for wearing out of line and tracks during train passing in relation to line category (i) and train category (j)

BRTKM_{ij} - number of gross-tonne km on the network in relation to line category (i) and train category (j)

 $C_{BRTKM_{y}}$ - charge per one gross-tone km in relation to line category (i) and train category (j)

The level of charge for the path of one train depends on the train gross mass. Gross-tonne km, in the sense of the calculation of the level of charge for the path of one train, is defined as a product of train km and train gross mass, which implies the total mass of all active locomotives and the total mass of all hauled stock.

	-		
Line category	Charge per one train km [RSD/TKM]	Charge per one gross-tonne km [RSD/GTKM]	
Main line	93,50	0,0858	
Regional line	63,77	0,0781	
Local line	10,53	0,0361	

Freight trains with electrical traction

Line category	Charge per one train km [RSD/TKM]	Charge per one gross-tone km [RSD/GTKM]
Main line	79,04	0,0858
Regional line	51,24	0,0781
Local line	10,07	0,0361

Freight trains with diesel traction

Passenger trains with electrical traction

Line category	Charge per one train km [RSD/TKM]	Charge per one gross-tone km [RSD/GTKM]
Main line	62,33	0,0686
Regional line	42,51	0,0625
Local line	7,02	0,0289

Passenger trains with diesel traction

Line category	Charge per one train km [RSD/TKM]	Charge per one gross-tone km [RSD/GTKM]
Main line	52,69	0,0686
Regional line	34,16	0,0625
Local line	6,71	0,0289



Factor depending on the train category [F] is applied to all types of freight trains and passenger trains and amounts to 1.0.

Charge for track access and use of service facilities (categories Ia and IIb)

Charges for track access and use of service facilities are defined based on the costs of railway traffic regulation and infrastructure capacities maintenance.

The level of unit charges is determined in relation to railway node (Subotica, Novi Sad, Beograd, Lapovo, Niš, Pančevo), train category (passenger trains, freight trains) and traction type (diesel, electrical).

The charging units are:

- 1) Number of trains;
- 2) Gross tonne km;
- 3) Number of serviced trains.

The charge is levied for the trains starting and finishing their running in the railway node, that is, transiting the railway nodes, as well as for the trains in railway nodes.

Serviced train is a train to which a service of using the service facilities in a railway node has been provided aiming to use the services of technical-wagon unit in train inspection, maintenance of wagons, railway vehicles and machinery.

Track access and use of service facilities (categories IIa and IIb)

Charge for the use of infrastructure when the trains are starting and finishing their running in the node, that is, when they are transiting railway nodes (NKIIa), as well as for the servicing of trains in the railway nodes (NKIIb) is determined as follows:

NKII = *NKIIa* + *NKIIb*

 $Kev:-^{NKIIa} = (\sum Va_{lmn} \cdot C_{Valmn}) + (\sum BRTKM_{lm} \cdot C_{BRTKM_{lm}})$

 $NKIIb = \sum Vb_{lm} \cdot C_{Vb_{lm}}$

1 - Node (Subotica (1), Novi Sad (2), Beograd (3), Lapovo (4), Niš (5), Pančevo (6))

m – Train category (passenger trains, freight trains)

n – Traction type (diesel, electrical)

 $(\sum Va_{lmn} \cdot C_{Va,lmn})$ - charge for the use of infrastructure capacities in the node for the package of services IIa in relation to node (l), train category (m) and traction type (n)

 Va_{lmn} - number of trains in the node in relation to node (l), train category (m) and traction type (n)

 C_{Valmn} - charge per one train for the used infrastructure capacities in the node, in relation to node (1), train category (m) and traction type (n)

 $(\sum BRTKM_{lm} \cdot C_{BRTKM_{lm}})$ - charge for wearing out of railway line and railway track when using the infrastructure capacities in the node, for package of the services IIa, in relation to node (l) and train category (m)

*BRTKM*_{*lm*} - number of gross-tonne km in the node, in relation to node (l) and train category (m)

 $C_{BRTKM_{Im}}$ - charge per one gross-tonne km in the node, in relation to node (l) and train category (m)

 $\sum V b_{lm} \cdot C_{Vb_{lm}}$ - charge for providing the services of train "servicing" in the node, for package of services IIb, in relation to node (l) and train category (m)



 Vb_{lm} - number of trains which were provided with the service (which were "serviced") in the node, in relation to node (l) and train category (m)

 $C_{Vb_{lm}}$ - charge per one train, "serviced" in the node, in relation to node (l) and train category (m)

Node	Charge for the use of infrastructure capacities in the node per one train [RSD/train]	Charge per one gross-tonne km in the node [RSD/GTKM]
Novi Sad	3.658,76	0,0801
Beograd	4.302,04	0,0894
Lapovo	4.987,87	0,0744
Niš	5.422,50	0,1171
Pančevo	3.257,01	0,0911
Subotica	4.097,11	0,0497

Freight trains with electrical traction

Freight trains with diesel traction

Node	Charge for the use of infrastructure capacities in the node per one train [RSD/train]	Charge per one gross-tonne km in the node [RSD/GTKM]
Novi Sad	3.607,21	0,0801
Beograd	4.145,57	0,0894
Lapovo	4.935,40	0,0744
Niš	5.293,94	0,1171
Pančevo	3.196,24	0,0911
Subotica	3.944,07	0,0497

Passenger trains with electrical traction

Node	Charge for the use of infrastructure capacities in the node per one train [RSD/train]	Charge per one gross-tone km in the node [RSD/GTKM]
Novi Sad	2.439,17	0,0534
Beograd	2.868,03	0,0596
Lapovo	3.325,25	0,0496
Niš	3.615,00	0,0781
Pančevo	2.171,34	0,0607
Subotica	2.731,41	0,0332

Passenger trains with diesel traction

Node	Charge for the use of infrastructure capacities in the node per one train [RSD/train]	Charge per one gross-tone km in the node [RSD/GTKM]
Novi Sad	2.404,81	0,0534
Beograd	2.763,71	0,0596
Lapovo	3.290,27	0,0496
Niš	3.529,29	0,0781
Pančevo	2.130,82	0,0607
Subotica	2.629,38	0,0332

5.4 Additional Services and Charges

Additional services include:

- Supply of electricity for train traction;
- Preheating of the passenger trains, water supply, etc.;
- Modified contracts for the service:



- (1) control of transport of dangerous goods,
- (2) assistance in transport of special trains (exceptional consignments).

"Infrastructure of Serbian Railways" will enable the use of the above mentioned services (provided by IŽS) to all railway undertakings that have been allocated a minimum access package of services, in a nondiscriminatory manner and upon their request.

Railway undertakings must present the request for the use of additional services in the capacity allocation process, please refer to Chapter 4.

In order to be able to use the above services a Railway Undertaking is obliged to conclude a separate contract with IŽS or with another service provider and pay the charge for provided service in accordance with the provisions of such contract.

More detailed information on provision of additional services can be obtained from IŽS.

"Infrastructure of Serbian Railways" JSC Railway Infrastructure Access Department 6 Nemanjina St 11000 Belgrade, Serbia Tel: +381 11 3618 214 Fax: +381 11 3616 814 <u>sektor.pzi@</u>srbrail.rs

The level of charges for additional services provided by the Infrastructure Manager is determined based on the costs incurred during the provision of these services.

Charges for using the additional services are applied in a non-discriminatory manner for all the railway undertakings, that is, service users.

When determining the level of charge the time norms for performing of tasks were used in accordance with the Methodology for determining the required number of workers for performing the planned scope of work ("Official Gazette of ŽTP Beograd" 10/85) and the Methodology for calculation of labour sales price per effective hour for the employees of "Infrastructure of Serbian Railways" (Decision of the Board of Directors 4/2015-53-17 dated 29.12.2015), and other valid railway regulations and documents.

The prices of additional services are determined in accordance with the Methodology for valuation of elements for determining the charges for the use of railway infrastructure. The levels of prices for additional services are determined as a product of standardized period for service performing and price of effective working hour of staff hired to provide the service, and they are solely based on the actual cost of work incurred during the provision of the particular service or directly determined by means of the Infrastructure Manager's separate decision.

Additional services are provided upon the Railway Undertaking's request, and the prices are applied in a non-discriminatory manner for all railway undertakings. Railway Undertakings will pay such prices according to the actual level of use.

- Supply of electricity for traction and charges

For the service of supply of electricity for traction please refer to: "Infrastructure of Serbian Railways" JSC Electrical Engineering Department 6, Nemanjina St 11000 Belgrade, Serbia Tel: +381 11 3618 241 Fax: +381 11 3618 130 direktor.etp@infrazs.rs



The prices of traction electricity depend on the prices of electricity determined by the supplier (currently JP Elektroprivreda Srbije), actual consumption costs, gross tonne km and train type. The calculation method is provided in Appendix 9.

- Preheating of the passenger trains

"Infrastructure of Serbian Railways" JSC is not providing services of preheating of passenger trains.

More information regarding the preheating of passenger trains are available at:

"Srbijavoz" a.d. 6, Nemanjina St. 11 000 Belgrade, Serbia Tel: +381 11 3614 811 Fax: +381 11 3614 811

- Services for transport of exceptional consignments and dangerous goods

a) Services for transport of exceptional consignments

IŽS provides the service of transport of exceptional consignments (vehicles or items) according to the provisions for transport of exceptional consignments prescribed under the Regulations on transport of exceptional consignments.

The service involves processing of railway undertaking's request to examine the possibilities for transport in terms of technical aspect and setting of other technical requirements and protective measures for transport of consignments that are not fulfilling the general technical standards for transport on the particular line section, e.g. loading gauge, axle loading etc. Any deviation from the standards is considered to be an exceptional consignment and a special procedure is required. The service involves additional engagement of IŽS's employees in preparation and carrying out of transport of exceptional consignments such as: defining of transport conditions, possible engagement of additional staff for accompanying of transport and inspection of tracks after the transport, possible temporary re-location of trackside facilities and equipment etc.

IŽS decides whether it is possible to accept certain transport and under which conditions. It is necessary that IŽS and the Railway Undertaking define the scope and specification of required services for each individual transport.

b) Services for dangerous goods transport

IŽS provides additional services to railway undertakings related to transport of dangerous goods. Control of dangerous goods transport for each individual transport is defined between IŽS and the Railway Undertaking, depending upon the specification of required services. The availability and method of providing this service on IŽS network will be determined based on the decisions and procedures which will be subsequently prescribed by IŽS.

Charges for services of transport of exceptional consignments and dangerous goods

The unit price of additional services regarding the transport of exceptional consignments and dangerous goods is determined based on the actual costs incurred in provision of such service and unit prices of staff hired from the public railway infrastructure manager and is applied in a non-discriminatory manner to all railway undertakings.

Issuing of approvals for transport of exceptional consignments



Operation	Measuring unit	Price in RSD VAT exclusive
Processing of request, issuing of conditions and informing by means of telegramme for the purposes transport of exceptional consignments	Request for transport of exceptional consignment	12.976,00

Accompanying of trains carrying exceptional consignments: involves accompanying of consignments by professional railway staff, as necessary, according to type and complexity of exceptional consignment transport as set out in the Regulations on transport of exceptional consignments.

Unit price for this service is determined according to effective working hours of hiring of the employee and number of persons accompanying the exceptional consignment.

Operation - operators	Measuring unit	Price in RSD VAT exclusive
Accompanying performed by an employee from	Effective hour of	1.844,00
traffic department	accompanying	1.844,00
Accompanying performed by an employee from civil	Effective hour of	1.339,00
engineering department	accompanying	1.339,00
Accompanying performed by an employee from	Effective hour of	1.453,00
electrical engineering department	accompanying	1.433,00

If the employee accompanying the consignment is entitled to daily allowance for the business trip in the country, the service price should also include the cost of realized daily allowances. The amount of daily allowances is determined in the Collective Agreement of the public railway Infrastructure Manger.

Transport of exceptional consignments with exceeded axle-loading

The unit price for approving the transport of exceptional consignment with exceeded axle-loading is 59,00 RSD/net tonnes VAT exclusive.

5.5 Ancillary Services and Charges

Ancillary services include the following:

- 1) access to telecommunications network
- 2) provision of additional information
- 3) technical inspection of rolling stock
- 4) ticketing services in passenger stations
- 5) maintenance services provided in maintenance facilities dedicated to high speed trains or other types of rolling stock requiring specific facilities where the works performed are not a routine daily maintenance and require the vehicle to be withdrawn from service
- **6**) other ancillary services

IŽS reserves the right to decide which of the available ancillary services will be provided and under what conditions. If IŽS is providing a particular service, it will provide it to all railway undertakings under equal conditions in a non-discriminatory manner and upon their particular request.

The charges for ancillary services provided by "Infrastructure of Serbian Railways" JSC will be determined based on the actual costs incurred during the provision of the said service and will be a subject to a separate contract concluded between the interested parties.



1) Access to telecommunications network

IŽS provides railway undertakings with the service of access to the telecommunications network in accordance with the market conditions. Railway Undertaking should define, together with IŽS, the scope and specification of required services.

2) Provision of supplementary information

IŽS provides, if available, the following supplementary information on the use of railway infrastructure to the railway undertakings:

- Provision of Timetable material (timetable graphs, timetable booklets) prepared and published by IŽS;
- Submission of excerpts from the local regulations of importance for railway transport or other documents.

For any further information the Railway Undertaking should define, together with IŽS, the scope and specification of required services.

3) Technical inspection of rolling stock

Technical inspection of rolling stock is performed upon obtaining of license for their use and prior to putting the vehicles into service.

Directorate for Railways prescribes the conditions to be fulfilled by the entities performing the technical inspection of vehicles and the manner for performing of technical inspection.

Only the rolling stock fulfilling the requirements prescribed by the Law on Safety can be included in the train and this is determined by means of a rolling stock inspection.

Railway Undertaking is responsible for proper composition of the train and it is obliged to check whether the train rolling stock is in a proper technical condition. Train composition and distribution of rolling stock in the train must ensure safe train movement and braking.

"Infrastructure of Serbian Railways" JSC is not providing the services of technical inspection of wagons and rolling stock.

4) Ticketing services in passenger stations

"Infrastructure of Serbian Railways" JSC is providing the ticketing services in passenger stations according to the special request of interested Railway Undertaking and according to its own capacities and assessment of impact on its staff's basic work process.

5) Maintenance services provided in maintenance facilities dedicated to high-speed trains or other types of rolling stock requiring specific facilities

The network operated by "Infrastructure of Serbian Railways" JSC currently does not have any maintenance facilities dedicated to high speed trains or other types of rolling stock requiring specific facilities providing the respective ancillary services.

6) Other ancillary services

IŽS provides other ancillary services:

Staff training and/or testing in line with the internal documents and technological procedures of IŽS.



7) Staff training and testing

The service of training and testing of public railway infrastructure user's staff is provided by the Infrastructure Manager in accordance with articles 60 to 64 of the Law on Safety in Railway Traffic ("Official Gazette of RS" No 41/2018) .The price for training and testing of interested users is determined as follows:

Cpp = Tpo + Tto + Tpz + Tos

This price includes:

- cost of practical training Tpo performed by minimum one expert from the Infrastructure Manager (familiarizing the candidates with the local conditions and technical capacities);
- cost of theoretical training Tto performed by minimum two lecturers (familiarizing with signalling and traffic regulations, special measures for occupational safety and protection as well as all important normative acts provisions of station regulations, technological work process etc., and if necessary provisions in connection to the transport of dangerous goods);
- cost of testing Tpz taking of expert exam regarding the familiarity with railway infrastructure performed by minimum four members of expert committee (president, 2 examiners from the expert field and 1 examiner on the provisions of measures for occupational safety and protection);
- cost of staff Tos hired for the provision of respective service according to the actual level of realization (daily allowances, travelling expenses, submission of required materials etc.)

The price for this service is determined in accordance with the separate Contract between IŽS and the interested party and specification of costs is provided in a descriptive manner and expressed according to the number of candidates and hired experts from the Infrastructure Manager involved in provision of this service.

5.6 Discounts

"Infrastructure of Serbian Railways" JSC does not approve quantity discounts.

5.7 **Performance Scheme**

One of the most important indicators of efficient network operations, both for Railway Undertaking and Infrastructure Manager, is train delay.

Train delays are monitored related to the causes of delays. Accordingly, the delays can be primary and secondary.

Primary delays are all train delays caused by interference or disturbance which led to the delay and that were not caused by delay or cancellation of other train.

Secondary delays are train delays caused by already existing earlier delay.

Overview of primary and secondary causes of train delays is presented in Appendix 7 of the Network Statement.

IŽS keeps a record of movements of all trains on its network and determines the causes of delay.

Delays can be caused by the following:

- Infrastructure Manager,
- Railway Undertaking,
- external factor.



Number of minutes of train delay is determined on the basis of deviation of train actual running time compared to the train running time envisaged by the Timetable.

The compensation for all primary train delays is calculated on the basis of the number of minutes of train delay and charged between IŽS and RU, if agreed under the Contract for the use of railway infrastructure. The reason for this is to motivate the Railway Undertaking and the Infrastructure Manager to minimize the Timetable deviations on the network and to increase the quality of transport service offered to the end users.

The compensation for delay is 0.1% of the charge for the entire train path, for every minute of delay. The total amount of the delay compensation for every individual train can be maximally up to 5% of the charge for the entire train path, for each party responsible.

For the delays of passenger trains less than 10 min per 100 km of allocated train path, that is, for the delays of freight trains of less than 40 min per 100 km of allocated train path, the charging between IŽS and RU is not performed. Calculation is performed solely for the entire train path, not for the particular parts of the path.

For the train paths shorter than 100 km the permitted delay is determined proportionally to the actual path length.

If the Railway Undertaking does not start the train 300 minutes after the prescribed departure according to the Timetable, it will be deemed that the train path of that train has been automatically cancelled for that day.

Train delays, caused by accidents or incidents, in respect of which the responsibility for the delay cannot be determined with certainty without the investigation procedure, will be calculated subsequently.

Delays caused by the external factor arise from the circumstances which are not under influence of the Infrastructure Manager or the Railway Undertaking. Delays caused by the external factor are the delays caused by the force majeure, or the delays caused by the third parties.

5.8 Changes to Charges

Charges for the minimum package of services and track access to service facilities, as well as charges for basic, additional and ancillary services, can be modified depending on the conditions on the market of the railway services, in which case it must be published at least six months in advance.

5.9 Billing Arrangements

Method and time schedule for calculation and payment of charges, will be determined in detail in the contract between the Infrastructure Manager and the Railway Undertaking.

Charges are collected through:

Finance Department 6 Nemanjina Str. 11 000 Belgrade, Serbia Phone: +381 11 3618 465 Fax: +381 11 3618 465 finansijeizs@srbrail.rs

The Finance Department defines the payment security instrument for the use of public railway infrastructure.

For the use of public railway infrastructure during the validity period of 2024/2025 Timetable, the payment security instrument is defined according to the following:

The RU undertakes to submit to "Infrastructure of Serbian Railways" JSC (Finance Department) with respect to the timely settlement of due obligations under the contract on the use of public railway infrastructure, 5



(five) blank solo bills of exchange registered with the National Bank of Serbia, bill of exchange authorization and a copy of the card of specimen signatures. Blank solo bills of exchange must be submitted within 15 days from the date of signing the contract on the use of public railway infrastructure, otherwise, the contract will have no legal effect. The term of validity of the bill of exchange authorization must be at least 30 days longer than the date of final settlement of the contractual obligation and is not related to the termination of legal effect under the Contract. The RU is obliged to submit to "Infrastructure of Serbian Railways" JSC, Finance Department, new instruments for securing the regular settlement of financial obligations in case the previously submitted ones are implemented, i.e. when other circumstances arise due to which the previously submitted instruments cannot be implemented, no later than 15 days from the new circumstance's occurrence.

The Finance Department monitors the realization of the payment of due obligations under the contract on the use of public railway infrastructure, and in case the RU does not settle the due obligations within the deadline, it has the right to activate bills of exchange, which were submitted in order to secure payment.

If during the duration of the Contract on the use of public railway infrastructure, due to a delay in the settlement of obligations, a security instrument is activated, the RU will be obliged to provide a bank guarantee as an instrument for securing the payment in the following contract. The level of the Bank Guarantee is 25% of the value of invoices issued under the Contract on the use of public railway infrastructure in the past twelve (12) months.

5.10 Tariff system

IŽS charges fee for the train path allocation procedure costs as follows:

- for the allocation of annual train paths for the 2024/2025 Timetable nor for the allocation of train paths under the requests for amendment of annual 2024/2025 Timetable performed within the deadlines prescribed in Appendix 4.4, IŽS will not charge procedure costs.

- for allocation of train path under the extraordinary request for amendment of the annual timetable amount to 17.137,00 RSD per train path.

- for allocation of ad-hoc train path amount to 12.213,00 RSD per train path.



6. OPERATIONS

6.1 Introduction

The transport operation on the railway infrastructure shall be such manner to ensure the protection of life, property and environment. The railway undertaking operating on the railway infrastructure will be obligated to comply with the regulations and provisions applicable to transport operations on the particular railway infrastructure.

6.2 **Operational Rules**

The list of applicable regulations and instructions related to operational rules is given in a separate Appendix 2.

At some locations on the infrastructure and in some cases, there are deviations from the applicable regulations (approved by the Directorate for Railways upon IŽS's proposal). The information about this is published by IŽS. The relevant address for these regulations, instructions and modifications is:

"Infrastructure of Serbian Railways" JSC Traffic Department 6 Nemanjina Street 11000 Belgrade Serbia Tel.: +381 11 3618 214 Fax: +381 11 3616 814 sektor.sp@srbrail.rs

6.3 **Operational Measures**

In case of traffic disturbances, IŽS, together with Railway Undertakings, will undertake all necessary measures to restore normal operating conditions as soon as possible.

Traffic disturbance will mean congesting of some parts of the network or stations that may occur as a consequence of disturbances occurring in traffic due to any reason.

6.3.1. Principles

In order to solve the traffic disturbances, IŽS will undertake appropriate measures to restore the planned Timetable, while taking into consideration the needs of passengers and users of freight traffic, as well as traffic safety. Aiming to solve the traffic disturbances, IŽS may apply operation rules under 6.3.2., cancel some trains or assign another train path in agreement with a Railway Undertaking, depending on the type of disturbance and expected duration.

In case a longer traffic disruption is expected, IŽS will, in agreement with railway undertakings, prepare an interim timetable for the period until regular operation is restored. IŽS may seek railway undertakings' assistance with the aim of normalizing the traffic operating conditions, even when such railway undertakings are not directly causing the disturbances, which may include using their rolling stock and personnel in order to normalize the traffic.

6.3.2. Operation regulation

For the purposes of restoring the normal traffic flow, the operational rules for railway traffic management will apply as set out in the Law on Safety in Railway Traffic, Traffic Regulations ("Official Gazette of RS" No 34/22 and 107/22), the Instructions on particular procedures in performing of traffic service on the territory of Infrastructure of Serbian Railways ("Official Gazette of Serbian Railways" No 43/22), the Instructions on organization and work procedures of operational service in the area covered by



"Infrastructure of Serbian Railways" JSC ("Official Gazette of Serbian Railways" No 21/17, 21/18 and 37/18) and other internal documents of IŽS.

In cases when traffic is interrupted on some part of the line due to a defect in the traction means of the RU in order to normalize traffic as soon as possible the IŽS operational service takes operational measures prescribed by article 34 of the internal act Instructions on organization and work procedures of operational service in the area covered by "Infrastructure of Serbian Railways" JSC ("Official Gazette of Serbian Railways" No 21/17, 21/18 and 37/18).

In case of delays and premature train dispatches, the rule applies that lower-ranking trains may not interfere with movements of higher-ranking trains. A lower-ranking train can be given the priority only if in such a way increase in delays is avoided and the higher-ranking train can make up for the delay on its further route. With same rank trains, priority is given to that train whereof delay might cause it to lose connections in connecting stations. If the connections are not in question, priority is given to that train which has a longer route to its destination station, i.e. which is running on time. Necessary measures to be taken in case of accidents and incidents are defined in the Law on Safety in Railway Traffic, by the Rules on reporting, investigating, recording, statistical monitoring and publishing of data on accidents and incidents ("Official Gazette of RS" No 32/21), Instructions on procedures in case of accidents and incidents ("Official Gazette of Serbian Railways" 44/21). Trains which are taking part in rectifying the disturbances caused as a result of accidents have the priority (ranking) over all other trains.

6.3.3. Foreseen and Unforeseen problems

Foreseen problems

Necessary measures to be undertaken in cases of foreseen problems such as: technical disturbances of signalling & safety and telecommunication devices, strong wind, natural disasters, snow etc., are governed by Traffic Regulations ("Official Gazette of Serbian Railways" No 34/22 and 107/22) and other regulations governing the above mentioned.

Unforeseen problems

In very urgent cases, when railway infrastructure is temporarily rendered unavailable for use, IŽS may, without prior notice, cancel train paths for the time period necessary to put the system back in working order. IŽS will notify all interested parties of the resulting situation.



7. SERVICE FACILITIES

7.1. Introduction

Services facility means a facility, including land, buildings and equipment, arranged in a particular manner, as a whole or partially, including the sidings connecting the network with the service facility, in order to enable provision and use of basic services provided in such facilities under the non-discriminatory and transparent conditions.

7.2. Service Facility Overview

Services facilities are:

1) station buildings, i.e. a part of station buildings, in passenger stations, intended for railway passengers, and other facilities used in passenger traffic, including the travelling information displays and the appropriate ticketing points;

2) freight terminals;

3) marshalling yards and train formation tracks, including the shunting tracks;

4) tracks for storing intended for railway undertakings' vehicles using the allocated infrastructure capacity;

5) maintenance facilities, with the exception of maintenance facilities for high speed trains or other types of rolling stock requiring specific facilities where the works performed are not routine works performed as a part of daily activities and require withdrawal of vehicle from service;

6) other technical facilities, including the cleaning and washing facilities;

7) inland waterways port facilities connected to railway activities;

8) facilities for provision of assistance;

9) facilities for fuel storing and supplying for which the prices are presented separately.

7.3. Service Facilities Managed by IŽS

IŽS will enable all railway undertakings, which have been granted the minimum access package of services for the use of infrastructure, to use all the services facilities managed by it in a non-discriminatory manner and upon their request.

7.3.1. Common Provisions

IŽS will enable all the railway undertakings with minimum access package of services to have track access to all the above mentioned services facilities in a non-discriminatory manner and upon their request, provided that railway undertakings have previously entered into a contract on the use of these facilities with facility managers and service providers.

Railway undertakings have to state the need to have track access to service facilities and to use them during the capacity allocation procedure, please refer to Chapter 4.

For the service of track access to service facilities, Railway Undertaking will be obliged to pay a charge to the IŽS based on the Contract for the use of infrastructure.

7.3.2 Use of station buildings in the function of passenger traffic

Appendix 6 contains an overview of locations where passengers may board/get off the train.

The stations along the narrow gauge lines are used for passenger service only.



"Infrastructure of Serbian Railways" will enable the use of station buildings, i.e. the part of station buildings, in passenger stations in the areas intended for railway passengers and of other facilities used for passenger traffic, including the travel information display and adequate location for ticketing services to all railway undertakings in a non-discriminatory manner and upon their request.

The use of parts of service points (station buildings, stops) and other facilities required for acceptance and dispatching of passengers also includes use of platforms and other surfaces required for access of passengers in them, as well as other areas enabling passenger movements between public road surfaces and the train.

The use of travel information displays includes the use of all existing visual information facilities already installed in individual stations.

Upon request of a Railway Undertaking IŽS will, where possible, provide a suitable area for the ticketing services.

7.3.3 Freight Terminals

The term "freight terminals" on the railway network operated by Infrastructure of Serbian Railways (IŽS), means all the railway service points used for freight operations where loading and unloading as transshipment operations are carried out.

The following types of terminals are distinguished: stations and transport forwarding, terminals for intermodal freight transport, port terminals.

Overview of services facilities for freight operations is presented in Appendix 6.

Combined transport on railway network can be performed at terminals for combined transport and at port terminals.

No	Railway station connected to the terminal	Freight terminal for combined transport	Address of freight terminal for combined transport	Terminal operator
1.	Beograd Marshalling yard (Belgrade Marshalling Yard)	ŽIT Beograd	Beograd Marshalling yard, Železnik, Lole Ribara 2.	"ŽIT Beograd" d.o.o., Beograd, Železnik, Lole Ribara 2
2.	Surčin	Nelt	Beograd, Dobanovci, Maršala Tita 206.	"Nelt Co" d.o.o., Beograd
3.	Novi Sad Marshalling yard (Novi Sad Marshalling Yard)	Luka (Port) Novi Sad	Novi Sad, Carinska 1.	"Luka Novi Sad" a.d., Novi Sad, Carinska 1
4.	Pančevo Varoš	Luka (Port) Dunav	Pančevo, Luka Dunav 1.	"Luka Dunav Pančevo" a.d., Pančevo, Luka Dunav 1
5.	Smederevo	Luka (Port) Smederevo	Smederevo, Radinac b.b.	"Luka Dunav – Železara Smederevo" d.o.o., Smederevo, Radinac b.b.
6.	Prahovo Pristanište	Luka (Port) Prahovo	Prahovo, Radujevački put b.b.	"Luka Prahovo IHP Prahovo– Krajina" d.o.o., Prahovo, Radujevački put b.b.

Table No 7: Stations connected to freight terminals



7.	Senta	Luka (Port) Senta	Senta Pristanisna I	"Luka Senta" a.d., Senta, Pristanišna 1
8.	Sremska Mitrovica	Luka (Port) Leget	Sremska Mitrovica, Jarački put 10	"RTC Luka Leget" a.d., Sremska Mitrovica, Jarački put 10
9.	Šabac	Luka (Port) Zorka Šabac		"Zorka transporti" d.o.o., Šabac, Narodnih heroja 1
10.	Niš Marshalling Yard	MBOX Terminals d.o.o	Freight-transport terminal in Niš Vojlovački zaseok 4 St. 18560 Popovac (Niš)	MBOX Terminals d.o.o
11	Batajnica	"Logistički centri Srbije" doo	Batajnica, Ulica Mladih gorana 136	"Logistički centri Srbije" doo

IŽS does not operate nor provide basic services in any freight terminal within the meaning of its definition of an arranged and organized area where the receiving, storage, preparation, transshipmenthipment and dispatching of various types of goods is carried out.

For more detailed information on the services provided by the freight terminal operator or the service provider, the following entities should be contacted:

1) Železnički integralni transport Beograd - ŽIT BEOGRAD d.o.o.

Addresses: Beograd Marshalling Yard (Belgrade Marshalling Yard), Lole Ribara 2 Železnik, Belgrade and Hajduk Veljkov Venac 4/1

11000 Belgrade, Serbia

Contact details: +381 (0)11 361- 6844, +381 (0)-1 361 - 6842, +381 (0)64 81040.

2) "Nelt Co." d.o.o. Beograd

Address: Maršala Tita 2016, 11272 Dobanovci, Belgrade Contact details: +381 (0)11 3779-143, <u>office@nelt.com</u>, <u>www.neltlsp.com</u> Information on the service facility operated by Nelt Co, i.e. on the industrial siding which is a part of Nelt terminal is provided in Appendix 3.10a.

3) DRY PORT TERMINALS DOO

Addresses: Luka Dunav 1, 26000 Pančevo and Uzun Mirkova 3/3, 11000 Belgrade Contact details: + 381 69 32 55 012, office@dpterminal , http//dpterminals.rs Information on the service facility are available on http//dpterminals.rs//

4) "MBOX Terminals" d.o.o

Address: Freight-transport terminal in Niš, Vojlovački zaseok St 4, 18560 Popovac (Niš) Contact details: +381603593499 e-mail: <u>operations@mboxt.com</u> Information on the service facility are available on <u>https://mboxt.com</u>

5) "Logistički centri Srbije" doo

Address: Ulica Mladih gorana 136, Batajnica e-mail <u>office@lcs.rs</u> Information on the service facility are available on www.lcs.rs



IŽS however provides the use of service points open for freight traffic, in accordance with Appendix 6 of this document, for loading, unloading and transshipmenthipment to all railway undertakings in a non-discriminatory manner and upon their request.

7.3.4 Marshalling Yards and Train Formation Facilities, including Shunting Facilities

Freight train formation yards

Freight trains may be split-up and formed at the marshalling, distribution and intermediate stations/yards, according to the user needs and requirements, and taking into account the particular technical and organizational restrictions.

Distribution Station	Distribution Section	Comments	
1	2	3	
BELGRADE MARSHALLING YARD*	Belgrade Marsh.Yard- Pančevo Main St. Belgrade Marsh.Yard - Ruma Belgrade Marsh. Yard - Lapovo Marsh.Yard Belgrade Marsh. Yard – (Mala Krsna) ¹⁾ – Lapovo Marsh. Yard Belgrade Marsh.Yard – Mala Krsna Belgrade Marsh.Yard – Novi Sad Marsh. Yard	¹⁾ -for the trains not entering the Mala Krsna station	
BOGOJEVO	Bogojevo - Sombor Bogojevo - Novi Sad Marsh. Yard Bogojevo - Erdut (HŽI)		
BOR FREIGHT STATION	Bor Freight St Požarevac Bor Freight St Zaječar Bor Freight St Prahovo pristanište		
BIJELO POLJE (ŽICG)	Bijelo Polje (ŽICG) - Vrbnica -Prijepolje Freight St.		
BRASINA	Brasina - Ruma Brasina – Zvornik ¹⁾ Brasina - Zvornik Novi (ŽRS)	¹⁾ -in both directions	
VRŠAC	Vršac - Pančevo Main. St. Vršac - Stamora Moravita (CFR SA)		
DIMITROVGRAD	Dimitrovgrad – Niš Marsh. Yard Dimitrovgrad –Kalotina Zapad		
ERDUT (HŽI)	Erdut (HŽI) - Bogojevo		
JIMBOLIA (CFR)	Jimbolia (CFR SA) - Kikinda		
ZAJEČAR	Zaječar - Niš Marsh. Yard Zaječar - Prahovo Pristanište Zaječar - Bor Freight St.		
ZVORNIK NOVI (ŽRS)	Zvornik Novi (ŽRS) - Brasina		
ZRENJANIN	Zrenjanin - Kikinda Zrenjanin - Novi Sad Marsh. Yard Zrenjanin - Pančevo Main St. Zrenjanin – Senta Zrenjanin – (Senta) ¹ – Subotica Freight St.	¹⁾ -for the trains not entering the Senta station	
KIKINDA	Kikinda – Jimbolia (CFR SA) Kikinda – Zrenjanin	¹⁾ -for the trains not entering the Senta station	

Overview of	distribution	stations-section	s for frei	oht trains d	neration
	uisti ibution	stations-section	5 101 1101	gni ir ams (peration



	Kikinda – Senta	
	Kikinda – (Senta) ¹ – Subotica Freight St.	
KOSOVO POLJE	Traffic is temporarily regulated by UNMIK railways	
	Kraljevo - K. Mitrovica Sever ¹⁾	¹⁾ -in both directions
	Kraljevo - K. Willovica Sever	²⁾ -in both directions
	5 I	
KRALJEVO	Kraljevo - Požega	³⁾ -for the trains not entering the $\mathbf{P} = \mathbf{T} \mathbf{T} \mathbf{T}$
	Kraljevo – Stalać ²⁾ $K = \frac{1}{2} \sum_{i=1}^{3} \sum_{j=1}^{3} \sum_{j=1}^{3} \sum_{i=1}^{3} \sum_{j=1}^{3} \sum_{j=1}^{3} \sum_{i=1}^{3} \sum_{j=1}^{3} \sum_{j=1$	Požega station
	Kraljevo – (Požega) ³⁾ – Prijepolje Freight St.	1). 1 .1 .1
	Lapovo Marsh. Yard – Mala Krsna	¹⁾ in both directions
	Lapovo Marsh. Yard – Resavica ¹⁾ Lapovo Marsh. Yard - Niš Marsh. Yard	²⁾ for the trains not entering the Mala Krsna station
LAPOVO	Lapovo Marsh. Yard - Kraljevo	Mala KISha station
MARSHALLING	Lapovo Marsh. Yard – Resnik - Pančevo	
YARD**	Main St.	
	Lapovo Marsh. Yard - (Mala Krsna) ²⁾	
	Belgrade Marsh. Yard	
	Lapovo Marsh. Yard – Belgrade Marsh. Yard	
	Mala Krsna – Požarevac	¹⁾ in both directions
	Mala Krsna – Lapovo Marsh. Yard	
MALA KRSNA	Mala Krsna – Belgrade Marsh. Yard	
	Mala Krsna – Smederevo ¹⁾	
	Mala Krsna – Pančevo Main St.	
	Niš Marsh. Yard - Lapovo Marsh. Yard	¹⁾ in both directions
NIŠ MARSHALLING	Niš Marsh. Yard - Preševo	
	Niš Marsh. Yard - Dimitrovgrad	
YARD	Niš Marsh. Yard - Zaječar	
	Niš Marsh. Yard – Kuršumlija ¹⁾	
	Novi Sad Marsh. Yard - Belgrade Marsh. Yard	¹⁾ in both directions
	Novi Sad Marsh. Yard- Subotica Freight St.	
	Novi Sad Marsh. Yard- Bogojevo	
NOVI SAD	Novi Sad Marsh. Yard –Pančevo Main St.	
MARSHALLING	Novi Sad Marsh. Yard- Zrenjanin	
YARD***	Novi Sad Marsh. Yard - Ruma	
	Novi Sad Marsh. Yard – Temerin ¹⁾	
	Novi Sad Marsh. Yard – Podbara ¹⁾	
	Pančevo Main St Zrenjanin	
	Pančevo Main St Vršac	¹⁾ in both directions
	Pančevo Main St Belgrade Marsh. Yard	²⁾ for the trains not entering the
	Pančevo Main St Novi Sad Marsh. Yard	Mala Krsna station
PANČEVO MAIN	Pančevo Main St Lapovo Marsh. Yard	
STATION***	Pančevo Main St Pančevo Vojlovica ¹⁾	
	Pančevo Main St Mala Krsna	
	Pančevo Main St (Mala Krsna) ²⁾ - Lapovo	
	Marsh. Yard	
	Pančevo Main St Požega	
PEĆ	Traffic is temporarily regulated by UNMIK	
TEC	railways	
POŽAREVAC	Požarevac – Bor Freight St.	
	Požarevac – Mala Krsna	
	Požega - Belgrade Marsh. Yard	
POŽEGA	Požega - Kraljevo	
rulega	Požega - Prijepolje Freight St.	
	Požega - Pančevo Main St.	
PRAHOVO	Prahovo pristanište - Zaječar	



PRISTANIŠTE	Prahovo pristanište - Bor Freight St.	
	Preševo - Niš Marsh. Yard	
PREŠEVO	Preševo - Tabanovce (IŽRSM)	
	Prijepolje Freight St Vrbnica -	¹⁾ for the trains not entering the
PRIJEPOLJE FREIGHT	Bijelo Polje (ŽICG)	Požega station
STATION	Prijepolje Freight St. – Požega	
	Prijepolje Freight St. – (Požega) ¹⁾ - Kraljevo	
PRIZREN	Traffic is temporarily regulated by UNMIK railways	
	Ruma - Novi Sad Marsh. Yard	
	Ruma - Belgrade Marsh.Yard	
RUMA	Ruma - Šabac	
	Ruma - Brasina	
	Ruma - Šid	
ROSZKE (MAV ZRT)	Roszke (MAV ZRT) - Horgoš - Subotica	
	Senta - Subotica Freight St.	
SENTA	Senta - Zrenjanin	
	Senta - Kikinda	
	Sombor - Subotica Freight St.	
SOMBOR	Sombor - Bogojevo	
	$Sombor - Vrbas^{1)}$	¹⁾ in both directions
STAMORA MORAVITA	Stamora Moravita (CFR SA) – Vršac	
(CFR SA)		
	Subotica Freight St Novi Sad Marsh. Yard	
	Subotica Freight St Senta	¹⁾ for the trains not entering the
SUBOTICA FREIGHT	Subotica Freight St Sombor	Senta station
STATION	Subotica Freight St. – Horgoš - Roszke	
STATION	(MAV ZRT)	
	Subotica Freight St. – (Senta) – Kikinda ¹⁾	
	Subotica Freight St. – (Senta) – Zrenjanin ¹⁾	
TABANOVCE (IŽRSM)	Tabanovce (IŽRSM) – Preševo	
TOVARNIK (HŽI)	Tovarnik (HŽI) – Šid	
ĐENERAL JANKOVIĆ	Traffic is temporarily regulated by UNMIK	
	railways	
ŠABAC	Šabac – Ruma	
ŠID	Šid - Ruma	
	Šid - Tovarnik (HŽI)	

NOTE: * For all trains not entering the Belgrade Marshalling Yard, the distribution station operations regarding the notification of traction unit staff on the introduced restricted speed runnings and any other announcements of importance for the traffic safety and regulation regarding the distribution sections toward the adjacent distribution stations are taken over by Ostružnica and Resnik stations.

** For all trains not entering the Lapovo Marshalling Yard, the distribution station operations regarding the notification of traction unit staff on the introduced restricted speed runnings and any other announcements of importance for the traffic safety and regulation regarding the distribution sections toward the adjacent distribution stations are taken over by Lapovo station.

*** Tomaševac station performs the distribution station operations regarding the notification of traction unit staff on the introduced restricted speed runnings and any other announcements of importance for the traffic safety and regulation regarding the distribution sections toward the adjacent distribution stations, as well as the distribution station operations regarding the regulation of train traffic on the railway lines that are not equipped with automatic block, interstation dependence and remote control devices, relating to train intersections and notification of train staff on the changes regarding the train intersections on Tomaševac – Pančevo Main Station and Tomaševac – Novi Sad Marshalling Yard distribution sections.



There are four marshalling yards on the network where most of the freight trains are formed and split-up, and these stations are at the same time the distribution stations: Belgrade Marshalling Yard, Lapovo Marshalling Yard, Niš Marshalling Yard and Novi Sad Marshalling Yard.

Due to the limited track capacities and the work organization, the train formation and splitting-up is **not permitted** at the following distribution stations: **Bogojevo**, **Dimitrovgrad**, **Preševo**, **Brasina**, **Šid**, **Mala Krsna and Zrenjanin**. The exception is Šid station where the formation of international freight trains and domestic feeder trains can be performed on the designated industrial sidings. The formation of trains at distribution stations Šabac and Požarevac can be performed only if these stations are loading/unloading stations for such trains.

Splitting up and formation of trains are also permitted at particular intermediate stations having the required track capacities: Velika Plana, Zrenjanin fabrika, Kragujevac, Kruševac, Radinac, Smederevo, Sremska Mitrovica, Crveni Krst and Čačak.

The following intermediate stations may also be the departure/terminal stations provided that they are at the same time the loading/unloading stations for such train: Adrovac, Aleksinac, Aleksandrovo predgrađe, Batočina, Brvenik, Valjevo, Vreoci, Grljan, Despotovac, Doljevac, Dragačevo, Elemir, Zvornik, Inđija, Jagodina, Kaona, Lazarevac, Leskovac, Majdanpek, Mataruška Banja, Odžaci, Pančevo Varoš, Pančevo Vojlovica, Paraćin, Petrovac Gložan, Pirot, Podbara, Prahovo, Prokuplje, Raška, Ristovac, Svilajnac, Svrljig, Stara Pazova, Stalać, Surčin, Ćuprija, Čoka, Užice freight station, Futog. The restriction relating to these stations also prescribes that it is not permitted to leave and gather wagons for the purposes of forming other trains.

If the RU requests that the departure/terminal station is the intermediate station that has not been listed, such requests will be considered separately and decisions will be made on such requests depending on the available infrastructure capacities and organization possibilities at the moment of the request submission.

Passenger train formation yards

Dispatching of passenger trains with classical units formed in the technical-passenger station Zemun is possible in Belgrade Center and Zemun stations. In Zemun station track No 11 is equipped with the ramp for loading and unloading of accompanied cars.

The dispatching stations for the EMU and DMU trains can be all stations for passenger traffic, depending on the available capacities and the traffic service hours.

Distribution station	Distribution section	Comments
1	1 2	
BEOGRAD CENTAR	Beograd Centar – Novi Sad	
	Beograd Centar – Ruma	
	Beograd Centar – Pančevo Main St.	
	Beograd Centar - Požega	
	Beograd Centar - Lapovo	
BIJELO POLJE (ŽICG)	Bijelo Polje (ŽICG) - Vrbnica - Prijepolje freight station	
BOGOJEVO	Bogojevo - Sombor Bogojevo - Novi Sad Bogojevo - Erdut (HŽI)	
VRŠAC	Vršac - Pančevo Main St. Vršac - Stamora Moravita (CFR SA)	
ERDUT (HŽI)	Erdut (HŽI) – Bogojevo	

Overview of distribution stations-sections for passenger trains operation



DIMITROVGRAD	Dimitrovgrad – Niš	
JIMBOLIA (CFR)	Jimbolia (CFR SA) - Kikinda	
	Zaječar – Niš	
ZAJEČAR	Zaječar - Prahovo Pristanište	
	Zaječar – Požarevac	
ZVORNIK	Zvornik – Šabac - Ruma	
Lionum	Zrenjanin - Kikinda	
	Zrenjanin - Novi Sad	
ZRENJANIN	Zrenjanin - Pančevo Main St.	
	Zrenjanin - Senta	
	Kikinda - Jimbolia (CFR SA)	
KIKINDA	Kikinda - Zrenjanin	
	Kikinda - Senta	
	Kraljevo – Kosovska Mitrovica Sever ¹	¹⁾ in both directions
	Kraljevo - Lapovo	in both uncertoins
KRALJEVO	Kraljevo - Požega	
	Kraljevo – Stalać ¹⁾	
	Lapovo – Belgrade Center	
	Lapovo - Kraljevo	
LAPOVO	Lapovo - Niš	
	Lapovo - Smederevo	
	Niš - Lapovo	
	Niš - Preševo	
NIŠ	Niš - Dimitrovgrad	¹⁾ in both directions
	Niš – Zaječar	
	Niš - Kuršumlija ¹⁾	
	Novi Sad – Beograd Centar	
	Novi Sad – Subotica	
	Novi Sad – Bogojevo	
NOVI SAD	Novi Sad – Vrbas ¹⁾	
	Novi Sad - Pančevo Main St.	
	Novi Sad – Zrenjanin	
	Novi Sad - Ruma	
PANČEVO MAIN	Pančevo Main St Zrenjanin	
STATION	Pančevo Main St Vršac	¹⁾ in both directions
	Pančevo Main St. – Beograd Centar	
	Pančevo Main St Pančevo Vojlov. ¹⁾	
	Pančevo Main St. – Novi Sad	
	Požarevac - Lapovo	
POŽAREVAC	Požarevac - Smederevo	
	Požarevac - Zaječar	
	Požarevac – Beograd Centar	
	Požega - Beograd Centar	
POŽEGA	Požega - Kraljevo	
	Požega - Prijepolje freight station	
PRAHOVO	Prahovo pristaništa Zaisčan	
PRAHOVO PRISTANIŠTE	Prahovo pristanište - Zaječar	
	Prijepolje freight station - Vrbnica -	
PRIJEPOLJE FREIGHT	Bijelo Polje (ŽICG)	
STATION	Prijepolje freight station - Požega	
v	Preševo - Niš	
PREŠEVO	Preševo – Tabanovce (IŽRSM)	
RUMA	Ruma - Šabac - Zvornik	
NUMA		l



	Ruma - Šid Ruma - Beograd Centar Ruma – Novi Sad	
ROSZKE (MAV ZRT)	Roszke (MAV ZRT)-Horgoš- Subotica	
SENTA	Senta – Subotica Senta – Zrenjanin Senta – Kikinda	
SMEDEREVO	Smederevo - Lapovo Smederevo - Požarevac	
SOMBOR	Sombor - Subotica Sombor - Bogojevo	
STAMOR MORAVITA (CFR SA)	Stamora Moravita (CFR SA) - Vršac	
SUBOTICA	Subotica - Novi Sad Subotica – Sombor Subotica - Senta Subotica - Horgoš - Roszke (MAV)	
TABANOVCE (IŽRSM)	Tabanovce (IŽRSM) - Preševo	
TOVARNIK (HŽI)	Tovarnik(HŽI) - Šid	
ŠABAC	Šabac - Ruma	
ŠID	Šid – Ruma Šid – Tovarnik (HŽI)	

7.3.5 Storage Sidings

IŽS network has the capacities for storing of rolling stock. Rolling stock storing services are provided by the IŽS.

Storing of standard passenger train sets, DMUs, EMUs and locomotives is carried out at all depots for accommodation and storing of rolling stock of "Srbija Kargo" JSC and "Srbijavoz" JSC.

Storing of freight wagons is carried out on special storage sidings for surplus freight wagons at marshalling yards Belgrade Marshalling Yard, Novi Sad Marshalling Yard, Niš Marshalling Yard, Lapovo Marshaling Yard, Subotica, Zaječar, Kikinda, Kraljevo, Pančevo Main St., Požega, Ruma and Sombor.

IŽS is not responsible for any damage which can occur on the rolling stock, that is, on the goods which is located in the stored wagons.

"Infrastructure of Serbian Railways" provides the service of storing of rolling stock to all interested railway undertakings which require storing of rolling stock, in a non-discriminatory manner and upon their request, and to the extent permitted by the infrastructure capacities.

7.3.6 Maintenance facilities

There are rolling stock maintenance facilities on IŽS network, but the maintenance services are not provided by "Infrastructure of Serbian Railways" JSC. Appendix 3.10. contains the details on the rolling stock maintenance facilities.

7.3.7 Other Technical Facilities, including Cleaning and Washing Facilities

"Infrastructure of Serbian Railways" provides the following basic services at technical facilities to railway undertakings in a non-discriminatory manner and upon their request:

Use of wagon scales in stations, where available, according to table 8 of this document;



- Fixed facilities for test braking in station Beograd Ranžirna (Belgrade Marshalling Yard);
- Use of freight loading/unloading ramp;
- Use of ramp for loading and unloading of accompanied cars;
- Use of loading clearance;
- Use of portal crane in Aleksinac station;

The need for using the basic services listed in bullets 1, 3, 4 and 5 must be presented by railway undertakings in the capacity allocation process, whereas the need for other services can be presented in a separate request.

More detailed information on provision of the above stated basic services can be obtained at:

"Infrastructure of Serbian Railways" JSC Traffic Department 6, Nemanjina St 11000 Belgrade, Serbia Tel.: +381 11 3618 214 Fax: +381 11 3616 814 E<u>-mail: sektor.sp@</u>srbrail.rs

"Infrastructure of Serbian Railways" does not have the special facilities and does not provide the services of rolling stock cleaning and washing.

Wagon scales

The list of stations in which are located wagon scales is given in the Table 8.

Table No. 8: Wagon scales

No.	Station	Carrying Capacity (t)	Length of weigh bridge (m)	NOTE:
1	Šid	100	20	Wagon scale is electronic.
2	Novi Sad Marshalling Yard	100	20	Wagon scale is electronic.
3	Pančevo main st.	100	20	Wagon scale is electronic.
4	Vršac	100	20	Wagon scale is electronic.
5	Zrenjanin Factory	100	20	Wagon scale is mechanic.
6	Subotica Freight St.	100	20	Wagon scale is electronic.
7	Sombor	100	20	Wagon scale is mechanic.
8	Niš Marshalling Yard	100	20	Wagon scale is electronic.
9	Požega	100	20	Wagon scale is electronic.
10	Čačak	80	15.5	Wagon scale is electronic.
11	Lapovo Marshalling St.	100	20	Wagon scale is electronic.
12	Belgrade Marshalling Yard	100	18	Wagon scale is electronic.
13	Dimitrovgrad	100	20	Wagon scale is electronic.

Fixed installations for brake control

Fixed installations for brake control are located at Beograd Marshalling Yard.

Cleaning and washing facilities

IŽS does not have special facilities for cleaning and washing of railway vehicles. The type, volume and place of cleaning of railway vehicles for passenger service are determined by the railway undertaking.

Other technical facilities

Ramps for loading and unloading of the load



"Infrastructure of Serbian Railways" JSC will enable usage of the ramps for loading and unloading of the load to all railway undertakings on the non-discriminatory way and upon their request. The need for usage of the ramps for loading and unloading of the load must be shown by the railway undertakings' in the capacity allocation procedure.

- Ramps for loading and unloading of the accompanied vehicles

Loading/unloading ramps for transport of accompanied vehicles are located in stations Zemun, Novi Sad, Subotica and Niš. The need for usage of the ramps for loading and unloading of the accompanied vehicles must be indicated by the railway undertakings in the capacity allocation procedure.

Loading gauge

Loading gauges that are in function are present at the following stations: Novi Sad Marshalling Yard, Vršac, Čačak, Požega, Dimitrovgrad, Jošanička Banja and Kragujevac.

On IŽS network there are more stations with loading gauges which are not in function currently. The correction of the list of loading gauges will be done upon putting malfunction loading gauges into the functional condition.

- Crane portal in Aleksinac station

Transfer station on the territory of IŽS is Aleksinac. Mobile portable crane PD 86 with capacity up to 32 t is used for transshipmenthipment.

Service for using of wagon scales

"Infrastructure of Serbian Railways" JSC provides the wagon scales services. The price for using the wagon scale amounts to 3,309.00 RSD/wagon without VAT.

Service of loading and unloading using the portal crane in Aleksinac station

The service of loading and unloading using the portal crane together with the staff of public railway Infrastructure Manager is defined by means of a separate contract concluded between the public railway Infrastructure Manager and the Railway Undertaking, i.e. the user of the said service.

Unit price for the use of portal crane for loading and unloading amounts to 150,00 RSD/net tonne of goods VAT exclusive.

IŽS is providing other basic services if required by the railway undertaking and subject to a special contract. Other basic services that can be provided are:

• manning of facilities

Manning of unmanned service points

Structure of manning of non-manned service points, upon the railway undertaking's request, consists of:

- manning of service points of public railway infrastructure manager upon the railway undertaking's request in function of traffic management or shunting movements in such service points outside the working hours for such service point, and
- manning of service points of the railway undertaking upon its request in function of traffic management or shunting movements in such service points because the railway undertaking does not possess adequate traffic staff.

Charge for manning of service points by traffic staff amounts to:

Work place	Train dispatcher	Switch operator
Price in RSD/hour VAT exclusive	1.236,00	955,00



Calculation for periods of manning of non-manned service points starts from the moment of takeover of service at the service point until the moment of handover of service for the purposes of train operation i.e. shunting movement of railway undertaking's train set, and in case of temporarily manned stations (station working hours with interruption) not taking into account the period when the station is manned during the working hours according to the timetable booklet.

In the stations where it is necessary to perform manning with the train dispatcher and the switch operator, the manning period is the same for both employees given the responsibility of both worker during the setting up of a train route.

7.3.8 Maritime and Inland Port Facilities

The following ports are connected to public railway network:

- Port area Novi Sad
- Operator: DP World AD Novi Sad, www.lukanovisad.rs

Information on the service facility are available at <u>https://www.dpworld.com/en/serbian/general-terms-and-conditions</u>

- Port area Smederevo Operator: HBIS GROUP Serbia Iron & Steel d.o.o. Beograd, <u>www.hbisserbia.rs</u>
- Port area Pančevo Operator: Port ''Dunav" AD Pančevo Granexport d.o.o.<u>www.granexport.rs</u> Specijalna luka d.o.o.

Information on the service facility are available at www.specijalnaluka.rs

- Port area Prahovo Operator: PD Elixir Prahovo, <u>https://www.elixirprahovo.rs</u>

Information on the service facility are available at <u>www.elixirprahovo.rs/logistika</u> and <u>www.elixirgroup.rs/usluge/logistika/luka-prahovo/</u>

- Port area Senta

Operator: Port Senta A.D.,

Information on the service facility are available at <u>www.luka-senta.rs</u>

- Port area Sremska Mitrovica
 Operator: RTC Luka Leget AD, <u>https://www.leget.rs</u>
- Port area Šabac
 - Operator: PD Elixir Zorka

Information on the service facility are available at <u>https://www.elixirzorka.rs</u> and <u>www.elixirgroup.rs/usluge/logistika/luka-sabac/</u>

7.3.9 Relief Facilities

IŽS has on its disposal a mobile relief facility – relief (auxiliary) train. The services of relief train in cases of remedying the consequences of accidents or incidents are provided by IŽS, using its relief trains and staff, located in Belgrade, Niš and Kraljevo. In order to use the relief train services, a Railway Undertaking must address IŽS in writing:

Center for relief train operations 6, Nemanjina St 11 000 Belgrade, Serbia Tel: +381 11 3620 899 Fax: +381 11 3620 899 Email: direktor.tkp@infrazs.rs



Price of services regarding the provision of relief assistance

The price for providing the basic service regarding the provision of relief assistance is determined based on the actual costs incurred during the provision of such service and it is applied in a non-discriminatory manner for all railway undertakings.

The price of transporting the relief train from the domicile station to the place of work and return to the domicile

No	Means of transport	Measuring unit	Price in RSD, VAT exclusive
1	Traction vehicle - locomotive of the operator – in operation, maneuver or expectation of operation		According to the operators bill
2	Vehicle of the working unit (ZOP, ETP, SP,) within "IŽS" – trolley, truck, etc.		According to the account of the working unit "IŽS" which performed transport
3	GEISMAR road-rail vehicle type V2R-730-S – road driving	hour	15.156,00
4	GEISMAR road-rail vehicle type V2R-730-S – railway driving	hour	18.156,00
5	Traction vehicle – locomotive "IŽS" or locomotive leased (locomotive operation + staff operation + energy) -in operation	hour	41.000,00
	-in expectation of operation	hour	15.000,00

Price for equipment and tools for the operation of relief (auxiliary) train

No	Asset description	Type of work	Measu ring unit	Price in RSD, VAT exclusive
1	Relief train	Expecting of work	hour	2.000,00
2	Relief train	Work on preparation and retrieval of intervention equipment	hour	4.000,00
3	GEISMAR road-rail vehicle type V2R-730- S	Work during intervention	hour	15.156,00
4	Jack EDK 1000 (99 72 9 471 001-4)	Expecting of work	hour	5.000,00
5	Jack EDK 300 (99 72 9 471 101-2)	Expecting of work	hour	5.000,00
6	Jack DHPD 65 (99 72 9 571 001-3)	Expecting of work	hour	5.000,00
7	Jack EDK 1000 (99 72 9 471 001-4)	Preparation, Work, Retrieval	hour	56.970,00
8	Jack EDK 300 (99 72 9 471 101-2)	Preparation, Work, Retrieval	hour	27.248,00
9	Jack DHPD 65 (99 72 9 571 001-3)	Preparation, Work, Retrieval	hour	30.146,00
10	LUKAS equipment	Preparation, Work, Retrieval	hour	7.066,00
11	WALTER trolley	Installation and removal	hour	6.000,00



12	WALTER trolley	Transport	hour	3.320,00
13	WALTER trolley	Remaining of trolley under the rolling stock – lump sum	hour	600,00
14	Stable power generation unit	Work	hour	2.400,00

Note: operating time is calculated in full hours – each started working hour of equipment and assets is counted as a full working hour.

Labour costs for relief train's staff

No	Type of work	Measur ing unit	Price in RSD VAT exclusive
1	Assistant on relief train	hour	704,00
2	Electromechanic	hour	981,00
3	Driver and operator of a two-way motor vehicle	hour	1.016,00
4	Rail crane operator	hour	1.027,00
5	Hydraulic equipment operator	hour	1.027,00
6	Locksmith on the relief train	hour	1.027,00
7	Rail vehicle mechanic	hour	1.027,00
8	Relief train manager	hour	1.126,00
9	Expert associate for circuit inspection	hour	1.175,00
10	Assistant relief train chief	hour	1.282,00
11	Relief train chief	hour	1.605,00
12	Employees participating in the work of relief train	pcs	1.800,00

Note: operating time is calculated in full hours – each started working hour is counted as a full working hour.

7.3.10 Refuelling Facilities

"Infrastructure of Serbian Railways" JSC is providing the services of fuel storing and issuing for refuelling of traction vehicles of all railway undertakings.

This relates to refuelling facilities at service points – stations and depots: Pančevo main St., Lapovo, Kraljevo, Požarevac, Požega, Sombor, Kikinda, Belgrade Marshalling Yard, Crveni Krst, Ruma, Zaječar, Zrenjanin, Vršac and Subotica.

Detailed information on the services of fuel storing and issuing for refuelling of traction vehicles are available at:

Department for Procurement and Central Warehousing 6, Nemanjina St 11 000 Belgrade, Serbia Tel: +381 11 3620 094 Email: nabavke.infra@srbrail.rs

Price for the service of storing and refuelling

The price for the service of fuel storing and issuing for the purposes of refuelling of traction vehicles of all railway undertakings is determined based on the actual costs incurred during the provision of this service and is applied in a non-discriminatory manner for all railway undertakings.

The service of fuel storing and issuing for the purposes of refuelling of traction vehicles amounts to 5.43 RSD per stored litre of diesel fuel VAT exclusive.




APPENDICES

- 1. Organizational chart of "Infrastructure of Serbian Railways" JSC
- 2. Internal regulations (documents) and technological procedures
- 3.1 Loading gauge JŽ I
- 3.2 Loading gauge UIC-GA
- 3.3 Loading gauge UIC-GB
- 3.3a Loading gauge UIC-GC
- 3.4 Electrified lines
- 3.5 Power supply facilities
- 3.6 Overview of signalling & safety devices equipping level
- 3.7 Overview of telecommunication devices equipping level
- 3.8 List of stations with industrial sidings on which it is possible to handle dangerous goods (RID goods)
- 3.8 b List of service points where it is possible to perform transshipment of dangerous goods
- 3.9 Alternative transport routes
- 3.10 Facilities for rolling stock maintenance
- 3.11 Railway infrastructure development projects
- 4.1 Request for train path allocation (form)
- 4.1.b Template for submission of traction vehicle technical data
- 4.2 Instructions for completion of Request for train path allocation (form)
- 4.3 Deadlines for annual 2024/2025 Timetable preparation
- 4.4 Deadlines for amendment of annual 2024/2025 Timetable

5.1. Overview of railway lines on which train running is possible when they are manned only with engine driver

- 5.2. Overview of the lines fulfilling the conditions for train running with an engine driver only
- 5.3. Geometry of pantograph (current collector) TYPE POS 254/III used on IŽS network
- 6. Register of infrastructure data
- 7. Overview of primary train delay causes
- 8. Overview of platforms and arranged surfaces in service points
- 9. Method for calculation of electricity consumption for train traction
- 10. Railway node boundaries





Appendix 1: Organizational chart of "Infrastructure of Serbian Railways" JSC



Appendix 2: Internal regulations (documents) and technological procedures


The internal regulations (documents) and the technological procedures applied by IŽS are listed in the Registry of regulations of importance for traffic safety i.e. in item 1.3 Internal general regulations of "Infrastructure of Serbian Railways" JSC.

The registry of regulations of importance for traffic safety is published on the web site of "Infrastructure of Serbian Railways" JSC in section About us/Library/Regulations/Safety Management System/Appendices to the Safety Management System Rules of Operation/Appendix 12.1 Library- Registry of regulations (О нама/Библиотека/Правиници/Систем управљања безбедношћу/Прилози Пословника система управљања безбедношћу/ Прилог 12.1 Библиотека-Регистар прописа).

Available on link https://infrazs.rs/izs-osnovni-podaci/biblioteka




Appendix 3.1. Loading Gauge ŽS I






Appendix 3.2. Loading Gauge UIC-GA






Appendix 3.3. Loading Gauge UIC-GB





Appendix 3.3a Loading Gauge UIC-GC



- A Pantograph movement space
- B-Area for positioning of platforms according to leaflet UIC 505-4, for the speeds of up to 200 km/h
- C Possibility of reserving the space for low platforms and specific installations



Appendix 3.4. Electrified lines

Main lines:

- 1. Beograd Centar Stara Pazova Šid State Border (Tovarnik)
- 2. Beograd Centar Rasputnica G Rakovica Mladenovac Lapovo Niš Preševo State Border (Tabanovce)
- 3. (Beograd Centar) Rakovica Jajinci Mala Krsna Velika Plana
- 4. (Jagodina) Rasputnica Ćuprija Ćuprija Paraćin
- 5. (Beograd Centar) Stara Pazova Novi Sad Subotica State Border (Kelebia)
- 6. Niš Dimitrovgrad State Border (Dragoman):
 - electrified on section Dimitrovgrad State Border
- 7. Beograd Centar Pančevo Main St. Vršac State Border (Stamora Moravita):
 ➢ electrified on section Beograd Centar Pančevo varoš
- 8. (Beograd Centar) Resnik Požega Vrbnica State Border (Bijelo Polje)
- 9. Beograd Marshalling yard "A" Ostružnica Batajnica
- 10. Beograd Marshalling yard "B" Ostružnica
- 11. Beograd Marshalling yard "A" Rasputnica "B" Rasputnica "K/K1" Resnik
- 12. Ostružnica Rasputnica "B" (Rasputnica "K/K1")
- 13. Beograd Marshalling yard "B" Rasputnica "R" Rasputnica "A" (Resnik)
- 14. (Beograd Marshalling yard "B") Rasputnica "R" Rakovica
- 15. Beograd Marshalling yard "A" Rasputnica "T" Rakovica
- 16. Beograd Marshalling yard "B" Rasputnica "T" (Rakovica)

17. connecting track in the area of Rasputnica "K/K1": (Rasputnica "B") - skretica "K" - skretnica "K1" - (Jajinci)

- 18. (Rasputnica Pančevački most) Rasputnica Karađorđev park Rasputnica Dedinje (Rasputnica G)
- 19. Inđija Golubinci
- 20. Novi Sad Novi Sad Marshalling yard Rasputnica Sajlovo
- 21. bypass track of station Mala Krsna: (Kolari) branching turnout 1 branching turnout 28 (Osipaonica)
- 22. Rasputnica Lapovo Varoš Lapovo Marshalling yard Lapovo
- 23. Trupale Niš Marshalling yard Međurovo
- 24. Crveni krst Niš Marshalling yard
- 25. Niš Rasputnica most (Niš Marshalling yard)

Regional lines:

- 1. Novi Sad Odžaci Bogojevo:
 - electrified on section Novi Sad Sajlovo
- 2. Stalać Kraljevo Požega:
 - electrified on section Kraljevo Požega

3. connecting track to station Požega: (Uzići) – branching turnout No 53 - branching turnout No 54 - (Dragačevo)

- 4. Smederevo Rasputnica Jezava Radinac Mala Krsna
- 5. Mala Krsna Bor Rasputnica 2 (Vražogrnac):
 - electrified on section Mala Krsna Požarevac
- 6. Subotica Horgoš State Border (Röszke)

Local lines:

- 1. Novi Sad Novi Sad ložionica:
 - electrified on section Novi Sad Blok 3 Novi Sad
- 2. Pančevo Varoš Pančevo Vojlovica



Appendix 3.5 Power supply facilities

No	Excilition	Chainaga
No	Facilities	Chainage
	ne 101 Beograd Centar – Stara Pazova – Šid – State Border– (Tovarnik)	
1.	PS Beograd Centar	000+000
2.	EVP Zemun	008+052
3.	PSN Batajnica	021+970
4.	PS Stara Pazova	034+794
5.	PS Putinci	053+600
6.	PSN Ruma	066+245
7.	PS Sremska Mitrovica	081+700
8.	EVP Martinci	094+200
9.	PS Kukujevci	105+000
10.	PS Šid	116+400
	ine 102 Beograd Centar – Mladenovac – Lapovo – Niš – Preše	vo – State Border–
(Tabano		007.726
11.	PSN Košutnjak	007+726
12.	PS Rakovica	008+656
13.	PS Kijevo	010+128
14.	EVP Resnik	014+020
15.	PS Klenje	024+800
16.	PSN Ralja	032+340
17.	PS Sopot Kosmajski	041+565
18.	EVP Mladenovac	053+100
19.	PS Glibovac	074+000
20.	PSN Mala Plana	084+350
21.	PS Plana	089+700
22.	EVP Markovac	099+345
23.	PS Lapovo Varoš	106+309
24.	PS Lapovo Putnička	109+207
25.	PSN Bagrdan	119+122
26.	EVP Jagodina	136+262
27.	PS Ćuprija	148+200
28.	PS Paraćin	154+971
29.	PSN Sikirica	165+025
30.	PS Stalać	176+154
31.	PS Braljina	186+600
32.	EVP Đunis	195+130
33.	PS Korman	205+540
34.	PS Aleksinac	214+077
35.	PSN Grejač	223+479
36.	PS Trupale	234+104
37.	PS Niš	243+287
38.	EVP Niš	248+755
39.	PS Doljevac	261+410
40.	PSN Pečenjevce	276+752
41.	PS Leskovac	287+910
42.	EVP Grdelica	300+580
43.	PS Džep	319+561
44.	PSN Suva Morava	332+860
45.	PS Vranjska Banja	347+765
46.	EVP Ristovac	365+370
47.	PS Bukarevac	386+617



48.	PSN Tabanovci	400+060
	Line 103 (Beograd Centar) – Rakovica – Jajinci – Mala Krsna – Velik	
49.	PS Beli Potok	017+800
50.	PSN Vrčin	026+400
50.	PS Mali Požarevac	042+800
52.	EVP Vodanj	042+800
53.	PS Mala Krsna	070+600
54.	PSN Lozovik	070+000
	Line 105 (Beograd Centar) – Stara Pazova – Novi Sad – Subotica – St	
55.	EVP Inđija	041+984
56.	PSN Beška	053+905
57.	PS Sremski Karlovci	065+685
57.	EVP Novi Sad	003+085
<u> </u>	PS Kisač	
		090+600
60.	PSN Zmajevo	102+600
61.	EVP Vrbas	119+480
62.	PS Lovćenac	129+637
63.	PSN Bačka Topola	143+850
64.	PS Žednik	157+620
65.	EVP Subotica	167+920
66.	PS Subotica	177+180
67.	PSN Subotica	184+450
	Line 107 Beograd Centar – Pančevo Main St. – Vršac – State Border–	
69.	PS Beograd Centar	000+000
70.	PS Pančevački Most	004+687
Main 1	Line 108 (Beograd Centar) – Resnik – Požega – Vrbnica – State Borde	er– (Bijelo Polje)
71.	PS Barajevo	015+420
72.	PSN Stepojevac	029+610
73.	PS Lazarevac	045+310
74.	EVP Slovac	059+248
75.	PS Valjevo	077+905
76.	PSN Lastra	093+056
77.	PS Ražana	111+239
78.	EVP Kosjerić	118+229
79.	PS Požega	140+420
80.	PSN Uzići	150+295
81.	PS Užice – teretna	162+319
82.	EVP Sušica	178+379
83.	PS Zlatibor	193+407
84.	PSN Jablanica	206+350
85.	PS Priboj	225+338
86.	EVP Pribojska Banja	232+750
87.	PS Bistrica	241+248
88.	PSN Prijepolje	257+226
89.	PS Lučica	264+695
90.	EVP Brodarevo	273+360
91.	PS Vrbnica	285+096
	Line 111 Beograd Marshalling yard "A" – Ostružnica – Batajnica	
92.	PS Železnik – ulaz	001+290
93.	PS Železnik – izlaz	002+615
94.	PSN Surčin	013+485
7 T.	1 51 , 541 em	0101700



Regiona	l Line 213 Stalać – Kraljevo – Požega	
95.	EVP Kraljevo	080+565
96.	PSN Ovčar Banja	120+900
	Regional railway line 201 Subotica - Horgoš - State Border -	
	(Röszke)	
97.	PS Bački Vinogradi	15+717

Remote	control centers	
98.	Centar DU Beograd	M2: 005+145
99.	Centar DU Niš	M2: 243+560
100.	Centar DU Novi Sad	M4: 078+038

Abbreviations:

EVP - Electric traction substation

PSN - Track sectioning post with neutral line

PS - Track sectioning post

CDU - Remote control center



Appendix 3.6 Overview of signaling & safety devices equipping level

	dunu pu uo	10	ţ	Γ		Π		Π				Π	Π	Τ	Π		Π			Τ	Τ		Τ	Τ	Τ		Τ	Γ	Π	Τ		Τ	T	Τ		Π		Π	Τ	Τ	Τ			T
s	qmund on the mund of the structure of th	urmouts									-				\parallel		$\ $					+	+	-	+	_			H	+		+	8						_		-	┝		ł
ling yard	thornal for graning of furnout		64																										\parallel			4									_			ļ
Devices in marshalling yards	Automatic positioning of mmout on the hump		77													55								_																				
Device	Marshalling yards without automatic marshalling	OI SIAHORS	17													1														-														
-	Marshalling yards with automatic marshalling	Number	707							_																																		
Signal equipped	Mechanicalsignal	Dalises	61														Ц																											ļ
Signal	Linght signal	NO OI	61		363	170	187		111	203			9	0 II	2	9	2	2	2		•	9	7			4		2	14	-														4
thor	Mechanical signal	RIIS 17	1				7	20			30	16																				4	4 00	2	s	8	Ξ			6	П			ļ
al type	Light signal	Igis IO	217	1.04	196	66	73	e	103	177	12	13	2	• -		4	2	1	-	-		_		-	m	4	- 4		28	2	m	\downarrow	=	;	ŝ	7	4	-		14	43			ľ
Sign	Mechanical signal	Number	7		2004		5	20	19		37	49			Ц		Ц		Ц		\downarrow	_	_	\downarrow	_		+		Ц	╞		4	11	7	-	~	Π	Ц		10	Π		L	ļ
-	langis Mai J	2 17	187	404	419	160	292	25	113	307	20	18	9	21	5	9	2	2	2		0	0	7	-	0	4	- +	5	48	0	4	\downarrow	-1	11	16	15	∞			23	64		\vdash	
out heating	Cas	Er of turnout	2																			_		_	4		+																	ļ
Tum	Electrical	odmun	40	4	196	79	85		79	104						-					Ľ	m				2			e	-	1	e.												ľ
Ń	d guide control and interlocking b means of turmout lock	11	92		180		138		87		247	83				15									39+6		77		36				12	667	32	66	73	2		92	195			00
rlocking	by means of electrical controller	urnouts	0T				25																																					
Turnout inte	Z interlocking by means of mechanical devices	Number of 1	6				4		8			63																				,	4		7		∞							
9	Central control desk and interlocking by means of electrical positioning devices	•	341	140	639	151	171		116	306	16	19		32	2				-	3	132	°				4			44	100	4		г	1	19	6				8	22			~~
4	Mechanical devices without signal turnout dependence	r	-				1	9	5		15													T	1		T						- 0	6	9	3	~			2	1			t
	Electrical devices without signal- turnout dependence	SUOL			1		2	12	1		4	1												2	-		-						"	n	-	2	-			7	-			Ī
ų	Electrical-mechanical devices wit signal-turnout dependence	imber of sta	0		1			27	1		1	8													2				1				1		1		2			2	7			
	gniacomplete relay interlocking	NN F	+																																-									Ī
10	Complete interlocking with relay electronic devices	~	51	-	55	15	17	2	5	34	2	1		2		1				1	- ,	-							2	-	Т		-		-	1				1	8			
	RAILWAY LINES	c	2 Beograd - Stara Pazova - Šid - State Border - (Tovamik)	Beograd - Mladenovac - Labovo - Niš - Preševo - State Border -	tantor allog of an an order an order	(Beograd) - Rakovica - Jajinci - Mala Krsna - Velika Plana	tara Pazova - Novi Sad - Subotica - State Border -	viš - Dimitrovgrad - State Border - (Dragoman)	Beograd Centar - Pančevo glavna stanica - Vršac - State Border - (Stamora Moravita)	(Beograd) - Resnik - Požega - Vrbnica - State Border - (Bijelo Polje)	apovo - Kraljevo - Lešak - Kosovo Polje - Đeneral Janković - State	Subotica - Bogojevo - State Border - (Erdut)	Beograd Centar - Novi Beograd	Beograd Centar - Kasputnica G - (Rakovica) Beograd Ranžirna "A" - Ostružnica - Batainica	virna "B" - Ostružnica	Beograd Ranžirna "A" - Rasputnica "B" - Rasputnica "K/K1" - Resnik	Ostružnica - Rasputnica "B" - (Rasputnica "K/K1")	Beograd Ranžirna "B" - Rasputnica "R" - Rasputnica "A" - (Resnik)	žirna "B") - Rasputnica "R" - Rakovica	Beograd Ranžima "A" - Rasputnica "T" - Rakovica	Beograd Kanzirna "B" - Rasputnica "1" - (Rakovica) vezni kolosek na područiu Rasputnice "K/K1": (Rasputnica "B") -	skretnica "K" - skretnica "K1" - (Jajinci)	Topčider - Rasputnica Savski most - (Novi Beograd) Topčider - Beograd spoljna - Beograd Dunav - Rasputnica Pančevački	ek stanice Beoerad Spolina: (Topčider) - Blok 1 "Obala" -	Blok 2 "Prelaz" - (Beograd donji grad)	(kasputnica Paneevaeki most) - Kasputnica Karadordev park - Rasputnica Dedinje - (Rasputnica G)	Indija - Golubinci Novi Sad - Novi Sad Ranžirna - Rasputnica Sailovo	obilazni kolosek stanice Mala Krstwa: (Kolari) - odvojna skretnica 1 - odvojna skretnica 78 - (Osinannica)	Rasputnica Lapovo Varoš - Lapovo ranžirna - Lapovo	ranzuna - Medurovo Viš ranžirna	Niš - Rasputnica most - (Niš ranžima) Snoini kolosek stanice Niš (Creeni krst) - odvoina skretnica 2 - odvoina	Ćele kula).	Subolica - Horgos - State Border - (Koszke) Daučeno Glarme etanica - Zmaianin - Vibinda - State Border - (Timbolia)	na stanica - zaciijanni - Kikinda - State Dotuci - (Jimbona	Banatsko Miloševo - Senta - Subotica Pančevo Varoč - Paeminica 2a - /Jahuka)	rancevo vanos - raspumua za - Januna) Novi Sad - Odžaci - Bogojevo	(Novi Sad) - Rasputnica Sajlovo - Rimski šančevi - Orlovat stajalište	- Sajlovo	Orlovat - Rasputnica 1a - (Lukićevo) Ruma - Čabac - Pasentrica Donia Borina - State Border - (Zvornik		(Platičevo) - Rasputnica 1 - Rasputnica 3 - (Stitar) Stalać - Kraljevo - Požega	spojni kolosek stanice Kraljevo: (Mataruška Banja) - odvojna skretnica broi 72 - odvoina skretnica broi 73 - (Adrani)	oroj ze osrojna suscina oroj 22. vromuj spojni kolosek stanice Požega: (Uziči) - odvojna skretnica broj 53 - odvojna skretnica broj 54 - (Dranačevo)	DICA DIOL 24 - (L/JARACCYO)
			Beoorad - Sta	Beograd - MI.	(Tabanovce)	(Beograd) - R	(Beograd) - S (Kelehia)	Niš - Dimitro	Beograd Centar - Pa (Stamora Moravita)	(Beograd) - R	Lapovo - Kraljevo Border - (Voltorio)	Subotica - Bo	Beograd Cen	Beograd Cen	Beograd Rank	Beograd Ran	Ostružnica - I	Beograd Ran	(Beograd Rar	Beograd Ran	vezni kolosek	skretnica "K"	Topčider - R: Topčider - Be	most obilazni kolos	Blok 2 "Prela	(Kasputnica I Rasputnica D	Indija - Golub Novi Sad - No	obilazni kolo. Advoina skret	Rasputnica L.	I rupale - Nis ranžirna - N Crveni krst - Niš ranžirna	Niš - Rasputi Snoini kolose	skretnica 4 - (Ćele kula)	Pančeno Glarina et	ranceo ora	Banatsko Mil	Novi Sad - O	(Novi Sad) - I		Orlovat - Ras	Novi)	(Platičevo) - Stalać - Kralj	spojni kolose aroj 72 - odve	spojni kolose.	OdVUIEI SPISI
	Railway Line No	-	101	_	102	103	104	105 1	106	107 (108	109		112	113	114	115 (116	117	118	_	~	121		28	31	125 1	-	128	129		132	1 000	_	203 1	-	206 (-	_	_	211 5	212	213	
	oN	-			2	ю	4	5	9	7	~	9	10	12	13	14	15	16	17	18	19	50	21	1	53	24	25	27	28	30	31	32	33	t	35	37	38	39	40	41	43	44	45	2



Operation Operation Operation Operation 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0
Image: Second	•
Automatic positioning of human and h	
	22
bioditv zbrez garilfadzaem olikationali i i i i i i i i i i i i i i i i i i	5
aufilearen olianaria autor a artiku zarte artiku z	•
	•
Signal equipped No No No No 19 19 19 19 19	1212
Openation Openation <t< td=""><td>263</td></t<>	263
2	1 1 338 1217
	2123
American	•
	630
∞ ∞ </td <td>1 7 4 4 2574</td>	1 7 4 4 2574
E D E D E D E D E D E D E D E D E D E D	31
¹ Central control desk and ∞ → ∞ ∞ → ∞	103
+ Central control desk and Central control desk and S ⊼ S ∞ interlocking by means of electrical positioning devices	2349
-Instruction size of the second secon	
+	55
- - <td>09</td>	09
	~
Image: Second	187
RAIL WAY LINES 2 Mala Krsm - Bor - Rasputnica 2 - (Vražognuc) Creeni kust - Zaječar - Prahovo pristamište Creeni kust - Zaječar - Prahovo pristamište Creeni kust - Zaječar - Prahovo pristamište Creeni kust - Zaječar - Prashovo pristamište Creeni kust - Zaječar - Prashovo pristamište Creeni kust - Zaječar - Prashovo pristamište Kuisumlija - Kastrat Kuisumlija - Kastrat Kuisumlija - Kastrat Kosovo Polje	(Višajičevo) - Raspunica Rača - Šremska Rača Paračin - Stari Popovač Surčin - Jakovo Bečmen (Beograd spoljnu) - km 2+290 odvojna skretnica - Fabrika šečera Šarganska osmiča - Torai: Torai:
Maha Krsma - Bo Maha Krsma - Bo Croeni krst - Zaji (Egotina) - Kara Kutishmilja - Kara Kutishmilja - Kara Kanovi Sado - Subolica - Subolica - Subolica Subolica - Subolica - Subolica - Subolica Subolica - Subolica - Subolica - Subolica Subolica - Subolica - Subolica Subolica - Subolica - Subolica - Kanovi Sado - Raspo Randora - Raspa Randora - Raspa Sectani - Jaša Ton Sectani - Jaša Ton Sectani - Jaša Ton Sectani - Jaša Ton Sectani - Jaša Ton Coda - Notisa Mathowa - Respu Mathowa - Respu Ma	(Vi: Parz Surd (Bed Šarg
Algo Algo Railwarg Line 1a 1a 1a 215 216 Creeni k. 217 Rosona 218 Rosona 219 Kursumi 210 Subotica 211 Rosona 212 Rosona 213 Rosona 214 Rosona 215 Kursumi 216 Subotica 217 Rosona 218 Rosona 301 Subotica 301 Rumski š 301 Rumski š 311 Back- Ka 313 Back- Ka 314 Rumski š 315 Rumova 316 Rumski š 317 Rumski š 318 Reformat 319 Rumski š 310 Souni 311 Rumski š 312 Rumova 313	410 (Viš 411 Para 412 Surč 413 (Bec 501 Šarg



											INTER	LOCKI	NG FAC	TLITIE	s								
													Level	crossing	safety c	levices							
			Intersta	tion deper device	ndence		Autor	matic b	oloc		Auton		itioning o sings	of level	Mam	ual positi cross	ioning ol sings	flevel	Traf	fic remote	contro	l devi	ices
		RAILWAY LINE	line	k line	oetween	line	k line	its		uipped with	ba	arrier or rier adinal		colour ignals	elect dev	trical ices	1000000000	anical rices	line	k line	ntrol centers	ntrol stations	ontrolled
No	Railway Line No		Length of single track line	Length of double track line	Number of distances between stations	Length of signle track line	Ength of double track line	Number of block points	Number of signals	Number of signals equipped with auto-stop devices	in station	on track	in station	on track	in station	on track	in station	on track	Length of signle track line	Length of double track line	Number of remote control centers	Number of remote control stations	Number of remotely controlled stations
1	la	2	3	4	5	6	7	8	9	10	11	12	pcs 13	14	15	16	17	18	к 19	20	21	pcs 22	23
1	101	Beograd - Stara Pazova - Šid - državna granica - (Tovarnik)						61	120	120	14	12								97+918	1	5	6
2	102	Beograd - Mladenovac - Lapovo - Niš - Preševo - državna granica - (Tabanovce)	6+000		1		14+150	195	443	289	37	53	1	1	2		8	4			2	38	15
3	103	(Beograd) - Rakovica - Jajinci - Mala Krsna - Velika Plana				93+143		41	81	81	11	3					1				1	12	4
4	104	(Beograd) - Stara Pazova - Novi Sad - Subotica - državna granica - (Kelebia)	15+020		4	133+722		61	121	121	15	8			2	1	1	2					
5	105	Niš - Dimitrovgrad - državna granica - (Dragoman Beograd Centar - Pančevo glavna stanica - Vršac -				16+100		6	11		5	7			3	4	7	4					
6	106	državna granica - (Stamora Moravita) (Beograd) - Resnik - Požega - Vrbnica - državna	82+200	19+070	14		19+600	10	26	26	4	2					8	1				1000	
7	107	granica - (Bijelo Polje) Lapovo - Kraljevo - Lešak - Kosovo Polje - Đeneral	287+013		33				-		3	9	1	15					287+013		1	26	9
8	108 109	Janković - državna granica - (Volkovo Subotica - Bogojevo - državna granica - (Erdut	69+820		11						3	5	2		1		7	4					┝──
10	110	Beograd Centar - Novi Beograd	09+820				2+887	2	4	4		5	1					10					
11 12		Beograd Centar - Rasputnica G - (Rakovica Beograd Ranžima "A" - Ostružnica - Batajnica				25+658	4+416	4	8 26	8 26	1	1									1		2
13	113 114	Beograd Ranžima "B" - Ostružnica Beograd Ranžima "A" - Rasputnica "B" - Rasputnica	1			5+902 10+419		2	2 8	2 8	1				2		1					1	1
14 15	115	"K/K1" - Resnik Ostružnica - Rasputnica "B" - (Rasputnica "K/K1")				2+121		1	2	2													
16	116	Beograd Ranžirna "B" - Rasputnica "R" - Rasputnica "A" - (Resnik)				4+538		2	2	2													
17 18	117 118	(Beograd Ranžirna "B") - Rasputnica "R" - Rakovica Beograd Ranžirna "A" - Rasputnica "T" - Rakovica				1+149 0+709																	<u> </u>
19	119	Beograd Ranžima "B" - Rasputnica "T" - (Rakovica) vezni kolosek na području Rasputnice "K/K1":				8+379		3	5	5	-												_
20	120	(Rasputnica "B") - skretnica "K" - skretnica "K1" - (Jajinci)				0+463																	
21	121 122	Topčider - Rasputnica Savski most - (Novi Beograd Topčider - Beograd spoljna - Beograd Durav - Rasputnica Pančevački mosi				3+578 6+257	4+519	1	1		-					1	0	0					
23	123	obilazni kolosek stanice Beograd Spoljna: (Topčider) - Blok 1 "Obala" - Blok 2 "Prelaz" - (Beograd donji grad)	71			1+757											1						
24	124	(Rasputnica Pančevački most) - Rasputnica Karadorđev park - Rasputnica Dedinje - (Rasputnica G)					1+591														c		
25		Indija - Golubinci	4+020		1 2	4+020		2	4	4		_											
20		Novi Sad - Novi Sad Ranžirna - Rasputnica Sajlovo obilazni kolosek stanice Mala Krsna: (Kolari) - odvojna	3+749		2	21207																	
27	127	skretnica 1 - odvojna skretnica 28 - (Osipaonica)				2+387					1												
28		Rasputnica Lapovo Varoš - Lapovo ranžirna - Lapovo					3+788																
29 30	130	Trupale - Niš ranžirna - Međurovo Crveni krst - Niš ranžirna				1+220 17+100	1	2	3	1													
31	131 132	Niš - Rasputnica most - (Niš ranžirna) Spojni kolosek stanice Niš: (Crveni krst) - odvojna			-	4+990 0+500		4	7		1	1 2	-					-				\vdash	
32 33		skretnica 2 - odvojna skretnica 4 - (Ćele kula) Subotica - Horgoš - državna granica - (Roszke)	24+351		5						3	-					2	2					
34	202	Pančevo Glavna stanica - Zrenjanin - Kikinda - državna granica - (Jimbolia)	1517518		14						4	10			1		11	4					
35 36		Banatsko Miloševo - Senta - Subotica Pančevo Varoš - Rasputnica 2a - (Jabuka)	80+264 1+600		14 1							1					2	2					
37	205	Novi Sad - Odžaci - Bogojevc (Novi Sad) - Rasputnica Sajlovo - Rimski šančevi -	89+457		10				-	-		1			1		7	4			_		—
38 39	206 207	Orlovat stajalište Novi Sad Ranžirna - Sajlovo Rasputnica	65+405 2+502		11						<u> </u>	1					4	3					<u> </u>
40	208	Orlovat - Rasputnica 1a - (Lukićevo) Ruma - Šabac - Rasputnica Donja Borina - državna	0+630		1																		
41	209	granica - (Zvornik Novi)				101+951				L	<u> </u>	3			4	3	3	6					<u> </u>
	210	(Platičevo) - Rasputnica 1 - Rasputnica 3 - (Štitar) Stalać - Kraljevo - Požega				135+733						2	1		2		4	5					
43		spojni kolosek stanice Kraljevo: (Mataruška Banja) - odvojna skretnica broj 72 - odvojna skretnica broj 73 -																					
44	213	(Adrani) spojni kolosek stanice Požega: (Uzići) - odvojna skretnica broj 53 - odvojna skretnica broj 54 -																					
45 46		(Dragačevo) Smederevo - Mala Krsna				11+742					1		1		1		2	2					
48	216	Mala Krsna - Bor - Rasputnica 2 - (Vražogrnac) Crveni krst - Zaječar - Prahovo pristanište										1			1		7	1					
49	217	(Rgotina) - Rasputnica 3 - Rasputnica 1 - (Trnavac) Doljevac - Kastrat - Kosovo Polje			<u> </u>				F						1							\square	\square
		Kuršumlija - Kastrat																					



											INTER	LOCKI	NG FAG	ILITIE	S								
						[levices							
Image: Note: Image: Note:<			Intersta		ndence		Auto	matic h	loc		Auton	natic nee					ioning of	floval	Trat	fic remote	contro	l devi	ces
2 3 Im Im <td></td> <td></td> <td></td> <td>device</td> <td></td> <td></td> <td>Auto</td> <td>matic 0</td> <td></td> <td></td> <td>Auton</td> <td></td> <td></td> <td>of level</td> <td>Man</td> <td></td> <td></td> <td>lievei</td> <td>110</td> <td>ne remote</td> <td>contro</td> <td>Idevi</td> <td></td>				device			Auto	matic 0			Auton			of level	Man			lievei	110	ne remote	contro	Idevi	
2 3 Im Im <td></td> <td>RAILWAY LINE</td> <td>line</td> <td>k line</td> <td>oetween</td> <td>line</td> <td>k line</td> <td>its</td> <td></td> <td>uipped with</td> <td>ba</td> <td>rier</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>line</td> <td>k line</td> <td>ntrol centers</td> <td>ntrol stations</td> <td>controlled</td>		RAILWAY LINE	line	k line	oetween	line	k line	its		uipped with	ba	rier							line	k line	ntrol centers	ntrol stations	controlled
1 1 <td>o ailway Line No</td> <td></td> <td>н</td> <td>I</td> <td></td> <td>н</td> <td>Г</td> <td>Number of block poin</td> <td>Number of signals</td> <td>Number of signals eq auto-stop devices</td> <td>in station</td> <td>on track</td> <td></td> <td>on track</td> <td>in station</td> <td>on track</td> <td>in station</td> <td>on track</td> <td>-</td> <td></td> <td>Number of remote co</td> <td></td> <td>Number of remotely or stations</td>	o ailway Line No		н	I		н	Г	Number of block poin	Number of signals	Number of signals eq auto-stop devices	in station	on track		on track	in station	on track	in station	on track	-		Number of remote co		Number of remotely or stations
51 20 [Index 0-1.segnetics 1Summing:								0	0	10	11	10		14	17	17	17	10			21		22
51 21 Kosov Poly: -Mcoling: -PC:			3	4	5	0	1	8	9	10	11	12	15	14	15	16	1/	18	19	20	21	22	23
51 22 10 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>-</td><td></td><td></td><td><u> </u></td><td></td><td>-</td><td></td><td>-</td><td></td><td></td><td>-</td><td><u> </u></td><td>-</td><td>$\left - \right$</td><td></td><td></td></td<>								-			<u> </u>		-		-			-	<u> </u>	-	$\left - \right $		
55 90 Solonia - Solonia Dinki 4+10 1 <td< td=""><td></td><td></td><td>-</td><td></td><td>-</td><td></td><td></td><td></td><td></td><td></td><td></td><td>2</td><td><u> </u></td><td></td><td></td><td></td><td></td><td></td><td><u> </u></td><td></td><td>+</td><td></td><td>-</td></td<>			-		-							2	<u> </u>						<u> </u>		+		-
59 92 Subsidies - Subsidies - Marcial conditionantics 2.7765 1			4+100	-	1					-		-	<u> </u>	1				A		<u> </u>			
57 30. Karju2-Hongs -				-	-			-				-	<u> </u>	1				+	<u> </u>	<u> </u>			
8 94 NoriSat - NoriSat Oxing 1 - 2000 3-659 2 0			21/43		1														<u> </u>				
99 99 90 10 1 <td></td> <td></td> <td>2+870</td> <td></td> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1</td> <td></td> <td></td> <td>2</td> <td></td> <td></td> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td>-</td>			2+870		1							1			2			1					-
Bitmski fanktiv 1- Rasputnica 1- Ra															-			<u> </u>					
60 80 Product 1		(Dimelui čenčenii) Desmutnice 1. Desmutnice 2																					
61 07 1000 1000 100 9 100 9 100 100 9 100 <td>60 300</td> <td></td> <td>0+910</td> <td></td> <td>1</td> <td></td> <td> </td> <td></td> <td></td> <td></td> <td></td>	60 300		0+910		1																		
Col 200 VindsScanbor 1 1 1 2 1															1		9						
63 20 Perovandin - Boxin 17035 3 <td></td> <td>1</td> <td>1</td> <td></td> <td></td> <td>-</td> <td></td> <td></td> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td></td>											1	1			-			1					
64 30 Apatin Fahrias - Stille'. Sombor 89-04 4 1 1 2 65 311 Bat - Kanvakovo 144420 2 1 1 1 1 2 <td< td=""><td></td><td></td><td>17+035</td><td></td><td>3</td><td></td><td></td><td></td><td></td><td></td><td></td><td>1</td><td></td><td></td><td>-</td><td></td><td></td><td>-</td><td></td><td></td><td></td><td></td><td></td></td<>			17+035		3							1			-			-					
65 311 Back-Aramukovo 14402 2 1 1 <td></td> <td>0</td> <td></td>												0											
66 312 Backa Palmka-Gajdobr 11+422 2 0 0 0 0 2 4 0 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>1</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>															1								
67 313 (Brasim) - Rasputica Donja Borina - Zvonak Grac 0 64 0															<u> </u>			4					
68 314 Sid - Stemska Rača Nova - državna granica - (Bijeljina) 25+612 1 1 2 1 2 1 1 03 315 Kikinda - Baratsko Arandelove 12+916 4 1 1 2 1						6+818											_						
69 315 Kikinda - Banatsko Arandelove 12+916 4 4 2 1	21					÷												2			\square		
70 316 Secanj - Jaša Tomić 10+363 1		Kikinda - Banatsko Arandelovo	12+916		4												2						
171 317 Zenjanin Fabrika - Vršac - Bela Crkv: 65-1348 4 1 1 1 4 1 1 1 1 3 1 1 1 3 1 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 1 3 1 1 1 3 1 1 1 3 1 1 1 3 1 1 1 3 1 1 1 3 1 <									-			-					-		<u> </u>				-
72 318 Pančevo Varoš - Pančevo Vojlovice 2+907 2 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 3 1 1 1 3 1 1 1 3 1 1 1 3 1 1 1 3 1 1 1 3 1 1 1 3 1 1 1 1 3 1 <td></td> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>												1					4						
73 319 (Ujima) - Rasputnica A - Rasputnica B - (Jasenovo) 0+488 1 <td></td> <td>1</td> <td></td> <td></td> <td>1</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>-</td>												1			1	3							-
1 320 spojni kolosek stanice Senta: (Čoka) - odvojna skretnica 23 - (Orom) 1 1 1 1 1 1 3 4 1 1 1 1 3 4 1 1 1 1 1 1 3 4 1 1 1 1 1 1 1 1 1 3 4 1																							
74 3.00 22 - odvojna skretnica 23 - (Orom) Image: Construction of the structure of		engini kolosak stanica Santa: (Čaka) - advoina skratnica																					
321 (Poårevac) - Rasputica Sopot Požarevački - Kostolac 9+900 1 1 1 1 3 4 1 1 75 322 Makovac - Reswica 1 1 1 1 1 3 4 1 1 1 1 3 4 1	74 320																						
76 322 Markovac - Resavica 9 53+250 1 1 1 1 1 1 3 4 1 1 77 324 Ovéa - Padinska Skela 18+580 1 18+580 1 <td< td=""><td>75 321</td><td></td><td></td><td></td><td></td><td>9+900</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	75 321					9+900																	
77 324 Ovča - Padinska Skela 18+580 1 18+580 1 18 1 18 1 18 1 18 1 18 1 18 1 18 1 18 1 18 1 18 1 18 1 <td< td=""><td></td><td>Markovac - Resavica</td><td></td><td></td><td></td><td>53+250</td><td></td><td></td><td></td><td></td><td></td><td>1</td><td></td><td>1</td><td>1</td><td></td><td>3</td><td>4</td><td></td><td></td><td></td><td></td><td></td></td<>		Markovac - Resavica				53+250						1		1	1		3	4					
78 324 Metohija - Prizren. Image: Constraint of the second	77 324		18+580		1																		
79 401 Bečçi - Vrbas Image: Construction of the second seco	78 324										1												
81 403 Alibunar - Seleuš 8+386 1 Image: Constraint of the select	79 401	Bečej - Vrbas															1						
81 403 Alibunar - Seleuš 8+386 1 <td>80 402</td> <td>Vršac - Vršac Vašarište</td> <td></td>	80 402	Vršac - Vršac Vašarište																					
83 405 Čoka - Novi Kneževac 12+300 2 1 <t< td=""><td></td><td></td><td>8+386</td><td></td><td>1</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>			8+386		1																		
84 406 Kikinda - Metanolsko sirčetni kompleks (km 6+413 7+255 1 <td></td> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td>												2						2					
85 407 Bogojevo - Dunavska obala 2+733 1																	1						
86 408 (Sombor) - Rasputnica Strilić - Bački breg 28+090 1					-																		
87 409 Sombor - Ridica 32+741 1 <td></td>																							
88 410 (Višnjićevo) - Rasputnica Rača - Sremska Rača 3+830 1 1 1 1 89 411 Paraćin - Stari Popovac 1																							
89 411 Paracin - Stari Popovac 1 </td <td></td> <td></td> <td>32+741</td> <td></td> <td>1</td> <td></td>			32+741		1																		
90 412 Surčin - Jakovo Bečmet 4+400						3+830																	
413 (Beograd spoljna) - km 2+290 odvojna skretnica - Fabrika šećera 0+600 0 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>1</td><td></td><td></td><td></td><td></td><td></td><td>1</td><td></td><td></td><td></td><td></td><td></td><td></td></t<>											1						1						
91 413 Fabrika šećera 04000 92 501 Šarganska osmica 04000	90 412					4+400									-								
	91	Fabrika šećera				0+600																	
Total 161 416 876 699 107 127 7 18 28 12 115 76 6 82 37	92 501																						
		Total			161			416	876	699	107	127	7	18	28	12	115	76			6	82	37



Appendix 3.6a Request for issuance of encryption keys for communication in the ETCS system

1. Identification data of the railway carrier:

Address:		

Contact person:

E-mail:

Phone/Mobile Phone	

2. Identification data of vehicles and equipment

	ETCS-ID	EVN	Home-	Baseline	OBU-	Requested
	(NID_Engine)	(European	KMC of		producer	begin of
	decimal form	Vehicle	the vehicle			validity
		Number)				
example	<i>996823</i>	91 83 9586	IZS	3.6.0	CRSC	2024/6/15
		616-0				

3. Determination of home KMC

 \Box the home KMC of the given OBU is KMC IZS

 \Box the mentioned OBUs do not have any home KMC assigned, we request that it will become the KMC IZS \Box home KMC is a KMC other than KMC IZS:

KMC ID Administrator of the given KMC:

Contact person:

.....

4. We request the allocation of encryption keys for:

 \Box all lines equipped with ETCS level 2 track section and operated by IZS,

 \Box for certain track sections (areas), specify which:

.....



E						H	VAL TERM	FINAL TERMINAL DEVICES	ICES					-	╞				4	EXCHANGE UNITS	UNITS					
						T	Telephone					H	Telegraph	_					Telephone				Telegraph	hh		
						-	Traff.remote control desks	ontrol	In	Trackside telephe	shones															
oN pine No	RAILWAY LINE	LB telephone devices CB telephone devices	Automatic telephone devices	Secretary sets	səuoqdələt Aqq	sənonqələr Aq	At operational dispatching centers	At railway stations At entry signals	slangis ixo 1A	At level crossings (PP)	At automatic block (APB)	Others	Teleprinters	Telefaxes Sound signalling devices	səəivəb gnillengis bruo2	undiste "qois té q qoi ${\rm N}^{\rm a}$		Cross-bar	EMD with electric motor dialler	ESK	من دور	Electronic	məlaya "qəla by dol"		Dispatching exchanges	sooivob gnidotaqsib noita?2
oV IBA				-	pcs	pcs				pcs	pcs	Η	H		cs type		type	pcs	Ц	type	pcs type		type		Н	pcs
-	2	-	+		2	8	+	+	12	13	14	15	-		18 19	20	21	22	-	25	26 27		29	30	31	5
5 10.	101 BGD-Sid-State Border	55 25	360	9		0	0	13 35		23	11	0 0	9 12	0 18	18	0 =	4		0		3	0 0	TW-39		0 ×	2 2
4 103				-	0	0	+	20 38	36	6 44	41	0	+	0 8	* ~	t		7 0	0		1	7 0	TW-39	1		45
2 104	4 (BGD)-S.Pazova-Indija-Subotica-State Border.	59 30	0 665	e	2	0	4	19 39	38	31	55	25	s	0 3	3 eb5	e	L60	0	0		2	0	TW-39	-	5	26
22 105	5 Nis-Dimitrovgrad-State Border.	2 0	28	0	11	0	0	4	9	16	9	0	0	0	6	0		-	0		-	0		0	0	
\square		46 0	245	9	5	0	-	7 30		4	12	15	9	0 5		0		0	0		0 dk	dkts 0		0	1	0
1 107		+	+	59	0	0	2 2	35 69	R .	28	70	70	15	+	59 ISKRA	A 2	0		Siemens 2	0	0 žeate	c 100 2	TW-39	- 0	~ ~	2
26 109	 Lapovo-Kraijevo-D.Jainovic-State Border. Subotica-Bozoievo-State Border. 	22 0	2	- 0	0	0	1 0	0	+ 0	4	0	1 0	1 0	0 0	4 -	- 0		- 0	0		0 omni	s3	6C-M 1	0	0	
+-		╞	0	0	0	0	0	-1	S	0	-	0	-	0		0		-	0		╞			0	0	_
-		8 0		0	0	0	0	9 0	S	0	4	0	0	0		0		0	0		0	0		0	0	_
+		+	-	0 0		0	0 0	2 0	-	2	4 0	0 0		0 0		0 0		• •	0		0 0	0		0 0	0 0	
13 114	DOU KAIIZITHA. DOSITUZIJKA 1 BGD RADŽITHA "A"-RASD."B"-RASD."K"-ReSnik	3 0		0	0	0 0		0	0	• •	7	0 0	0 0	0	0 0	• •		• •	0 0		0	0		0 0	0 0	
-		2 0	0	0	0	0	0	0 2	0	-	3	0				0		0	0		0	0		0	0	0
10 116		6 0		10	0	0	4	4	3	0	2	0	2	1 (0	0		-	0		0	0		0	0	_
+		1	+	+	0	0	0	-	-	0	-	0	0		0	0		0	0		0	0		0	0	_
+		0 0 E c	+	+	0 0	0 0	0 0	0	+	0 0	0 -	0 0	+	+	0 0	• •		• •	0		0	0		0 0	0 0	_
16 120		3 0	8	01	• •	0		5 4	0	• •	- 0	0	0 0		0	• •	-	• •	0		0	0		0	0	
+	Topčider-Rasp.Savski Most-(Novi BGD)	1 0	+	┝	1	0	0	1 3	-	0	-	0	10	0	0	0		0	0		0	0		0	0	
		2 0		0	2	2	0	0	0	6	0	0	2		0	0		0	0		0	0		0	0	_
27 123	3 (Topč)-Blok 1Obala-BGD Spoljna-Blok 2 prel Avidence -> Bare Part Bare Desire (Barbar)	- 0	0	-	0	0	0 0	-	0	0	•	0 0	-	-	0	0		• •	0		0 0	0		0 0	0 0	
+		0 0	-	0	0	0	-	0 2	0	0	2	0	-	0	0	0		• •	0		0	0		0	0	
24 126	+ +		$\left \right $	$\left \right $	0	0	$\left \right $	$\left \right $		0	0	0	0	0 1		0		0	0		0	0		0	0	_
+		0 0		0	0	0	0 0	0,00	+		•	0 0	0.	0	_	•	+	•	0		0	0		0	0	_
30 129	5 Lapovo Varos-Lapovo Kanzirna-Lapovo 3 Trunale-Niš Ranžima-Međurovo	2 0	7 58	• •	• •	0 0	+	4 2 4	0 0	0 0	• •	0 S	- 2	0	- 0				0 0		0 0	0		0 0		
		0 0			0	0	0			0	0	0	0		0	0		0	0		0	0		0	0	
		0 1		0	0	0	0	0 0	0	0	0	0	0		0	0		0	0		0	0		0	0	_
18 132	2 (Cr.Krst-Skr.2)-Skr.3-Skr.4-(Cele Kula)	0 0	0	0 0	0	0	0 0	0 0	0 0	0 0	0	0	0 -	0 0	0 0	0		0	0 0		0	0		0 0	0	
+-	-	╞	~	+	0	0	0	1 0		-	0	0	-	+	13 fb5			-	0		0	0	TW-39	-	0	
32 203		-			0	0	0	0 1	0	0	0	0	0			0		0	0		0	0		0	0	0
-		+	-	0	0	0	0	0	0	0	0	0	+	0		0		0	0		0	0		0	0	_
39 205		0 9	+	0 0	15	0 0		000				0 0	0 0	0 0		• •			0 0		0 0	0 0		0 0	0 0	_
+-	-	0	10	0	0	0	0	0	0	0	0	0	0	0		0		0	0		0	0		0	0	
-	-			0	0	0	0	0	0	0	0	0	0	0		0		0	0		0	0		0	0	0
47 209	Rum	15 1	45	0	0	0	0	0	0	0	0	0	0) 0	_	0		0	0		0	0		0	0	_
+		21 0	80	0 0		0	0 0	× c	7 0	4 0		~ ~	7 0	00			-		0		0 0	0 0		0 0	0 0	~ ~
34 215	5 M.Krsna-Bor-Rasputnica "2"-(Vražogmac)	26 0	125	9	20	4	0	10 3	0	16	0	0	0 01	-	1 0	-		• •	0		0	0		0	0	
35 216		12 0	200	2	16	0	0	1 2	-	0	0	0	0	0		-		0	0		0	0		0	0	_
64 212	8 (Niš)-Doljevac-Kastrat-Kosovo Polje	7 ()	e 0	0 0	•	0	0 0	00	0	0	•	0 0	0	0	_	•	_	•	0		0	0		0	0	_
62 219 56 270	9 Kursumlija-Kastrat 1 (Backwo)-P securvice "1", Kučuwlija	00	0 0	0 0	0 0	0 0		00	0 0	0 0	• •	0 0	0 0					• •	0 0		0 0	0 0		0 0		_
76 301	1	0	0	0	0	0	0	0	0	0	0	0	0	0		• •		• •	0		0	0		0	0	
-		0 0	0	0	0	0	0	0	0	0	0	0	0	0		0		0	0		0	0		0	0	_
-	3 Kanjiža-Horgoš	0 0	0	0	0	0	0	9 0	0	0	0	0	0) 0	_	0		0	0		0	0		0	0	_
36 304	Novi Sad-Novi Sad ložionica	+		-	0	0	0	0	0	0	0	0	+	0		0		0	0		0	0		0	0	_
37 305	5 Podbara-Rasput. "3"-Rasput. "2"-(Kać)	0 0	0	0	0	0	0	0 0	0	0	0	0	0	0	_	0	_	0	0		0	0	_	0	0	_

Appendix 3.7 Overview of telecommunication devices equipping level



					sooivob gnidotsqsib noitst2	pcs	32	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	181
					Dispatching exchanges	pcs	31	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	10
	- Her	ud				pcs	30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
	Talaara	1 clegraph			məisyz "qəiz yd qəiZ"	type	29																													
						pcs	28	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	s.
					Electronic	type	27																								8					
STINUES					SE	pcs	26	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	17
EXCHANGE UNITS						type	25																													
EX	000	one				pcs	24	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
	Talanhona	I cicpn			EMD with electric motor dialler	type	23																													
							22	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	12
					Cross-bar	type	21																													
					"Siep by step" system	pcs	20	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	17
						type	19																		1											-
		_			səəivəb gnillengis bnuo2	┢	┢	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	156
	- term	rapn			Telefaxes	pcs	17	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	=
	Talac	I clegraph			Teleprinters	pcs	16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	88
					Others	pcs	15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	126
			honor	INTER	(BIA) Abold sitemotus 1A	pcs	14	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	397
			Teacheida talanhonae	datas antes	At level crossings (PP)	pcs	13	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	284
s			Trad	11000	slangis tixo 1A	pcs	12	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	351
DEVICE					slangis yuna 1A	pcs	11	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	415
TERMINAL DEVICES			remote control	2	snoitels yewlier 1A	pcs	10	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	201
FINAL TE	Laborations	I cicphone	Traff.remote	â	At operational dispatching centers	pcs	6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	24
-	ſ	Ī			sənordələr Aq	pcs	~	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	*
					sənordələt Aqq	pcs	7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3	0	0	0	0	0	0	0	0	0	0	0	0	96
					Secretary sets	pcs	9	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	182
				_	səsiyəb ənodqələt əttemotuA	pcs	5	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	4	0	0	0	0	0	0	0	0	0	0	0	0	4598
					CB telephone devices	pcs	4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	262
					LB telephone devices	pcs	3	0	0	0	0	0	0	0	0	0	0	0	3	0	0	0	6	0	0	0	0	0	0	0	0	0	0	0	0	880
					RALLWAY LINE RALLWAY LINE	No	2	45 306 (Rim.Šančevi)-Rasput "1"-Rasput. "3"-(Podb.)	33 308 Vrbas-Sombor	69 309 Petrovaradin-Beočin	74 310 Sonta-Apatin fabrika-Strilić-(Sombor)	54 311 Bač-Karavukovo	55 312 Bačka Palanka-Gajdobra	46 313 (Ruma)-Rasp.Donja Borina-Zvomik Grad	52 314 Šid-Sremska Rača Nova-State Border.	60 315 Kikinda-Banatsko Aranđelovo	71 316 Sečanj-Jaša Tomić	81 317 (Zrenjanin)-Zrenjanin fabr.Vršac-Bela Crkva	67 318 Pančevo Varoš-Pančevo Vojlovica	319	320	321	63 322 Markovac-Resavica	66 323 Ovča-Padinska Skela	+	404	59 405 Coka-Novi Kneževac	61 406 [Kikinda-MKS (ind.kolosek)	58 407 Bogojevo-Dunavska obala	72 408 Sombor-Bački Breg	73 409 Sombor-Ridica	79 410 (Višnjićevo)-Rasput.Rača-Sremska Rača	68 411 Paračin-Stari Popovac	77 412 [Surčin-Jakovo-Bečmen-(Boljevci)	57 413 (Bgd spoljna)-km 2+290-Fabrika šećera	Total:



										OT	OTHER TELECOMMUNICATION DEVICES	SCOMMU	NICATIC	IN DEVIC	SE									
	Device	s for recol	Devices for recording of transmitted statements	nsmitted	Dé	Devices displaying accurate time	ying accur	ate time	<u> </u>	ΡA	PA devices			Inter	Interphones		Pow	Power supply devices	devices	Pa	Passenger visual information display	sual inform	ation dis	olays
RAILWAY LINE RAILWAY LINE RAILWAY LINE	8 channels	12 channels	l6 channels	24 channels	snoinste 10 rodnul/	Clock exchange units	Master clocks	Impulse regenerators	Aumber of statons	rəifiqmA	Speakers	olosnos onofiqorsiM	snoinsis fo redmuN	lnlerphone exchange units	For indoor installation	For outdoor installation	Acummulator batteries	Rctifiers	Сопчетегь	Motor electric generator units	Zanions to rodanu	Control desks	systqsib noitsmoita	zdzoid noitsmroful
- No	pcs	pcs	pcs	pcs	pcs		pcs p	pcs pcs			pcs	pcs	pcs	pcs	pcs	pcs	pcs	pcs	pcs	pcs	pcs p		pcs p	pcs 57
5 101 BGD-Šid-State Border	1	1	0	00	3	2			+	22	ŧ ~	35	0	0	0	0	16	16	0	Η		0 0		
	9	2	0	-	9	2			\$23 20		325	20	9	4	38	17	72	11	0	1	1			
 103 (BGD)-Rakovica-Jajinci-M.Krsna-V.Plana 104 (RGD)-S Paywa-Indija-Suborica-State Border 		0 -	0 -	0 -	20	0 0	3	20 1	18 1 133 3		9 134	- U	0 -	0 0	0 -	0 0	25	25	0 0	0 %	0 -	0 0	0 0	
105	-	0	0	0	0	0	2	3 2	20 1	-	3	-	0	0	0	0	7	13	0	0	. 0	H	0	
6 106 BGD Centar-Panéevo-Vfsac-State Border. 1 107 (BGD)-Resnik-Podgorica-Bar	1	0 0		0 0	34	9	34 3	34 21	92 2 212 7	7	72	9			3	1 0	3 62x12V 222x2V	47	0 0	0 0	0	6 0 8 0	0 0	0 0
20 108 Lapovo-Kraljevo-Đ.Janković-State Border.	-	0	0	0	6	0	6	0	3	3	24	0	0	0	0	0	16x6V 28 2	26 2		0	0	0	0	
110	0 0	0 0	0 0	0 0	0 0	0 0	0 -	0 -	0 4	0	0	0 9	0 0	0 0	0 0	0 0	5	~ ×	0 0	0 0				
++	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	
15 112 BGD Ranžima "A"-Ostružnica-Batajnica 14 113 BGD Ranžima "B"-Ostružnica	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	+ 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 3	0	0 0	0 0	0 0	00	0 0	
114	00	0 0	0.0	0.0	0 0	0 0	000	000		00	00	00	00	0	0 0	000			0 0	0 0	000		000	
116	0	0	0	5	0	0	1	0	20 0	o v	20	-	0	0	0	0	1	- m	0	0	0			
	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0	00	0 0	0 0	0 0	0 0	0 0	0 0	0	0 0	0 0	0 0	0 0	000		
119	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
 16 120 (BGD Ranz, "A"-Ras.B)-Ras.K-Ras.K1-Jajinci 20 121 Tranidor-Pase Sovet: Mort-ANovi BGD) 	0 0	0 0	0 0	0 0	6 0	0 0	3	0	0 0	4 0	31	2	0 0	0 0	0 0	0 0	- 6	2	0 0	0 0	0 0	00		
122	0	0	0	0	0	0	0	0	0	1	5	1	0	0	0	0	• 0	0	0	0	0	0		
123	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-	~
 31 124 (VUKOV Sp.)-Kas.K.Park-kas.Dednije-(Kakov.) 19 125 Indija-Golubinci 	0 0	0 0	• •	0 0	0 0	0 0	0 0	0	0	0	0 0	0 0	0 0	0	0 0	0 0	0 0	0 0	0 0	0 0	0 0			
24 126 N.Sad-N.Sad Ranžirna-Sajlovo Rasp. 41 127 Obilizani Edizash Mala K rema	0 0	0	0 0	0 0	0 0	0 0	0 0	1 0	10 0	0	00	0 0	0 0	0	0 0	0	1	1	0	0	0 0	00		~ ~
128	0	0	0	0	0	0	2	2	1	-	2	1	0	0	0	0	9 60	9 6	0	0	0	0	0	
129	0 0	0	0	0 0	0 0	0	- 0	0	6 I	9 0	35	1	0	0	0 0	0 0	2	e 0	0	0 0	0 0	00	-	
23 131 Niš-Raputnica Most-Niš Ranžima)	00	00	00	00	0 0	000	000	00	0	000	00	0	0 0	00	0 0 0		0	0 0	0 0	000	000			
201	0 0	0 0	• •	0 0	0 0	0 0	1	0	0	1	9 6	1	0 0	0 0	0 0	0	2	2	0 0	0 0	0 0	00		
202	-	0	0	0	0	0	0	0	2	2	7	2	0	0	0	0	2	9	0	0	0	0		
 22 20.5 Banatsko Mitosevo-Senta-Subolica 44 204 Pančevo Varoš-Rasputnica "2a"-(Jabuka) 	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0	0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0	0 0	0 0	0 0	0 0	0 0		
39 205 N.Sad-Sajlovo Rasputnica-Bogojevo 40 206 (N.Sad)-Sajl.RaspR. Šanč. Orl staj(Tomaš)	0 0	0 0	0 0	0 0	0 0	0 0	0 0	00	0 0	00	0 0	0 0	0 0	0	0 0	0 0	0	0 0	0 0	0 0	0 0	00		~ ~
207	0	0	0	0 0	0	0 0	0	00	0	0	•	0	0	0	0 0	0	0	0 0	0	0	0 0	0		
209	0 0	• •	0 0	0 0	0 0	0 0	0 0	00	0	0	0 0	0	• •	0	0 0	0 0	0	0 0	0 0	0 0	0	0 0		
50 211 Stałać-Kraljevo-Požega 40 214 Smadarano Mala V rema	0 0	0 0	0 0	0 0	2 0	0	2		4	2	20		0 0	0	0 0	0 0	17	20	0 0	0 0	0 0	0 0		
215	0	0	0	0	4 00	0	2	7 1	10 3	4	22	- 6	• •	0	0	0	18	10	0	0	0			
35 216 Niš-Zaječar- Prahovo pristanište 64 218 (Niŝ)-Dolievac-Kastrat-Kosovo Polie	0 0	0 0	0 0	0 0	1	0 0	0	0 0	0	2	20	- 0	0 0	0 0	0 0	0 0	5	1 0	0 0	0 0	0 0	00		
219	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
56 220 (Barlovo)-Rasputmea "1"-Kursumlija 76 301 Subotica-Subotica fabrika	0 0	0 0	• •	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0		0 0	0 0			
302	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
65 303 Kanjiža-Horgoš	•	0	•	0	0 0	0	0	0	0	0	0	0	0	0	0 0	0	0 -	0 -	0	0 0	0 0	0	-	
305	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0	0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0	0	0 0	0 0	0 0	00		
45 306 (Rim.Šančevi)-Rasput "1"-Rasput. "3"-(Podb.) 33 308 Vyhse-Sombor	00	0 0	0 0	0 0	0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0 0	0	0 0	0 0	0 0	0 0	0 0		
309	0	0	0	0	0	0		0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	
310	0	0	0	0	0	0	0	0	0 0	0	0	0	0	0	0	0	0	0	0	0	0 0	0	0 0	_
55 312 Bačka Palanka-Gajdobra	0	0	0	0	0	0	+	+	0	0	0	0	0	0	0	0	0	0	0	0	+	\vdash	-	



Interphones Power supply devices Passenger visual information displays	OTHER TELECOMMUNICATION DEVICES	zykłącib noitermolnił 🐰 🖧 o o o o o o o o o o o o o o o o o o						control contr			╟──╏─────┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼				Participante a construction of the second se	0 0	Production Product	0 0	Description Description <thdescription< th=""> <thdescription< th=""></thdescription<></thdescription<>	And Contraction And Contra	Provises displaying accurate time Provises displaying accurate time Provises displaying accurate time 0	Devises displaying accurate time Devise displaying accurate time Devise displaying accurate time Devise displaying accurate time Devise displaying accurate	Participations Provised displaying accurate time Devices displaying accurate time 9	Transmitted Transmitted
1 1	Interplane Interpl	H	0	0		\square	0	0	0	0	H	H	H			H	0	0 0	0 0 0	0 0 0	0 0 0			
0 0 0 0 0 0 0 0 0 0 0 0 0 0 <td>Interplane Interplane Interpl</td> <td></td> <td>0</td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>_</td> <td></td> <td>0</td> <td>-</td> <td></td> <td>0</td> <td>0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0 0 0</td> <td>0 0 0 0 0 0</td> <td></td>	Interplane Interpl		0	0			0	0	0	0		_		0	-		0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0	0 0 0 0 0 0	
0 0 0 0 0 0 0 0 0 0 0 0 0 0 <td>Interplote Interplote Interpl</td> <td></td> <td>0</td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>_</td> <td></td> <td></td> <td>0</td> <td>-</td> <td></td> <td>0</td> <td>0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0 0 0</td> <td></td> <td></td>	Interplote Interpl		0	0			0	0	0	0	_			0	-		0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0		
0 0 0 0 0 0 0 0 0 0 0 0 0 0 <td>Interplane Motion console Motion cons</td> <td></td> <td>0</td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> <td></td> <td>_</td> <td>_</td> <td></td> <td>0</td> <td>0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td></td> <td></td> <td></td>	Interplane Motion console Motion cons		0	0			0	0	0	0				_	_		0	0 0	0 0 0	0 0 0	0 0 0			
0 0 0 0 0 0 0 0 0 0 0 0 0 0 <td>Interplane Interplane Interpl</td> <td></td> <td>0</td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> <td></td> <td>0</td> <td>_</td> <td></td> <td>0</td> <td>0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0 0 0</td> <td>0 0 0 0 0 0</td> <td></td>	Interplane Interpl		0	0			0	0	0	0				0	_		0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0	0 0 0 0 0 0	
0 0 0 0 0 0 0 0 0 0 0 0 0 0 <td>Interplote Monotonic <</td> <td></td> <td>0</td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> <td></td> <td>0</td> <td>_</td> <td></td> <td>0</td> <td>0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0 0 0</td> <td>0 0 0 0 0 0</td> <td></td>	Interplote Monotonic <		0	0			0	0	0	0				0	_		0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0	0 0 0 0 0 0	
0 0	Interplane Motor of console Motor of stations Motor statistic number of statistis number of statistic number		0	0			0	0	0	0				0	_		0	0 0	0 0 0	0 0 0	0 0 0			
0 0	Interplane Monotonal console Monotonal consoconal console Monotonal console		0	0			0	0	0	0				-	_		0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0	0 0 0 0 0 0	
0 0	Interplane Material		0	0			0	0	0	0				0	-		0	0 0	0 0 0	0 0 0	0 0 0			
0 0	Interplane Interpl		0	0			0	0	0	0				0	~		0	0 0	0 0 0	0 0 0	0 0 0			
0 0	Interplane Matrix Mat		0	0			0	0	0	0				0			0	0 0	0 0 0	0 0 0	0 0 0		0 0 0 0 0 0	
0 0	Power supply Microphone console Microphone co		0	0			0	0	0	0					\sim		0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0		
0 0	Interplane Material		0	0			0	0	0	0							0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0		
0 0 0 1 3 Specukeers 0 0 0 1 3 Specukeers 0 0 0 0 2 3 Specukeers 0 0 0 0 3 Specukeers Specukeers 0 0 0 <	0 0		0	0			0	0	0	0							0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0	0 0 0 0 0 0	
0 0 0 2 3 Stochshore 0 0 0 2 3 Munber of stations 0 0 0 2 3 Munber of stations 0 0 0 3 3 3 Munber of stations 0 0 0 3 3	Power supply Microphone console Microphone console Microphone console Microphone console Microphone console Microphone console Microphone		0	0			0	0	0	0							0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0	0 0 0 0 0 0	0 0 0 0 0 0
0 0 2 3 3 4 10 <td>Interplote Point Point</td> <td></td> <td>0</td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> <td>0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0 0 0</td> <td>0 0 0 0 0 0</td> <td></td>	Interplote Point		0	0			0	0	0	0							0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0	0 0 0 0 0 0	
0 1 2 Specukers 0 2 3 Mucrophone console 0 2 3 Mucrophone console 0 2 3 Mucrophone console 0 3 3 Mucrophone console 1 3 3 <	Power supply Power supand supand supand supply Power supply		0	0			0	0	0	0)	-		0	0 0	0 0 0	0 0 0	0 0 0			
0 4 7 5 Speakers 0 2 7 5 Munber of stations 0 3 5 Munber of stations 0 3 5 Notorelation 0 3 5 Motorelation 0 3 5 5 1 3 5 5 1 3 5 5 1 3 5 5 1 3 5 5 1 3 5 5	Power supply book Power supply book Power supply supply book Power supply book Power supply supply book <td></td> <td>0</td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> <td></td> <td>0</td> <td>\sim</td> <td></td> <td>0</td> <td>0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0</td> <td>0 0 0 0 0</td> <td>0 0 0 0 0 0</td> <td></td>		0	0			0	0	0	0				0	\sim		0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0	0 0 0 0 0 0	
○ 2 S S ○ 3 S ○ S </td <td>O S Nitcrophone console Interphone 0 5 Nitrophone console Mitcrophone Mitcrophone 0 5 Nitrophone Mitcrophone Mitcrophone Mitcrophone 0 4 Possibilitation Mitcrophone Mitcrophone Mitcrophone 0 5 Possibilitation Mitcrophone Mitcrophone Mitcrophone <t< td=""><td></td><td>0</td><td>0</td><td></td><td></td><td>0</td><td>0</td><td>0</td><td>0</td><td></td><td></td><td></td><td>0</td><td>\sim</td><td></td><td>0</td><td>0 0</td><td>0 0 0</td><td>0 0 0</td><td>0 0 0</td><td>0 0 0 0 0</td><td>0 0 0 0 0 0</td><td></td></t<></td>	O S Nitcrophone console Interphone 0 5 Nitrophone console Mitcrophone Mitcrophone 0 5 Nitrophone Mitcrophone Mitcrophone Mitcrophone 0 4 Possibilitation Mitcrophone Mitcrophone Mitcrophone 0 5 Possibilitation Mitcrophone Mitcrophone Mitcrophone <t< td=""><td></td><td>0</td><td>0</td><td></td><td></td><td>0</td><td>0</td><td>0</td><td>0</td><td></td><td></td><td></td><td>0</td><td>\sim</td><td></td><td>0</td><td>0 0</td><td>0 0 0</td><td>0 0 0</td><td>0 0 0</td><td>0 0 0 0 0</td><td>0 0 0 0 0 0</td><td></td></t<>		0	0			0	0	0	0				0	\sim		0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0 0	0 0 0 0 0 0	
1 3 Plocatocres 2 3 Montor or stations 3 3 Montor or stations 4 3 Montor or stations 5 3 Montor or stations 4 3 Montor or stations 5 3 Montor or stations 6 3 Montor or stations 7 3 4 8 5 Montor or stations 9 5 Montor or stations 10 7 7 11 7 7 12 8 Montor or stations 13 9 Montor or stations 13 9 Montor or stations 14 9 Montor or stations 15 9 Montor or stations 16 17 Montor or stations	45 55 35 35 35 45 56 35 35 35 45 57 35 35 35 45 58 35 35 35 45 58 35 35 35 45 58 35 35 35 47 58 35 35 35 47 58 35 35 35 47 58 35 35 35 47 58 35 35 35 47 58 35 35 35 48 37 35 35 35 50 36 37 35 35 51 37 35 35 35 52 37 35 35 35 53 37 35 35 35 53 37 35 35 35 53 36 35 35 35 54 36 36 36 36 55 36 36 36 36 56 36 36 36 36 57 37 35		0	0			0	0	0	0				0	-		0	0 0	0 0 0	0 0 0	0 0 0	0 0 0 0		
3 Speakers 3 Shercophone console 3 Minnber of stations 3 Monor installation 3 Por indoor installation 3 Por indoor installation 3 Monor electric generator units 3 Por indoor installation 3 Por indoor installation 3 Por indoor installation 4 Por indoor installation	S Miscrephone console Interphone DS Miscrephone console Miscrephone DS Pumber of stations Miscrephone DS Portiador installation Miscrephone DS Portinstallatinon Miscrephone D		\vdash			-	50		┝	┝					0	_	41	40 41	39 40 41	39 40 41	37 38 39 40 41	36 37 38 39 40 41	35 36 37 38 39 40 41	34 35 36 37 38 39 40 41
Speakers Microphone console Mumber of stations For indoor installation For outdoor installation For outdoor installation For outdoor installation Converters Converte	Microphone console Mumber of stations For indoor installation For outdoor installation For outdoor installation Converters Motor electric generator units Motor electric generator units Motor electric generator units Motor electric generator units Motor electric generator units			\vdash			bcs		\vdash	┝	┝		\vdash	ď	so	-	pcs	pcs pcs	pcs pcs pcs	pcs pcs pcs	pcs pcs pcs pcs	pcs pcs pcs pcs pcs	pcs pcs pcs pcs pcs pcs	pcs pcs pcs pcs pcs pcs
tions shays units stallation balleries balleries balleries	ionse le la		sysəb lottro				Acumulator	ni roobtuo ro ^z	sni 100bni 10 ⁵			11109 1 11420		maililan	PIS TO LOOUIDA		eloc	nəgər əsluqmi Əolə yrailiary	Master clocks Impulse regen Auxiliary cloc	Master clocks Impulse regen Auxiliary cloc	Clock exchang Master clocks Anziliary cloc	Yumber of sta Clock exchang impulse regen impulse regen	4 uxiliary clock Marter clocks Clock exchang Clock exchang Vaster clocks Vaster clocks	4 uxiliary clock Master clocks Clock exchang 24 chamber of sta 24 chamber of sta
	Interphones Power supply devices		s		c generator units		r batteries	noitallation	stallation			əlosnoə			SHOP		icks	icks nerators	s nerators	s nerators	zinu ogo z zotrators zdos	zinu ogo z zotrators zdos	zinu ogo z zotrators zdos	zinu ogo z zotrators zdos



Operation <				-	CABLE SYST	EMS		1						MULTI-CHANNEL DEV	CLUDE.	TCES					I
<			Dverhead	lines		Cable li	nes			Analogue	telephon						-	Digital tel	cphone		
in in<	RAILWAY LINE			səldeə beərhəvO	STKA	VIS	Fiber optic	Local	slanneda 5 of qu	Up to 12 channels	Over 12 channels		1992 O 19	TelegalaT		s\vidM 2	77: - 17 o	S/IIGIAI Q	s/iidM 221	arəfiilqma bnuorg əvodA	In-ground amplifiers
observation 0 <th< td=""><td>c</td><td>km 3</td><td>km 4</td><td>km</td><td>km 6</td><td>km 7</td><td>km</td><td>km o</td><td></td><td>\vdash</td><td>type</td><td>pcs</td><td></td><td>type 18</td><td>pcs</td><td>type</td><td></td><td></td><td>Π</td><td></td><td>-</td></th<>	c	km 3	km 4	km	km 6	km 7	km	km o		\vdash	type	pcs		type 18	pcs	type			Π		-
Non-solute solution 0	D-Šid-State Border	0	0	0		0	0	0	0	-	-	+	-	iskra	0	07			+	-	0
Constructional 0	iD-Mladenovac-Niš-Preševo-State Border.	0	0	0		162,917	0	111,88			-	4	_	iskra	_	siemens	0	-	20107		0
the control of the contro of the control of the control of the control of the control of t	GD)-Rakovica-Jajinci-M.Krsna-V.Plana	0	0	0	0	105,043	0	0	0	Z 12 3		+	$\left \right $	iskra	3		0	0		0	0
me me<	GD)-S.Pazova-Indija-Subotica-State Border.	0	0	0	135,857	15,878	0	71,00	0					AUSO UTB ISKRA	4		0	0			0
The sector	5-Dimitrovgrad-State Border.	0	0	74,00	∇	0	0	3,67	0						0		0	0			0
eta functione 0 0.00 0.000 0.	3D Centar-Pančevo-Vršac-State Border.	2,00	0	13,00	0	26,000	0	10,000	_				0	iskra	_	siemens	0				0
The function of a participant of a	GD)-Resnik-Podgorica-Bar	0	0	0		0	0	63,144	EI 1				28		9		0			+	0
diametricity 0 </td <td>povo-Kraljevo-Đ.Janković-State Border. botica-Bogoievo-State Border.</td> <td>• •</td> <td>0 0</td> <td>90,34</td> <td>0 0</td> <td>5,350 0</td> <td>0 0</td> <td>5,347</td> <td>-</td> <td>-</td> <td></td> <td>-</td> <td>-</td> <td></td> <td>0 0</td> <td></td> <td>0 0</td> <td>0 0</td> <td></td> <td>-</td> <td>0 0</td>	povo-Kraljevo-Đ.Janković-State Border. botica-Bogoievo-State Border.	• •	0 0	90,34	0 0	5,350 0	0 0	5,347	-	-		-	-		0 0		0 0	0 0		-	0 0
International 0 <	cograd Centar-Novi Beograd	0	0	0	0	3,648	0	0	0	0			-	iskra	0		0	0			0
Tertonic point of point	GD Centar-Rasputnica"G"-(Rakovica)	0	0	0	0	0	0	0	0	0				iskra	0		0	0		+	0
Explore 0 </td <td>OD Ranžima "A"-Ostružnica-Batajnica GD Ranžima "B"-Ostružnica</td> <td></td> <td></td> <td>0 0</td> <td>0</td> <td>11.755</td> <td>0 0</td> <td>0 0</td> <td>0 0</td> <td></td> <td></td> <td>-</td> <td>+</td> <td></td> <td>0 0</td> <td></td> <td>0 0</td> <td>0 0</td> <td></td> <td>+</td> <td></td>	OD Ranžima "A"-Ostružnica-Batajnica GD Ranžima "B"-Ostružnica			0 0	0	11.755	0 0	0 0	0 0			-	+		0 0		0 0	0 0		+	
Here I	GD Ranžirna "A"-Rasp."B"-Rasp."K"-Resnik	0	0	0	0	34,460	0	0	0	0		0 0	0	iskra	0		0	0		0	-
Construction 0 </td <td>stružnica-Rasp."B"-(Rasp."K"-Resnik)</td> <td>•</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>00</td> <td></td> <td>+</td> <td>-</td> <td></td> <td>0</td> <td></td> <td>0</td> <td>0</td> <td></td> <td>-</td> <td>-</td>	stružnica-Rasp."B"-(Rasp."K"-Resnik)	•	0	0	0	0	0	0	0	00		+	-		0		0	0		-	-
Tubeline 0<	u Kanzima BKasp. KKasp. A. GD Ranžima "R"-Rakovica		0 0			0007101	0 0	0 0				+	+		0 0		0 0	0 0		+	
TarT-Totholesione000 <td>JD)-BGD Ranžirna "A"-Rasp."T"-Rakovica</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>22,559</td> <td>0</td> <td>5</td> <td></td> <td>-</td> <td>+</td> <td></td> <td>-</td> <td>T</td> <td>0</td> <td>0</td> <td></td> <td>+</td> <td>10</td>	JD)-BGD Ranžirna "A"-Rasp."T"-Rakovica	0	0	0	0	0	0	22,559	0	5		-	+		-	T	0	0		+	10
New Network 0 <th< td=""><td>iD Ranžima "B"-Rasputnica "T"-(Rakovica)</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td></td><td>-</td><td></td><td></td><td>0</td><td></td><td>0</td><td>0</td><td></td><td></td><td>5</td></th<>	iD Ranžima "B"-Rasputnica "T"-(Rakovica)	0	0	0	0	0	0	0	0	0		-			0		0	0			5
Ultilization 0 </td <td>JD Ranz. "A "-Ras.B)-Ras.K-Ras.K1-Jajıncı očider-Rasn Savski Most-(Novi BGD)</td> <td>• •</td> <td>0 0</td> <td>0 0</td> <td>0 0</td> <td>2,130</td> <td>0 0</td> <td>0 0</td> <td>0 0</td> <td></td> <td></td> <td>+</td> <td>+</td> <td></td> <td>0 0</td> <td></td> <td>0 0</td> <td>0 0</td> <td></td> <td>+</td> <td></td>	JD Ranz. "A "-Ras.B)-Ras.K-Ras.K1-Jajıncı očider-Rasn Savski Most-(Novi BGD)	• •	0 0	0 0	0 0	2,130	0 0	0 0	0 0			+	+		0 0		0 0	0 0		+	
Obline-Hole, 2peri 0	očBlok 10bala-Blok 2 prelRas.Pan.Most	0	0	0	0	0	0	0	0	0		+	+		0		0	0	0	+	-
	pč)-Blok 1 Obala-BGD Spoljna-Blok 2 prel	• •	0	0	0	0	0	0	0	00		+	+		0		0 0	0		0	
	ja-Golubinci	0	0	0	0	9,536	0	0	0	0					0		0	0			0
	ad-N.Sad Ranžirna-Sajlovo Rasp.	0	0	0	\leq	0	0	2,700	0	0		-			0		0	0		-	0
	azni kolosek Mala Krsna ovo Varoš-Labovo Ranžima-Labovo	• •	0 0	0 0	0 0	0 0	0 0	0 0	0 0			+	+		0 0		0 0	0 0		+	
	oale-Niš Ranžima-Međurovo	0	0	0	0	0	0	0	0	0				iskra	-		0	0			1
	eni Krst-Niš Ranžirna Pasautnica Most-Oliž Panžinna)	• •	0 0	0	0	0 17 757	0	31 500	0 0			+	+		0 0		0 0	0 0		+	-10
r. 0 0 10 0 4.45 0	.Krst-Skr.2)-Skr.3-Skr.4-(Čele Kula)	0	0	0	0	0	0	0	0	0		-	+		0		0	0		0	0
Intrate-state before: 0 -2.0 -1.2 <	ootica-Horgos-State Border.	0	0	10	0	0	0	0	0	0					0		0	0		+	-
	icevo Olavna-Zrenjanin-Kikinda-State Border.		C0'7	41,4	C,I	0						+	+				0	0		+	1
	natsko Miliosevo-Senta-Subotica	>	n	0	-	0	0	-	_	>	_	+	-+		>		0	n		+	P
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $	čevo Varoš-Rasputnica "2a"-(Jabuka) od Soilono Domitnico Dominico	0	0	0	0	0	0	0	0	00		+	-		0 0		0	0 0		+	0
	sad-Sajl.RaspR.ŠančOrl.stai(Tomaš)	0	0	0	0	0	0	0	0			+	+		0		0	0		+	0
	ad Ranžirna-Sajlovo Rasputnica	0	0	0	0	0	0	0	0	0			-		0		0	0	0		0
	ovat-Rasputnica "1a"-(Lukićevo)	0	0	0	0	0	0	0	-	0		-	-		0		0	0	0		-
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	na-Sabac-Rasp.Donja Borina-State Border.	• •	0 0	0	0	0 00	0 20 02	0 27 003	+	,		+	+		0		0	0 0		-	
	ac-majevo-rozega ederevo-Mala Krsna	• •	• •	0,41		26.4	0	0	+	4		+	+		00		0 0	0 0		+	
	crsna-Bor-Rasputnica "2"-(Vražogrnac)	0	0	0	0	0	0	0	0	0				iskra	-		0	0			0
worbalic 0<	-Zaječar- Prahovo pristanište	0	0	0	0	0	0	47,000		0				iskra	0		0	0	0		0
International and)-Doljevac-Kastrat-Kosovo Polje	0	0	0	0	0	0	0	0			+	+		0		0	0		+	-
	šumlija-Kastrat Jovo). Pasournica "1", Kuršumlija	• •	0 0	0 0	0 0	0 0	0 0	0 0	0 0	00		-			0 0		0 0	0 0		+	
	otica-Subotica fabrika	0	0	0	0	0	0	0	0			+	+		0		0	0		+	10
	otica-Subotica bolnica	0	0	0	0	0	0	0	0	0		-			0		0	0		-	0
	ıjiža-Horgoš	0	0	0	0	0	0	0	0	0		-	-		0		U	0)		9



	Π	rspliftens bruorg-nI	pcs	27	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
		srəftilqms bnuorg əvodA	pcs	26	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
			pcs	25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Digital telephone	s/iidM 221	type	24																														
	Digita	s\idM 8	pcs	23	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
			type	22																_	_		_											
			pcs	21	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
EVICES		s\iidM 2	type	20																														
VEL D			pcs	19	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	31
MULTI-CHANNEL DEVICES		Telegaph	type	18																														
		rəfilqms bnuorg-nl	pcs	17	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	44
		erofilqms bruorg ovodA	pcs	16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	50
	ne	Over 12 channels	pcs	15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	8
	slepho.		type	14																														
	Analogue telephone	<i>a</i> 5	pcs	13	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	28
	Analo	Up to 12 channels	s type	12																														
		slanneda 5 of qu	e pcs	Ξ	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4
Ľ			type	10																_														
		Local	km	6	0	0	0	0	0	0	0	0	0	0	0	0	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	427,07
	Cable lines	Fiber optic	km	~	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	72,950
STEMS	Cable	AT2	km	7	0	0	0	0	0	0	0	0	0	0	0	0	9	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	507,024
CABLE SYS		¥XLS	km	9	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1041,453
U	ines	overhead cables	km	5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	263,142
	Overhead lines	гоп топ-	km	4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	31,650
	0	Two-wire overhead lines SiBr	km	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2,000
		RAILWAY LINE		2	i Podbara-Rasput. "3"-Rasput. "2"-(Kać)	 (Rim.Šančevi)-Rasput "1"-Rasput. "3"-(Podb.) 	Vrbas-Sombor		Sonta-Apatin fabrika-Strilić-(Sombor)	Bač-Karavukovo	Bačka Palanka-Gajdobra	(Ruma)-Rasp.Donja Borina-Zvornik Grad	 Šid-Sremska Rača Nova-State Border. 	Kikinda-Banatsko Arandelovo	 Sečanj-Jaša Tomić 	 (Zrenjanin)-Zrenjanin fabr. Vršac-Bela Crkva 	Pančevo Varoš-Pančevo Vojlovica	(Uljma)-RaspB-(Jasenovo)	Senta-Odvojna skr. 22 Senta	 (Požarevac)-Rasput.Sopot PožKostolac 	Markovac-Resavica	Ovča-Padinska Skela	Alibunar-Seleuš	· Vladimirovac-Kovin	Čoka-Novi Kneževac	Kikinda-MKS (ind.kolosek)		Sombor-Bački Breg	Sombor-Ridica	 (Višnjićevo)-Rasput.Rača-Sremska Rača 	Paracin-Stari Popovac	: Surčin-Jakovo-Bečmen-(Boljevci)	 (Bgd spoljna)-km 2+290-Fabrika šećera 	Total
		o ^N ənil yewl	isЯ		305	306	308	309	310	311	312	313	314	315	316	317	318	319	320	321	322	323	403	404	405	406	407	408	409	410	411	412	413	
1			٥N		37	45	33	69	74	54	55	46	52	60	11	81	67	78	48	70	63	66	53	80	59	61	58	72	73	79	68	77	57	



			RADIO DEVICE														
			Locomotive dispatching radio devices Traffic running networks (2m)						Station radio networks (0,7m)								
	Railway line No	RAILWAY LINE	Exchange units (with railway line splitter)	Length of covered railway line	Frackside stations	Locomotive stations	Number of networks	Radio link	Repeaters	Fixed stations	Mobile stations	Movable stations	Number of networks	Repeaters	Fixed stations	Mobile stations	Movable stations
ON 1	Rai		pcs	km 20	pcs	pcs 21	pcs	pcs	pcs	pcs	pcs	pcs	pcs	pcs	pes	pcs	pcs
1 5	101	2 BGD-Šid-State Border	28 1	29 100	30 8	31 0	32 0	33 0	34 0	35 0	36 0	37 0	38 8	39 0	40 8	41 0	42 21
3	102 103	BGD-Mladenovac-Niš-Preševo-State Border. (BGD)-Rakovica-Jajinci-M.Krsna-V.Plana	3	377 100	42	8	0	0	0	0	0	0	17	3	19	3	53 3
2	104	(BGD)-S.Pazova-Inđija-Subotica-State Border.	1	155	10	4	0	0	0	0	0	5	7	1	16	0	74
22 6	105 106	Niš-Dimitrovgrad-State Border. BGD Centar-Pančevo-Vršac-State Border.	0	0 20	0 4	0	0	0	0	0	0	0 4	3	0	3	0	12
1	107	(BGD)-Resnik-Podgorica-Bar	1	176	35	0	0	0	0	0	0	0	14	1	13	4	35
20 26	108 109	Lapovo-Kraljevo-Ð.Janković-State Border. Subotica-Bogojevo-State Border.	0	0	0	0	1 0	0	1 0	16 0	4	0	0	0	0	0	0
7	110		1	10 10	0 2	164 0	0	0	0	0	0	0 0	0	0	0	10 0	0
8	111 112		0	20	2	0	0	0	0	0	0	0	0	0	0	0	0
14 13	113	BGD Ranžirna."B"-Ostružnica BGD Ranžirna "A"-Rasp."B"-Rasp."K"-Resnik	0	0 20	03	0	0	0	0	0	0	0 0	0	0	0	0	0
25	115	Ostružnica-Rasp."B"-(Rasp."K"-Resnik)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
10	116 117	BGD Ranžirna "B"-Rasp."R"-Rasp."A" (BGD Ranžirna "B")-Rasp."R"-Rakovica	0	8	4	0	0	0	0	0	0	0	6 0	1 0	3	0	19 0
9	118	(BGD)-BGD Ranžirna "A"-Rasp."T"-Rakovica	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
12 16		BGD Ranžirna "B"-Rasputnica "T"-(Rakovica) (BGD Ranz."A"-Ras.B)-Ras.K-Ras.K1-Jajinci	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0 12
29	121	Topčider-Rasp.Savski Most-(Novi BGD)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
28 27	122 123	TopčBlok 1Obala-Blok 2 prelRas.Pan.Most (Topč)-Blok 1Obala-BGD Spoljna-Blok 2 prel	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
31 19	124 125		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
24	125		0	0	0	0	0	0	0	0	0	0	4	0	4	0	11
41 21	127 128		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
30	129	Trupale-Niš Ranžirna-Međurovo	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
17 23	130 131		0	0	0	0	0	0	0	0	0	0	5	0	8	2	19 0
18	132	(Cr.Krst-Skr.2)-Skr.3-Skr.4-(Ćele Kula)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
51 43	201 202	Subotica-Horgoš-State Border. Pančevo Glavna-Zrenjanin-Kikinda-State Border.	0	0	0	0	0	0	0	0	0	0 2	0	0	0	0	0
32	203	Banatsko Miloševo-Senta-Subotica	0	0	0	0	1	0	2	8	0	6	0	0	0	0	0
44 39	204 205	Pančevo Varoš-Rasputnica "2a"-(Jabuka) N.Sad-Sajlovo Rasputnica-Bogojevo	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
40 38	206 207		0	0	0	0	1	0	2	18 0	0	4	0	0	0	0	0
42	207	N.Sad Ranžirna-Sajlovo Rasputnica Orlovat-Rasputnica "1a"-(Lukićevo)	0	0	0	0	1	0	0	1	0	0	0	0	0	0	0
47 50	209 211	Ruma-Šabac-Rasp.Donja Borina-State Border. Stalać-Kraljevo-Požega	0	0	0	0	1 0	0	1	8	0	2	2	0	2	0	5
49	214	Smederevo-Mala Krsna	0	0	0	0	0	0	0	0	0	0	4	0	4	0	12
34 35	215 216	1	0	0	0	0	0	0	0	0	0	0 4	0	0	0	0	0
64	218	(Niš)-Doljevac-Kastrat-Kosovo Polje	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
62 56	219 220	Kuršumlija-Kastrat (Barlovo)-Rasputnica "1"-Kuršumlija	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
76	301	Subotica-Subotica fabrika	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
75 65	302 303	Kanjiža-Horgoš	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
36 37	304 305		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
45	306	(Rim.Šančevi)-Rasput "1"-Rasput. "3"-(Podb.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
33 69	308 309	Vrbas-Sombor Petrovaradin-Beočin	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
74	310	Sonta-Apatin fabrika-Strilić-(Sombor)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
54 55	311 312	Bačka Palanka-Gajdobra	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
46 52	313 314		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
60	315	Kikinda-Banatsko Aranđelovo	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
71 81	316 317		0	0	0	0	0	0	0	0	0	0	0	0	0 2	0	0 4
67	318	Pančevo Varoš-Pančevo Vojlovica	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
78 48	319 320		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
70	321	(Požarevac)-Rasput.Sopot PožKostolac	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
63 66	322 323		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
53 80	403 404	Alibunar-Seleuš Vladimirovac-Kovin	0	0	0	0 0	0	0	0	0	0	0	0	0	0	0	0
59	405	Čoka-Novi Kneževac	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
61 58	406 407		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
72	408	Sombor-Bački Breg	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
73 79	409 410	Sombor-Riđica (Višnjićevo)-Rasput.Rača-Sremska Rača	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
68 77	411 412	Paraćin-Stari Popovac	0	0	0	0	0	0	0	0	0	0 0	0	0 0	0	0	0
57		(Bgd spoljna)-km 2+290-Fabrika šećera	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1		Total:	9	996	122	176	8	2	11	89	4	27	83	6	95	20	298



Appendix 3.8. List of service points where it is possible to perform the transshipment of dangerous goods

The user or the authorized person is liable for safe transshipment and provision of required permits for transshipment issued by the competent authorities (ministry, local self-government, etc.) in case such permits are prescribed by law or by-laws. The Infrastructure Manager is not obliged to control permits and approvals issued by the competent authorities. In case of an accident during transshipment, the user or authorized person undertakes all necessary measures for making handling point functional.

Transshipment of the respective dangerous goods may be carried out on the handling point (handling area, ramp), i.e. the facility placed beside the track referred to in column 3, Table 1 of this Appendix. Transshipment shall be performed in compliance with the applicable regulations of the Republic of Serbia in the field of transport of dangerous goods, health and safety at work, environmental protection, waste treatment, fire protection, etc., complying with the essential safety measures which shall be provided as follows:

Keeping, disposal and storage of dangerous goods in the area of service point, including handling point is prohibited.

The handling point where transshipment is carried out must be enclosed or in any other way separated from passenger transport or from the handling point (loading, unloading, transshipment) with the goods not classified as dangerous (not RID). If a handling point is not enclosed, the client must mount movable fence which shall be removed upon handling (made of plastic orange material used in construction).

The handling point where transshipment is carried out shall have "RID – warning plate on the handling point". In case an IŽS' service point, within which there is the place of handling with dangerous goods, does not have "RID – warning plate on the handling point", the user of the handling point (consignee, consignor or authorized person) is obliged to provide the said plate at their own expense during the entire period of handling. The plate shall be made of sheet, with red colour base, on which the text with white letter is inscribed. The text shall read: RID WARNING – HANDLING WITH DANGEROUS GOODS. Minimum plate size is 600x500 mm. The plate shall look like as indicated:



Transshipment of the dangerous goods is carried out during the visible part of day, but it may be performed at night, with electrical lighting whereby the electrical devices that cannot cause fire or explosion may be used. In case an IŽS service point, within which there is the point of handling with dangerous goods does not have capacity for electrical lighting, the user of the handling point shall be obliged to provide necessary lighting at their own expense during the entire period of handling.

In case that said track is under OCL, during transshipment the voltage must be turned off and the track shall be secured in a duly manner.

Road vehicle engine shall be turned off during transshipment.

The disposal of the flammable and material which may cause or intensify fire is prohibited. Furthermore, it is forbidden to dirty the handling area with oil or oil derivatives (out of road freight vehicle).



Fire lighting or work with any open flame, use of tools which sparks and the devices with burner as well as smoking are forbidden during transshipment.

The user of the handling point (consignee, consignor or the authorized person) is obliged to perform cleaning and remove waste, which has been generated during the process of handling with dangerous goods, to the dumpsite, upon the completion of handling activities, in accordance with the Law on Waste Management, Law on Environmental Protection and other legislation and by-laws in the field of environmental protection. In case the user of authorized person does not clean the area after transshipment and does not take waste to the respective dumpsite outside the station, the railway undertaking shall perform cleaning.

The user of the handling point is obliged that, in the process of handling with dangerous goods, comply with the Law on Transport of Dangerous Goods and Law on Protection at Work (to take care on safety and health at work of their employees on the handling point), and particularly to get them acquainted, in a proven manner, with the hazards of stay in railway area (general safety of movement in IŽS's service points, way of conduct in service points, restrictions in movement, hazards from high voltage and other hazards).

Simultaneous transshipment at the same place of handling with dangerous goods of different classes is forbidden.

The service points where transshipment of certain dangerous goods from railway wagons into road vehicle and vice versa is performed are given in the Table of this Appendix.

Upon the request of the interested parties, Infrastructure of Serbian Railways JSC may approve transshipment of other dangerous goods, as well as in service points not given in the Table of this Appendix, in case there are conditions met for handling in the service point, and if the approval of the competent authority is provided for the goods that are being transshipped if it is prescribed by the law (ministries, local self-government units, , i.e. the Ministry of Interior's services).

For more information please contact:

"Infrastructure of Serbian Railways" JSC Traffic Department 6 Nemanjina St., 11000 Belgrade, Serbia Phone/Fax:+381 11 36 18 214 E-mail:sektor.sp@srbrail.rs

The table consists of 7 columns, with the following content:

- column No 1 "ordinal No";
- column No 2 "Name of a service point";
- column No 3 "Track", contains ordinal number or name of track in accordance with Station regulations (transport dispatching point or loading point);
- columns 4, 5 and 6 "Dangerous goods", contain NHM code, UN item/number for indication of hazards and class of dangerous goods, whose transshipment may be carried out;
- column No 7 "Notes", contains specific information relating to specific boxes.

			Dangerous goo			
No	Name of service point	Track	NHM	UN / number for hazards indication	Class	Notes
1	2	3	4	5	6	7
1.	Adrovac	1	3105 20 3102 30	2067/50 1942/50	5.1 5.1	



			2105 20	2067/50	5 1	
2.	Aleksinac	1	3105 20 3102 30	2067/50 1942/50	5.1 5.1	
			3102 30	2067/50	5.1	
3.	Bagrdan	6	3102 30	2007/30 1942/50	5.1 5.1	
		1 5 5	3105 20	2067/50	5.1	
4.	Bačka Topola	1, 5, 7	3102 30	1942/50	5.1	
5.	Ror Fraight	1	3105 20	2067/50	5.1	
э.	Bor Freight	1	3102 30	1942/50	5.1	
6.	Valjevo	II line	3105 20	2067/50	5.1	
0.	v aljevo		3102 30	1942/50	5.1	
7.	Velika Plana	1	3105 20	2067/50	5.1	
			3102 30 3105 20	1942/50 2067/50	5.1 5.1	
8.	Vranje	1	3105 20 3102 30	2067/50 1942/50	5.1 5.1	
			3105 20	2067/50	5.1	
9.	Vršac	11, 19	3102 30	2007/30 1942/50	5.1 5.1	
10	Church X	1	3105 20	2067/50	5.1	
10.	Grejač	1	3102 30	1942/50	5.1	
11.	Žednik	1, 6a	3105 20	2067/50	5.1	
11.		-	3102 30	1942/50	5.1	
12.	Zmajevo	5	3105 20	2067/50	5.1	
12.			3102 30	1942/50	5.1	
13.	Zrenjanin	1, 10	3105 20	2067/50	5.1	
	5	,	3102 30	1942/50	5.1	
14.	Zrenjanin Factory	1	3105 20 3102 30	2067/50 1942/50	5.1 5.1	
	-		3102 30	2067/50	5.1	
15.	Jagodina	1, 8	3102 30	2007/30 1942/50	5.1 5.1	
1.6	¥7'1 ' 1	20. 21	3105 20	2067/50	5.1	
16.	Kikinda	20, 21	3102 30	1942/50	5.1	
17.	Kula	1	3105 20	2067/50	5.1	
1/.	Kula	1	3102 30	1942/50	5.1	
18.	Lapovo	1	3105 20	2067/50	5.1	
	<u>r</u> • • •		3102 30	1942/50	5.1	
19.	Lapovo marshalling yard	Station for	3105 20	2067/50	5.1	
		disinfecting New track	3102 30 3105 20	1942/50 2067/50	5.1 5.1	
20.	Leskovac	INCW HACK	3103 20 3102 30	2067/50 1942/50	5.1 5.1	
			3105 20	2067/50	5.1	
21.	Lešak	1 short	3102 30	1942/50	5.1	
22	Mala Krana	1	3105 20	2067/50	5.1	
22.	Mala Krsna	1	3102 30	1942/50	5.1	
23.	Mladenovac	1,7	3105 20	2067/50	5.1	
43.		1, /	3102 30	1942/50	5.1	
			3105 20	2067/50	5.1	
			3102 30	1942/50	5.1	
		2317	2807 00	1830/80	8	
24.	Novi Sad Marshalling	2, 3, 4, 7 Locomotive and	2806 10 2815 12	1789/80 1824/80	8 8	
∠ - ⊤ .	Yard	freight stations	2808 00	2031/80	8	
		freight stations	2809 20	1805/80	8	
			2815 11	1823/80	8	
			2828 90	1791/80	8	
25.	Ostružnica	1	3105 20	2067/50	5.1	
			3102 30	1942/50	5.1	
26.	Palanka	1	3105 20	2067/50	5.1	



r		T	3102 30	1942/50	5.1	
			3105 20	2067/50	5.1	
27.	Pančevo varoš	1				
			3102 30	1942/50	5.1 5.1	
28.	Pančevo Main St.	20, 21	3105 20	2067/50		
		· ·	3102 30	1942/50	5.1	
29.	Paraćin	1	3105 20	2067/50	5.1	
			3102 30	1942/50	5.1	
30.	Pirot	1	3105 20	2067/50	5.1	
			3102 30	1942/50	5.1	
31.	Požarevac	1	3105 20	2067/50	5.1	
			3102 30	1942/50	5.1	
			3105 20	2067/50	5.1	
32.	Požega	19	3102 30	1942/50	5.1	
			3102 30			
33.	Prijepolje Freight	13	3105 20	2067/50	5.1	
	i iijepoije i teight	10	3102 30	1942/50	5.1	
34.	Prokuplje	1	3105 20	2067/50	5.1	
54.	Tokupije		3102 30	1942/50	5.1	
35.	Resavica	Right dead-end	3105 20	2067/50	5.1	
55.	Kesaviea	track	3102 30	1942/50	5.1	
36.	Ruma	1, 2	3105 20	2067/50	5.1	
50.	Kullia	1, 2	3102 30	1942/50	5.1	
37.	Sviloinee	1	3105 20	2067/50	5.1	
57.	Svilajnac	1	3102 30	1942/50	5.1	
20	S	1 10 11	3105 20	2067/50	5.1	
38.	Senta	1, 10,11	3102 30	1942/50	5.1	
20	Courstoon	20, 21	3105 20	2067/50	5.1	
39.	Sombor	20, 21	3102 30	1942/50	5.1	
40.	Successive Mitnessive	1.0	3105 20	2067/50	5.1	
40.	Sremska Mitrovica	1,9	3102 30	1942/50	5.1	
41	Stala (1 shout tus als	3105 20	2067/50	5.1	
41.	Stalać	1 short track	3102 30	1942/50	5.1	
40		1, 33, 34 and 36	3105 20	2067/50	5.1	
42.	Subotica	freight station	3102 30	1942/50	5.1	
40	<u></u>	1	3105 20	2067/50	5.1	
43.	Ćićevac	1	3102 30	1942/50	5.1	
	<u> </u>	1	3105 20	2067/50	5.1	
44.	Ćuprija	1	3102 30	1942/50	5.1	
15		1	3105 20	2067/50	5.1	
45.	Užice Freight	1	3102 30	1942/50	5.1	
1.5	Č × 1	1 1 1 1	3105 20	2067/50	5.1	
46.	Čačak	1-dead-end track	3102 30	1942/50	5.1	
·	ă 1		3105 20	2067/50	5.1	
47.	Šabac	1,7	3102 30	1942/50	5.1	
48.	Stara Pazova	7	3102 30	1942/50	5.1	
			3105 20	2067/50	5.1	
49.	Kruševac	1	3102 30	1942/50	5.1	
50.	Vrbas	10,11	3105 20	2067/50	5.1	
			3105 20	2067/50	5.1	Only for goods
51.	Bajmok	1	3102 30	1942/50	5.1	in sacks
		1	3105 20		5.1	III SUCKS
52.	Futog	1	3102 30	2067/50	5.1	
l			5102 50		J.1	



No	Regular route	Distance (km)	Alternative route	Distance (km)
1	Subotica-Novi Sad	98.5	Subotica-Sombor-Vrbas-Novi Sad	150.5
2	Subotica-Novi Sad	98.5	Subotica-Sombor-Bogojevo-Novi Sad	165.4
3	Subotica-Novi Sad	98.5	Subotica-Zrenjanin-N.Sad	230.6
4	Subotica-Belgrade	175.6	Subotica-Zrenjanin-Pančevo- Belgrade	234.6
5	Novi Sad-Belgrade	77.1	Novi sad-Orlovat-Pančevo-Belgrade	148
6	Kikinda-Subotica	96.4	Kikinda-Orlovat-N.Sad-Subotica	271
7	Belgrade-Lapovo	109.6	Belgrade-Požega-Kraljevo-Lapovo	306.1
8	Belgrade-Lapovo-Kraljevo	194.3	Belgrade-Požega-Kraljevo	221.4
9	Belgrade-Niš	243.5	Belgrade-Požarevac-Zaječar-Niš	372.9
10	Belgrade-Požega	154.9	Belgrade-Lapovo-Kraljevo-Požega	260.8
11	Belgrade-Požega-Vrbnica(ŽCG)	299.3	Belgrade-Lapovo-Kraljevo-Požega- Vrbnica(ŽCG)	405.2
12	Belgrade-Smederevo	83.1	Belgrade-Mladenovac-V.Plana- Smederevo	132.8

Appendix 3.9. Alternative transport routes

Note: For departure/terminal station the names of the nodes are given, and various service points may be comprised within the respective node.



Appendix 3.10. Facilities for rolling stock maintenance

Maintenance of railway vehicles is performed in accordance with the Rulebook on Railway Vehicle Maintenance ("Official Gazette of RS", No 144/20).

Service facilities for provision of the basic services- where the works on the maintenance of vehicles are executed, and which are not carried out regularly as the part of daily activities requiring the vehicle to be detached from traffic are the organizational units of the other companies and Infrastructure of Serbian Railways JSC does not provide this type of services.

In accordance with the available data, service facilities and basic maintenance services provided by the Joint Stock Company for Passenger Railway Transport "Srbijavoz", Belgrade are as follows:

Location	Address	Facility	Primary Purpose	Basic Information
	Milana	Depot Zemun	Maintenance of electric rolling stock and passenger coaches	Area: 10.200 m2 6 tracks of unit length 220 m
Zemun	Rešetara bb	Depot for underfloor wheel lathe	Wheel processing of rolling stock	Area: 350 m2 It has underfloor wheel lathe without dismantling of wheel-sets
		Workshop	Regular maintenance of electric and diesel locomotives	Area: 85 m2 Disposes of service canal of 36m and platform but without a canopy
Lapovo	Lava Tolstoja 10	Maintenance depot	Maintenance of electric and diesel locomotives and motor trains	Area: 1.part 1088 m2 and second part 625 m2 It has two running lines 2 out of which there are two canals on one line in the length of 50m and 20m. It disposes of single-axle weighbridge for measuring and adjusting the axle load of the rolling stock.
Sombor	Braće Miladinom 1	Hangar	Maintenance of DMUs, and may be used for maintenance of freight wagons and diesel locomotives	Area:1337,5 m2 It has two tracks of the length 78 m and 24 m; it disposes of underfloor wheel lathe for wheel processing on rolling stock without dismantling. Area: 687 m2
		Depot for railbuses		has 1 track in the length of 78 m
Zrenjanin	Dr Vase	Depot for railbuses	Maintenance of railbuses and replacement of wheel-sets of 711 DMUs	Area: 277 m2 1 canal in the length of 27 m
Zaenjanin	Stajica 2	Depot for DMUs	Maintenance of DMUs	Area: 432 m2 1 track in the length of 34 m
Vršac	Pavliški put bb	Depot for maintenance of rolling	Inspections and extraordinary repairs of smaller scope on diesel traction units and	Area: 787 m2 Two tracks in the length of 40 m



		stock	DMUs, as well as the overhauls of freight wagons	
Zaječar	Železnička bb	Workshop for repair of locomotives	Maintenance of diesel traction units and freight wagons	Area: 1250 m2 4 track out of which two are, unit length- 50 m

For more information on the provision of basic services in the above facilities responsible is their user in "Srbijavoz", Belgrade, Department for Rolling Stock Maintenance.

Contact point: Director of Department for Rolling Stock Maintenance - Mr. Vladan Petrović Address: 6 Nemanjina St. 11000 Belgrade, Serbia E-mail: vladan.petrovic@srbrail.rs Phone: +381 64 845 22 64

Information on the service facilities and services provided by the Joint Stock Company for Freight Railway Transport "Srbija Kargo", are available on the web-site: <u>http://www.srbcargo.rs/rs/usluzni-objekti</u>. Information on the service facility and services provided by Šinvoz is available on the website <u>www.sinvoz.rs</u>.



SR PNEUMATIK

1

23000 ZRENJANIN, MANASTIRSKA BR. 13A PIB:101165889 MBR:54681496 TEL : 062/268-128, pneumatik.zrenjanin@gmail.com

INFORMACIJA O USLUŽNOM OBJEKTU SR PNEUMATIK ZRENJANIN

ZRENJANIN, april 2024



		. Opšte informacije
1.1.	Uvod	SR Pneumatik Zrenjanin je uradio Informaciju o uslužnom objektu na osnovu odredbi Pravilnika o elementima informacije o uslužnom objektu (Sl.glasnik RS broj 66/2019) Naziv uslužnog objekta je objekat za održavanje I spade u kategoriju 5, shodno članu 15. St. 2 Zakona o železnici (Sl.glasnik RS broj 41/18) Ova informacija je dostavljena upravljaču infrastrukture radi objavljivanja u Izjavi o mreži.
1.2.	Operator uslužnog objekta	Uslužnim objektom upravlja operator SR Pneumatik Zrenjanin, Manastirska 13a, kontakt Adamov Milivoj +38162268128
1.3	Period važenja I postupak ažuriranja	Ovaj dokumenat se ažurira po potrebi I nema definisan period važenja.
		2. Usluge
2.1.	Naziv usluge	 Sertifikovana radionica za održavanje železničkih vozila obavlja usluge: pregledi P1, P3,P6,P12 lokotraktora, drezina, lokomotiva; tekuće održavanje (opravke manjeg I srednjeg obima) lokotraktora, drezina, lokomotiva; kontrolni pregledi I tekuće održavanje obavlja se u depou vlasnika , osim kada je potrebno vozilo dovesti u pogon SR Pneumatik Zrenjanin. specijalizovana radionica za održavanje kočnice železničkih vozila.
		Opis uslužnog objekta
3.1	Spisak svih postrojenja	Uslužni objekat SR Pneumatik Zrenjanin, sastoji se od sledećih postrojenja na lokaciji Zrenjanin Takovska 104: -radionica za popravku lokotraktora,



		 Radionica raspolaže svom potrebnom opremom, mašinama I alatima neophodnim za popravke I održavanje železničkih vozila u radionici I na terenu. Uslužni objekat SR Pneumatik Zrenjanin na lokaciji "Tatravagonka Bratstvo" doo Subotica, Bikovački put 2 Subotica: Hala sa kolosekom I svim pratećim alatima I uređajima koji se koriste u procesu održavanja železničkih vozila se koristi na osnovu Ugovora o poslovno- tehničkoj saradnji od 29.12.2023. godine. Hala ima priključak na javnu železničku
3.2.	Mesto	mrežu. Zrenjanin, Takovska 104
		Subotica, Bikovački put 2
3.3.	Radno vreme	Radno vreme uslužnog objekta je 7-15 časova ponedeljak-petak, osim za vreme verskih I državnih praznika
3.4.	Planirane izmene tehničkih karakteristika	Ne planiraju se izmene tehničkih karakteristika
		4. Naknade
4.1.	Informacije o naknadama	Metodologija : norma sat Naknada za pristup uslužnim objektima se ne naplaćuje. Cena za pojedine usluge po norma satu, u zavisnosti od složenosti posla po ponudi , nakon izvršene defektaže.
4.2.	Informacije o popustima	Uslužni objekti ne nude popuste

5.1.	Pravni zahtevi	Za pristup je potrebno sklapanje ugovora ili narudžbenica.
5.2.	Tehnički uslovi	Železnička vozila namenjena za rad na koloseku širine 1435 mm I maksimalnog osovinskog opterećenja 22 t.
5.3.	Samopružanje usluga	Uslužni objekat ne dozvoljava mogućnost samopružanja usluga.
5.4.	IT sistemi	Uslužni objekat ne nudi korištenje IT sistema
- March March	The local division of	6. Dodela kapaciteta
6.1.	Zahtevi za pristup uslužnom objektu ili uslugama koje se pružaju u objektu	Podnosilac zahteva je dužan poslati zahtev za ponudom za uslugu na e-mail :pneumatik.zrenjanin@gmail.com , ili usmeno na telefon +38162268128 Rok za obradu zahteva je 3 radna dana Prihvatom ponude, usluga se pruža na osnovu ugovora i narudžbenice. Po završetku usluge sačinjava se zapisnik o izvršenim uslugama.
6.2.	Odgovor na zahtev	Rok za obradu zahteva je 3 radna dana Usluga se temelji na osnovu ugovora, narudžbenice I zapisnika o izvršenoj usluzi.
6.3.	Informacije o promenama tehničkih karakteristika I privremenim ograničenjima kapaciteta	Uslužni objekat nema privremenih ograničenja kapaciteta koji mogu uticati na rad. U slučaju privremenih ograničenja, obaveštava se upravljač infrastrukture.





Information on the service facility MIN Lokomotiva doo



INFORMACIJE O USLUŽNOM OBJEKTU MIN LOKOMOTIVA DOO

MIN Lokomotiva doo

Šumadijska 1, 18000 Niš

+381 18 415 1131

E-mail: min.lokomotiva.kabinet@gmail.com

Internet adresa: https://www.minlokomotiva.rs/

April 2024. godine



1



SADRŽAJ

1.1 UVOD	3
1.2 OPERATOR USLUŽNOG CENTRA	3
1.3 PERIOD VAŽENJA I POSTUPAK AŽURIRANJA	3
2.1 OPIS USLUGE	3
3.1 SPISAK SVIH POSTROJENJA	4
3.1.1 PROIZVODNI POGON ZA REDOVNO ODRŽAVANJE	4
3.1.2 PROIZVODNI POGON ZA VANREDNO ODRŽAVANJE	4
3.1.3 MAGACINI	
3.1.4 ŽELEZNIČKA INFRASTRUKTURA	5
3.2 MESTO USLUŽNOG OBJEKTA	5
3.3 RADNO VREME USLUŽNOH OBJEKTA	5
3.4 PLANIRANE IZMENE TEHNIČKIH KARAKTERISTIKA	6
4.1 INFORMACIJE O NADOKNADAMA	6
4.2 INFORMACIJE O POPUSTIMA	6
5.1 PRAVNI ZAHTEVI	6
5.2 TEHNIČKI USLOVI	6
5.3 ZAKUP KOLOSEKA U USLUŽNOM OBJEKTU	6
5.4 IT USLUGE	6
6.1 ZAHTEV ZA KORIŠĆENJEM USLUŽNOG OBJEKTA ILI USLUGAMA KOJE SE	
PRUŽAJU U USLUŽNO OBJEKTU	6
6.2 ODGOVOR NA ZAHTEV ZA PONUDOM	7
6.3 INFORMACIJE O DOSTUPNOM KAPACITETU I PRIVREMENIM	
OGRANIČENJIMA	7
7.1 PROSTORNI PLAN USLUŽNOG OBJEKTA	





1.1 UVOD

Informaciju o uslužnom objektu MIN Lokomotiva je izradila u skladu sa odredbama Pravilnika o elementima informacije o uslužnom objektu ("Službeni glasnik RS", broj 66/19). MIN Lokomotiva doo spada u kategoriju 5), po članu 15, stav 2 Zakona o železnici (" Službeni glasnik RS" broj 4/218), odnosno spada u kategoriju Objekata za održavanje.

Fabrika za proizvodnju i remont šinskih vozila MIN Lokomotiva osnovana je 1884-te godine kao glavna radionica srpskih državnih železnica za popravak i pregled parnih lokomotiva.

Nad MIN Lokomotivom proglašen je stečaj 2015.godine. Maja 2018.godine. MIN Lokomotiva je kao pravno lice kupljena je od strane sadašnjih vlasnika (fizičkih lica).

Osnovna delatnost MIN Lokomotive doo je remont i održavanje železničkih vozila, projektovanje i proizvodnja novih železničkih vozila i pružanje raznih usluga vezano za železničku industriju.

1.2 OPERATOR USLUŽNOG OBJEKTA

- Naziv uslužnog objekta : MIN Lokomotiva doo
- Adresa: Šumadijska 1, 18000 Niš
- Kontakt osoba za uslužni objekat: Dejan Avramović
- Broj telefona: +381 18 415 1131
- E-mail: min.lokomotiva.kabinet@gmail.com
- Internet adresa: https://www.minlokomotiva.rs/
- Radno vreme: 7.00-15.00, osim vikendom i praznicima

1.3 PERIOD VAŽENJA I POSTUPAK AŽURIRANJA

Ovaj dokument se ažurira u vreme objave inforamcije, osim ako su zbog izmena u sadržaju nužne vanredne izmene

2.1 OPIS USLUGE

Osnovne usluge koje pruža uslužni objekat:

- Redovno održavanje, koje se obavlja periodično i unapred planira
- Vanredno održavanje koje se obavlja radi otklanjanja kvarova, nedostataka, istrošenja i zagađenja u toku eksploatacije

Redovno održavanje obuhvata:

- Kontrola železničkih vozila u toku eksploatacije
- Pranje i čišćenje







- Servisni pregled
- Kontrolni pregled
- Redovnu opravku

Vanredno održavanje obuhvata:

- Vanredne opravke manjeg ili većeg obima
- Vanredno pranje i čišćenje

3.1 SPISAK SVIH POSTROJENJA

Uslužni centar MIN Lokomotiva doo sastoji se od sledećih celina

- Proizvodni pogon za redovno održavanje
- Proizvodni pogon za vanredno održavanje
- Radionica za ispitivanje lokomotiva na promenljivom naponu
- Radionica za ispitivanje brzinomera
- Radionica za održavanje elemenata vešanja i ogibljenja
- Magacin u zatvorenom prostoru
- Magacin na otvorenom prostoru
- Železnička infrastruktura

3.1.1 PROIZVODNI POGON ZA REDOVNO ODRŽAVANJE

- Ukupna površina pogona za redovno održavanje je : 1100m2, podeljena u dva objekta
- Proizvodni prostor je opremljen kolosecima i mosnim dizalicama od 5t
- Proizvodni pogon je tehnološki opremljen za redovno održavanje dizel i elektro lokomotiva

- Ulaz/izlaz vozila u pogon je omogućen je preko 5 ulazno/izlaznih koloseka povezanih preko preko prenosnice nosivosti 150t sa glavnim kolosekom ka stanici Niš

3.1.2 PROIZVODNI POGON ZA VANREDNO ODRŽAVANJE

- Ukupna površina pogona za vanredno održavanje je: 2500m2

- Proizvodni pogon za vanredno održavanje opremljen je kolosecima i mosnim dizalicama od 45 t (3 komada) i 5t (2 komada)

- Proizvodni pogon za vanredno održavanje opremljen je tehnološki za održavanje železničkih vozila

- Ulaz/izlaz vozila u pogon omogućen je preko 4 ulazno/izlaznih koloseka povezanih preko preko prenosnice nosivosti 150t sa glavnim kolosekom ka stanici Niš





 Proizvodni pogon za vanredno održavanje je opremljen viljuškarima i transportnim kolicima za unutrašnji transport

- Radionica za ispitivanje brzinomera tipa Hasler je opremljena atestiranom probnicom, nalazi se u sklopu pogona za redovno održavanje

 Radionica za održavanje elemenata vešanja i ogibljenja se nalazi u delu pogona za vanredno održavanje železničkih vozila i tehnološki je opremljena za održavanje elementa vešanja i ogibljena železničkih vozila

3.1.3 MAGACINI

- Površina zatvorenog magacina je oko 200m2. Magacin je opremljeno stalažama za smeštaj rezervnih delova i opreme.

 Otvoreni magacin ima površinu od 500m2 i koristi se smeštaj crne i obojene metalurgije, tehničkih gasova i ulja i maziva

- Zatvoreni i otvoreni magacini su povezana preko prenosnice sa glavnim kolosekom ka stanici Niš

- Zatvoreni i otvoreni magacini imaju putnu vezu sa glavnom saobraćajnicom

3.1.4 ŽELEZNIČKA INFRASTRUKTURA

- Ukupna dužina koloseka na lokoaciji (spoljašnji i unutrašnji) je oko 2000m

- Uslužni objekat je povezan sa železničkom stanicom Niš sa jednim matičnim kolosekom, koji se preko skretnice usmerava na koloseke prema pogonu.

- Dozvoljeno opterećenje koloseka je 22t po osovini, dozvoljena brzina na koloseku je 5km/h

 - Železnička vozila se sa glavnog koloseka prebacuju na koloseke u okviru proizvodnih kapaciteta preko specijalnog transportera-prenosnice nosivosti 150t

3.2 MESTO USLUŽNOG OBJEKTA

- Šumadijska 1, 18000 Niš
- Geografska širina 43°19'07"
- Geografska dužina 21°52'39''
- Priključak na javnu putnu mrežu
- Priključak na javnu železničku mrežu preko železničke stanice Niš

3.3 RADNO VREME USLUŽNOG OBJEKTA

- Ponedeljak-petak od 7.00-15.00h
- -Vikendom i praznicima su neradni dani





3.4 PLANIRANE IZMENE TEHNIČKIH KARAKTERISTIKA

- Ne planiramo izmene tehničkih karakteristika

4.1 INFORMACIJE O NADOKNADAMA

- Metodologija izračunavanja nadoknade je norma čas (NČ)
- Nadoknada za pristup uslužnom objektu se ne naplaćuje
- Cene usluga su definisane zvaničnim cenovnikom

4.2 INFORMACIJE O POPUSTIMA

 Operator uslužnog objekta može u specijalnim okolnostima nuditi popust na usluge koje se nude korisnicima prema međusobnom dogovoru uz poštovanje zahteva operatera o čuvanju poslovne tajne

5.1 PRAVNI ZAHTEVI

- Za pristup uslužnom objektu potrebno je sklapanje ugovora ili narudžbenica

5.2 TEHNIČKI USLOVI

- Uslužnom objektu mogu pristupiti železnička vozila standardne širine 1435mm

 - Uslužnom objektu mogu pristupiti vozila sa maksimalnim dozvoljenim osovinskim opterećenjem od 22t po osovini

5.3 ZAKUP KOLOSEKA U USLUŽNOM OBJEKTU

- Zakup koloseka u uslužnom objektu je definisan posebnim cenovnikom

5.4 IT USLUGE

- Uslužni objekat ne nudi IT usluge

6.1 ZAHTEV ZA KORIŠĆENJE USLUŽNOG OBJEKTAILI ZA USLUGAMA KOJE SE PRUŽAJU U USLUŽNOM OBJEKTU

 Podnosilac zahteva dužan je poslati Zahtev za ponudom na e-mail adresu min.lokomotiva.kabinet@gmail.com. Ili preko telefona na broj + 381 018 415 1131

- Usluga se pruža na osnovu potpisanog ugovora ili narudžbenice

- Za izvršenje usluga potrebno je da se najavi odgovornom licu u uslužnom objektu 2 dana unapred

- Podnosilac zahteva dužan je u zahtevu za ponudu navesti:

- 1. Vrsta usluge koja se traži
- 2. Osnovne podatke o železničkom vozilu
- 3. Vremenski period za korišćenje usluga



4. Potrebu za magacinskim prostorom ukoliko takva potreba postoji

5. Posebni zahtevi

6.2 ODGOVOR NA ZAHTEV ZA PONUDOM

- Rok za obradu zahteva i davanje ponude je do tri radna dana u zavisnosti od složenosti zahteva

 Osnovni kriterijum za određivanje rasporeda i kapaciteta uslužnog objekta jeste da prednost kod raspoređivanja ima podnosilac zahteva koji ima potpisan ugovor ili je ispostavio narudžbenicu ili je u završnim pregovorima sa vlasnikom uslužnog objekta o pružanju usluge

- U slučaju da dođe do kolizije u zahtevima, a koji se odnose na kapacitete uslužnog objekta prednost ima onaj podnosilac zahteva koji ima dugoročni ugovorni odnos sa vlasnikom uslužnog centra ili je po redu podnošenja zahtev bio ispred ostalih podnosilaca zahteva za uslugom. Ako i pored navedenih kriterijuma dođe do problema u korišćenju kapaciteta uslužnog centra odgovorno lice uslužnog centra će nastojati da razgovorom i koordinacijom sa korisnicima izvrši preraspodelu kapaciteta i po potrebi uvede drugu smenu kako bi svi korisnici bili adekvatno usluženi.

6.3 INFORMACIJE O DOSTUPNOM KAPACITETU I PRIVREMENIM OGRANIČENJIMA

 U slučaju vanrednih događaja koji mogu privremeno ograničiti kapacitet uslužnog objekta ili obavljanje planiranih radova odgovorno lice uslužnog centra će o tome obavestiti sve korisnike o nastalom događaju i o ograničenjima, kao i odgovrajuće službe koje upravljaju infrastrukturom.

7.1 PROSTORNI PLAN USLUŽNOG OBJEKTA

- Prostorni plan fabrike MIN Lokomotiva



Appendix 3.10a. Information on the service facility managed by Nelt Co



Nelt Co d.a.a. Maršala Tita 206 P. fah 530 11272 Dobanovci Srbija t +381 11 3779 100 f +381 11 3779 140 office@nelt.com www.nelt.com www.neltlsprs PIB 100037645 MB 17304712

Sektor za pristup železničkoj infrastrukturi Nemanjina 6, Srbija Datum: 21.12.2020.

PREDMET: INFORMACIJE O USLUŽNOM OBJEKTU – Industrijski kolosek "NELT Co", koji je deo Nelt Terminala

U stanici Surčin na pruzi Beograd Ranžirna, Park B - Ostružnica - Batajnica za javnu železiničku infrastrukturu kojom upravlja "Infrastruktura Železnice Strbije" ad priključen je industrijski kolosek čiji je vlasnik "Nelt.Co." d.o.o. Beograd.

Industrijski kolosek je namenjen samo za prijem i otpremu kolskih pošiljaka i isti se ne koristi za potrebe prevoza opasnih materija.

Industrijski kolosek počinje u nastavku četvrtog koloseka stanice Surčin odvojnom skretnicom br:2, u km. 14+166,57 pruge Beograd Ranžirna A– Ostružnica – Batajnica.

Industrijski kolosek "NELT Co" doo Beograd, odvaja se od javne železničke infrastrukture, kojom upravlja "Infrastruktura Železnice Srbije" ad, u stanici Surčin koja je nalazi u km 14+635,60 (*sredina stanične zgrade*) jednolosečne elektrificirane pruge Beograd Ranžirna, Park B - Ostružnica - Batajnica.

Skretnica br. 1c industrijskog koloseka "NELT Co" doo Beograd , matični kolosek razdvaja na dva kraka odnosno na dva koloseka

Industrijski kolosek je ukupne građevinske dužine 1293,31m i sastoji se od tri dela i to: • matičnog koloseke građevinske dužine 616,00 m

- Kolosek I građevinske dužine 348,00 m
- Kolosek II građevinske dužine 343,31 m

Koloseci I i II imaju korisnu dužinu svaki po 300 m tako da je ukupna korisna dužina na industrijskom koloseku 600 m.

Industrijski kolosek oposobljen je za kategoriju pruge C2 odnosno za:

- najveću dozvoljenu masu po osovini do 20 t/os (200 kN/os) i
- najveću dozvoljenu masu dužnom metru do 6,4 t/m (64 kN/m)

Koloseci I i II su na industrijskom koloseku vezani samo sa jedne strane tako da se na drugom kraju završavaju grudobranima,.

Manevru od stanice Surcin do Industrijski kolosek "NELT Co", za sada obavlja železnički operater "Srbija Cargo" ad.

Posedujemo 1 reach stacker kojim vršimo manipulacije kontejnera sa voza koji pristigne na Industrijski kolosek "NELT Co",

Cena za manipulacije punih kontejnera naplacuju se EUR 25 a praznih kontejnera EUR 20. obracunata u dinarskoj protivvrednosti





Neit Co d.a.a. Marŝala Tita 206 P. fah 530 11272 Dobanovci Srbija

t +381 11 3779 100 f +381 11 3779 140 affice@nelt.com www.nelt.com www.neltlsp.rs PIB 100037645 MB 17304712

Radno vreme Nelt terminala je radnim danima od 08h – 21h, subotom od 08h-16h, nedelja je neradni dan. Praznicima ne radimo

Nelt terminala Ul. Maršala Tita 206, 11272, Dobanovci +381 60 8318595 +381 11 3779 33 www.nelt.com

S poštovanjem,

UNUTRASNI Intermodatni tephna Nelt



Appendix 3.11. Railway infrastructure development projects

The National Assembly, upon the proposal of the Government, passes the National Program for the railway infrastructure, which contains:

1. the existing characteristics and condition of the railway infrastructure of the Republic of Serbia;

2. strategy for construction, reconstruction and maintenance of the railway infrastructure;

3. development components in the construction of the new infrastructure capacities of special significance for the Republic of Serbia;

4. defining of the structure, time schedule for realization of priorities, level and sources of the financial assets needed for completion of the National Program activities.

National Program is passed for a five-year period.

Based on the National Program, the Infrastructure Manager prepares the annual program for construction, reconstruction and maintenance of the railway infrastructure, organization and regulation of the railway traffic.

No	Project	Estmated commencement of works (date or quarter)	Duration of works	Works' execution method
1	Modernization (construction and reconstruction) of railway line Belgrade –Subotica –state border (Kelebia) section Novi Sad - Subotica	December 2021	Q3 2025	As of April 7, 2022 complete traffic interruption is valid between the service points Novi Sad (excl.)- Subotica (excl.)
2	Reconstruction of Niš – Brestovac section, from km 244+600 (exit from Niš station) to km 267+430 (entry into Brestovac station)	October 18 th , 2021	Q2 2025	Works are executed during daily line closures. Starting from April 19 th , 2022 traffic is performed with diesel locomotives
3	Civil engineering reconstruction of Niš – Dimitrovgrad railway line, section Sićevo - Dimitrovgrad	November 11 th , 2023	Q4 2026	Execution of the works and traffic performance according to the schedule: 36/36/36/60. Total line closure in the duration of 91 days starting Q1 2026.
4	Electrification of Niš – Dimitrovgrad railway line, section Sićevo - Dimitrovgrad	March 2024	Q4 2026	Execution of the works and traffic performance will be realized alternately in intervals agreed with the Contractor.
5	Construction of northern bypass around city of Niš: 1. Crveni Krst – Pantelej – Matejevac 2. Trupale – Crveni Krst 3. Trupale – Niš Marshalling Yard	Q4 2023	Q3 2025	Execution of the works and traffic performance will be realized alternately in intervals agreed with the Contractor.



Appendix 4.1. Request for train path allocation (form)

Fax.

Application form for train path allocation

Railway undertaking - operator:

Address:

Contact person:

Tel.

Place and date:

1. BASIC INFORMATION ON THE REQUESTED TRAIN PATH									
	Train No in	Desired tir	ne	Route	Route				
Train type	the previous timetable	departure	arrival	from	to	via			
NOTES									
2. TRAIN TIMETAR	BLE INFORMATIO	N	I						

e-mail:

2. TRAIN TIMETABLE INFORMATION									
Stops in service points	Staying time in service points [min]	Running calendar							

3. TRAIN	INFORMATI	ON					
	Additional				Braking	5	
Type of traction, serial No of traction unit, route	traction units, serial No of traction unit, function in the train, route	Series and No of the wagon /motor unit	Train mass [t]	Train length [m]	Туре	Percentage [%]	Maximum train speed [km/h]

4. OTHER REQUIREMENTS

L.S. SIGNATURE



Appendix 4.1a. Request for train path allocation (e-papir)

Republic of Serbia JSC "Infrastructure of Serbian Railways" Rail Infrastructure Access Department <u>www.infrazs.rs</u>

REQUEST

FOR TRAIN PATH ALLOCATION

Basic information about the applicant														
Business name / title														
Head office														
Contact phone														
Name and surname of the representative														
Identification number									PIB					
Email address														

Basic data on the required train path								
	Number of	Desire	d time	Route				
Train type	e train i previous TT		arrival	from	to	via		
Note								
	Т	rain timeta	ble data					
Stops in service points	Staying time in service points [min]			Ru	nning calendar			
	Train data							



	Additional				В	Fraking	
Type of traction, serial No of traction unit, route	traction units, serial No of traction unit, function in the train, route	Series and No of the wagon /motor unit	Train mass [t]	Train length [m]	Туре	Percentage [%]	Maximum train speed [km/h]
			Special	note			

I am aware that, if I do not submit the stated data, necessary for the decision-making of the body within 8 days, the request for initiating the procedure will be considered irregular.

The request can also be submitted on sektor.pzi@srbrail.rs

In _____ , on _____

Applicant's signature



INFORMATION FOR THE APPLICANT


Deadline for resolving the submitted request	30 days before the start of the timetable
--	---





Appendix 4.1b Template for submission of traction vehicle technical data

1.	Series	1116
2.	Description	BoBo
3.	Length	19280 mm
4.	Weight	88 t
5.	Maximum speed	230 km/h
6.	Inertia factor	1,15
7.	Resistance formula	
	$W=a+b\cdot v+c\cdot v^2$	a = 1020
		b = 8,44
		c = 0,25

8. Traction diagram and braking diagram







V

[km/h]

0

40

50

60

96

100

110

9. Traction type

electric



Appendix 4.2. Instruction for completion of the Request for train path allocation

	Column name	Data type	Explanation
	Train type	М	 Specify train type: Passenger train (pursuant to Articles 32 and 34 of Traffic Rulebook, Official Gazette of RS No 34/22 and 107/22) Freight train (pursuant to Articles 33 and 34 of Traffic Rulebook, Official Gazette of RS No 34/22 and 107/22)
	Train No in the previous Timetable	С	Specify the number of the train from the previous Timetable, whose path elements match applicant's request (e.g. 541, 40760,)
1.	Desired time	M/N*	Specify the desired time of the train departure from the origin station or the time of arrival to the destination station
	Route	М	Specify the origin and destination station of the train route and characteristic service point between those two stations which defines the train route
	Note	М	 Specify request type: annual request (for the new Timetable) request for regular or extraordinary amendments to the valid Timetable while specifying the number of regular amendment (I, II, III, IV or V amendment) ad hoc request
	Stops in service points	М	Specify all service points where the train needs to stop
2.	Staying time in service points	М	Specify the needed staying time in each service point (in minutes) where train staying is necessary
	Running calendar	М	Specify running calendar for regular trains. If a path is requested for the optional train, enter the indication "optional", and for trains under the ad hoc request specify the train running date
2	Type of traction, serial No of traction unit, route	М	Specify traction type (electric or diesel), serial number of traction (operating) locomotive and route of each particular locomotive if there is change of traction type on the required route
3.	Additional traction units, serial No of traction unit,	М	Specify number of additional traction units, traction units type (electric or diesel), serial number, position on the train (double heading, banking,) additional traction unit running route



	function in the train, route		
	Series and No of the coach/multiple-unit set	М	For passenger trains, specify coach series (letter designation of coach series) and number of coaches on the train i.e. series, number and serial number of multiple-unit sets (DMU/EMU)
	Train mass	М	Specify total train weight in the format of a sum of weight of hauled vehicles and the weight of all operating locomotives (Q+L)
	Train length	М	Specify train length in metres without the length of operating locomotives in service
		М	Braking type: specify braking type (G, P, R, Mg,)
	Braking	M/N**	Braking percentage: specify braking percentage which has to be considered during timetabling
	Maximum train speed	М	Specify maximum train speed considering characteristics of vehicles on the train
4.	Other requirements	С	Specify other requirements of the train such as: shunting of vehicles, change of train composition, connection, staff shift, type of intermodal transport unit, dangerous goods type, special consignments, train stays at border-crossing, technical stops (inspection, water supply, waste handling and similar) and time period required, need for additional track capacities (side tracking, pre-heating/cooling, forming of trains and similar), need for access to other additional service facilities and similar.

Legend:

 $M-data \ is \ mandatory$

C – data is conditional (mandatory, if the condition is fulfilled)

 $M\!/N^*$ - data is mandatory for passenger trains/data data is non-mandatory for freight trains

 $M/N^{\ast\ast}$ - data is mandatory for international trains/data is non-mandatory for domestic trains For multiple-unit sets running in domestic traffic, specify the maximum braking percentage provided by the multiple-unit set

Note: Upon receipt of the request for path allocation, IŽS will provide the RU with the infrastructure data based on which the RU will calculate the train running times and submit them to IŽS.



Appendix 4.3. Deadlines for annual 2024/2025 timetable preparation

Phase	Authority	Deadline
Submission of requests for path allocation for international passenger trains	RU	12.02.2024
Regular deadline for submitting allocation requests for annual timetable	IM	15.12.2023-18.04.2024
Coordination and harmonization of requests	IM/RU	09.04.2024-01.07.2024
Presentation of the First Draft timetable to RU	IM	01.07.2024
Draft review – remarks, suggestions, proposals and opinions	IM/RU	02.07.2024-02.08.2024
Draft timetable 2024/2025	IM	30.08.2024
Solving of problems and questions	IM	02.09.202409.09.2024
Extraordinary requests (remaining capacities)	RU	04.10.2024
Final deadline for capacity allocation according to extraordinary requests (remaining capacities)	IM	25.10.2024.
Timetable coming into effect	IM	15.12.2024



Amendment No	Submission date of requests for amendments to annual timetable	Deadline for capacity allocation	Application date for amendments to annual timetable
I	16.12.2024.	17.01.2025.	03.02.2025.
П	10.02.2025.	20.03.2025.	07.04.2025.
Ш	21.04.2025.	23.05.2025.	15.06.2025.
IV	07.07.2025.	15.08.2025.	01.09.2025.
V	11.08.2025.	19.09.2025.	06.10.2025.

Appendix 4.4. Deadlines for amendments to annual 2024/2025 Timetable



Appendix 5.1. Overview of railway lines on which train running is possible when they are manned only with engine driver

Train running with engine driver only in a traction unit, without train crew (engine driver – without train crew), can be performed on the following lines:

- Belgrade Center-Stara Pazova Šid state border (Tovarnik);
- (Belgrade Center) Stara Pazova -Novi Sad Subotica state border (Kelebia);
- Belgrade Center Junction G Mladenovac-Lapovo-Niš-Preševo state border (Tabanovci);
- (Belgrade Center) Rakovica Jajinci Mala Krsna Velika Plana;
- Belgrade Center Pančevo Varoš (Vršac);
- Belgrade Center Resnik Požega Vrbnica state border (Bijelo Polje)
 Section Resnik-Požega-Užice;
- Inđija Golubinci;
- Novi Sad Novi Sad Marshalling Yard Open line junction Sajlovo;
- Belgrade Center Novi Beograd;
- Belgrade Center Open line junction G (Rakovica);
- Belgrade Marshalling Yard "A" Ostružnica Batajnica;
- Belgrade Marshalling Yard "B"- Ostružnica;
- Belgrade Marshalling Yard "A"-Open line junction "B"-Open line junction "K/K1"- Resnik;
- Ostružnica Open line junction "B" (Open line junction"K/K1");
- Belgrade Marshalling Yard "B" Open line junction "R"-Open line junction "A"-(Resnik);
- (Belgrade Marshalling Yard "B") Open line junction "R" Rakovica;
- Belgrade Marshalling Yard "A" Open line junction "T" Rakovica;
- Belgrade Marshalling Yard "B" Open line junction "T" (Rakovica);
- Connecting line in the area of Open line junction "K/K1": (Open line junction "B") switch "K" switch "K1" (Jajinci);
- Topčider Putnička (km 4+195) Open line junction G (Rakovica)³;
- (Open line junction Pančevački most) Open line junction Karađorđev park Open line junction Dedinje – (Open line junction G);
- By-pass line of Mala Krsna station: (Kolari) junction points 1 junction points 28 (Osipaonica);
- Open line junction Lapovo Varoš Lapovo Marshalling Yard Lapovo;
- Trupale Niš Marshalling Yard Međurovo;
- Crveni krst Niš Marshalling Yard;
- Niš Open line junction Most (Niš Marshalling Yard);
- Mala Krsna Požarevac (Bor);
- Pančevo Varoš Pančevo Vojlovica;
- Smederevo Open line junction Jezava Radinac Mala Krsna;
- Novi Sad Marshalling yard Open line junction Sajlovo.
- Subotica Horgos State Border (Röszke).

On the other lines, in particular cases, train running can be performed with engine driver – without train crew in compliance with terms stipulated in the Traffic Rulebook ("Official Gazette of the Republic of Serbia", No 34/22 and 107/22).

³ By virtue of the Conclusion of the Government of the Republic of Serbia No 340-2989/2022 dated April 7, 2022, the Decision of the Shareholders' Meeting of Joint Stock Company for Public Railway Infrastructure Management "Infrastructure of Serbian Railways" Belgrade concerning the termination of public railway traffic, dismounting and reconstruction of infrastructure capacities on railway line Topčider Putnička (km 4+ 195) – Open line junction "G" – (Rakovica), has been approved.




Appendix 5.2. Overview of the lines that do not meet the conditions for train running with an engine driver only

List of Infrastructure of Serbian Railways lines that do not meet the conditions for operation of traction units with an engine driver only (other lines meet the conditions):

- (Belgrade Center) – Resnik – Požega- Vrbnica- state border (Bijelo Polje)

➢ Užice − Vrbnica section.





Appendix 5.3. Geometry of pantograph (current collector) TIP POS - 254/III used on IŽS network



Appendix 6. Register of infrastructure data

		əbutitl A	30		97,6 82 1	1.20	92	87.6		84,3	70.11	84 06	2	79.11	84,96	101,57	96,94	102,06	01.7	84,77	81,77	84,66	87,29	83,79	86,71	84.93													\square	225,5
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$		aguag gaibao. Loading	29		1-52	I-S2	I-S2	I-S2	I-S2	I-SZ	1-S2	1.2		I-S2	I-S2	I-SZ	I-S2	I-SZ		I-SZ	I-S2	1-S-1	I-S2	I-SZ	I-SZ	I-S				I-S2	I-SZ	I-S-I		I-SZ	I-SZ	I-SZ	I-SZ	7.5	I-S2	I-SZ
$ \begin{array}{ $		<i>←</i>	28			_	-	-		-	-		•	-	-	3	2	-	+			m	0			-	$\frac{1}{2}$		\vdash		-	-			\vdash	1		1 1	-	
Mathem memiliad Mathem memiliad <th< td=""><td></td><td>\rightarrow</td><td>27</td><td></td><td></td><td></td><td>4</td><td>,</td><td></td><td>•</td><td>-</td><td>- ~</td><td>,</td><td></td><td>m</td><td>0</td><td>-</td><td>v</td><td>, -</td><td>0</td><td></td><td>-</td><td>2</td><td></td><td>•</td><td>+</td><td>1</td><td></td><td></td><td></td><td>5</td><td>0</td><td></td><td></td><td>7</td><td>∞</td><td>\$</td><td>3 9</td><td>:5</td><td>15</td></th<>		\rightarrow	27				4	,		•	-	- ~	,		m	0	-	v	, -	0		-	2		•	+	1				5	0			7	∞	\$	3 9	:5	15
$ \begin{array}{ c c c c c c c c c c c c $		sqolS	26		10	2	1	5		2	-	•	>		0	9	2	4	n	2		m	2		,	۰ 4					2	•			3	0	•	> 0	-	\rightarrow
Mark LINEs Mark LI	aniinA	aniloni	25								-			3 9/0			0 1				0		0	0					0											
$\label{eq:constraints} \eqref{eq:constraints} eq:constraint$	[%] u	Gradient of the statio	24																										0											
$ \begin{array}{ $	sn		23		9		69	20		250	002			2	499	250	300	99 90 90 90 90 90 90 90 90 90 90 90 90 9	1000	1000	130	1000	1000	150	•••••	1500				<u></u> 30	22	<u></u>			40	30	2	200	30	30
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$		dispatching of passer	22		<u>م</u> م	- e-	P/F^{1}	~ ~	ъ	4	D C	D/F	н	P/F	P/F	P/F	ط 1	P P		P/F		d .	P/F		F	1			Ч		¢	-	4	Ч	P/F		d 2	뷥머	· •	P/F
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$			21		P I	>	Ч	Þ		Ч	F			þ	4	ግ	D	4	·Þ	р <mark>н</mark>		Þ	D				1		Ч		¢	4			Ч	Þ	;	5 =	, D	Ч
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	mon	slq gnibsol-bnə\-əbi8	20				s			S	Ŭ	2 0	2	s	s		s	C/F	1	s															s		¢	^		s
Image: Single of the service point with the service of the form the service of the service of the form the service of the service of the form the service of the s		Freight car scales	19																									(June)												
Image: Single of the service point with the service of the form the service of the service of the form the service of the service of the form the service of the s	ວເດ	- ebos miod esivies	18		16052	16012	16002	16001		16204	16501	10001	16204	16501	16503	16505	16506	16507	16508	16509	16510	16511	16513	16514	16515	16517		Tahand	16052			16103	70101	16101	15501	15401	15408	15403	15404	15405
$\begin{tabular}{ c c c c c c c c c c c c c c c c c c c$	the service point	t gninose 10 ronneM	17		=	:	11	1		=	:	: :	: =	Ξ	11	-	-	-	•			-			•	-	1	rder -	-	-	- •	-	-	•	1	1	•		• •	-
$\begin{tabular}{ c c c c c c c c c c c c c c c c c c c$	noitslu	ຊອາ ວີເປີຣານ ໃດ າອກກະເທັ	16	nik)	RC with TWT	RC with TWT	RC with TWT	RC with TWT RC with TWT	RC with TWT	RC with TWT	PC with TWT	RC with TWT	THE THE AL	RC with TWT	RC with TWT	RC with AB	RC with AB	RC with AB PC with AB	RC with AB	RC with AB	RC with AB	RC with AB RC with AB	RC with AB	RC with AB	RC with AB	station distance		š - Preševo - state ho	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB
$\begin{tabular}{ c c c c c c c c c c c c c c c c c c c$			5	Tovar	d 6	3	6 P	d 2		9 P	-	d S	110		d 6	d 5	d 5	y P	3 5	e e	+	d 3	d 5					N-O	9 P							d 2			+	
$\begin{tabular}{ c c c c c c c c c c c c c c c c c c c$			15	ler - (5 an 4 an		8 an	1 an		5 an		4 an	9 and		5 an	4 an	4 an	4 30	4 an	2 an		2 an	4 an			4 31		2000	5 an						3	1 an		4 m	1-	2
Maximum permitted Maximum permitted Maximum permitted 0 0 1 <			14	e bord	506	070	411	209		238		651			443	749	786	653	911	672		667	673			ē		I - Je	506		000	/02			730	707		19/	659	692
Maximum permitted Maximum permitted Maximum permitted 0 0 1 <			ES	- stat	9 %	h		4		2	-	_	_	2			~	-			+	~	~				$\frac{1}{2}$	denor	9			-	+	+		5		+	+	
Matrix Matrix<	Я⇔А		13 N LIN	- Šid	5 and		1 and	3 and		1 and	1000	1 and	9 and	2 and	1 and	2 and	2 and	pue C	2 and	4 and		4 and	2 and			7 9110		- Mis	5 and			4			3	1 and	1	4 ~	1-	2
Main mediover in mediover in the service point Main mediover in the mediover in the service point Main mediover in the mediover in the mediover in the service point Main mediover in the mediover in the mediover in the mediover in the mediover in the mediover i		train length	12 MAR	azova		-		66		-		-		-			601	+	+	: 8	1	14	+		-	-	1	ovica	80		ŝ	62		t	30	60	5	- 5	30	92
Maine of service point Maine of service point Maine of service point Maine of service point 101 1 1 1 0 1 0 1 0 1 0 1 0 1 0 1 0 <td< td=""><td></td><td></td><td>1</td><td>Stara I</td><td></td><td>` </td><td>*1</td><td></td><td></td><td></td><td></td><td></td><td>F</td><td>Ļ</td><td>F</td><td></td><td>Ŭ</td><td></td><td>1</td><td></td><td></td><td></td><td>41</td><td></td><td></td><td></td><td>Šid)</td><td>- Rat</td><td></td><td></td><td>+</td><td>+</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>			1	Stara I		` 	*1						F	Ļ	F		Ŭ		1				41				Šid)	- Rat			+	+								
1000000000000000000000000000000000000	permitted		10 1	grade -								00 ^{II} 20	F	20 - 12	н	8	ç	20		20	-		30			80	: (mixed,	5" NO			-	+				30		30	:	
1000000000000000000000000000000000000	á		6			5	4			4									_	-	8		-	8	2	_	traffi	NCT				_		1	4	4	*	t z		4
Image: constraint of the second sec			8	10		+		_		-	+	+	-	_	_	+		-	+		-+	-	+	+	-	-	r freigh	LE EN	-	-	-	+	+	-			-	-	+ +	+
1000000000000000000000000000000000000		-	2			+		-		_	-	+			-	\vdash		+	+		+	-	+	\vdash	+	-	loes fo		-	_	-	+	+	+	\vdash		-	+		+
Image: constraint of the second sec			9			+				_	-	-	-	-		-		+	-		+	_	-	\vdash	+		n dista	HO -			_	+	_	+			_			
Image Image <th< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>ints and statio</td><td>rad Centar</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></th<>																											ints and statio	rad Centar												
Image: Signed state in the			4 5		0+000 BEOGRAD CENTAR 3+442 NOVI BEOGRAD	5+216 TOŠIN BUNAR	8+532 ZEMUN	11+053 ALTINA 12+248 ZEMUN POLJE	13+799 KAMENDIN	19+031 BATAJNICA ^P	22+006 KM 22+006 SC	24+044 STARA PAZOVA P	20+616 BATAINICA F	27+106 NOVA PAZOVA ^F	34+944 STARA PAZOVA ^F	44+361 GOLUBINCI	53+713 PUTINCI	59+800 [KRAL]EVCI 64-855 [RTMA.4	73+419 VOGANi	81+721 SREMSKA MITROVICA	86+100 LAČARAK	94+076 MARTINCI 00+200 RTI7MIN	05+018 KUKUJEVCI/ERDEVIK	09+100 BAČINCI	112+700 GBARAC	21+950 STATE BORDER	an distances for passenger traffic (Novi Sad) , ^T data for service poi	departure for the LFS zemuni 107 Report		1+337 OPEN LINE JUNCTION DEDINJE	4+416 OPEN LINE JUNCTION G	8+533 KAKOVICA	10+700 ENECEVAC 10+880 OPEN LINE JUNCTION A	11+729 KUEVO	14+059 RESNIK	17+930 PINOSAVA	20+121 RIPAN KOLONIJA	21+51 / KIPANJ 24+760 KT FNiF	29+592 RIPANJ TUNEL	34+730 RALjA
1920: 1930: 1930: 1930: 1930: 1940: 10112: 1930: 1940: 101012:		ma ni sontrei D	3		3 447	1,774	3,316	*2,625	1,551	5,232	2,975	7 838	0.00%	*6.556	7,838	9,417	*8,708	6,087	8 564	8,302	4,379	7,976	5,818	4,082			oints and stat	OI AILIVAL AIK		1,337	3,079	*1,/38	0.180	0,849	2,330	3,871	2,191	3 443	4,832	5,138
Bit Bit <td></td> <td>ген цаск</td> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>.583</td> <td>31.2</td> <td>1.10</td> <td>1</td> <td>+</td> <td></td> <td></td> <td>1978.</td> <td>.6</td> <td>881.</td> <td>21.</td> <td>10</td> <td></td> <td></td> <td>681</td> <td>.01.</td> <td>20</td> <td>_</td> <td>Truce p</td> <td>nposes</td> <td>·E6</td> <td></td> <td></td> <td>188</td> <td>1.00</td> <td>).£0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>		ген цаск	2						.583	31.2	1.10	1	+			1978.	.6	881.	21.	10			681	.01.	20	_	Truce p	nposes	·E6			188	1.00).£0						
		Kight mck	-		.90.E0	12, 0	101						+			2009. ²⁰ 0			1								a for se	ne br	<u>50</u>	57								03.09	1884.	



	9britil A	30										103,9	0,201	105,4		107,4			5,611		126,3		134,6	1364	141,1	144, 6		148,5			164		173,4	10/,/			184,9		190,5
	ogueg gaibeo.L	29	ŽS-I ŽS-I	ŽS-I	ŽS-I	ŽS-I žs-1	ŢS-1	ŽS-I	I-SZ	ŽS-I	ŽS-I	ŽS-I	ŻS-I	ŽS-I	1-SZ	ŢS-I	ŽS-I	ŽS-I	ZS-1	I-SZ	ŽS-I	I-c7	ŻS-I	I-SZ	ŽS-I	ZS-I	ŻS-I	ŽS-I	ZS-I	72-1	ŽS-I	ŽS-I	ŻS-I	ZS-I	ŽS-I	ŽS-I	ZS-1	ŽS-I	ZS-I ŽS-I
resistance of the line [daV]	\leftarrow	28	4 v	o v		4	4		2			9 9	, 	9		~		•	m		e		4	"	5	2	m	e			2		4 4			•	-		
gniluA	\rightarrow	5 27	~			m	-	4	0 0	+		√ 4	+	4	_	4	-	\vdash	4		2		4	٣		4	4	4	_	_	2			n			•		_
Ruling gradient	Slope Slope	-		1 1		4	1 4	3 1	8 7	+	$\left \right $	4 0 7	+	4 6	-	4 3	-	\vdash	4 ∾		5 3	+	4	~	5 3	~ ~	3 2	3 2	+	+	5 2		6 4 4	2	$\left \right $		•	$\left \right $	_
I	Oradient of the statio		3,5			1,3	1.1		2,0			4,0		0'0		0'0			- C		0,0		4,4		5,0	4,0	1,0	1 1	+		0.0	,	5,0				0,0		0,0
sn	іры әлгиә таді	23	800	520		500	800	500	950 700	945	1000	700	800	500	1000	800	800	800	800	400	350	2000	1150	1000	300	299	350	600	500	005	2000	700	1000	1000	10000	1200	700	700	1500
nce and ngers/freight	Open for the accepta dispatching of passer operations	22	P	P	Ч	P/F	ᅯ	P/F	PF PF		ч,	P/F		Ч	<u>م</u> م	P/F	Ч	Ч	HI C	4	P/F	ᅯ	P/F	P/F		<u>م</u> ا	- <u>-</u>	P/F	~	- A	P/F	Ч	P/F	۲, d	٩.	а ¦	P	ď	P P/F
	Occupancy of service		Þ	4 Þ		Þ	þ	Ч		•		а, р	•	Ч		Ч		6	a,		Ч		Þ	٩	þ	Þ	Þ	þ			Þ			1		f	a ,		<u>с,</u>
moth	slq gnibsol-bnə/-əbiS		v	2		s		s	s	2		s							×		s		s	s				s			s		s	0		4	2 2		s
	Freight car scales	19												_			-							-									-	_		-	+		
	- sbos miod soivis		15407	13701	13702	13703	13705	13706	13707	13402	13403	13404	13406	13450	13301	13303	13304	13305	13350	/0001	13310	13312	13313	13314	12501	12502	12503	12504	12505	12500	12507	12508	12509	12520	12511	12512	12514	12515	12518 12516
he service point	t guinuses to recuring t	17			$\left \right $	-	-			-	H		-	-	_	-		H	-	-	-	+		-	-	-	-	-	+	+	-	$\left \right $		-	$\left \right $		-	$\left \right $	
noitalu;	ຊອາ ວມີໂຮນຳ V າອກກຣM	16	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB RC with AB	AB	AB	AB	AB	AB	AB	AB	AB	AB	AB	AB AB	AB	RC with AB	RC with AB	RC with AB RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with TWT	RC with TWT RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT RC with TWT	RC with TWT	RC with TWT RC with TWT
B→A	acceptance of the longest trains	15	4 "	n m		2		3	ω 4			S		4 and 5	1	4 and 5			4 and 5		3 and 4		4 and 5	6	-	2		2 and 3			2 and 3		3 and 4	2 and 3			and 4		4
Direction	Maximum permitted train length Tracks for		656 640	838		969	797	642	742 866	3		812		657 4		626			cI/		679		620 4	825	799	612	677	590 2			508	+ +		498			60		738
B←A	acceptance of the longest trains		4 "	n m		2	ĩ	3	~ ~	,		4		2 and 3		2 and 3			2 and 3		5 and 6		2 and 3	3 and 4	2	3 and 4	2	4 and 5			4 and 5		1 and 2	4 and 5		5	and 3		3
Direction	Maximum permitted train length Tracks for		667 651	838		693	798	647	746	2		855		530 2		710 2	-		/88		702 5		615 2	559 3	+	648 3	677	666 4			574 4	\vdash		245			5/1 2		744
pəəds	Left track										8		0 <u>1</u>		20			2	+	120	╘	50		30										100					
Maximum permitted	Right track		10	2	100			100				70					0 <u>0</u>			120		30		100	30	8	50							100					
Â	Railway line categor	9	22	5 2	4	25	5 Z	<u>7</u>	침침	1 Z	4	2 2	4	4	42	2	4	4	32	5 2	7	7 7	4	침본	4	22	5	4	4	4 2	Ā	<u>7</u>	42	7 Z	4	4	4 4	<u>7</u>	<u>7</u>
	Olass of railway line	8	M	M	Μ	M	N N	Μ	××	W	Μ	M	W	Μ	M	W	Μ	M ;	Z	N	M	M	Μ	Z Z	Μ	M	M	Μ	X	Z X	M	Μ	M	a M	Μ	M	N N	Μ	M
əui	Single/double-track l	7	s o	n N	s	ŝ	n N	s	s s		۵			۵			٩	<u>n</u> 1							s	s v	n N	s				۵			۵			۵	
1	Type of service point	9			3	•	n 0			• m	~	1 1	~~~	1	~ ~		m	~ •	- •	0 0	,	n m		~ -	2	~ ~			с (m m	-	~		- m	~	~ ·	- n	~	-1 3
	Distance in km Chainage Mame of service point	4	6,240 47+748 VLAŠKO POLJE 5 363 53±110 MT ADENOVAC	950+09			2,1/10 /0+520 KAIAKE 3.680 74+000 GLIBOVAC		7,006 85+570 MALA PLANA 4 864 90+434 VFLJKA PLANA			2,577 100+302 MARKOVAC 6.011 106+3131 ADOVO VAROŠ	108+001	109+600	4,500 114+100 BRZAN 2 875 116+075 MTI OČEVO	120+300			3,842 153+23/ JAGODINA 5 462 140+700 CTT :E	5,281 145+981 OPEN LINE JUNCTION CUPRUIA		2,930 166+600 DRENOVACIAN		2,000 173+600 LUCINA 2,710 176+310 STALAČ		4,586 186+486 BRALJINA 3 014 100+400 CEPOVIOR AŽAN:	192+216	194+939		2,20/ 201+400 DONJ LJUBES 2,100 203+500 GORNAT LJUBEŠ			210+480	3,11/ 214+19//ALEKSINAC 3,271 217+468 NOZRINA			0,035 222+705 GKEJAC 5,245 227+950 SUPOVAČKI MOST		3.281 232+590 VRTISTE 2.349 234+939 TRUPALE
public transport	Left track	2				03.09.	.+00						.48	81.	60 [.] E	0	-				1	881.	6.5	.782 .28.5.		03.09.	884.			.06	61.8	; 0, 1()	\downarrow		.488	81.60	.£0	
Date of handover to	Right track	1				9 °	Ĭ			•	7561	.20.	60	1120	51.10).20	24611	80 77 8	1973.		6	3613 0	587	.9.5 1884.		03	18			.48	81.6	50° E()			*866	51.20	.62	



	abritilA	30	188,8	0.001	102	194.1			194		201,6		211,5		217.0	220.0	248,2	255		282,6	297,2	500,9	324.4	333,3		346.7	367,5	371,9		383,0	1,140	427.2	459,2				129,9	148,8		124,6	13,4	178.6	157,0
	ogueg gaibeo.L	29	ŽS-I	ŽS-I	1-27	I-cz	ŽS-I	ŽS-I	1-S2	I-SZ	ŽS-I	ŽS-I	I-SZ	7c 1	1-52	1-SZ	ŽS-I	ŽS-I	Į-SŽ	ŽS-I	ZS-I	1-52	1-SŹ	ŽS-I	ŽS-I	I-SZ	ŻS-I	ŽS-I	I-SZ	ZS-I	1-52	ŽS-I	ŽS-I	ŽS-I		Ťe.1	Į-c7	ŽS-I	ŽS-I	ŽS-I	I-SZ	I-SZ	ŽS-I
[Nsb] anil adt	←	28		-	0				~		1	-			,		-	2		1	1	•		2		4	+	ŝ	-	m -	-	-	$\left \right $	15	┢		. 0	-		10	1	,	
Ruling resistance of	\rightarrow	27	5		• •	n 0			4		2		S		0	1 4	s.	9		2	• •	×	2	2		2	2	9		ŝ	n	~	13	÷		1	n 1	Ξ		• •	~	Ξ	-
gradient	Slope	26	2	~ •	4 4	• •	-	-	~	0	0		+	0			-	-	-	m	+	0 4	• •	٢	-	o v	m	4	4	m 0	-	•		13		•	_	-			•	•	
Ruling	aniionI		5 5	-		5 5	-		4-	- 0	1 1	2	4	C1 C	1 0	<u> </u>	. <mark>8</mark>	31 6			1 0		15 8	6	ŝ	0 0	6	2 5		7,5	∩ ∝				0	4,9 1	7,9 12				0'0	8.7 9	
[%] u	Gradient of the station	24	0 5,48			0 1,04			1/0		0,91		0 2,44		0 1 71		0	7 4,31	1 1		5,65		0 5 45		0	0 2.69	1	0 0,92		<u>۲</u>		0 11.0		0									
st	operations Minimum curve radiu	33	950	550	C67	8	5000	2000	00/	4000	20000	1900	1000	1600		2000	2500	327	300	29(300	300	300	300	950	1000	400	450	400	350	450	009	400	30(350	i õ	298		300	300	27	350
gers/freight	nsear fo guidoted aib	22	P/F	E F	L'L	L A	4	P.	al a	-	P/F	ч	<u>م</u> ا	- P	-	P/F	4	P/F	4	Ρ/F	~ r	24	P/F	P	<u>م</u> 4		P/F	P/F	<u>م</u>	P/F	L A	•	P/F		F	-	Ч.	ሳ	4	م و	~ A	4	<u>а</u>
	Occupancy of service Open for the acceptar	21	Ч	f	24 P	ч p		-	4		D		ь	+	F		Þ	Þ	$\left \right $	Þ	Þ	5	F	ь	+	D	Þ	4	-	-, c	4	Þ	A.		F	24 E	о _Р	þ		D:	ь	Þ	Þ
	elq gnibeol-bno/-obi2	20		Ę	2/E	s	+		s N	+	s		s	╈		s		s		S/E		+	s.		+			s		s u	0		s		F	-	+				+	t	Ť
	Freight car scales	19				t	\vdash		╈					+	1	+				•.					+					+					F		+				+	$^{+}$	┢
OIC	J - sbos mioq ssivisZ	18	12550		10201	12302	12304	12303	11001	11003	11004	11005	11006	11007	11008	11050	11010	11011	11012	11013	11014	11079	11016	11017	11018	11019	11020	11021	11022	11023	11025	11026	11027	11028	16103	10103	15602	15603	15615	15604	15605	15607	15608
ne service point	Manner of securing th	17	-					•	-		1		-		-	•	-	1		1		-	-			-	-	-	•		-	1	-					-			-	-	-
noitelu	ւցո շՈներ 10 ոշութ/	16	AB	AB with TWT	AB WITH I W I	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB PC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	station distance	- Jajinci - Mala Krsna - Velika Plana	ΔR	AB	RC with AB	RC with AB	RC with AB	RC with AB RC with AB	RC with AB	RC with AB
	longest trains	<u> </u>									d 3				+										+	_		d 3							- Veli		<u> </u>			and 2	+	+	
B→A	Tracks for Tracks for		3	,	η.	-		ľ	<u> </u>		2 and		2		-	10		4		ŝ	m (~	-		2	2	2 and	ľ	m -		-	~		Lisna Lisna		4	~		1 an	<u> </u>		2
Direction	Maximum permitted train length	14	662	001	488	640			601		623		632		750	648	690	526		648	632	/08	668	865		653	648	650		623	6	684	609		fala K	707	706	573		801	714	613	603
	longest trains				+	+	\vdash		+					+		+									+				-	-					- P		+			-	+	+	+
V→B	acceptance of the Tracks for	13	e	•	~ -	- -			4		2 and 3		7		-	4	-	4		e	m	7	~	-		2	2	2	•	m -	-	-	m	:	uïe-	4	4	m		- '	m	-	2
Direction	Maximum permitted train length	12	686	007	490	020 656			000		608		639		773	695	686	537		688	596	00/	572	858		651	648	648		618	f	687	610			707	710	643		815	11/	606	596
pəəds	Left track	11	_	60													0			_									_						ar) - F	_					_		
mumixeM permitted	Right track	10	50	30		-1	-	20			-	30		Ş			100	65		<u>8</u>		30	_			R	-		<u>8</u>	5		- 95	40	F	Beograd centar) - Rakovica	8	60					+	
1	Railway line category	0	+ +	-	-	5 2	4	4	42		D 4	<u>5</u>	Z i	45	5 2		4	4	4	<u>5</u>	212	5 2	2	4	45	5 2	4	<u>5</u>	4	ă	5 2	5 A	4		— H	42	7 7	<u>7</u>	4	42	2 2	5 2	D 4
	Class of railway line	~	М	≥;	Z	z Z	M	X :	Z	Z Z	Μ	M	Z	Z	₹≥	¦≥	Z	M	M	X	2	z ≥	ž	Z	Z	ZZ	M	M	Z :	Z	₹≥	Z	M	M	<u></u>	2	Z X	M	M	X :	≥≥	۲ ۲	Z
əu	lingle/double-track li	2	s		^ہ د	n v	s	s	s o	n v	s	s	s	s o	2 00	2 00	s	s	s	s	s s	n v	2	s	s	n v	s	s	s	s o	n v	s s	s	s	ũ	n u	n v	s	s	s	s s	n v	s
	Type of service point	9	-	; 12		- ~	m	ε,		n m	-	m	-	m "		۰ ۰	0	-	m		~ ~	~ ~	-	-	ŝ	n 0	-		m		- ~	0	-	13		- 4	> -	-	m	۰ 7	- ~		-
	Name of service point	5	005 CRVENI KRST	741 JUNCTION POINT 1 - 3 NIŠ	245+585 NLS 240+460 MEDITPOTIO	253+946 BELOTINCE	441 ČAPLjINAC	257+010 MALOŠIŠTE	451 DOLJEVAC 261 POČANE	2037201 AOCAIVE 265+854 PUKOVAC	267+942 BRESTOVAC	270+834 LIPOVICA	275+564 PECENJEVCE	2/8+831 ZIVKOVO 20+300 DBTBOTT ESPONA ČYT	2007-200 FALDOU LEGINO VACAL	287+568 LESKOVAC	295+779 DORDEVO	301+863 GRDELICA	308+610 PALOJSKA ROSULJA	725 PREDEJANE	319+671 DžEP	322+880 MUMIN KAMEN 376+338 ŠFI INCF	320+501 VI.ADIČIN HAN	334+066 SUVA MORAVA	135 LEPENIČKI MOST	339+033 STUDAL 341+437 PRIBOJ VRANISKI		354+206 VRANJE	415 NERADOVAC	365+725 RISTOVAC	022 BUJANOVAC 712 LETOVICA		309 PREŠEVO	400+452 STATE BORDER		0+/00 KAKUVICA 3±708 ODEN I INF II INCTION 21	916 JAJINCE	16+277 BELI POTOK	20+350 ZUCE	21+242 ZUCE	24+885 VRCIN 27+840 K A SAPOVAC	2/1-040 MASAFOVAC 31+265 LIPE	36+894 MALA IVANČA
	Chainage	4																																	10.0		-						
	Distance in km	3	6,066	1,736	0,842	4.484	1,495	1,569	4,441	2.593	2,088	2,892	4,730	3,26/	1 675	5 593	8,211	6,084	6,747	4,115	6,946	3.457	3 253	4,475	2,069	2,382	6,578	6,191	7,209	4,310	106,1	5.838	5,759	8,143		3 000	*1,581	*5,419	4,073	0,892	3,643	3.425	5,629
transport public	Left track	2	884.		T															ø														1		088	200			-			
Date of handover to	Right track	-	03.09.1884.	9. 9.0	0															1888																20 10 1088							



	əbuitlA	30	135.4		123,4	1001	08 0	, o,	83.0	2	• ••	1,00			83,6	9 V0	0,29	111.4			119,8	c'071	84 06	111	142,2	81,2	C, KI	82,1		82.6	0,20			84.73	83.43	83.63	83,83	87,58	109,86	110,35	100.93	4,701		
	ogueg gaibeo.l	29	ŽS-I ŽS-I	ŽS-I	ŽS-I	ŽS-I	1-07 20-1	ŻS-I	ZS-I	ŽS-I	ŽS-I	1-07	1-07 ŽC 1	ŽS-I	ŽS-I	ŽS-I	1-07	1-S2			ŽS-I	1-07		ŽS-I	ŽS-I	I-SZ	I-SZ	ŽS-I	ŽS-I	1-07	1-07 201	1-07	1-SZ	ŽS-I	ŽS-I	ŽS-I	ŽS-I	ŽS-I	ŽS-I	ZS-I	1-07	ŢS-I	ŽS-I	ŽS-I
resistance of the line [daV]	\leftarrow	28	0		5	,	- 4	•	Ś	`		V	+		1	~	7	4 4			1			1	6	۰ <u>ت</u>	2	•		6	-			2	0		-	4	9	، و	2 0	4		
Builug	\rightarrow	27	'		1		• •		'			~			-	4	<u></u>	× 0			0			10	+	-	•	2		v				5	-	-	-	4	9	ŝ	2 0	+		
Ruling gradient	Slope		8	+	0	+	0 4	+	4	+		°			-	_	4 0 - 7	-			•	-	\vdash	0	+	-		2		-	+			2	2			4	9	-	2 C	+		\vdash
	Gradient of the statio		0.8 0		2,2 0		0,2		0 2 0			14			0,6 1			5,/ 8 8	_		~	+	41	5,5 10			0 0'c	4,0 2		9 0 0				0.0	0.0	0.0	0,6 1	0,5 4	1,0		0 0			
sr	uiber əvruə muminiM	23	350		700	¢ ¢ t	0001	8	280	8		002	8		1000	000	000	200				1		4500	3500	3500	nci	1200		2005			T	390	5000	5000	6000	5000	5000	2000	0000	70007		
	operations operations		ᆋᆋ	م	Ч	¢	<u>,</u> 5		P/F		<u>م</u> و	. P	<u>م</u> ہ	Ъ	Ρ	~ ~	., e	P/F			P/F	L/L	p/F	P	а,	f	.	Ч		٩	4		T		4	. d.	P P	Ч	ď	PF	<u>л</u> р	-		
	Occupancy of service Open for the acceptar	21	<u>д</u>	-	D	;			٩		$\left \right $	╞	5		Ρ	-	5			$\left \right $	<u>م</u> و	1	٩	- -	Ы	.	5	Þ		C	>			D	D	Þ	D	<u>д</u>	Þ			5		\vdash
	elq gnibeol-bnə/-əbi2					1			s.	2			1		s		1	s	1		s o	2	s.	2						ш	4						Η		-	s	t	+		
	Freight car scales	19																					L																	Yes	1			
SIC	I - sbos tniog ssivisZ	18	15616 15609	15610	15611	15612	15614	13509	13551		13502	13503	13500	13510	13504	13505	13500	13401			13351	01cc1	16503	16801	16802	16805	10900	16807		16808	10000				23302	23303	23304			23404	23407	40107		
he service point	tt gnines of securing th	17	-		1	•		•				-	•		1				•	9	• •	-	=	::	Ξ	=:	-	11		:	:			11	11	=	11	11	11	=	= =	-		
noitelu	தன அரச்பர் 10 சரமகM	16	RC with AB RC with AB	RC with AB	RC with AB	RC with AB	RC with AB	AB	AB AR	RC with AB	RC with AB	PC with AB	PC with AB	RC with AB	RC with AB	RC with AB	PC with AB	RC with AB	Paraćin		station distance	station distance eder - (Valahin)	641 1 and 2 443 5 and 6	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	BC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT	RC with TWT
	acceptance of the ongest trains	15	~			,	~ c	1	4			,	4		3		~ ~	7 4	ija - Pa		~ ~	4 tote ho	nd 6	1 and 2	1 and 2	4	7 0110 7	2 and 3		4 and 5				1 and 2	and 2	3 and 4	3 and 4	4 and 5	and 4	and 2	5 and 4	7 11		Π
B→A Direction	rain length Tracks for		619		617	-	870		633			545	2		610	764	0	866 866	a - Cupr		5	oyz uhotica - c	443 5 a			-	24/ I a	725 2 a		403 4 3	-	-	╞	746 1 a	+	+			ŝ		876 1 a	-		$\left \right $
	ongest trains Maximum permitted	-	6	-	6]	-	9 2		ý	-			-		6]	-	4 ŭ	~ ×	Ćuprij		-	Set 1		-	+	+	+			+	+	_		-	-	-		\vdash		_	+	-	\vdash	\vdash
Direction A→B	Tracks for acceptance of the	13	٣		°	,	n c	1	4			ç	1		3	•	n	~ m	.04 (Jagodina) - Open line junction Cuprija - Cuprija -		3 and 4	Nori Sa	1 and 2	3 and 4	3 and 4		+ pup c	4 and 5		4 and 5				3 and 4	3 and 4	1 and 2	1 and 2	2 and 3	1 and 2	3 and	1 and 2 3 and 4	NIID C		
	maximum permitted train length	12	624		612	000	050	8	620			545	£		608	103		785	n line		240	7010	- 20Va -	566	694		74	636		407	761			650	738	311	660	531	739	904	CS 00	104		
permitted speed	ும் புக <u>்</u> டு	11	80			5	3			20					8) - Ope	50			סומומ במ	200	8		160	100	120	100	50	120	180	2				200	3				160	
mumixeM	Right track	10	8			•	4			Ś					Ĭ				godina	ſ		1 I	100 (DCOBIAU CCIIIAI) - 31414	000	200		160	100	120	100	50	120	180	2				200	202				160	100
Å	Railway line category	6	<u>7</u> 4	5	<u>7</u>	4	5 2	2	2 2	2	25	3 2	5 2	5	D4	25	\$ 2	5 2	04 (Ja		25	5		4	<u>7</u>	Z Z	5 Z	4	42	3 2	5 2	5 2	5 2	5 7	4	4	<u>7</u>	4	4	<u>7</u>	3 2	5 2	4	4
	onil yewliss of sailway line	8	M	M	Μ	Z :	z >	X	ZZ	M	M	Z		N	Μ	Z	2	ZZ			Z	N	n	М	M	Z	ZZ	Μ	M	z >		₹ ≥		M	M	Z	Z	M	Z	Z	z >	N	Μ	Μ
əui	li asert-slduob\slgni2	2	s s	s	s	s	nu	s	s s	s	ŝ	0 0	2 0	n N	s	s	<u>^</u> 0	n v			s	0 501		Δ	۵			۵	D 4					D	P			۵	D					Ω
	Type of service point	6	3	3	1	3	7	3	12	12	3	<u>-</u>	3	n w	1	3				9		-	-	1		• •	9	1	6	12	- 0	o	0	1	-	-	-	-1	1			- 6	9	
	Name of service point		39+600 BRESTOVI 41+300 MALI POŽAREVAC	43+167 DRAŽANi/ŠEPŠIN	I	AC		66+570 RALjA SMEDEREVSKA	6/+800 JUNCTION POINT 1 MALA KRSNA 69+068 MAT A KRSNA	JUNCTION POINT 28 MALA KRSNA	j 110 A TO A	NICA	MUA VIVA	CI CI	LOZOVIK/SARAORCI	VAC	90+220 KKNJEVU/IKNUVCE 04 - 620 KKNJEVU/IKNUVCE	94+039 VELIKO UKASJE 99+706 VELIKA PLANA		0+000 OPEN LINE JUNCTION CUPRIJA			TA3OBA	42+862 [NBUA		62+058 OPEN LINE JUNCTION KARLOVACKI VINOGRA	02+812 SNEMISMI KANLUVUI 70+212 KM 70+212 SC	70+870 PETROVARADIN	KM 72+381 SC	UN POINT & NUVI SAD	133 SC	122 SC 584 SC	804 SC	KA		STEPANOVIĆEVO	0/	NOVA	LOVĆENAC - MALI IĐOŠ	TOPOLA	Οιταμιν	401 SC	+282 SC	175+305 BLOK 1 SUBOTICA
			39+600 BRESTOVI 41+300 MALI POŽ.	DRAŽAI	47+771 UMČARI	ZIVKOV	60+600 KOLARI	RALJA S	JUNCTION PO MALA KRSNA	IUNCTI	71-995 SKOBAL	76+7/05 OSIPAONICA	77±817 I IICAVČINA	SARAORCI	LOZOVI	MILOŠEVAC VPNEEVO/TE	NUNEV VEL INV	99+706 VELIKA PLANA		OPEN L	0+500 CUPRUA	FANAL	CTAPA	AUBUA	BEŠKA	OPEN L	KM 70+212 SC	PETROV	72+381 KM 72+381 SC	77+010 NOVI SAD	70+133 KW 70+133 SC	80+684 KM 80+684 SC	82+304 KM 82+304 SC	84+044 RUMENKA	KISAČ	STEPAN	ZMAJEV	VRBAS	LOVĆEI	BACKA TOPOLA	VATIMO	KM 168-	KM 172-	BLOK 1
	oganiage	4	39+600 41+300	43+167	47+771	52+315	617+09	66+570	67+800		71+995	C0(++/	77-202	81+417		87+717	077+06	99+706		000+0	0+500	07++/	34+044	42+862	54+032 BEŠKA	62+058	70+212	70+870	72+381	77+010	70-173	80+684	82+304	84+044	90+407 KISAČ	97+300		113+610 VRBAS NOVA		143+536	15/+145 ZEDNIK 166+510 NATIMOVIĆFVO	168+401	172+282	175+305
	Distance in km	3	2,706	1.867	4,604	4,544	5 300	5,961	1,230	1,196	1,731	1 437	1 615	3,600	1,350	4,950	60007	*5.586			0,500	0770		7,918	11,170	8,026	4,400	0,658	1,511	*0.210	0113	1 561	1 620	1.740	6.363	6.893	5,214	11,096	15,913	14,013	0 374	1.882	3,881	3,023
handover to transport transport	лали шаск		01.06.	1924.				1 1						10.12.	1880.										10.12	1883.		1							_	_	1	23.10.1961.						
To stad	Right track	-																																				23						



	9butitl A	30		115,02		188.3			100		207,2		219,5	235,3		245	607	267		286,9	314				0,1+0	368,5		416.5	C'011		445,8	Τ								77.1
	əgueg gaibeo.I	50	ŽS-I	1-57	I-SZ		ŽS-I	ŽS-I	1-SZ	ŢS-I	ŽS-I	ŽS-I	ŽS-I	ŻS-I	ZS-I	1-52	1-57	ŢS-1	ŽS-I	ŽS-I	ŽS-I ŽS-I	ŽS-I	ŽS-I	ŽS-I	I-cz	ŽS-I	ŽS-I	1-SZ	ŽS-I	ŽS-I	ŽS-I	1-67		ŽS-I	ŽS-I	1-67	1-07	ŽS-I	ŽS-I	I-SZ
the line [daV]	\leftarrow	28		+	2				4	+	-		1	1		-				1					•	1		-	•		9	•		1	_	2	00	+	+	4 0
Ruling resistance of	\rightarrow	27	•	•	~				y		4		5	8		2	-	2		6	7			r	\	7		~	•		10	17		÷	•	4	-		-	-
gradient	aqol2			n	_		7	0	0 "	_	-	0	-	_	+		+	+	0	•		+	0	•	0			• -	•	0	+	>		4	•	×	~	\square		
gniluA	anilon1			0 7	~		2	4	2 C			9			s I					9	0 6	1	m			9	4	9 ×		0		=	0	•	٢	<u> </u>	-	\square		0 0
[%] u	Gradient of the statio	24		<u>Σ</u> , Ι					, ,		2,5			3,09		00		00		7 4,9	0.0				0,4	8,0		8 5			9,5		0'0					Ц	_	0,0
sn	Minimum curve radi	23		300	30		300	500	2000	3000	1000	310	30(õ	ĕ	Š Š	4	5 05	00	49	350	40	40(00	30(50(55(3000	202	205	500	20		300	600	20/5	800			600
	Open for the accepta dispatching of passer operations	22	щ	.		P/F		Ч	<u>م</u>	•	4	Ρ	Ч	4	ŕ	- n	- A	-	4	م	<u>م</u> م	4	ď	<u>م</u> 1	24	P/F	д,	~ ^	-	- -	P/F		Ч	ሓ	ᆔ		ᆈᅀ	4	٩.	P/F
	Occupancy of service	21	<u>ы</u>	4		4				•	4		D	д,	+	6	4	Ь		Ч	<u>م</u>			F	4	4		E	>		P4		ч		P. P	<u>,</u>	6	H	д,	<u>م</u> م
	slq gnibsol-bnə\-əbi2			ц		S/E								+	╈				1			t		+	1	s		v	+	\top	SE					+		Ħ		s s
			Yes	+											+			+				1		+				+			Yes				+	+	+	\square		Yes
	- ebos miod estrice			25450	23499	12551		12401	10400	70171	12404	12405	12406	12407	12408	10410	12426	12411	12412	12413	12414 12415	12416	12417	12427	12419	12420	12421	12422	12424	12425		12498	16052	16053	16054	16015	16015	16006		22001 21001
he service point	t guinuses to renumM	17		=		-			-	•	-			~		×	+	~	•	9	~	-		-	0	9		4	-		9		1		•	-	-			4 4
noitelu	ຊອາ ວເກີຣາ 10 າອກແຣM	16	RC with TWT				AB	AB	AB	AB	AB	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance border - (Stamora Moravita)	(mit a notate n torring)	AB with TWT	with	AB WITH I W I	AB	AB	AB	AB station distance
B→A	acceptance of the longest trains	15	1 and 2	1 and 2		3 3			~	,	4			2		2 and 3	CDIR	2 and 3		2	2 and 3			-	C DIE 7	2 and 3		2 and 3			2	order - ()	3			1	6		7	4 and 5 2 and 3
Direction	Maximum permitted train length Tracks for	14		405	-ė	488			009	8	009			524	+	603	+	614 2		791	713 2	1			7 +70	624 2		6 9 69	-		711	state b	400			+	697		-	800 4 471 2
	acceptance of the longest trains			1 and 2	to hards	- State UDI del - (ULA BUILIAIL 3 488 3			~		4			5		_	CDIR	~			2 and 3	+		-	C DUE 7	3		~			2	80 Solution - State - State - State	8 and 10		+	+	~	\square	_	4 and 5 1 2 and 3 4
A→B Direction	Tracks for	-		+											_	ſ	4	2 and	+			+		-	+	2 and		pue C	+			tanica -	8 an		_		_		+	-
	Maximum permitted train length	12		404	200 200 100 Dimitrorimed	490			600	8	599			524		603	8	614		791	713				024	624		909	222		710	latma s	364				697	\square	_	810 471
permitted peed	Гей и яск	Ξ	100	+	ž 200	- s										30	20												20		0	au Iřevo o		- 9	2		50	60	3	50 100
mumixeM	Right track		100	+	200 106 Ni														-			-			_						_			_	2			10		
Å	Railway line categor	0	4	₹ i	Ā		ñ	D3	ñ	ŝ	ñ	D3	D3	ñ	ñ	ĥ	ŝĔ	ŝ	ñ	ñ	ñ	ñ	ñ	ñ	ŝã	ß	ñ		ŝ	ñ	ã,	Centar Let		4	4	52	5 2	Ā	4	<u>7</u> 2
	Class of railway line	~	X :	Ξ	×		Μ	M	ZZ	X	Z	Μ	M	Z	₹;	≤ ≥	Z >	i Z	Z	Μ	MM	Σ	M	Z :	Z	Μ	N	ZZ	Z	Σ	Z,	M		Z	Z :	z >	₹ >	Σ	Σ	ZZ
əui	Single/double-track I	2		٦l			s	S	s s	s s	s	s	s	s	s	20	2 00	n N	s	s	s s	s	s	s	n v	s	s	s v	n v	s	s	5 5 M 107 Beograd		٩						۵ls
:	Type of service point	9	•	-	13		12	ŝ	m -	• ~		3	2		m	n c	v		~ ~	1	3	m	m	~ (7 m	-	ŝ	m -	• •	n m	;	51 P	-	7	ۍ ر	~ ~	n (~	۰ ۳		
	Distance in km Chainage Name of service point				8,085 184+635 STATE BORDER	0+241 NIŠ	0,495 0+736 JUNCTION POINT 4 NIŠ		1,634 3+400 VOJNA BOLNICA 2 061 5+461 (7F1 F RTIT A		[4,200 14+700 PROSEK		5,361 22+509 OSTROVICA		2,741 29+500 KADUV DUL 2.201 31±700 D01 AC				5,232 44+912 BELA PALANKA	3,588 48+500 CRKVICA 5 000 53+500 ČTFLIK				1.91/ 00781/ STAINCEINE 3.483 67+300 SOPOT	5,635 72+935 PIROT	76+900	4,800 81+700 VELIKI JOVANOVAC 4 403 86+103 811K/0V/O					0+000 BEOGRAD CENTAR			1,888 4+088 PANCEVACKI MOSI 2 412 7±100 KRNi a Č a MOST				*7,631 20+200 PANCEVO GLAVNA *3.007 18+206 PANČEVO VAROŠ
transport	Distance in km		0		~		0		-		4							10	m	S	<u> </u>	_	2	<u>،</u>	1		m	4			4	0	.56		50.5	+			2	_
Date of handover to public	Right track	1										01.06	1887												111	1887.							-		50.E	+	.25	61.1	1.1	11.10.1935.



	3 Minimum curve radit 2 Gradient of the statio 3 Incline	00 1 34	3,5	5,2	350 6,2 3 600 0,7		600 0,2 200 0.0	300 2,5 7	1905 3,0 3	8	300 2,5 11	400 1 6	•	400 0 0	400 0 3		450 1 5	500 1 3	450 1,7 4	500 2 7		600 23 7	300 1,2 15		300 2,5 16		300 1 10	300 2 0	•	500 2 0	+	500 7,5 0	2		∞		500 1,5 4 400 1.5 11
pue and	Open for the acceptar dispatching of passen operations		_		A A		4	P P/F		P/F				_	T P/F		P/F	P/F	-	J P/F	<u>е</u> ,	P/F	_	Ч		4 A			Ч,		<u>ц</u> ч			Ρ	U P/F	4 4	
	Freight car scales 5 Side-/end-loading pla 2 Occupancy of service	s s	s N	+	S	S U		Yes S/E		S	+			S	S	S P	S	S	s U	S		~					n	SP	,	Þ	_	Yes S P				+	S/E P
	1 Banner of securing 1 5 Service point code - 1	7 21002	7 21003	+	8 21005 8 21006	+	21008	7 21009	21099	1 15501	1 15201	1 15202	15204	1 15205 15205	15207	1 15250	1 15209	1 15260	1 15211	1 15213	15214	CI2CI 1 15051 1	1 15101	15112	1 15102	1 15103	1 15105	1 15106	15109	1 15107 15116	15113	1 15150	1	15111	1 15110	15114 15115	1 15108 1 15151
noiteiu	ຊອາ ວເມີຍານ 10 າວແທນ ກໍ	station distance	station distance	station distance	station distance station distance	station distance	station distance station distance	station distance	station distance	- (Dijelo rolje)	RC with station distance	RC with station distance RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance PC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance PC with station distance	RC with station distance RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance RC with station distance	RC with station distance RC with station distance			
Direction B→A	Tracks for acceptance of the longest trains	2 and 3	3 and 4	3 and 4	2 and 3	2 and 3		4 and 5			4	~	`	3		4	2	4	3	3		4	- 2		ŝ	m	3	9		m		Sf			3		~ ~
	longest trains Maximum permitted train length	3 663	4	+	3 662	3 665		5 643		Deugrau Centar) - Nestitk - Forega - VIUIICa - State 0010e1	595	768	8	574	504	706	602	652	601	602		503	520		566	¥	552	544		549	+	649f	_		553	_	563 552
Direction A→B	train length Tracks for 5 acceptance of the	2	+	+	2 2 and	5 2 and		3 4 and		0 3	4	~	$\left \right $	3	4	9 4	1 2	9 4	8	0		4				۳ ۳	4			1	+	7f Sf			4 3	_	2 0 2 8 0
pəəds	Left track Maximum permitted	+	836	743	662	665		643		730 730	594	171		572	504	689	601	649	598	009		905	553		568	543	554	544		551		647f	μ		554		566
Maximum permitted	S Right mack	-			100				50 SO		9		85		06	2	95			100							1	2							100		06
	د Class of railway line الاعناسمي انne category و المناسعة المناسعة المناسعة المناسعة المناسعة المناسعة المناسعة المناسعة المناسعة المن	-	+	+	M D2 D2	+		M D2	M D2	cograd	-	M M	+ +				M N			N N			+	$\left \right $	M Z		+	-	M D4		-	N N	+			M M M M	
	Single/double-track li		+	+	~ ~			-		-	~			~ ~	-	-	~ ~	-	~ .	-	~		1	~	-	+		^	~ '		+		\square			s s	
əui			s s	S	s s	s	s s	s s	s		S	N N	s s	s v	n v	s s	s v	s s	s	n N	s	n v	s s	s	S	s s	2 V	S	s	s v	n v	101			-+-	_	
	nioq əsivrəs fo əqyT	+	•	1	3 S	1 S	3 2		13 S	1	+	s s		2 S	_	1 S	1 0 0	_	1 2 2	n 1 N N	\vdash	v v v	2 <mark>2</mark>	3 S	_	2 S		1 S	3 S	2 C	0 00	+	12	3	2	<u> </u>	$\left \right $
	 Chainage Name of service point Type of service point 	BANATSKO NOVO SFLO	VLADIMIROVAC 1	ALIBUNAR 1	BANATSKI KARLOVAC 1 3	1	2 m	VRŠAC	13	0+425 RESNIK 1	BELA REKA 1	4C 3	CENTAR 3	2 2		1	LAZAREVAC 1 TM 46+000 SC 0	3C	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	EVO 3	3	~ -	2	3	•••	3			<u> </u>		GLIMAČ 3		N POINT 53 POŽEGA				56+974 SEVOJNO 61+900 UIŽICE TERETNA
	Name of service point	+007 BANATSKO NOVO SFLO	45+855 VLADIMIROVAC	53+554 ALIBUNAR 1	3 1	70+337 ULjMA 1	75+300 VLAJKOVAC 81+707 OPEN LINE ITINCTION A TITAMA 6	- 1	_		7+637 BELA REKA 1	mc	17+900 BARAJEVO CENTAR 3	23+094 VELIKI BORAK 23+094 VELIKI BORAK 2 27±738 I TECPAVAC POLITIBAD SEVI		37+262 VREOCI 1	0 1	52+600 LAJKOVAC	58+982 SLOVAC 1	4,918 03-900 MLADEVO 3.254 67+154 DIVCI 1 S	69+243 LUKAVAC KOLUBARSKI 3	~ -	84+570 VALjEVSKI GRADAC 2	91+600 LESKOVICE 3	94+048 LASTRA 1	_	111+352 RAŽANA 111 1	118+881 KOSJERIĆ 1	123+400 TUBIĆI 3	6,442 129+842 KALENICI 1 S 3 758 133+600 OTAN; 3 7 5	135+800 OLAIN 135+800 GLIJMAČ 3	140+787 POŽEGA 1	142+489 JUNCTION POINT 53 POŽEGA	145+600 RASNA	149+262 UZIĆI	KA RAMPA	



	sbrittA	30	418,4	520,5		631		784	612,5		c,18c	390.3			447,7	0.023	453,2		505 2	561.5	553,7			109		129,5			153.0	171 6	7,11,0	2001	236.5		241,9	239	216		210,3	187.7	101.1		202,4
	ogueg gaibeo.I	29	ŽS-I	ZS-1	I-SZ	ŽS-I	ŽS-I	I-SZ	I-SZ	Į-SŽ	25-1	ŽS-I	ŽS-I	ŽS-I	ŽS-I	ŻS-I		ZS-I	5 2	I-SZ	ŽS-I	ŽS-I		ŽS-I	ŽS-I	ŽS-I	ŻS-I	1-57	1-52	Į-SZ	Že.I	I-SZ	1-SZ	ŢS-I	ŽS-I	ŽS-I	ŽS-I	ŻS-I	ZS-I	72-1 Ž	ŽS-I	ŽS-I	ŻS-I
the line [daV]	\leftarrow	28	1	•		•		7	18		2	17			4	_	-	~	-	•	6	S	\vdash	~	+	•			4	-		,			12	4	9	+	Ś	~	-	+	~
Ruling resistance of	\rightarrow		18	28		18	18	16	'		•	•			∞	C	- ;	10	1	0	5	~		m		9			1	3 0	n	~	-	+	12	<u> </u>	m		m	_			~
Ruling gradient	Incline Slope		16 0	0	+	18 0		16 2	0 17		9	0 17			8	-	0 0	8	10	0		8		2	+	5 0			~		-	0	10	-	12 10	-	∞	+	2	0	-	\square	-
	Gradient of the statio		2,5 1	2,3	+	1,5 1		2	2,5 0		2	0			1,5 8			1,5		0	1 1	-	\vdash	2.4 2		3,2 5				20		43			4,2 1		2,0		4,5	18		\square	1,0
	Minimum curve radi		400			400		400	300		000	300			300	010	350	400	350	400	400	-		250		550			250	550	2	300	300	8	300	375	300		300	300	~~~		290
	Open for the accepta dispatching of passer operations	22	Ч	а, I	ᆔᆆ	P/F	P/F	<u>م</u> م	. e.	,	а, р	P/F	Ч	Ч	P/F	<u>е</u> ,	а, <mark>Р</mark>	P/F D	ч <u>с</u>		Р		•	P/F	Ρ	Р	<u>ч</u>	- , r	<u>л</u> р	P/F	-	P/F	4	, _P	Ρ/F	Ч	P/F	Ч	P/F	P/F	Р	Ч	P/F
	Occupancy of service		P	Þ		D	D	Þ	IJ	:		Р			U	E	1	Ч	11	, D	Ρ		٩	4	•	U				D d	•	Р	, U)	Ρ	D	Ч		D	٩	-	+ +	Р
molti	side-/end-loading pla				_				_			S					4	s				_		S						S	2	S	2 00	2	s	s	S	_	s	v	2	\square	s
	Freight car scales	15	<u>،</u>		9 ~	2	~	4 4	0			000	0	6	0	ø,	- 0	~ ~	2 ~	14	5	~		>	5	~	4	0	0 0				,	. ~	~	4	2	-	0		<u> </u>	-	
DIC	Service point code -	18	15153	15/01	15716 15717	15702	15703	15704	15706	15721	10/21	15708	15722	15709	15710	15718	11/21	15712	15713	15714	15715	15723	13450	13201	13202	1320	13204	15202	13200	13250	13200	13210	13211	13212	13213	13214	13215	13221	13216	1321	13219	13220	13251
he service point	Manner of securing t	17		-		-	-	-	-		-	-				•	-	-	-	-	-	_	-	- 00		8			×	° 0		~	• •	, 	∞	∞	-	_	∞	~	<u>`</u>	\square	4
noitslu	ຊອາ ວ່າໃນນາ 10 າວແທຍM	16	RC with station distance	RC with station distance	RC with station distance RC with station distance	RC with station distance	RC with station distance	RC with station distance RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	RC with station distance	station distance	- LESAK - NOSOVO FOJE - DELICIAL JAHKOVIC - SIALE DOTUCT - (VOLKOVO) 530 7 2043 563 5 264 6	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance station distance	station distance	station distance	station distance
B→A	acceptance of the longest trains	15		-		3			5		-	4			3	-	+	5	~		3	uis ctato	5 and 6	2	1	3			~	n	, ,	č	2 C	1	2	2	3		2	¢	4		4
Direction	Maximum permitted train length Tracks for	14	346	547	+	539	486	231	536		2/2	553			549		202	499	655	696	544	- Index	563 53	-		722			73.4	844	5	558	632		614	620	566		597	746	2	H	738
	acceptance of the longest trains				+	3		~ ~	2			4			3	+	+	~	~			- Gard	Delleta	C MIR 2	Η	3		+	~	+		0			\vdash	2	~		5	- -		\square	4
Direction A→B	train length Tracks for			_	+			_										_				Delie	- olio-	+						_								_	_			\square	
	Maximum permitted	12	353	545		539	486	331	550		5/4	551			551		20/	495	553	738	547		530	660		722			121	844	5	558	632		614	620	591		597	746	1		738
speed permitted	Гей илск				50		;	2	03	20				30						20		T -taža	CSAK - D	65				100									40	2					
mumixeM	Right track			_					-				-	-				_		_								_		+		+	_	+	-	-					+		
	Railway line categor		<u>5</u>	+	<u>7</u> 7			22	+	4	-	5 2	+	-		-		-	5 2	+			Margevo		ទ		-	+	-	38	+	+	-	+	-	Ű	<u>ញ</u>	<u>ဗ</u>	88	38	38	+ +	8
	Class of railway line		M ;	+	ZZ			ZZ	-		ZZ				Μ	-	+	-	Z >	+		M	- DOVO -	Σ			Z;	+	ZZ	-	+	+	+	M	+	-	M	+	+	-	+	Μ	
	Single/double-track I		s	+	s s			S S	-		N V	-	-	-		_	+	_	0 V	+	\vdash			N N	+		-	_		2 00	+	2 00	+	2 S				+	+	+	n N	+	S
	nioq service point	-	(m m	2	-	~ ~		<u>س</u>	~ ~		· ~	3		~ ·				10	1	100	<u>-</u>	-	3	-	~ (γ γ	η -	-	- ~		-	• m	-	-	-	m	- (- m	~~~	~	-
	Chainage Name of service point		163+881 UŽICE	1/0+644 STAPARI	173+400 RISTANOVICA POLJE 176+000 TRIPKOVA	178+350 SUŠICA	185+225 BRANEŠCI	193+320 ZLATIBOR 200+300 RIENICA 71 ATIBORSEA	205+407 JABLANICA	211+600 GOLEŠ	214+832 STKPCI 210+500 R A Č A	225+290 PRIBOI	228+300 POLICE	232+800 PRIBOJSKA BANJA	241+278 BISTRICA NA LIMU	246+300 DžUROVO	252+616 PKIJEPOLJE	255+856 PRUEPOLjE TERETNA 250+600 lytet trv / žrtiba	2597-000 VELIAN ZUFA 264-641 I HČICF	273+329 BRODAREVO	285+193 VRBNICA	287+438 STATE BORDER		3+405 BATOČINA	8+300 GRADAC	12+284 BADNjEVAC	15+800 RESNIK KRAGUJEVAČKI	18+451 MILATOVAC	20+600 CVETOJEVAC 224435 IDVANDVZAC	28+829 KRAGUJEVAC	201922 24/0D	34+100 GROŠNICA	39+551 DRAGOBRAĆA	44+600 VUČKOVICA	47+586 KNIĆ	53+474 GRUŽA	60+598 GUBEREVAC	62+100 TOMICA BRDO	66+335 VITKOVAC	/0+081 MILAVCICI 73+035 VITTANOVAC	79+100 SUMARICE	81+900 SIRČA	84+744 KRALjEVO
	Chainage	4																																									
	Distance in km	3	1,981	0,/03	2,756	2,350	6,875	8,095	5,107	6,193	3,232	5.790	3,010	4,500	8,478	5,022	0,310	3,240	5 041	8.688	11,864	2,245		2.739	4,895	3,98	3,516	100'7	2,149	6 494	0.471	2,800	5 451	5.04	2,986	5,888	7,124	1,502	4,23	3,15	5,165	2,800	2,844
handover to public transport	Right track Left track						21.05.	1976.									21.05.	19/6.								03 03	1887.										22.12.	1929.					
Date of	,;u																																										



	əbutitl A 🖔	R	271,4		233,4	304,2		343,1	379,8		393	106 3	C'00+	416,5				441	151	t		470	101	491	496,6		497	93.7	85,1	85,3		86,6	88.7	2,00 80 8	119.6	118,3	124,6	124,7	124,5	119,3	113,2
	S Loading gauge	ŻS-I	ŻS-I	ŽS-I		ŽS-I	ŽS-I	I-SZ	ŽS-I	ŽS-I	ŽS-I	T-SZ	1-52	ŻS-I	ŻS-I	ŽS-I	ŽS-I	ŽS-I	1-52	I-SZ	ŽS-I	ŽS-I	ŻS-I	52	ŻS-I	ŻS-I	5-1		ŽS-I	ŽS-I	I-SZ	I-SZ	1-02		ŻS-I	ŽS-I	ŽS-I	ŽS-I	I-SZ	ŽS-I	ŽS-I
resistance of [Mab] anil adt	≈ →	3	•	•	<u> </u>	0		•	1	÷	1	ų	n	9				1	-	۲		4	,	n 4	· ~				5	-	•	- 4	n v		•	S		4	~		9
Builug	→ [2	_	9		^ «		_	~	∞	5	S	4		9	-		_	8	۰	+		∞	,	~ ~	+				-		_	n r	n v	~	0	m		4	m	+	e
Ruling gradient	Slope	+	0				_	0	0	\vdash	•	-	-	~	-		_	0	_	4		-	•		+	$\left \right $	_	\vdash	5	-	-	-			-	5	$\left \right $	4	~	+	3 6
	2 Gradient of the statio	+	0,4 5		67 6			7,0 6	4,1 7		2,2 4		+	4,8 4			_	0,0 6	9 00			0,0 5		0,0 0			-		0,2 0	0,2 1			9 0 0					2,5 4	2.5 3		1,0 3
sn	Minimum curve radi	3	300		000	250		300	270	300	250	000	R	300	300			300	200	200		300	000	000	300		<u>8</u>		3000	2000		2000	1000	000	3000	3000	1900				610
	Open for the accepta dispatching of passer operations	44	P/F	<u>م</u> ۱	<u>م</u> م	. _с ,	Ч	P/F P	P/F	P/F	P/F	P T	2	P/F		Ρ	Р	P/F	P/E	P	, ₄ ,	P/F	d 2	P/F	P/F		a		P/F	Ч		P/F	P/F	1		P/F		P/F	Ρ/F		P/F
	Cocupancy of service	1	Ч			ÞÞ		4	Р	H	ч.	F	4	Þ				Ч	ρ	4		Ч	;) <mark>4</mark>				Ρ	D	1	F- F	ч <u>р</u>	. •	• Þ	Ч		þ	P.	•	Р
moth	slq gnibsol-bnə\-əbiS 🗧	3	s					s	s			ũ	0	s					Ũ	2		s	¢	n v	s				s				S/F								S/E
	5 Freight car scales	2			_																										_		Vec			Ц	\square	$ \rightarrow $	_		\square
DIC	- sbos triote point code -	2	12101	12102	12103	12105	12116	12106	12107	12108	12109	12110	12112	12113		12117	12114	12001	12002	12021	12004	12005	12019	12000	12008		12022	25471	25470	25501		25502	05556	04401	24403	24404	24405	24406	24407 24408	24409	23450
he service point	1 Manner of securing t	;	~		4 4	. ω		2	∞	e	∞	ų	n	∞				1	•	•			•		10		2		1	5		Ś	0 4	- 4	n v	S		S	s		4
noitelu	да оШалого ГиаШа ≂ ≂	station distance	station distance	station distance	station distance station distance	station distance	station distance	station distance station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance		station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance station distance	station distance	station distance										
	Acceptance of the longest trains	2	~	T,	2 0	5		2	3		2	~	7	2				2	~	_		8	,	<u>-</u>		,	(Fedut)		and 4	2 and 3	1	2 and 3	2 and 4	7 and 3	2 and 3	and 4		2 and 3	2 and 3		2 and 3
B→A Direction	train length Tracks for	-	-				-	9	4	05	9	-	-	~			_	3	9	7		9	-	2 4	9		- !	-	3		+	-	7 6	10	+		\vdash		-	+	
	Maximum permitted	-	631		630	658	_	586	644	1005	576	103	5	638				473	570	+		576	1	545	64		te horder	_		573	-	-	202	+	-		$\left \right $	617	733	+-	594
A⇔A	Tracks for 5 acceptance of the longest trains	2	٣	•	2 0	2	1	2	3		2	¢	1	2				2	0 and 2			3	•	- -	-		1 vo - cta		3 and 4	2 and 3		2 and 3	2 and 4	5 pure C	2 and 3	3 and 4		2 and 3	2 and 3		2 and 3
Direction	train length	4	631		630	658		586	644	1005	576	667	5	638				479	610	+		587	\$	94	630		13/ Boonier	2000	730	513	+	+	505	+	+	525	+	617	716	-	594
	Maximum permitted	-	0		9	0		ŝ	ò	2	ŝ	V.	5	9				4	ý	5		ŝ	4	ň	0				7.	S		4	o v	ñ V	ŝ	ŝ		0	1		S
permitted speed	⊐ Left track	-				40 (50)							50 (60)								50						10 13/ 1 10 Subotica - Rogoievo - state		(0 1) UC						0000	40 (0c) 0 1					
mumixeM	5 Right track	_			~ ~		~	~ ~	~	~	~		_		-	~	~	~	~ ~			_	~		1		-1-			~	~	~						_	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		~
Å	 Railway line categor 	<u>່</u> ບິ	3	ΰ	38		8	88	S	ິ ເ	<u>ເ</u>	3 3	3 Ű	0 0	Ű	C	ິ ພ	ິ ເ	ñ	ĥ	ñ	ñ		ŝĔ	n n n	ñ	ñ		C	ñ	ñ		ŝĔ						ññ		D3
	Class of railway line	+	+	+	22	+ +		ZZ		Z		22	+	+	Σ	Μ	Σ		2 2	+	-	+	-	ΞΞ	+	+	-		Μ		+	-	2 2	+	+	Σ	+			-	M
	✓ Single/double-track l			$\left \right $	N N		_	s s		s		S O	+	+			s		n o	_	-	$\left \right $	S C	2 00	+		N N		S		+	S S	0 0	2 00	s s	s	\square		s s	s s	s
1	of Type of service point	12	-	~ ·			<u>س</u>	- ~	-	~	- (m -	- ~	-	13	3	3		η -	- m	n w	-	~ ·	- ~	-	12	-	13	1	'	0			-	-		m	-	<u>- </u>	• m	-
	4 Aame of service point	ľ			9 100+899 BOGUTOVACKA BANJA 0 108+861 DOBRF STRANF			3 127+293 USCE 7 132+800 LOZNO				/ 14/+600 KVATI							0 1//+900 DKEN 0 182-8001 EBOS ATTÉ					0 202+000 BAINJSKA 0 208+200 VALAČ		2	0 0+120 KOSOVSKA MITROVICA SEVEK	41+076 STATE BORDER	9 43+815 BOGOJEVO			8 58+636 PRIGREVICA		83+360		-		115+374	3 118+557 LjUTOVO 4 123+761 ŠEBEŠIĆ		131+872
	mJ ni sonsteid «	0.970	8,199	3,487	3,499	9,252	5,487	3,693	3,323	2,190	5,140	4,147	5 300	4,288	2,412	1,200	3,324	3,376	000,0	5 200	0.500	3,800	3,400	002.0	2,700	2,367	*0,120		2,739	6,252	0,541	8,028	7 370	0 010	14,132	7,671	6,673	3,529	3,183	4,460	3,651
transport	ے Left track	4	.05.	1931.		07.08.			00 00	1031				12.02.	1951.						12.02.	1931.					-				1870.							1869.			_
Date of handover to	- សរុទ្ធារ ជាទ្	•	24	15		00	4		5	0	-			12	<u>-</u>						12	15								20	18						=	181			



5 Acceptance of the longest trains 5 Manner of traffic regulation 5 Manner of traffic regulation 5 Service point code - UIC 5 Stervice point code - UIC 5 Side-/end-loading platform 5 Side-/end-loading platform 5 Side-/end-loading platform 5 Side-/end-loading platform 6 Projeght car scales 7 Occupancy of service point 3 Side-/end-loading platform 4 Sides/eng of passengers/freight 6 Projeght car scales 7 Occupancy of service point 8 Minimum curve radius 9 Gradient of the station [%o] 10 Side-inter 11 Side-inter 11 Side-inter 12 Side-inter 13 Side-inter 14 Side-inter 15 Side-inter 16 Side-inter 17 Side-inter 18 Side-inter 19 Side-inter	1 10 11/ 10 11/ 20 21 22 23 24 23 20 27 26 29 29 Batainica		station distance 1 16202 S P	station distance 1 16002 C D F 000 050 7 1 0 2	1 16204 S P P/F 300 0.0 2 6 2		2 1 16201 Yes P F 0 7 1 9 2 3S1		line junction "K/K1" - Resnik	7 1 16201	1 U 350 15 0 17 -	1 U 500 9 7 10 8	station distance 1 15501 S P P/F	N/M1) 16202 S	station distance 1 T	nik)	1 16201 Yes P F	station distance 1 400 7,0 6 1 6 1 ŽS-I	station distance 1 5,6 2 1 4 1	nn "R" - Rakovica	5 station distance 1 1 16103 P P 300 7 5 7 5 $2S_{1}$	- Rakovica	1 16021 P F	5 station distance 1 16103 P P 300 3 8 4 0 25-1	-	"T" - (Rakovica)	station distance 1 10201 Y cs F F 5 1 6 1 ŽS-I	"B") - turnout "K" - turnout "K1" - (Jajinci)		000 0,0 0 2 - 2		AB with TWT 1 1 180 2 5 4 - ŽS-I	E E 10071 11	and 4 Y Y Y 10801 11	AB 1 16505 P P/F 3000 00 3 5 7 7 2/5-1 1016			and 2 station distance 4 108/1 Yes P F 400 3 1 3 2 2S-1 block bost distance 1 23301 P 700 45 3 2 3 3 2S-1 84.5	1 - junction point 28 - (Osipaonica)		7 - 7
noineiugen ວ່າໃນຊາ 10 ກອດແຄ່ຟ 🕇			tation distance	tation distance	tation distance		tation distance		nn "K/K1" - Re		tation distance	tation distance	tation distance		tation distance	tion "A" - (Res		tation distance	tation distance	akovica	tation distance	tovica		tation distance		sovica)	tation distance	urnout "K" - tu		tion Dedinie -		AB with TWT		!	AB	ailovo		tation distance lock post distance	1 point 28 - (Os	Dr AB	OK MILLAN
Maximum permitted train longth Tracks for Tracks f	stružnica -	780 7 and 8	2 and 3	2 0100 2	4	- Ostružnica	2		"B" - Open line		s		730 3	Copen line junction 845 2 3 and 4		- "X		-s		line junctionN "R" -	+	line junction "T"	789 8 and 9	702 5 st		"B" - Open line junction "T" - (Rak	12	en line junction "B") - ti		ev nark - Onen line inno				200 5 and	749 4 and 5	- Open		798 1 and 2			_
Z train length Tracks for A→B Zaceptanee of the longest trains	XARD			733 3	853 3	Beograd MARSHALLING YARD "B'	750 2	300 and track loco Makiš 2 is 2914m	- Open line junction "B" - Open line				730 3	R45 3 and 4		Open line junction			_	g yard "B") - Open	702 4	g yard "A" - Open		702 4		t yard "B" - Open		junction "K/K1": (Open line junction		- Onen line innction Karadordev nark			dija - Gol	044 I and 2	655 2 and 3	marshalling va		798 1 and 2	Krsna: (Kolari) - ju		
Z Kight track Maximum permitted Left track Peed	Beograd MARSHALLING			30	-	0	<u> </u>	and track loco	yard "A"		00		0	Open	50	vard "B" -		30	_	rad marshalling	30	eograd marshalling	30			ad marshalling yard	30	Open line	60			R		80 80	- 08	Sad - 1	8	2	ation Mala	100	
 Type of service point Class of milway line Class of milway line 		1	1 S M D4	1	I S M D4		1 S M D4	£11.	1-2	1	s	X	1 S M D4		6 S M D4	seograd marsh		6 S M D4	2	116 (Beograd	1 S M D4	117 B	S N	1 S M D4		118 Beograd	6 S M D4	at the area of	2	120 (Onen line innction Pančevački most)	2	6 D M D4	-	;	14 D M D3 1 S M D3	122 Novi		1 S M D3 4 S M D3	ion track of th	<u> </u>	17 N C 71
A Chainage A of service point A service point	•	0+000 BFOGRAD MARSHALLING YARD A		14±500 STIPČN	25+658 BATAJNICA	-	0+000 BEOGRAD MARSHALLING YARD B 5+902 OSTRUŽNICA	Distance between Belgrade Marshalling Yard B and Belgrade Marshalling Yard A via junction points 302	2	0+000 BEOGRAD MARSHALLING YARD A	2+776 OPEN LINE JUNCTION B	8+857 OPEN LINE JUNCTION K	10+419 RESNIK	0+000 OSTRUŽNICA	2+121 OPEN LINE JUNCTION B		1+772 BEOGRAD MARSHALLING YARD B	4+895 OPEN LINE JUNCTION R	6+309 OPEN LINE JUNCTION A	A DOCTORNAL WAR WAR ADDRESSED	4+895 OPEN LINE JUNCTION K 5+798 RAKOVICA		5+250 BEOGRAD MARSHALLING YARD A	5+612 RAKOVICA	Distance between the open line junction T and Ostružnica station is 5604 m		1+//4 BEOGRAD MAKSHALLING YAKD B 2+483 OPEN LINE JUNCTION T		8+872 OPEN LINE JUNCTION K		0+000 KARAĐORĐEV PARK	1+491 DEDINJE	0.007 11111	0+896 INFILA	1+949 [INDUA 1] 4+708 [GOLJJBINCI		0+000 JUNCTION POINT 6 NOVI SAD	1+850 NOVI SAD MARSHALLING YARD 3+677 SAJLOVO		0+000 JUNCTION POINT 1 MALA KRSNA 2+214 ITINETION BOINT 28 MALA KPENA	2+214 JUINUTION FUENT 20 MALA MANA
 – Right track Date of handover to public J. Left track public Distance in km 	-		28.05 3.300	1067	11.158		02.08. 1970. 5.902	Distance between Belgrac		02.08.			1967. 1,562	28.05	1967. 2.121		00.00	1070 3,123	1,414		20.10. 1988. 0,903		02.03.	1970. *3,129	Distance between the ope		02.03. 1970. 0,709			1907. 0,403		1,491	-	10.12.	1883. *1.949 *3 527			1992. 1.850 1.827	1005	1314	2,214



		əbutitlA 8	00	102,6	105,5				188.8	187,7					82,6		84,5	82.6	04.5	C, FO	84,5	84.73		84,5	84,73	87,58	84,2	87,58	7,10	109,9		81,2 79,2		113,2	110.1	110,4
		egueg gaibeo.1 S	2	Ţ-Sź	ŽS-I		ZS-I	I-SZ		ŽS-I	1-52		ŽS-I				ŽS-I		, i	5		ŽS-I	1		Į-Sž		ZS-I	1.2%	5	ZS-I	ŽS-I	I-SŽ		Į-Sž	I-SŽ	I-SZ
		ې <u> </u>	q	-	1	-		-	┥┝			-		-	11		-	-		+			┥┝		-	-			+				i	H	++	
	-	\rightarrow ξ	17	2	4		3	-		0	ç	ì	5			-	5		- 4			Ŷ			5		2	4	·			1			-	-
			-		+			_	$\left \right $			-					-		-	+			┥┝		_		4		+			2	$\left \right $	\mid	4	
1 1						_	~	0 m	┥┝		, v		~	-				00	_	1	5			Ť		5,0	0,0 1			0,	\square	0,0		0,		2
1 1			-				300	1000 450			400	2	293								4						_			-			i			
1 1		operations	-	\vdash	+	-		+									-	\vdash		+	H		┥┝		\square	\vdash			+	\vdash	\square		í I			+
1 1 2			77		Ч	D/D	P/F	4	đ	P/F	P/F				~			La la								ď		ď		Ч				Ρ/F		
3 1 3	nioq :	Cocupancy of service	17	<u>م</u> م	Р,	٩	4 84	4	•	· P-					A		4	٩	P	4	ď	F		<u>م</u>	Þ	Ч	H	<u>а</u> Г	•	סם		D			1	2
1 1	ntiorm		-			V			v		S/E				ŝ			S									щ	μ	1				ł	S/E		
1 1		5 Freight car scales	1					_						-	~		_			-		_	┥┝	_	\square						\square			H		
No. No. <td>nic</td> <td>- Service point code -</td> <td>2</td> <td>13405 13407</td> <td>13450</td> <td>1261</td> <td>12601</td> <td>12301</td> <td>12550</td> <td>12601</td> <td>12551</td> <td></td> <td></td> <td></td> <td>_</td> <td></td> <td>_</td> <td></td> <td></td> <td>_</td> <td></td> <td></td> <td></td> <td>23301</td> <td></td> <td></td> <td>23306</td> <td></td> <td>4</td> <td>\vdash</td> <td></td> <td>16805</td> <td></td> <td>23450</td> <td>22706</td> <td>w107</td>	nic	- Service point code -	2	13405 13407	13450	1261	12601	12301	12550	12601	12551				_		_			_				23301			23306		4	\vdash		16805		23450	22706	w107
Image: constraint of the second sec	he service point	t gunner of securing t	1	- 4	-	-			╞	• •		kula)		-	= =		Ξ	=	1	-	:	=		=		Ξ	-	=-	•	1	\square	e 11		-		-
No. Open of service point No.	noitalu	દ્વે Manner of traffic reg	10 - Lapovo ***)	station distance	station distance		AB	AB AB				1	AB				station distance		station distance	SIGNOT CONTRACTOR		P.C. with station distance			RC with station distance		station distance	station distance	ica	station distance	station distance	with station			station distance	station distance
Indext of the field o			vard	9 10	~	010	+				3 mg ya	11			d 5	Π		d S		1		C Pu	1		1d 2	od 5	nd 4	1d 5	Subot	nd 2		nd 2		nd 3		
Indext of the field o		Tracks for	alling	9 an		Medur					u suan	oint 2		-	4 ar			4 ar				1 31	-		1 ar	4 aı	3 aı	4 ar 3 ar	3lok 1	1 ar				2 at	-	7 7
Indext of the field o			narsh	836	563	ard - N 738	885	543	alling	88	488	tion p		E	493			403		RF		746	۲ ۲		746	532 532	938 3.1.1.	532	đe - B	876		356	s.	594 -	120	20
Indext of the field o						ling y			marsh		ī.				d 5			-		enka		44			44	d 3			redgra	d 4	4	d 2 d 2		d 3	5	7 10
Indext of the field o					S	rrshall		-	- Niš 1	~	3	krst)		l-Sajlo	4 an		2	4 an		Rum		3 an	Run		3 an	2 an			no pu	3 an		1 an	, NAL	2 an	-	1 41
Indext of the field o	Direction		o Varo	849	664	Niš ma 744	733	580	ii krst	733	490	Crveni		ovi Sad	492		5	VI Sad		- ovoli		650	i lovo		650	as Nov 531	943 as Nor	531	csandr	907	XI-1 XI	356	KEGIO	594 594	120	0(7
Interface Interface <t< td=""><td></td><td></td><td>Lapov</td><td>. 5</td><td></td><td>1</td><td></td><td></td><td></td><td>-</td><td></td><td></td><td></td><td>ž</td><td></td><td></td><td>ľ</td><td>ž–</td><td></td><td>- ^{SS}</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>1.1</td><td></td><td></td><td>NOTIPX</td><td></td><td></td><td></td><td></td></t<>			Lapov	. 5		1				-				ž			ľ	ž–		- ^{SS}									1.1			NOTIPX				
Induction Induction <t< td=""><td></td><td>Sight track</td><td></td><td></td><td></td><td>125 Tn</td><td>30</td><td>ŝ</td><td>12</td><td>о С</td><td>30 30</td><td></td><td>30</td><td></td><td>65</td><td></td><td>80</td><td></td><td>80</td><td></td><td>80</td><td>6</td><td></td><td>80</td><td>10</td><td>09</td><td>\$</td><td>60</td><td>ovićev</td><td>30</td><td></td><td>60</td><td></td><td>ne 107</td><td>2</td><td>10</td></t<>		Sight track				125 Tn	30	ŝ	12	о С	30 30		30		65		80		80		80	6		80	10	09	\$	60	ovićev	30		60		ne 107	2	10
Indextreme Indextreme Indextreme 1 2	A	Railway line categor			B 2	-	4	<u>5</u>	1			of the	4							1			1		-				Naum	ñ	D3	D4			ñ	52
Indextrement Indextrement Indextrement Indextrement 1 2 3 4 Chainnage 1		o Class of railway line	open	· >	M		M	ΣX		M	Þ	track	М				X		2	E.		Z			M		M	Z	8	Z	M	M			P4 P	4 🕰
Image: Construct of the product of the prod	əu	م Single/double-track ا	- .	<u> </u>	D		s	s s	1	s	v	cting	s				s		Ũ	2		v	2		s		s	v	2	s	s	s			ŝ	s s
Image: Construct of the product of the prod		Type of service point	•		-	-		- 0	1 -		1	Conne	12		- ~	6	4	-	m z	+	4	<u>و</u> ا	•	40		-	-		•	- 5		6		-	00	0
Ability of the field												128 (1									1							
1 1 <th1< th=""> <th1< th=""> <th1< th=""> <th1< th=""></th1<></th1<></th1<></th1<>		92snisrl) «	_	0+000 2+100	3+788	235+243 TRIDALE	238+177	239+280 241+268	000+0						0+000	2+201	3+33(0+000 NOVI SAD	1+995 NOVI SAD	00010	000+0	0+285		0+000 SAJLOVO 0+331 KM 000+331	3+323 RUMENKA					166+519 171+962	175+305	0+000 RASPUTNICA KARLOVAČKI 0+683 KARLOVAČKI VINOGRADI		000+0	1+082 1+813	3+848
Of a bash mgi M Image: Constraint of the con		y Left track	7				0	1		ci	5		90				1			Ĩ											1	5.				II.
	handover to	- Right track	-	.£491.	L'†I		104			194	194		01.0																			10.0				16.1



	Altitude	30	107.7	102,3	90,7	,	17	11	80	82	105	70	78,0	80,0	81,0	81,3	78,9	77,6	80.8	80,8	77,5	80,8	79,3	78,9	80,5					70.3	80.4		82,0	85,5	84,8	82.5	82,5	83,1	89,6 103.0	106,6	108,4	109,6
	əgurg gaibro.l	29	1-SZ	ŽS-I	ŽS-I	1.07	ŽS-I	ŽS-I	ŽS-I	ŢS-I	ŽS-I	ŽS-I	ŽS-I	1-52	ŽS-I	ŽS-I	ŽS-I	ZS-I ře I	I-SZ	ŽS-I	ZS-I	1-52	ŽS-I	ŽS-I že I	Į-SZ	ŽS-I		ŽS-I	ŽS-I		ŽS-I	ŽS-I	ŽS-I	ŽS-I	ŽS-I	1-67	I-SZ	ŽS-I	ZS-I ŽS-I	I-SZ	ŽS-I	ŽS-I
resistance of the line [daV]	\leftarrow	28	m	4	4 v	-		2		- 7	• •	3	4	•	2	4	-	2		1	۰ ۱	n ~	0 0		-	1			1		4	•	4	\vdash	5	13	+	13		<u> </u>	2	2
Ruling	\rightarrow	5 27	-	2	4 4	-		-	7		• •	4		4	5	$\left \right $	0	S		2	1 4	0	1		-	÷			m		0	-	9		9	10	-	10	٢	-	7	m
Ruling gradient	Slope Slope		- -	2 4	4 4 4 4	-		1	2		• •	4 3		4 0	5 2	$\left \right $	3 v	5	+	2 1	0	0 C	1 2		+ -	0 0		\vdash	2	╞			4 3		6 5	10 10	-	10 10	C	-	2 2	3 2
[%] u	Gradient of the statio		1,8	1,8			0'0	0,0	0,0	0,5	30	0,5		0,0	0,0	3,0	0'0	0,0	0.0				0,0	0,0	00					00		00		0,0		000			3.0	2°C	3,2	
sn	піры элго титіпіМ	23	3600	200	3600		250	009	300	200	1000	400	300	005	650	400	300	500	1000	500	550	480 500	480	475	1903						400		500	500	800	2005	300	300	400	1000	1000	3000
nce and gers/freight	Open for the accepta dispatching of passen operations		P/F	P/F	P/F		P/F	Ρ	P/F	P P/F	P/F	Ρ	P/F	4	P/F	P/F	P/F	P/F		P/F	P/F	P/F	P/F	D/E	F					D/F	p	•	P/F	Ρ	P/F		P/F				P/F	
	Occupancy of service	21	4	Þ	<u>ч</u>		ч ;	þ	Þ	<u>م</u> د	, D	D	ч,	а,	F	ч	<u>с</u> , г	4		F	F= F	- =	ы	P	4 [-			D		F	- 12)	H	Þ	F		Ч				Þ	
պյուս	siq gnibsol-bnə\-əbiS	+					s		s	s s	s s	s	s		s		4	s		s	s	n	s	v	n N					v	2 00		s	s	s		s					
	Freight car scales		+ ~				Yes	0	~	-			0.0	~	-	l Yes	_	~	+	-+		_				_	FIC	-					~		-			\mathbb{H}	010	+		5
DIC	l - əboə mioq əəivrəS	18	23/04	23702	23701	66167	22001	22002	22003	22004 22005	22006	22201	22202	22205	22204	22501	22550	22503		22504	22505	000077	22509	22801	22803	22899	FRAF	16104		00500	200122	22602	22603	22604	22605		23801		23802	23804	23805	23806
he service point	d gnines of securing t	17	-	-			4 4	-		» -	• ∞	8	2	01 0	2∞	4	۲.	-		~	~ 1	- «	2	-	+ 0		FOR	m		2	9		6	10	0	-	• •	-			4	
noitelu	ຊອງ ວດີໂຣປ ໃດ າອກແຣM	16	station distance station distance	station distance	station distance	- (Jimbolia)	station distance	station distance	station distance	station distance station distance	station distance	station distance	station distance	station distance station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance station distance	station distance	station distance	station distance	station distance	+041) - Beograd Dunav - Open line junction Pančevački most - LINE CLOSED FOR TRAFFI مما تسميناهد رابيد طـــــ(2010 - كمعمد انبية نيسرينمبي 2010 - الاعلمينيين)	station distance	station distance		station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance
	acceptance of the longest trains	5	and 4	2 and 3	3 and 4	order	nd 5	nd 3	nd 3	2 and 3 3 and 4	and 3	nd 3	2 and 3	7 00	nd 3	2 and 3	nd 3	and 3	t	nd 3	and 3	2 and 3	nd 3	0	and 3		ački m	11		a 14 3	and 3		nd 3	2	nd 4		2 and 3	H	T	t	nd 3	
Direction B→A	Tracks for		m	+		- state border	4 and		2 and		-	2 and		1 and	2 and		00	2	_	5	+	+		-	- 0		ančev			ubotic	10	+	2 and		3 and		+	+	_	\downarrow	2 and	H
	Maximum permitted train length	14	643	706	618	- epui	835	249	473	537	534	617	665	502	524	633	585	629		647	519	537	740	CV0	619		tion P	615		11a - Si 740	268		523	570	619		523				600	
	acceptance of the longest trains	<u>د</u>	and 4	2 and 3	3 and 4	- Zrenjanin - Kikinda	nd 5	nd 3	2 and 3	2 and 3 3 and 4	nd 3	2 and 3	2 and 3	1 and 2	2 and 3	2 and 3	2 and 3	and 3		2 and 3	and 3	2 and 3	2 and 3	0 00	2 and 3		line in			o - Ser	2 and 3		2 and 3	2	3 and 4		2 and 3				2 and 3	
Direction A→B	Tracks for		3 a	+		njanin	4 a			-	-			-	-	$\left \right $	+	5	_	+	+	+		-	+		on lin			ilošev	+	+		\vdash	-		-	+	\downarrow	+	+	\vdash
	train length Uaximum permitted	12	054	677	626	a - Zre	845	409	473	537	534	617	665	502	524	633	585	629		647	519	537	740	CVO	619		av - 01	100		sko M 740	268		523	570	619		523				600	
pəəds	Left track	11		0		stanic	_				70)			40)	(80)		_					70)			_		d Dun		20	205 Banatsko Miloševo - Senta - Subotica							100	3U)				
mumixeM bettimneq	Right track	10		120		Glavna stanica	9	5			50 (70)			30 (00		80		30	30		50 (70)	Ĩ		60		-041) - Beograd Dunav - Open line junction Pa 204 Tončidar (tor 4±105) - Onen line innetion		20	205			60			20		20 (30)				
Å	Railway line categor	0	4 4	54	<u>4</u>			ñ	5	A	K A	A	D2	P Z	: A	B2	B	83 B	a G	B2	B3	A A	4	<u>ຕ</u>	38	ΰ	41) - I		D 4		Ű	80	Ű	ΰ	، 2	A A	: P	A	A A	r P	A	A
	onil yawlish fo szalO	∞ (× ×	4 24	24 P4	2 Pan	ρ	4 24	Я	~~~	4 24	Я	2	* *	4	2	<u>م</u>	24 P	4 🖂	Ч	24	× ~	4 24	24 P	4 24	2		Í	ы		¥	2	R	ч	بر	× 2	: ~	2	24 24	4 🛩	ъ	ĸ
əui	l hard-slduob/slgni2	6	s s	2 S	s v	2	ŭ	n v	s	s s	s so	s	s	n v	s	s	s	s o	n v	s	s s	n v	n N	s o	n N	s	rad (k		٩		v	s	s	s	s	n v	s s	s	s v	n v	s	s
1	Type of service point	0	- ~	0			- 4	• •	-		• ••		- (2 9	• -	-	•		30	-		- =	-	m -	-	13	onji G	-	ø	-	- ~	m	-	∞	- 0	<u>ح</u>	-	12	m "	n m	-	m
	Diatance in km Chainage of service point	4	3,810 7+658 PALIC 4 099 11+757 HAJDUKOVO		8,599 24+018 HORGOŠ 3.870 77+807 STATE RORDER		1 462 17.660 OBENTERE TENED			7,059 33+858 CREPAJA 7.467 41+375 DFBFF15AČA	45+835	56+271		04+045 64+760		84+398	88+795	8,680 97+475 ELEMIR 1 555 00-020 ITMCTION DODUT 1D	102+000 KM 102+000 SC	105+815	112+702	8,922 I21+024 NOVI BECEJ 15 514 I37+138 RANATSKO MILOŠEVO POL (F	141+291	7,309 148+600 DERIĆ 11 514 140+114 PTPTNDA	11+099	14+423 STATE BORDER	203 Beograd Donji Grad (ku	5+700 TOPČIDER TERETNA	1,095 6+795 OPEN LINE JUNCTION G	0+356 BANATSKO MII OŠEVO	4 740 5+105 BOČAR	10+700		7,167 25+230 OSTOJIĆEVO		38+407	000+0	1+391	*3,129 42+293 GORNJI BREG 6 017 40±210 BOGAPAČ	0,91/ +9+210/ DOGANAS 5,013 54+223 DOLINE	3,825 58+048 OROM	
transport	Left track	2														Ц	89.			1					-				881	╞				<u> </u>	+			\vdash				
Date of handover to public	Right track		18/0.								09.04	1884.					04.05.1889									/ כאו .וו.כו		1	0.50 0.71 0.71		15.09.	1896.	15 00	1896.		1915.				14.11.	1889.	
																	-									-		1.0					1					L				—



	sbuittA	30	113,2	17	77		81,3	84,9 84,8	85,6	85,9	84.4	85	85,4				86,4	83,1		81,8	618 81	78,6	88,4	77.4	79,8	82,8 80.5	80				80,3	2,00	101,0	81,6	81,8	80,0 79,2
	ว ฐมธฐ ฐกib ธ 0.1	29	I-SZ		ŽS-I		ŻS-I ŻS-I	ŽS-I ŽS-I	ŽS-I	ŽS-I	1-07	ŽS-I	ŽS-I	ŽS-I			Ĭ-SŽ	I-SZ	ŽS-I	ŽS-I	1-C7	1-SŽ	ŽS-I	ZS-I	ŻS-I	ŽS-I	ŽS-I		ŽS-I	ŽS-I	Ťc T	103	Ťe.T	I-SZ	ŽS-I ŽS-I	I-SZ
resistance of [Mab] onil off	\leftarrow		7 6				0	2 4	6				1	-	4		\vdash	Ś			4	4	m		0	m v	+			1		-	-	- m	++	
Ruling 10 constrainer	\rightarrow		2		-		2	5 5	2	•		• •	3	_				9		4 (3	2	~		11	5	• •			4	v	- 1		n w	++	
Ruling gradient	Slope Slope	+	2 2 2		-	\vdash	5 7	4 4 3	1	-	→ C	1 0	1 0	-	7			2	$\left \right $	5 0	2 4	4	5	_	8	4 1				3 0	c	+	v 0	+	++	+
	Gradient of the statio		1,0	0,45	0,5		0'0	0,0		1,0	0,1						4,0				0,0	0,0		3.0		4,0					0'0		0,0			0 [°] D
sn	iber əvruə muminiM	23	500		500		100	400 300	450	900	300	30	300					450		1000	1000	500	450	950	400	400	300				300	201	300	005	200	400
and and a second s	operations of passer dispatching of passer	22	P/F	Ρ/F			Ρ/F	P/F P	P/F	Ч	D D		P/F	E.	L			Ρ/F		Ρ/F	P/F	ط م	P/F	ᆔᆆ	A	<u>ч</u>	Ч	Į.	F				P/F	ᆈᇝ	P/F	1
	Open for the accepta	21	4	4	D	P	H	4 D	H	F	ч р	, D	P.	F	4		ч,	<u>ч</u>		Þ	Þ	D	F		Þ	Þ	о <mark>е</mark> ,			Ч	Þ	1	d 1	2	P 4	+
molte	slq gnibsol-bnə\-əbi8	20	S/E	s			s	s s	s	5	0	s	s	c	0			s		s	s		s		s	s s	2				s		s v	n N	so o	0
	Freight car scales	19																										Yes						\downarrow		
	- ebos miod esivies	ć	23450/	21001		23301	24003	24004 24005		25001	20022			25403	4		23301	23001	+		22309	22307	+	22304	22303		22203	16871 Yes		23301	22301		16550			10004
the service point	t guinuse fo renneM	17	4		Ц	-	~	4 1	2	-	1 4	10	-	•	-		-	10		∞ \$	2 8	_	4	_	2	5	2 2	4	•	-	10	4	- 6	n 9	m	-
noiteluy	યુગ ગી161 10 ગગાહM	16	station distance station distance		station distance		station distance station distance	station distance station distance	station distance	station distance	station distance	station distance	station distance	station distance	Station distance	-Open line junction Sajlovo - Rimski šančevi - Orlovat stajalište	station distance	station distance station distance	station distance	station distance	station distance	station distance station distance	station distance	station distance station distance	station distance	station distance		junction	station distance	block post distance	station distance	- (Zvornik Novi)	etation dietance	station distance	station distance	station distance
B→A	acceptance of the scceptance of the ongest trains	15	2 and 3	206 Pančevo Varoš - Open line junction 2a - (Jabuka) 506 - 506			2 and 3	2 and 3 1 and 2	2 and 3	-	C DITE 2	1 and 2	2 and 3		+ nue c	evi - Or		2 and 3		2 and 3	2 and 3 2 and 3		2 and 3		2 and 3	2 and 3 2 and 3	and 2	Open line			2 and 3	border -	5 and 6	C OTTR	2 and 3	
Direction	Maximum permitted rain length Fracks for		594 2	tion 2a 506 2	Poievo		544	624 2 710 1	387 2		427				70	ski šano		558			548		573 2				253 1	Sajlovo O			1a - (Lukicevo) 555 2 and 3	a - state	639 5	+	628	+
	acceptance of the ongest trains		and 3	a line junct 2 and 3	- Odžaci - Bogoievo			and 3 and 2	~	-	C DIE 2	-		_	+ 0110 C	o - Rim		2 and 3		<u> </u>	-	+	and 3		~	2 and 3						a Borin	and 6	<u>_</u>	2 and 3	+
Direction A→B	Tracks for		2	Open li 2 ar	d - Odž	_	2 and	1		-	-	1 -	5	-	+	1 Sajlov				00	5	_	2		2 and	00	1 1	NG YA		_		ⁿ Do	5 at	4		
	Maximum permitted rain length		594	/aroš - C	Novi Sad		544	624 710	387		457	240	686	000	nc/	unction		558		593	548		573		804	787	253	HALLD			555	i junctio	639	ŝ	628	
speed speed	Left track	\square		ičevo V	00 1 207 1		50			B		27	6	100		in line j	40				60 (80)				60 (80)		30	MARSE	10	20	30 30	oen line		1007	(08) 0/	
mumixeM	Kight track	1	_	06 Pa						_				_		Ope					ŏ —		_		ŏ H	_		i Sad			71017					_
	Railway line categor		A		D 2			ññ		D3 ²⁾					ŝ	vi Sad)		88	+	_	+	AA	++	AA	$\left \right $	A A	R A	9 Novi	C	S	<	- Š		ŝ		ŝŝ
	onil yawlim to seelO		* *		24	2	~~~~	* *		24 P	+	-		24	+	208 (Nov		2 2	+	_	4 24		++	××	+	_	+	8		R	9	Rui	Ω.	+	++	* *
	Type of service point Single/double-track l		s s	-	S	4 S	s s	1 S 10 S		s s	0 0	10 S	1 S	3 S S	2	5	4	1 6 S	+			10 S S	++	n e N N		s v	2 S		s	4 S	د ۲ ا		, , , , , , , , , , , , , , , , , , ,	- 8	++	2 2 2 2
	nion solvres to envT	9				4			1		-		-				4				-	1 °						-		4				100		
	Distance in km Chainage Service point	4 4 24 - 500 DHZOTIO	2,521 04+592 BIKOVO 12,093 76+685 SUBOTICA	0+275 PANČEVO VAROŠ	1,264 1+539 OPEN LINE JUNCTION 2a	0+000 SAILOVO	*6,029 9+100 VETERNIK 3,454 12+554 FUTOG	12,557 25+111 PETROVAC-GLOŽAN 4,431 29+542 BAČKI MAGLIĆ		8,132 44+224 PARAGE			4,208 65+448 KARAVUKOVO	1908. 7,023 72+471 BOGOJEVO SELO	+,214 / 0+003 DOGOJE VO omis Gajdobis, Odžici and Karavikovo line category A			*6,479 10+148 RIMSKI SANCEVI *2.984 14+608 OPEN LINE JUNCTION 1			32+224	6,170 38+394 VILOVO/GARDINOVCI 5 451 43+84511.0K		1,700 51+132/DONJI 111EL 2.713 53+845/KNIČANIN			0,875 76+256 ORLOVAT STOP	1+141 NOVI SAD MARSHALLING YARD	1+595	*2,048 2+185 SAJLOVO	0 6 20 75+915 ORLOVAT 0 6 20 76+545 ORENT THE HINGTION OPT OVAT 15		0+517 RUMA 10 827 11±344 RIFD ANOVCT			2,473 21+373 OPEN LINE JUNCTION 1
public transport	प्रधा ग्राउद्द	$\left \right $	-	4	-		*	-					5		ea of service p			+					-		\parallel					*						+
Date of handover to	kight track	1		09.04.	1894.								24.12.	1908	1) At the an		31.05.	196	00 00	1889		02.07	1889	1927.		10.5					11 00 1035	100.11		05.11.	1901	



	sbuittA	30	79,1	78,5	70.1	1,61		82,4	91.2	90,8	96,2	105,2	109,4	114,4	122,3	110.0	135.6	134,6	136,9	1,161		79,3					144	144	147.4		153,4		167,5		169,5	174,8		186.8	100,0		195,2	1004	1,2V2	198
	эдигд дпірго.І	29	ŽS-I	ZS-I	1-07	ŽS-I	ŽS-I	ŽS-I	I-SZ	ŽS-I	ZS-I	ŢS-1	ŽS-I	ŽS-I	ŽS-I	1-07	Į-S2	ŽS-I	ZS-I Ťe I			ŽS-I	ĺ	• · · ×	1-07	ŽS-I	ŽS-I	ZS-I	1-S2	ŢS-I	ŽS-I	ŽS-I	ŽS-I	ŽS-I	ZS-I	ŻS-I	ZS-I	1-07	I-SZ	ŢS-I	ŽS-I	ŽS-I	I-SZ	ŽS-I
[Visb] anil adt	\leftarrow	28		2				1	2		1	•			4	~	h	5		· 9	•		İ				10	2	2		Ś		7		Ś	S		v	>		4	٢	-	0
Ruling resistance of	\rightarrow	27		2				5	2		5	e			4	~		5	v	<u>،</u> ا		•					10	2	2	•	Ś		7		Ś	S		y	>		4	-	•	8
Ruling gradient	Slope	- 1		2				•	-		•	0			4	۰ د	+	4 2		> 4	+	•	ł		_	-	~	-	6	+	5 1		2	_	+	۳ 	_	د د	+	+	4	4	_	2
	Gradient of the statio			0,0		+		0,0			1,0	0,0	0,0	0,0						+ 0		•	ł			+	3,4 7	0 2	44		5,3		0,8 7			5,3 4		4 55 6		+	0,75 4	+	+	0
sn	ibri əvruə muminiM	23	600	300		300		000	8		700	8	700	700	700		8 8	700	700	900	R	300	ĺ				200	250	250	ŝ	700		200		ŝ	500		005	2		500	300	2	300
	Open for the accepta dispatching of passer operations	22		P/F			Ч	P/F	P/F	Ч	P/F	P/F	ч	Ч	P/F	ъ. р	P/F	P/F	<u>م</u> م	24				P/F	ъ, р.	, ₆ ,	P/F	P/F	<u>ч</u> р		4	Ч	Ч	4	P/F	م 1	<u>م</u> و	24 P		- -	Ч	P P	E/F	P/F
	Occupancy of service	21		Ч				ч.	Þ		Þ	4			4	F		Ч	٩	24	1		1	Ч			Þ	ч	F	>	Þ		D		ግ	Þ		F	>		D	٩		H
ntform	slq gnibsol-bnə\-əbiS	20		S/E											s			s						s			s	s	v.	2	s		s		s	s		v	2		s	C/F	10	s
	Freight car scales	19																																					T	\square		\bot	Ţ	
DIC	- sbos mioq ssivasZ	18		16350			16300	16301	16303	16304	16305	16307	16308	16309	16310	10311	16313	16314	16315	16310				13352	1221	12202	12203	12204	12218	12206	12207	12220	12208	12209	12210	12211	12212	12210	12217	12214	12215	13220	10701	13001
he service point	Manner of securing t	17	-	2	-	-		∞	4		∞	4			4	-	-	4	~	n	-			-			∞	4	ç	1	~		2		2	7	_	¢	4		2	4	-	3
noitslu	ຊອາ ວເປີຄານ 10 າອການຄັ້	16	station distance	station distance	station distance	station distance	station distance	station distance	station distance station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	- (Štitar)	station distance			station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance
V-G	acceptance of the longest trains	15						and 2	and 3		and 3	and 3			and 3	and 2		and 4			nction 3		Ī				2	4	6	1	~		8		m			~	,	+	3	4		3
B→A Direction	train length Tracks for	14						614 1	497 2		542 2	614 2			853 2	0 1/25	+	618 3			i line ju		Požega				412	714	586	8	625		602		693	80		647	Ē	+	657	738	ĉ	605
	longest trains Maximum permitted			d 3				and 2 (-	$\left \right $	~	~				-		and 4 (- Oper		evo - Po						+	+					+					+		+	+	
Direction A→B	Tracks for Tracks for	1	_	2 and				-	2 and 3	\vdash	2 and	1 2 and			2 and 3	bas C	1	m			(Platičevo) - Open line junction 1 - Open line junction		Stalać - Kraljevo -	4				4	6		~		3			۳ ۵	_	~		_	3	4		
	Maximum permitted train length	12		467				614	497		542	614			853	123		618			n line ji			582			412	714	586		625		602		693	680		647	5		657	738	-	605
permitted peed	Left track	Ξ		9	R		70.7801							60 (80)						50	- Ope	50	213			30 (50)										25 (40)								
mumixeM	Right track	10					20	2						8							čevo)					8										52								
Å	Railway line categor	9	ã	ñ	4 2	S ۲	D3	B3	A	A	¥ <	K N	D3	D3	¥,	4		D3	۵	48	Plati	ß		Ę	3 8	8	ΰ	ខ	87 87	B	B2	B 2	B 2	B 2	B	B	B 2	29 28	ä	B2	B2	E E	4 4	D 4
	onil yewlien to szelO	∞	2	2	4 0	4 ~	¥	2	× ~	2	24 P	4 🗠	×	ч	2	4 0	4 🗠	×	22 P	4 2	212	R		f	* *	"	2	2	* *	: ~	2	×	¥	¥	2	2	2	≤ ₽	4 ~	4	ъ	~ P	4 🗠	R
əni	Single/double-track l	٢	s	s	0 0	n v	s	s	n v	s	s o	n v	s	s	s	0 0	n v	s	s o	n v		s			n v	s	s	s	n v	s s	s	s	s	s	s	s	s	n v	n v	s	s	s s	n v	s
:	Type of service point	9	0	-	y	0	3	c) r	n	m	~		e	3	(n -	- ~	1	~ v	• "		9 9		(n m	n m		(n -	• ~		m	-	3	-		~ °	n -	- ~	n w		~ -	12	1
	Name of service point				03+095 SABAU (end km) 04-219 ADENT TNE TITNETION 3	1+394 OPEN LINE JUNCTION 2 1+394 OPEN LINE JUNCTION 3	000 MAJUR	725 ŠTITAR	14+300 DUBLJE MACVANSKO 22+031 PETLOVAČA	25+800 RIBARI	28+713 PRNjAVOR MACVANSKI	000 LEŠNICA	900 JADARSKA STRAŽA	45+400 LIPNICA	51+396 LOZNICA	33+400 LUZNICA FABRUNA 56±192 VOVIT : AČA	61+700 GORNIA KOVILIAČA	65+354 BRASINA	67+800 DONJA BORINA 69-665 ODENT DIE JEDICTION DONIA DODINA	2021 OFEN LINE JUNCTION DUNJA BURLINA 2001 STATE BORDER		0+000 OPEN LINE JUNCTION 1 0+675 OPEN LINE JUNCTION 3	-	0+374 STALAČ	1+400 GRAD STALAC 3+887 MRZENICA	8+970 MAKREŠANE	11+923 DEDINA	14+559 KRUSEVAC	19+400 CIILUK 21+384 KOŠEVI	25+308 GLOBODER	017 STOPANjA	700 DONJA POČEKOVINA	547 POČEKOVINA	38+949 TRSTENIČKI ODŽACI			238 LIPOVA	258 I DIMINAU 551 PODI INAVCI	59+938 VRANEŠI	225 VRBA	381 RATINA	908 SIRCA 501 EE AL (EVO	JUNCTION POINT 73 KRALJEVO	78+637 ADRANI
	ogeniedO				012-0																																						72+538	
	Distance in km		0,579	0,763	0,980	0,682	2,606	3,725	c/c,0 7.731	3,769	2,913	1,700	3,900	6,500	5,996	2,004	5.517	3,654	2,446	*0,800	2005	0.675			2.487	5,083	2,953	2,636	4,841	3,924	3,709	4,683	1,847	3,402	3,506	6,745	4,038	2,400	2.287	2,287	3,656	3,027	0.917	6,099
transport transport transport	Right track Left track	1 2	03.06.	1934.							15.05.	1950.					_		15.05.	00 03 1978					15 05	1909.							-		01.12	1958.					_			_
To ated	,																			ľ																								



	sbutitlA	30		212,4	228,7		228,4	127 2	c'1c7	250,3	291,6	006 0	4.0.74										70,9		85,1		0.00	0,68				83,0				76,2		123,1	175 3	129.2		105,3		
	ogueg gaibeo.L	29	ZS-I	1-C/2	ŻS-I	ŽS-I	ŽS-I	<u>Ťc 1</u>	I-SZ	ŽS-I	ZS-I	ZS-I ŽS-I	ŻS-I	ŽS-I	ŽS-I	ZS-I		ŽS-I	3	ŤC T	1-07		ŽS-I	I-SZ	ŽS-I	ŽS-I	I-SZ	1-62				,	I-SZ	1-07	ŽS-I	ŽS-I	ŽS-I	ŽS-I	I-SZ	ŽS-I	ŽS-I	ŽS-I	ŽS-I	ZS-1
[Mab] anil adt	←	28		•	~		4	v	h	٢	0	4	,			S	F	\top	-	H	1				8		-	4		+			r	-		10		2	+	10	H	10	+	-
Ruling resistance of	\rightarrow	27		•	8		4	v	n	7	6	v	n l			5									14		r	-					•	-	~) 1		10	:	3		2		
gradient	sqolS	26	•	7	~		4	~	+	-	7	-	•			-		\perp							7		-	4					4	•	•	~		2	c			2	\downarrow	
guiluA	anilonl	25		•	4,6 7	1 1	4			5,7 6	8	3				S	-	+	_		-		0		12			•		_		2	•	7,0	6	0		0,0 10	10		0,0	8,5 2	+	
[%] u	Gradient of the statio	24					6,6		0,1/	Ś	, M	33	ŝ.										0,0					5				0,7				0,0			4.0	. 0				
sn	dominim Minimum curve radi	23	002	000	600		900	2005										_		L			185		250		150	450					020	ncc		300		800				400		
	dispatching of passer operations	52	ᆔ	24 P	-	4	<u>е</u> ,	4	1	P/F	<u>م</u> 1	P P	- 	4		ΡF							P/F	٩	ΡF		<u>م</u>	L.L.				Ρ/F	A	i e	4	. A.	, _P	P/F	<u>م</u> م	4	4	ΡF	<u>م</u> ہ	ч,
	Occupancy of service Open for the accepta	1	-		Þ	$\left \right $	D	6	<u> </u>	Þ	D	-	+	-		4	₽ŀ	+	-	\vdash	+		A.		Ρ		F	2	D	+		д,	-	1	+	D	+	Ъ	=	5	Б	4	+	_
	slq gnibsol-bns/-sbi2	+	+	0	s	+	s	0	+	s	-		+			s	TRAFFIC	+	-	\mathbb{H}	+						0	-	-	+	- 1	s	-	-	+	-	+	-	╧	-	H	$\overline{+}$	+	-
	Freight car scales	$ \rightarrow $	+		-			200	2	\square		-				Yes	FOR T	+	-	\square	+									+				+		+	+		+	+	+	+	+	_
ວາດ	- shos mioq ssivis2		13002	13004	13005	13014	13006			13007	13008	13013	13015	13011		U	OSED FO	T	(0		1		13670	13602	13603		13604	10051				13551	14551	14606	14502	14503	14504	14505	14506	14508	14509	14510	14511	14522
he service point	Manner of securing t	17	,	n	~		2	~	n	m	m	~	,		1	-	티	+	gačev		-		e		1		-	-		1			•	n	9	» »	,	8	-	4	2	~	+	_
noitslu	ຊອາ ວເປີຣາປ ໃດ າອດແຣM	16	station distance	station distance	station distance	station distance	station distance		2	station distance station distance	- junction point No 54 - (Dragačevo)		Krena	PHONE	station distance	station distance station distance	station distance	station distance	station distance	station distance			nac)		station distance	station distance	station distance	station distance	station distance	station distance	station distance station distance	station distance	station distance	station distance	station distance	station distance								
	acceptance of the longest trains	15	,	n	3		and 3	~	7	~	2	~	,			-	on point	+	- junctio		D4		3		3			4 0 luka			- (Vražogrnac)	4		7				2	۰ د	1 61		e	-	_
B→A Direction	train length Tracks for	14	20	000	605		602 2	077	2	615	527	618	2			-	72 - junction	+	t No 53	\vdash	Radina		458	+	743		6	Smederevo luka		+	1:	333	5	1	-	-		540	533	676	$\left \right $	604	+	_
	longest trains Maximum permitted		-				3	•	•	ľ	0		, 					+	 junction point No 	+	- ENEL		4	_	1					_	- Bor - open line junction2	•	-	-		-	+	Ś	-		H		+	
a⇔A	acceptance of the	13	•	n	~		2 and	ç	N	m	2	~					point No		nction		al noi		m		3		-	Jezav			ine ju	4	•	7				2	6	10		m		
Direction	train length Tracks for		_	•	2	+	_	-	+	2	2	-	, ,	-		-	junction p	+			- 10		~	+	1		-	ction	\vdash	+	pen l	9		_	+	+		0	~	0	Η	4	+	-
	Maximum permitted		ŝ	000	605		602	077	ò	615	62	619	5				- junc		(Uzić		, line		458		711		009	le iun			3or - c	62	542	7				540	533	676		604		
pəəds	Left track	Ξ			80							100	2				(Mataruška Banja)		of the station Požega: (Uzići)	50	One			2			20	217 Open line function Jezava			sna - I		40						60 (80)	2				
mumixeM bettimped	Right track	10			8							1	1				iška B		on Po	S S	Prevo	CICNO		^				17 0		•	218 Mala Krsna		4						907	3				
ĥ	Railway line categor	0	42	3 2	5 4	D4	42	42	5 2	D 4	4	2 2	5	4	D 4	4	lataru	Ű	e stati	2	Smed		4	<u>5</u> 2	D4	8	ខ	- ``		5 A	8 Ma		Z Z	5 2	B	B2	D3	<u>B</u>	ñ	ñ	ñ	<u>B</u>	ñ	D3
	Olass of railway line	\vdash	+	2 P	4 🕰	2	24	× 0	4 64	2	2	24 P	4 24	24	ы			2			216 216		R	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	R R	ы	<u>م</u> ا	¥	-	~ ~	2		24 F	4 0	4 🗠	- er	: 24	2	2 2	4 24	2	2	2	Я
əui	l asra-slduob/slgni2	2	s s	n v	n so	s	s	s u	n v	s	s	s v	n s	s	s	s	ralje	Ś	track	5	2		s	s s	s	s	s o	2		s s			s s	<u>n</u> u	n v	s s	s s	s	s s	n v	s	s	s s	s
	Type of service point	9	~ •	- 6	Ξ	~	,	m -	- ~	-	2	m -		3	12		tion K	12	scting	12	2			~ v	1	12	m -	_	9	9 -			m •	- ~	n m			1	~ ~	10	10	,	ۍ ر	3
																	214 Connecting track of the station Kraljevo:		215 Connecting track												-													_
	Name of service point		C C	ALLA MAT	NCI	ći	AĆE	GA V	SANI	VOR	R BANjA	4 DO A ČEVO	Li	ČKO	136+034 JUNCTION POINT 54 POŽEGA		214 Connecting	0+444 JUNCTION POINT /2 KKALJEVO 0+000 JUNCTION POINT 73 KRALJEVO	A DESTRUCTION OF THE ADDRESS OF THE	0+000 JUNCTION POINT 54 POŽEGA	LION PULNEDS PUZEUA	-0+870 BEGINNING OF THE LINE	EREVO	1+749 OPEN LINE JUNCTION JEZAVA 3+250 GODOMIN	NAC	9+124 JUNCTION POINT 64 RADINAC	000	I KKSNA	0+000 OPEN LINE JUNCTION JEZAVA	2+484 OPEN LINE JUNCTION JUGOPETROL 4+011 SMEDEREVO LUKA		KRSNA	LjUBICEVSKI MOST	NEVAC VIČEVO	90+000 SOPOT POŽAREVAČKI	ŠINAC/BRATINAC	100+800 BARE/KASIDOL		OVAC	NE	EVA BARA	OVO/KLENJE	APIC	ENOVAC
	ogeniedO	4		88+610 GORIČANI	92+260 MRŠINCI	94+500 KUKIĆI	96+303 ZABLAĆE	99+000 BALUGA	110+200 TRBUŠANI	112+994 PRUEVOR	120+494 OVCAR BANJA	127+200 JELEN DO 128+366 DP ACAČEVO	129+900 GUGAL	133+700 BORAČKO	136+034 JUNC	136+107 POZEGA	VIAA H DAT	0+000 JUNC		0+000 JUNC	ONIOL 201+0	-0+870 BFGD	-0+057 SMEDEREVO	1+749 OPEN 3+250 GODO	6+711 RADINAC	9+124 JUNC	9+466 VRANOVO	10+8/2 MALA	0+000 OPEN	2+484 OPEN 4+011 SMED		71+272 MALA KRSNA	82+200 LjUBICEVSK	80+100 FUCAKEVAC 80+100 TTC-0VTCFVO	0000 001+68	95+632 BUBU	100+800 BARE	102+727 STIG	106+350 MAJILOVAC 100+055 SIR AKOVO	116+414 LjUBINjE	122+272 ČEŠLjEVA BARA	126+038 RABR	131+800 MUSTAPIC	133+900 MISLJ
	Distance in km	~	2,891	4 160	3,650	2,240	1,803	2,097	4.659	2,794	7,500	6,706	1.534	3,800	2,334	0,073		*0.444	1.1.1	150	257,0	\mid	0,813	*1,832	3,461	2,413	0,342	1,400		2,484			10,928	1 337	0.990	5,542	5,168	1,927	3,623	7.359	5,858	3,766	5,762	2,100
public transport	Left track	2							+		-			<u>~</u>		_	╞		-	001.	+	╞						-	-					+						<u>.</u>				
Date of handover to	Right track	-		20.00	1955.					28.11.			28.11	1976.						25.09. 2001.				10 11	1888							01 12	1920							12.03.	1939.			



		9briti A	30	127,0	153,0	154,1			0010	210,0		289,2	376.0	1010		474,5			518,3		4261	1071	364,6	356,4	278,7	152,1					286,6		443	F	2747	1,510				245,7		216,2			188,5				
		ogueg gaibeo.L	50	ZS-I	I-SZ	ŽS-I	ŽS-I	ZS-I	1-S-1	I-SZ	ŽS-I	ZS-I	ZS-I	I-SZ	ŽS-I	ŽS-I	ŽS-I	I-SZ	I-SZ	1-57	1-52	ŻS-I	ŽS-I	ŽS-I	ZS-I	I-SZ	ŽS-I	ZS-I		ŽS-I	ZS-I	ZS-I	1-22	1-07 20 1	1-07	102	1-52	I-SZ	ŽS-I	ŽS-I	ŽS-I	ZS-I	ZS-I	ZS-I	ZS-1	1-02	1-54		
		←		_				_				1				1		\rightarrow	_		4	2			10	11		-			,				÷	3			-		$\left \right $		_	-	+	-	-	-	
		\rightarrow	27	0	11	3		~	•	ע		9	15	3		16		1	15		1			3	,	• •	1	ı.			13		1	2	Y	h						1		(m				
		sqolS	26	7	2	-		•	-	-		•		+				_			14		13	11	2	99	0	°			_		_	+	=	:				10		0	_	Ľ	•	\downarrow	_		
				_					۲ د	> >		,0			-			_	4								0	•				_			v 0	2 2	+		+				_			+	+	_	
	[%] u	Gradient of the statio						-													ſ	1																	╞				_			\downarrow	_	-	
	sn			45(40(30(100			30	35(30(35(35(25(250	6)õ					25(24(5	150	2				25(25(_	- 104	_	_	_	
1 1	nce and 1gers/freight	dispatching of passer		م م	P/F	Ρ	Ч	<u>е</u> , с	4	P	Ч	P/F	A, A		Ч	P/F	d	<u>а</u>	<u>م</u> ہ	- , c	л <u>а</u>	- A	Р	P/F	d 2	P/F			P/F	Р	Ρ/F	а, с	L A	-	7	1/1	đ	4	, _P	d,	Ч	Ч	<u>е</u> , і	d L	1/d	4	۹	•	
(1) (2) </td <td></td> <td></td> <td>+ +</td> <td>Þ</td> <td>H</td> <td></td> <td></td> <td></td> <td>+</td> <td>+</td> <td>+</td> <td>_</td> <td>-</td> <td>+</td> <td></td> <td></td> <td></td> <td></td> <td>Þ</td> <td></td> <td>Þ</td> <td></td> <td>U</td> <td></td> <td></td> <td>+</td> <td></td> <td></td> <td>\vdash</td> <td></td> <td>H</td> <td></td> <td>+</td> <td>+</td> <td>ρ</td> <td>•</td> <td></td> <td>Þ</td> <td>)</td> <td></td> <td>+</td> <td>Þ</td> <td>_</td> <td>-</td> <td>-</td> <td>_</td> <td>_</td> <td>_</td>			+ +	Þ	H				+	+	+	_	-	+					Þ		Þ		U			+			\vdash		H		+	+	ρ	•		Þ)		+	Þ	_	-	-	_	_	_	
1 1	ntform		+		ŝ				ũ	0		s	U	2		s		_	_		<i>S</i>	2		s	č	n v			s		s		<i>v</i>	2	U	2			_	s		S	_	_	2	+	+	_	
1 1		Freight car scales	5	~	0 +	5		~ ~	200				_		_	+	~	~		~ ~	0		0	5	+			-		~	_	~	+		0		~			H		-	+			+		_	
1 1	OIC	- əboə mioq əəivrəS	18	1451	14514	14515	1451	1452	14510	14520	14521	1440	1441(14403	14411	14404	14408	1441	1440	1440	14400	14413	14350	1430	1430	14302			12550	1400	1400	1400	1400	14006	14003		14008	14000	14010	14011	14012	1401	1401	1401	1401(1401	14010		
1 1	he service point	t gninose to rannaM	17		_	7			•	-		1	-	•	\vdash	1		-	-		-	•	1	4					-		8		+	•	•	•	+	~	,		$\left \right $		-	-	-	+	_	_	
1 1	noitslu	ฐศ วทีโธน ใง างกกรM	16	station distance br>station distance		station distance		station distance	etation distance	Oldiaceas and the																																							
1 1 1 2		longest trains		_						+		4	~	, _		3		_	_		_	-	3	3	,	n m			_		3		+	+	c	4	+	~		\parallel	\square	8	_		~	+	+	_	
10 10<	v⊷a	acceptance of the	15	2	2	2			•			3 and				and					-	•		2 and	7	2 and		vo Por	m		2 and		~		Per l			and		2		2 and			and				
101 101 <td></td> <td>train length</td> <td></td> <td>2</td> <td>36</td> <td>00</td> <td></td> <td></td> <td>Ş</td> <td>2</td> <td></td> <td>81</td> <td></td> <td>+</td> <td>t</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>99</td> <td></td> <td></td> <td></td> <td>+</td> <td>+</td> <td></td> <td>Prahov</td> <td>62</td> <td></td> <td><u>4</u></td> <td></td> <td>02</td> <td>2</td> <td>5</td> <td></td> <td></td> <td>+</td> <td></td> <td>83</td> <td></td> <td></td> <td>-</td> <td></td> <td>-</td> <td>+</td> <td>+</td> <td>-</td>		train length		2	36	00			Ş	2		81		+	t						99				+	+		Prahov	62		<u>4</u>		02	2	5			+		83			-		-	+	+	-	
Induction Induction <t< td=""><td></td><td></td><td></td><td>ŝ</td><td>9</td><td>2</td><td></td><td>_</td><td>ų</td><td>ĥ</td><td></td><td>9 4</td><td>4</td><td></td><td>-</td><td>5</td><td></td><td>_</td><td>_</td><td></td><td>ÿ</td><td></td><td>8</td><td>2</td><td>-</td><td></td><td></td><td>1</td><td>10</td><td></td><td>4</td><td>_</td><td>4</td><td>-</td><td>4</td><td>F a</td><td>+</td><td>+</td><td>-</td><td>ŝ</td><td>\square</td><td></td><td>_</td><td>+</td><td>+</td><td>+</td><td>+</td><td>_</td></t<>				ŝ	9	2		_	ų	ĥ		9 4	4		-	5		_	_		ÿ		8	2	-			1	10		4	_	4	-	4	F a	+	+	-	ŝ	\square		_	+	+	+	+	_	
Image: constraint of the sector of	g←V	acceptance of the	13	5	2	2			ç	n			pue			and					-	•	and 3	and	~	and		- Zaie	m				~		Pure	alla		and		5		and		ŀ	and				
1 1				0	9	0		-		4	$\left \right $		+	+	\vdash		_	+	+	-	9	_			-	-		i krst	6			-	-	+	-		+	+	-	~	$\left \right $		-	+	-	+	+	-	
Image: marker in an operator in a sector of the s				52	63	70			22			88	Ey	3		53					99	8	65	58	43	2018		Crven	68		6		47	F	10	P		51	1	62	Ц	61			8				
Inductor no		Left track	Ξ					0												9	2							1		2				2					0		×				(ac	(nc)			
Image: manual constraints Im		Right track	9					Ś													T							219 (0				ø					0			'			ç	07			
Induction in human constraints And the form of service point And the form of service point And the form of service point 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 100000 10000 100000 100000 100000 1000000 1000000 1000000 1000000000000000000000000000000000000	Â	Railway line categor	0	ñ	A A	Α	A	٩	A 4	K N	A	Y	88	88	ΰ	Ű	C	8	80	3	38	88	C3	S	80	38	ΰ	8		B 2	B2	B2	2 2	i i	20	18	12	12	B2	B 2	B 2	B2	B 2	B	<u>8</u> 6	žβ	18	1	
Image: Instruction Image:		Olass of railway line	∞	<u>م</u>	4 24	Я	2	<u>م</u>	¥ 0	4 24	2	ъ	24 P	: ~	2	ч	Я	<u>م</u>	22 P	× 6	× ~	: 2	R	ч	22 F	4 24	2	24		ч	2	24 F	4 🗠	4 0	4 0	4 🗠	; ≃	4 ~	: 24	: ~	2	2	2	2	<u>ب</u> ا	z P	4 🗠	1	
All and over to bubble bubble All and over to bubble All and over to bubble 2 3 3 4 2 3 4 5 2 3 4 5 3 106-607 2/UD 4/05 146-607 2/UD 5 15:05. 3 146-607 2/UD 4/05 146-607 2/UD 5 15:06. 4/05 146-607 2/UD 4/05 146-607 2/UD 5 146-607 15:06. 3/06 148+58 KLOEVA 5 3/00 146-607 2/UD 5 146-607 15:06. 3/06 148+58 KLOEVA 5 3/00 146-607 1/00 10:08 108-607 108-607 1/00 1/00 1/00 1/00 10:08 108-607 108-607 1/00 1/00 1/00 1/00 10:01 02-900 109-607 1/00 1/00 1/00 1/00 1/00 1/00 10:01 02-900 108-600 1/00 1/00 1/00<	əui	Single/double-track	2	ŝ	n so	s	s	ŝ	n u	n so	s	s	s v	2 00	s	s	s	s	s s	n o	n v	2 v	s	s	s s	n so	s	s		s	s	s s	0 00	2 0	0 0	2 0	2 00	2 00	s s	s	s	s	s	s i	s s	<u>n</u> 0	2 00	,	
Imandovertion Imandovertion Imandovertion 1 2 3 4 5 1 1 2 3 4 5 5 3 4 5 5 3 4 5 5 5 3 4 5 5 5 5 3 3 4 5 5 5 5 5 3 3 4 5 5 5 5 3 3 4 5 5 5 5 3 3 4 5 5 5 5 5 3 3 6 7 7 2 5 5 3 3 6 7 7 2 5 3 3 6 7 7 2 2 1	;	Type of service point	0	- ,	n	-	m	~ ~	n -	- ~	m		m c	1 m	m	-	3	~	2	n r	n -	• ~	1	-	~ •		9	9	-	m		m r	n c	م ا	n -	- 0	· ~		۰ ۳	0	m		ŝ	ر س	- •	n r	n «	,	
Панабочет ю палабочет ю Палабочет ю галари палек Палабочет ю галари 15:05: 2 2.167 1 2 2 3.382 3.4568 15:05: 3.206 3.3206 3.3206 10:00: 3.382 3.882 3.4568 10:00: 3.3206 3.3206 3.3206 10:00: 3.3206 3.3206 3.3206 10:00: 2.2900 3.3201 3.3206 10:01: 2.2900 3.3201 3.3206 10:01: 2.2900 3.3201 3.3206 10:02: 2.2900 3.3201 3.3206 10:02: 2.2900 3.3201 3.3201 10:02: 2.3000 3.3201 3.301 10:02: 2.3000 3.301 3.301 10:02: 2.3000 3.3201 3.301 10:02: 2.3000 3.301 3.301 10:02: 2.3000 3.301 3.301 10:02: 2.3000 3.301 3.301<		Name of service point	5	2 A TTUTT A 2	NA LUNDA		CA	CA		DVAC	EV KAMEN	PEK	ng D		SELO		VE	KA	1000	SKI MUST	SKL POLOK VIVEL i	цу. К		ETNA	SLATINA		VE JUNCTION 3	VE JUNCTION 2	KRST	8	VAC	VREZINA	NI VI		0	16 SC	202	A	II MILiKOVAC			AC	ZUNIČE	UNICE	0	A KEKA 700	UN NIC A	LOUI CONTRACTOR	
Панабочет ю палабочет ю Палабочет ю галари палек Палабочет ю галари 15:05: 2 2.167 1 2 2 3.382 3.4568 15:05: 3.206 3.3206 3.3206 10:00: 3.382 3.882 3.4568 10:00: 3.3206 3.3206 3.3206 10:00: 3.3206 3.3206 3.3206 10:00: 2.2900 3.3201 3.3206 10:01: 2.2900 3.3201 3.3206 10:01: 2.2900 3.3201 3.3206 10:02: 2.2900 3.3201 3.3206 10:02: 2.2900 3.3201 3.3201 10:02: 2.3000 3.3201 3.301 10:02: 2.3000 3.301 3.301 10:02: 2.3000 3.3201 3.301 10:02: 2.3000 3.301 3.301 10:02: 2.3000 3.301 3.301 10:02: 2.3000 3.301 3.301<				UZD Z	ONA	ČEVO	RESNI	RESNI	LUJA	SILIKO	AGOJE	INAUL	BELIL	SIKOV	AOLE	AOLE	RNJAN	SULAJ.	ROVO			EZONI	R	R TER	RSKA	OTINA	ENLEN	ENLIN	VENIK	NTELE	TEJEV	KNJA	AMAD	La Vitre	DI IC	104540	FVAC		RLIŠK	DVIS	OŠTE	JAŽEV	RNJE 2	NJE ZU	NICEV	TITZU	ATAR		
Панабочет ю палабочет ю Палабочет ю галари палек Палабочет ю галари 15:05: 2 2.167 1 2 2 3.382 3.4568 15:05: 3.206 3.3206 3.3206 10:00: 3.382 3.882 3.4568 10:00: 3.3206 3.3206 3.3206 10:00: 3.3206 3.3206 3.3206 10:00: 2.2900 3.3201 3.3206 10:01: 2.2900 3.3201 3.3206 10:01: 2.2900 3.3201 3.3206 10:02: 2.2900 3.3201 3.3206 10:02: 2.2900 3.3201 3.3201 10:02: 2.3000 3.3201 3.301 10:02: 2.3000 3.301 3.301 10:02: 2.3000 3.3201 3.301 10:02: 2.3000 3.301 3.301 10:02: 2.3000 3.301 3.301 10:02: 2.3000 3.301 3.301<					10 KA	2 KU	10 NE	2 NE			40 BL.	52 MA	1 E	1 I AS	10 VL	37 VL	000		CE CE	N KK	0 MA	10 BR	11 BO	50 BO	2 BO	9 RG	12 OP.	15 OP	77 CR	33 PA	32 MA	3	1 CR		HI O	N N N	NO	DAT C	12 SVI	78 PO.	41 RG	SS KN	<u>5 GO</u>			THE NEW		1	
100 10 10 10 10 10 10 10 10 10 10 10 10		Chainage	4	136+00	144+54	148+58	153+61	156+45)/+6CI	166+80	170+74	178+85	181+8(191+80	194+70	197+18	200+20	202+30	205+61	18+/07	211+80	217+50	221+40	224+35	231+05	244+69	249+03	250+04	56+0	7+45	12+38	20+64	50-05	37.60	10-07	45+01	46+01	40+33	51+69	60+8)	62+74	68+30	72+1(75+01	81+9(00100	0+90	1111	
131 132 130 <th 130<="" td="" th<=""><td></td><td>Distance in km</td><td>~</td><td>2,167</td><td>3,896</td><td>4,036</td><td>5,034</td><td>2,876</td><td>5,208</td><td>3,218</td><td>3,940</td><td>8,112</td><td>2,948</td><td>4.126</td><td>2,900</td><td>2,487</td><td>3,013</td><td>2,100</td><td>3,373</td><td>2,12/</td><td>3 400</td><td>2,300</td><td>3,901</td><td>2,949</td><td>6,742</td><td>6,618</td><td>4,333</td><td>1,013</td><td></td><td>6,536</td><td>*4,977</td><td>8,263</td><td>2 804</td><td>2 2.42</td><td>7.418</td><td>5 808</td><td>0.004</td><td>3 322</td><td>2.360</td><td>9,186</td><td>1,863</td><td>5,624</td><td>3,740</td><td>2,908</td><td>6,894</td><td>*2 921</td><td>7 868</td><td></td></th>	<td></td> <td>Distance in km</td> <td>~</td> <td>2,167</td> <td>3,896</td> <td>4,036</td> <td>5,034</td> <td>2,876</td> <td>5,208</td> <td>3,218</td> <td>3,940</td> <td>8,112</td> <td>2,948</td> <td>4.126</td> <td>2,900</td> <td>2,487</td> <td>3,013</td> <td>2,100</td> <td>3,373</td> <td>2,12/</td> <td>3 400</td> <td>2,300</td> <td>3,901</td> <td>2,949</td> <td>6,742</td> <td>6,618</td> <td>4,333</td> <td>1,013</td> <td></td> <td>6,536</td> <td>*4,977</td> <td>8,263</td> <td>2 804</td> <td>2 2.42</td> <td>7.418</td> <td>5 808</td> <td>0.004</td> <td>3 322</td> <td>2.360</td> <td>9,186</td> <td>1,863</td> <td>5,624</td> <td>3,740</td> <td>2,908</td> <td>6,894</td> <td>*2 921</td> <td>7 868</td> <td></td>		Distance in km	~	2,167	3,896	4,036	5,034	2,876	5,208	3,218	3,940	8,112	2,948	4.126	2,900	2,487	3,013	2,100	3,373	2,12/	3 400	2,300	3,901	2,949	6,742	6,618	4,333	1,013		6,536	*4,977	8,263	2 804	2 2.42	7.418	5 808	0.004	3 322	2.360	9,186	1,863	5,624	3,740	2,908	6,894	*2 921	7 868	
10 12 10 12 10 13 10 <th10< th=""> 10 10 10<!--</td--><td>oilduq</td><td>Left track</td><td>2</td><td></td><td></td><td></td><td></td><td>Si s</td><td>- No</td><td></td><td>8 %</td><td>į</td><td></td><td>1</td><td>1</td><td><u> </u></td><td>4 7</td><td>2</td><td></td><td></td><td></td><td>1</td><td></td><td>.1967.</td><td></td><td>si b</td><td>8 8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>12.</td><td>ri Ri</td><td>1</td><td>1</td><td>1</td><td></td><td></td><td>+</td><td></td><td>14.</td><td></td><td>+</td><td></td><td>-</td></th10<>	oilduq	Left track	2					Si s	- No		8 %	į		1	1	<u> </u>	4 7	2				1		.1967.		si b	8 8								12.	ri Ri	1	1	1			+		14.		+		-	
	Date of Date of	Right track						5 <u>1</u> 5	5		10, 10	•					8	19						29.11	ei ŝ		(j)								15.	19								19					



	əbuitlA	30	148	1	128	116,1	T	115	1		84,4	66.6			56,9	56,7		30.1	40.3	55,4			T			353,3				194			212,3				T	241		255	248.8	0,012	067
	əgusg gaibso.l	50	I-S	жс-1 7с т	I-SZ	ŽS-I	I-S	ŽS-I	I-SZ	ŽS-I	1-S2		ŽS-I	ŽS-I	ŽS-I	I-S	I-SZ	1-07	1-SZ	I-S	ŽS-I	ZS-I		ŽS-I	ŀ	ŽS-I	ŻS-I	ŢS-1		Ťe T	5 5	ŽS-I	ŽS-I	ŽS-I	ŽS-I	ZS-I	1-52 Že 1	I-SZ	ŽS-I	I-S	1-52	1-07	7
[Vab] suil str	←	28	7	₹ *C	-	8		1	_	$\left \right $	2	9	+		4	-		4	-	-	18		_	5 Ž	+	, Z		1	-	, 			8			CN PC		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	PLN				-
Ruling resistance of	\rightarrow	-	S		2	0		ç	_		7		\vdash			6	+	-	• 00	<u>ہ</u>	+			1	F	0	1	~	- 1	+	+		∞				+	~			•	N	
gradient	aqolS	26	2		9	~		1		•	×	4			3	•		4	- ~		17			m		0		10	2	٢	0	• •	0	0	0	- 4	^ <	0	0	0	0		>
guiluA	ənilən		_		-	8		10			-	•				~	_	-		2				•		~		, ,	_	•	• ~	0	9	Ś	4	%	^ •			9		0 0 0	-
	Gradient of the statio	· · ·	0,0		0'0			3.0			1,0	0.0				0,0			0.0											0,71			5,8					0		0,0	60		2,0
sn	т Міпітит сигуе гаді		240		300	250		250	007		007	250			250	250		250	250	250	250			_		_				305	600	300	600	600	300	450	1000	300	300	1000	350	0026	NCC
nce and Igers/freight	Open for the accepta dispatching of passer operations	3	Ρ/F	f	P/F	P/F		0	4	<u>а</u> 1	, 0	P/F	Ч	Ч	Р	<u>م</u>	4	đ	P/F	P/F	P/F									<u>م</u> م	- A	, _Р	Ч	Ч	Ч	<u>م</u> م		P/F	Ч	P/F	4		4
	Occupancy of service	+ +	-		4	P -1		F	-			4				Þ	_		٩	-	\vdash			\square	;	Þ		ÞÞ		A			Þ		_			F		Þ	F	+ +	C
ntform	slq gnibsol-bnə/-əbiS		S		s	S						s			s	S	_	v	2 V	2 V	S	_				s	_	S		S			S					S		S	v	2 0	2
	Freight car scales	12	_	-				-			+ 1/	~ ~		~	~		_	2 00		- 10		_	-	\vdash	┝	~	+	~		_			~		+	~ "		+ 50			~ ~		_
	- sbos tniog soivis		14021	1400	14060	+		14101	+		14104	+	+	14108		-	14111	14113	-	-	14170					11113		11113		11001	11121	11102		11129	11104	11119	11104	+	11130	_	11108		11110
he service point	J gninose fo renneM	1	0		4	∞		-	∞	8	~	~	-		8	∞	+	~	2	00	m	_	9	0	Ì	0 0	+	9	<u>}</u>	-	+	+	~		-	+	+	4		10	~	<u>, ;</u>	10
noitslu	ຊອາ ວມີໂຮນ ໃ ດ າອດຕະM	16	station distance	станични	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	- (1 mavac)	station distance		station distance		station distance		station distance	station distance		station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance
	longest trains		đ3		and 2	and 3		and 3	3		7.0	and 3			and 2	and 3	+	6	and 3	q 3	d 2	ŧ		Η	mlija		+				+	+	d 2		+	+	+	╈		and 3	~		
B→A	Tracks for acceptance of the	15	2 and		1 an	2 an			7 9II		I and	2 an			1 an	2 an		2 and 3	2 an	2 and	1 and		nctio		Kuršu	2		2	olje	~			1 and 2					~		2 an	000	5	r
Direction	train length Maximum permitted	14	656		828	819		540	1		504	721			511	547		320	283	613	429		line junction "		"1" - Kuršumlija	618		618	- Kosovo Polje	601			564					661		585	480	10/	283
	longest trains		-		-	\vdash		-	+		_	+	+			-	+	+	-	-	\vdash			\square	tion.		-	618 2 61	- Kos	+	+	+			-	+	+			-	+		_
a←A	acceptance of the Tracks for	13	2 and 3		1 and 2	2 and 3		2 and 2			1 and 2	2 and 3			1 and 2	2 and 3		2 and 3	2 and 3	2 and	1 and 2		- Open		e junc	2		2 2	astrat	4			1 and 2					m		2 and 3	bue C	2 0110 2	n
Direction	train length		+		-	$\left \right $		540	+		504	+				+	+	320		-	\vdash			\square	n lin	8	-,	ansur 8	Doljevac - Kastrat	00	+		564		+		+	-		_	+	++	285
	Maximum permitted		656		828	819		Ŷ	5		ž	721			511	547		8	1 50	613	4				do -	618		618 618	oljeva	90			Š					661		585	480	ŕ	ň
permitted peed	Гей ияск	Ξ	100	60(80)	60 (70)		65								40							-	- Open line junction	9	rlovo	20		50	223 D(20								
mumixeM	Right track	9		00	09		0								4									4	221 (Barlovo) - open line junction	0		6	2						0								
Â	Railway line categor	6	B2	B2	B2 B2	ΰ	80	8	38	8	3	3 8	ΰ	<u>8</u>	C	8	80	3 8	3 8	30	ΰ	ິ	gotina)	ΰ	2	A	A	4	:	ģ		BI	B1	B1	B1	B1	2 2		A	A ·	A A	A A	r,
	Olass of railway line	~	2	a, p	4 24	2	<u>م</u>	× 0	4 🖂	2	× 0	4 🗠	2	×	Я	~	<u>م</u>	4 🗠	4 🗠	: 24	2		720 (Kg	R	F	¥	¥	~		ρ	4 🗠	4 24	¥	2	ч	24 P	× P	4 🗠	ы	2	× ¤	4 22 0	4
əui	l astrack l	2	s,	- 0	n so	s	ŝ	s u	n v	s	n u	n v	s	s	s	s	s s	n v	n v	n v	s	s	3	s	f	s	1	v	,	v	2 00	s S	s	s	s	s s	n u	2 00	s	s	n u	າ່ວາມ	2
1	Type of service point	0	(<i>0</i> °	n	-	v v	• -	- ~	~ ·	- ~		m	m	10		~ r	<u>م</u>	- 1	•	-	1	9	0		- 0	1	- 9	,	- ~	n m	n m		m	e	ŝ	n r		m	~	- n	- ~ ~	8
	point																											RAT															
	Name of service point		GRLJAN	100+900 KM 100+900 115	10/+500 11MOK 111+606 ZAJEČAR	2	121+000 OPEN LINE JUNCTION 2	121+900 OPEN LINE JUNCTION 1 124-631 TENAVAC	ČOKONJAR	SOKOLOVICA	130+190 1ABAKOVAC 138+764 TABAKOVAČYA PEVA	BRUSNIK	TAMNIČ	151+330 CRNOMASNICA	RAJAC	156+828 ROGLJEVO	VELJKOVO	103+000 MUNAUNA 167+850 KOBIŠNICA	174+128 NEGOTIN	PRAHOVO	PRAHOVO PRISTANIŠTE	185+079 END OF LINE	OPEN LINE JUNCTION 3	0+439 OPEN LINE JUNCTION 1		53+534 OPEN LINE JUNCTION 1 55+894 KURŠUMLIJA	END OF LINE	0+000 KURŠUMLJIA 2+320 ODEN I INF TI INCTION K A STRAT		0+247 DOLjEVAC 3+300 č 4 mvovac	TOPLIČKI BADNIFVAC	JASENICA	10+096 ŽITORAĐA	11+000 ŽITORAĐA CENTAR	REČICA	14+700 LUKOMIR	10+225 PUDINA 10+200 B A BINI DOTOV	PROKUPLiE	GORNJA DRAGANJA	31+734 TOPLIČKA MALA PLANA	34+500 BKESNICICI 37±844 BFI OI iN	5/〒011 DELOLJEN 40+700 TOPLICA MILAN 40-718 DI OグMIV	LUCINIA
	Spainage	4							128+533	131+387										182+015	184+578		000+0		100.00						4+800	6+597	10+096										
	Distance in km	m	*7,052	3,860	4,306	7,228	2,16	0,900	3,902	*2,871	4,809 7 568	6.892	2,804	2,870	2,136	3,362	3,364	4 242	6 2.78	7,88	2,563	0,501		0,439		2,560	0,46	2 320		2 052	150	1,797	3,499	0,904	1,700	2,00	2C'T	3.527	2,687	6,720	2,700	2,856	210,2
public transport	Азыт Пэ.	\square									14.											╡		\dashv	╞		-						لــا ع	s S S S S S S S S S S S S S S S S S S S	j			1	2			12 6	_
Date of Dandover to	Right track	-									1914.																						20	1025					04 17	1929		04.12. 1929.	
																												1											-		_		



		S Altitude	313.6	0 [°] CTC		T		201.4	581,4	430,4	200.0	2,000					84,2	84,9	84,5	02 7	89.2	89,5	88,2					113,2	109,2	110,3		75,9	1				83,1	70.5	<i>د. 1</i> / 81.5	81
		S Loading gauge	ŽC.I	I-SZ	ZS-I	ŢS-1	ŽS-I	ZS-I že I	I-SZ	ŽS-I	ZS-1 Žc 1	ŢS-I	ŽS-I	ZS-I				ŽS-I	ŽS-I	7c 1	I-c7	ŽS-I	ŽS-I						ŽS-I	ZS-I		,	ZS-I		Ť¢.	1-07	3	ŽS-I	I-SZ	ŽS-I
		³⁸ →				'				÷		•	•					2	2	•	~		-										•		~			_		•
	guiluA		+		00	-	0	00			-	+							-	_	-	$\left \right $	-									\vdash	_			+			+	0
	Ruling		+	+ +	+	+	\vdash	+						_						_	_											\vdash	_			+		_	+	-
	[%] u	2 Gradient of the statio	000	2 ⁴													0,0																							0,0
1 1 2 3 3 4 1	sn		Ş	8 8	<u>8</u>	38	8	<u></u>	88	8	<u></u>	9 8	8	8					S S	2 3	2 3	45	2		Z				30									45	18	60
1 1 2 2 3 3 4 2 3 3 4 2 3		nsear to guidotequib	6	4	<u>م</u>		ď	- , -	<u>ч</u> ч	<u>е</u> , е	а, р	4	Ч										P/F		ITATIO			P/F				Ľ,	ULC L	2			P/F	P	L/C	
1 1 2 3 3 4 1			+	>	:	Þ		-	-	+	11						\vdash	U	D	C	U		_		XPLO				U			н	LR AF				\vdash	-	+	D
1 1 2 2 3 3 4 2 3 3 4 2 3	ntorm		+		_			Ŭ	2	S	_		$\left \right $	_			S		+	+	+				OFE			S/I		_			FOR 7		-	-	S	-	2 00	s
1 1 2 2 3 3 4 2 3 3 4 2 3			-	11126	11112		11122	11125	11127	11116	11123	11120	11118				23306	24202	24203	24205	24206	24207	<u> </u>		INE OUT			23450	24313				CLOSED	CTOOTD			23001	23002	23004	23005
1 1	he service point	ti gainer of securing ti	╀	++	+	0 0		+			_	_						2	-	_	2		-		/AY L			_				10	10 1			-	\vdash			
1 1	noitslu	ஜு அரசு 01 மரி ஜ	etation distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	station distance	a)**)	SERVICE		station distance	station distance	station distance	station distance	station distance	station distance		RAILW				station distance	station distance DR TRAFFIC	- (Kać)		station distance	3" - (Podbara)	etation distance	SIGILOID CUSICING	,	station distance	station distance	station distance
Image Name of service point 1 0 <td></td> <td></td> <td>, ,</td> <td>4</td> <td></td> <td></td> <td></td> <td>,</td> <td>7</td> <td>nd 3</td> <td>,</td> <td>1</td> <td>Ħ</td> <td></td> <td>Drenic</td> <td>RAIN</td> <td>nd 4</td> <td>nd 3</td> <td>nd 3</td> <td>C 101</td> <td>nd 3</td> <td>2</td> <td>nd 3</td> <td></td> <td></td> <td></td> <td></td> <td>nd 3</td> <td></td> <td>SED F</td> <td>ion "2"</td> <td>nd 2</td> <td></td> <td>iction "</td> <td></td> <td></td> <td>nd 3</td> <td>0</td> <td>nd 2 nd 3</td> <td>2 and 3</td>			, ,	4				,	7	nd 3	,	1	Ħ		Drenic	RAIN	nd 4	nd 3	nd 3	C 101	nd 3	2	nd 3					nd 3		SED F	ion "2"	nd 2		iction "			nd 3	0	nd 2 nd 3	2 and 3
Image Name of service point 1 0 <td>B→A Direction</td> <td>Tracks for</td> <td></td> <td></td> <td>_</td> <td>_</td> <td></td> <td>_</td> <td></td> <td></td> <td>~</td> <td></td> <td>\square</td> <td></td> <td>ec -</td> <td>DEDT</td> <td>\vdash</td> <td></td> <td></td> <td></td> <td>+</td> <td></td> <td>2</td> <td>ika</td> <td></td> <td></td> <td>ic.</td> <td></td> <td></td> <td></td> <td>e junct</td> <td>1 1 3</td> <td>-</td> <td>ine jur</td> <td></td> <td>-</td> <td></td> <td></td> <td>-</td> <td></td>	B→A Direction	Tracks for			_	_		_			~		\square		ec -	DEDT	\vdash				+		2	ika			ic.				e junct	1 1 3	-	ine jur		-			-	
Image Name of service point Distance C.C. 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 2064 49-900 2064 49-900 2064 99-900 2064 99-900 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-400 1334 53-400 1305 59-400 1306 59-400 1307 59-400 2195 57-480 5820 50-50-50 1315 54-665 1316 59-400 13205 59-400		Maximum permitted	410	F				22	2	56	ÿ	Ŷ		_	iuncti	SPENI	\vdash		_	ĩ	60			a fabr			-a hole	592		a LINI	en lin	4		open 1		Žaba	255	24	_	278
Image Name of service point Distance C.C. 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 2064 49-900 2064 49-900 2064 99-900 2064 99-900 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-400 1334 53-400 1305 59-400 1306 59-400 1307 59-400 2195 57-480 5820 50-50-50 1315 54-665 1316 59-400 13205 59-400	G V	🗔 acceptance of the	ç	4				•	7	and 3	ç	4			m line	V SU	and 4	and 3	and 3	c pue	and 3	2	and 3	Subotic			Subotio	and 3	and 2	žionic	3" - of	and 2		1.,1" -		nčevi	and 3	C Pro-	and 3	2 and 3
Image Name of service point Distance C.C. 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 2064 49-900 2064 49-900 2064 99-900 2064 99-900 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-400 1334 53-400 1305 59-400 1306 59-400 1307 59-400 2195 57-480 5820 50-50-50 1315 54-665 1316 59-400 13205 59-400		ل train length	410		+			557	/((103	C6+			vo Polje etna - op	ORARII	\vdash			-	+		-12	botica -			hotica -	594 2		vi Sad La	unction,	445 1		e junctio		Rimski ša	558 2		+	278 2
Image Name of service point Distance C.C. 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 2064 49-900 2064 49-900 2064 99-900 2064 99-900 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-400 1334 53-400 1305 59-400 1306 59-400 1307 59-400 2195 57-480 5820 50-50-50 1315 54-665 1316 59-400 13205 59-400						_								-	4 Koso olie Ter	r TEMF	\mid				_			301 Su	6					ON - (2	en line j			pen lin		306]			+	L
Image Name of service point Distance C.C. 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 2064 49-900 2064 49-900 2064 99-900 2064 99-900 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-400 1334 53-400 1305 59-400 1306 59-400 1307 59-400 2195 57-480 5820 50-50-50 1315 54-665 1316 59-400 13205 59-400		ස් track							•					2	22 Dovoso	Sombo				•					1				•	cm 1+04	ara - op	1		čevi) - (1(•		•
Image Name of service point Distance C.C. 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 3293 46-646 2064 49-900 2064 49-900 2064 99-900 2064 99-900 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-430 1334 53-400 1334 53-400 1305 59-400 1306 59-400 1307 59-400 2195 57-480 5820 50-50-50 1315 54-665 1316 59-400 13205 59-400	Å	vo Railway line category	V	4 V	A A	4 Y	Α	A \	A	A	A A	4 V	Ą	Α	225 Ko	Vrbas -		C 2	3	A A	A	A	Α		S	S				A' Sad 0	4 Podba		ຍຮ	ski šan	Ű	3		A A	A	Α
Image Distance Image Distance C Name of service point P. Ppe of service point Distance 3.928 46-646 BARLOVO 0 0 Distance 3.928 46-646 BARLOVO 0 0 0 Distance 3.928 46-646 BARLOVO 0			+	+ +	+	+	\vdash	+	-	+	+	+		-			-	-	-	-	-		2			H			Ч	3 Nov	30		-	S (Rim	-	+		_	+	Γ
Electron Name of service point 5 5 6 338 46-646 BARLOVO 5 398 46-646 BARLOVO 5 398 46-646 BARLOVO 5 398 46-646 BARLOVO 5 2054 49-300 NOVOSELSKE LIVADE 1331 1331 54-880 NOVOSELSKE LIVADE 2,54 2,31 54-880 NOVOSELSKE LIVADE 2,35 1,700 52-910 RUDRA 1,000 2,555 69-880 KOSANCE VAN 3,105 3,105 79-900 VISOKA 2,355 3,105 79-900 VASILJEVAC 2,315 3,105 79-910 NUSTRA 2,315 3,105 79-930 NUSTRA 2,315 3,105 79-930 NUSTRA 2,315 3,105 79-930 NUSTRA 2,316 3,105 73497 2,4971 3,105 79-930 NUSTSRA 2,316 3,105 79-9405 2,916 3,105 7349 2,910 3,105 7349			+		+	_				++	_	_	\vdash	_			Ŀ	s	_	_	o s		S		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	S			s	S 05		Ŀ	_	-		4	\vdash	_	2 00	s
End A Dist Chaines 3 4 3 4 3 4 3 4 3 4 3 4 3 4 3 4 3 3 3 4 3 3 3 3 3 3 3 3 3 3 4 5 1 700 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3 5 3		trior evines to em/T o						-						-			-	-				-	-			\square		-	-			-					-			-
in km in km 3.3288 3.328 3.328 3.328 3.328 3.328 3.328 3.328 3.328 3.328		Name of service point 5		KE LIVADE	C TON 1	JUNCTION KASTRAT				A RAČA	IKANI	IVAN C		CATIVE LINE						ĩ					FABRIKA	巴	ą.		BOLNICA	Æ			JUNCTION 3		JUNCTION 1 IT INCTION 3	C NOTTONOC	NČEVI	AK	CI	
0.0 0.0 <td></td> <td>4 Chainage</td> <td>46+646 BARI OVO</td> <td>49+300 NOVOSELS</td> <td>52+000 PEPELJEVA</td> <td>54+855 OPEN LINE</td> <td>59+100 VISOKA</td> <td>60+800 LjUSA</td> <td>67+325 DEŠIŠKA</td> <td>69+880 KOSANIČK</td> <td>75+805 POSANICA</td> <td>79+000 VASILJEVA</td> <td>83+057 MERDARE</td> <td>84+400 ADMINISTI</td> <td></td> <td></td> <td>37+137 VRBAS</td> <td>47+653 KULA</td> <td>54+971 CRVENKA</td> <td>62+0/0 SIVAC</td> <td>75+440 KLiAJIĆEV(</td> <td>79+695 ČONOPLjA</td> <td>89+710 SOMBOR</td> <td></td> <td>3+708 SUBOTICA</td> <td>6+139 END OF LIP</td> <td>permissible speed is 20 km</td> <td>1+255 SUBOTICA</td> <td>3+600 SUBOTICA</td> <td>4+000 END OF LI</td> <td></td> <td>4+413 ПОДБАРА</td> <td>6+582 OPEN LINE 7+650 OPEN I INE</td> <td>DEEN FRA</td> <td>0+000 OPEN LINE</td> <td>01210 OFFIN FUNE</td> <td>10+270 RIMSKI ŠAI</td> <td>16+766 BACKI JAR</td> <td>27+355 GOSPODIN</td> <td>34+016 ŽABALj</td>		4 Chainage	46+646 BARI OVO	49+300 NOVOSELS	52+000 PEPELJEVA	54+855 OPEN LINE	59+100 VISOKA	60+800 LjUSA	67+325 DEŠIŠKA	69+880 KOSANIČK	75+805 POSANICA	79+000 VASILJEVA	83+057 MERDARE	84+400 ADMINISTI			37+137 VRBAS	47+653 KULA	54+971 CRVENKA	62+0/0 SIVAC	75+440 KLiAJIĆEV(79+695 ČONOPLjA	89+710 SOMBOR		3+708 SUBOTICA	6+139 END OF LIP	permissible speed is 20 km	1+255 SUBOTICA	3+600 SUBOTICA	4+000 END OF LI		4+413 ПОДБАРА	6+582 OPEN LINE 7+650 OPEN I INE	DEEN FRA	0+000 OPEN LINE	01210 OFFIN FUNE	10+270 RIMSKI ŠAI	16+766 BACKI JAR	27+355 GOSPODIN	34+016 ŽABALj
		w Distance in km	3 078	2,654	2,700	1.521	4,245	1,700	4.515	2,555	3,820	3,105	4,057	1,343			μ	10,516	7,318	2 004	9.740	4,255	10,015		3.708	2,431	maximun		2,345	0,400			2,169	11/17	0100	0120		0,496	7.621	6,661
101 101 <td>public public</td> <td></td> <td>up to km 002+330</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>01 03 1060</td> <td>-</td> <td></td> <td></td> <td></td> <td>L</td>	public public																										up to km 002+330								01 03 1060	-				L



ns see and thorn thorn thorn thorn	Manner of securing the Service point code - 1 Service point code - 1 Side-/end-loading pla Open for the acceptare operations Operations Oradient of the statio fineline Slope Datalient of the statio fineline Datalient of the statio Datalient of th	19 20 21 22 23 24 25 26 27 28	3 P 0.0	stance 16316 700 2,0 ZS-I 140,1	4 16317 2 13 700 0,0 4 2 5 3 Ž5-1		21001 S P P/F 0.5 77	1 1101 D D D 200	T ZIIVI T T JVV Z/V Z/V <thz th="" v<=""> <thz th="" v<=""> <thz th="" v<=""></thz></thz></thz>		stance 1 0,0 10 10 13 ŽS-I 83.1		1 13404 S P P/F	stance 6 13901 S P F 338 1,9 3 3 4 4 ZS-I 101,7 stance 13007 500 75-I 25-I	13903 500	U 600 0,0 8 0 8 - ŽS-I	6 13905 S T F 600 1,0 7 0 7 -	stance 13906 A 400 ZS-I 25-I 245.9 stance 6 1307 S U 250 10 0 11 - ŽS-I 245.9	13908 400 ZS-I	stance 6 13909 S U 230 0,0 16 0 18 - ŽS-I 271,5	200		7 21009 Yes S/E P P/F 280 2,5 2,0 2,5 2,0 2,5 2,0 2,5 2,0 2,5 2,0 2,5 2,0 2,5 2,0 2,5 2,0 2,0 2,0 2,0 2,0 2,0 2,0 2,0 2,0 2,0	21301 2.15 4 3 6 3 2.5-1 1	21302 948 0,0	9 21303 U	9 21305 S U 300 2 0 5 4 6 4	300 1,5 ŽS-I	7010 JE 26 26 26 20 20 20 20 20 20 20 20 20 20 20 20 20	/ 21009 T65 S/E F P/F 2,3 25-1 101		22850 S P P/F 80 10 - 22851 S P P/F 80			1 16203 S P F	10 16205
	scrisptance of the longest trains Manner of traffic reg	15 16 a - Zvornik Grad		2 and 3 station distance		-	vica 2 and 3	station distance	station distance	22 - junction point 23 - (Orom)	station distance		5	3 station distance station distance	station distance		3 station distance	2 station distance		4 station distance	station distance		4 and 5	station distance station distance	station distance	1 and 2 station distance	and 3 station distance		2 5 4 4	4 and 5	(km 6+413)	2 and 3 station distance	OR TRAFFIC	RAFFIC	3	station distance
speed Direction B→A	Left track Maximum permitted train length acceptance of the longest trains longest trains train length Tracks for	9 10 11 12 13 14 15 Brasina) - ODFN LINE II INCTION Domai Borina - Zuomik Grad		208 2 md 2 308	0/1 0000 7 0/1		309 Pancevo Varos - Pancevo Vojlovica 506 2 and 3 506 2 ar	17A 3 2nd A 17A		Senta: (Coka) - junction point		311 Markovac - Svilajnac - Despotovac - (Resavica)	4	667 3 667			790 3 790	764 2 764		506 4 506	312 Matchiis - Drizran **)	313 Vršac - Bela Crkva	643 4 and 5 643 4 a			753 1 and 2 753	681 2 and 3 681 2 3		- Vršac Vašarište	045 4 and 2 045 4 2	 Metanolsko sir	842 2 and 3 842	103 Bogojevo - Dunavska obala LINE CLOSED FOR TRAFFIC	404 Paraćin - Stari Popovac LINE CLOSED FOR TRAFFIC	402 Surcin - Jakovo Decinen 733 3 733	
əu	Type of service point Single/double-track li Class of railway line Railway line category Railway line category	308/		3 S L A 50	ц		1 309	3 S L D2 1 S T D2 50		310 Connecting track of the station	12 S L A 40	2		1 S L B2 3 S L A	s s	Г	S	3 S L A 1 S L A	Г	ц,	S L A		,	n n	3 S L A 30	L A	2 3 L A	ц	 -	2 S man C2 50	402 Kikinda	1 S man A 40		404 Paračin -		1 S man A 20
	Distance in km Chainage Name of service point	3 4 5	68+685 OPEN LINE JUNCTION DONJA BORINA	1,915	1,846 75+300 ZVORNIK GRAD	$^{\circ}$ up to km 074+000 the maximum permissible speed is 10 km/h	0+568 PANČEVO VAROŠ	0,732 1+300 PANČEVO STRELIŠTE 1 614 2-014 DANČEVO VOTI OVIČA	0,561 3+475 END OF LINE	A TRADE OF TRACK ROUTING TO DE DE	0 757 39+164 JUNCTION POINT 22 SENTA		0+500	9,432 9+932 SVILAJNAC 7 568 17+500 SEDLARE		27+470	34+820	1,580 36+400 VOJNIK 6.164 42+564 DVORIŠTE		7,560 53+360 RESAVICA	0,390 53+/50 END OF LINE			1+118 88+004 OPEN LINE JUNCTION B JASENOVO 8+599 97+263 POTPORANi	102+699		V+134 114+049 4+418 119+067	2+433 121+500	0.55015000	2,857 3+415 VRSAC VAŠARIŠTE		6 285 6+285 MSK (INDUSTRIAL TRACK)			12+100 SURČIN	3,400 15+500 JAKOVO-BEČMEN 1 000 16+500 END OF I NF
Date of handover to public transport	Right track Left track	1 2		15.05. 1950.	1	4) up to km 074		11.11.					01.09.	1951.	29.11.	1951.			1967.					20.07.	1808.		01.11.1856									



	Инфраструктура железнице Србије а.д.
1	

		9 Altitude	30																								
All of the service point		эдияд даірво.І	29							H		╡	+														
Name		←	28								╈	╈	1														
		\rightarrow																									
Image: Control of the control of th		ədolS	26																							rations	
	guiluA	Incline	25												-											ght ope	
	[%] u	Gradient of the statio	24												he line)											for frei	
Bit B	sn	Minimum curve radi	23												e end of t											ngers and	
Bit	gers/freight		22							A. 1	م ہ	,	1		wards the											g of passer	
 			_								_		4)2). ning to											patchin	
με αριθούους το το μοτούρους το το ματούρους												-	+		31, 20(begin			-								und disp	
Image: Second second marked in the second	ttorm	-									+	_	+		May 3 m the	ł										tance a	
μαι		Freight car scales	16							$\left + \right $	+	+	+		dated l 'k (fro	s hords	- 001 m									accept	
Discretion Discretion 1	DIC	l - əboə mioq əəiviəS	18												002 - 153 (he left trac	13 State	T. Jian									pen for the	
α σύσοιο Πρακολομοι 1	he service point	J gninose fo renneM	17							μ	+	+	4		o 300/2(ator to tl											i points o	
Distance Distance Distance Distance Distance Distance 1 <td< td=""><td>notislu</td><td>ຊອາ ວເປີຣານ 1 o າອດຕຣM</td><td>16</td><td>D FOR TRAFFIC</td><td>ric</td><td>FIC</td><td>FFIC</td><td></td><td>ad)</td><td></td><td>station distance</td><td>station distance</td><td>station distance</td><td></td><td>y 31, 2002 (records No right and the denomina</td><td></td><td></td><td>ig point</td><td></td><td>d signals.</td><td>id signats.</td><td></td><td></td><td></td><td>а</td><td>ight), and P/T for service</td><td></td></td<>	notislu	ຊອາ ວເປີຣານ 1 o າອດຕຣM	16	D FOR TRAFFIC	ric	FIC	FFIC		ad)		station distance	station distance	station distance		y 31, 2002 (records No right and the denomina			ig point		d signals.	id signats.				а	ight), and P/T for service	
Description 1 <		longest trains		OSE	CAFF	CAF	IRAI		išegr	\vdash	+	+	+		ed Mar to the			atchir		outs ar	ours au ignals ignals.				atforn	t of fie	
Description Description Description Description Description Description 1 <t< td=""><td>R→A</td><td></td><td>15</td><td>CL</td><td>R TF</td><td>R TI</td><td>OR .</td><td>E</td><td>S-</td><td></td><td></td><td></td><td></td><td>ŀ</td><td>s, date elates</td><td></td><td></td><td>rt disp</td><td></td><td>1 turno</td><td>and si and si</td><td></td><td></td><td></td><td>ling pl</td><td>upmen</td><td></td></t<>	R→A		15	CL	R TF	R TI	OR .	E	S-					ŀ	s, date elates			rt disp		1 turno	and si and si				ling pl	upmen	
Dial of order to biologicar		-	4	ΓN	DFO	DFO	EDF	Y LI	order	\vdash	+	+	+		ailway nator r	a		anspo		etweer	mouts				id-load	transsh	
Distriction Distriction 10 distriction 1 districtin 1 districtin		Maximum permitted	1	(ina)	OSE	OSE	TOS	LWA	ate B						MIK n mune	chang		and the		ance b	een tu een tu s.				and er	ng and	
Image: Second			13	(Bije	ECI	ECI	NE	RAI	a - St						nd UN ly: the	Sheed		Iraffic		enend	e betw e betw e betw signal	ri.			h side	mloadi	
Image of the			-	ler -	E	LIN	ra LI	RIST	Gor						ade ar paratel					tical d	ncau a endanc ndancs ts and	signals			nt wit	ding, u	
Diamo or to phone of restricts point A A A A A 1	noitzeria		12	ate bord	a Skela	Fabrika	Gajdob	I-TOUI	Mokra						IP Belgn track sep					e is techn	e is recun ical depe cal deper n turnout	aphore s	e signals		rvice poi	ions (loa	
Description Description Description Description Description 1		Left track	11	ova - sta	adinsk	Apatin .	anka - (JSEUN	Vitasi -					>	tween Z for each	-	2.			tes. Then	es. Luere e is techni is techni e betwee	s and sen mals.	emaphor		or the ser	ht operat	
Distribution Distribution 1<		Right track	10	ča No	ča - F	nta - /	ca Pal	M	rgan V		ň	2	7	ŀ	aent be ovided	nd eto		stop		nd rout	There There Indano	ia keys ore sig	s and s		d S/E f	points ar freigi	
Distance of the offer in t	A	канмау ние сабедог	6	ca Ra	77 OV	18 So1	Bačk)1 Šai	\vdash		+	+		Agreen are pro	noint a		on and d stop		mals an	routes. routes. routes. ro depe	outs v emaph	umout		rm and	ervice] spen fo	
Date of the off			8	rems	4	4	409		S	\vdash	+	+	+		orary <i>F</i> e data	nding :	9	junctic oint an		uts. sig	urs, sig ls and i s and i ere is n and se	en turn s and s	ween th		platfo	med se oints o	
Image of the second of the	211		~	~						\vdash					Temp ack, th	in rec		an e	5	tumo	, signa signal als. Th	betwe	ce beth nd diff		oading	ily mai rvice p	
Description Description 1 <td></td> <td></td> <td>2</td> <td>106 Š</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>\vdash</td> <td>+</td> <td></td> <td>_</td> <td></td> <td>to the left tr</td> <td>Ē</td> <td>16</td> <td>292</td> <td>for DN</td> <td>ion od</td> <td>non od mouts, nouts, t signa</td> <td>idance veen ti</td> <td>oendan outs ar</td> <td>gnal.</td> <td>n end-l</td> <td>porari for se</td> <td></td>			2	106 Š						\vdash	+		_		to the left tr	Ē	16	292	for DN	ion od	non od mouts, nouts, t signa	idance veen ti	oendan outs ar	gnal.	n end-l	porari for se	
Data dover lo public Name of service point 1 1 2 1 1 2 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 4 1 3 3 1 3 3 1 3 3 1 3 3 1 3 <td< td=""><td>:</td><td>trice points fo by</td><td>9</td><td>4</td><td></td><td></td><td></td><td></td><td></td><td></td><td>- ⁻</td><td></td><td>2</td><td>:</td><td>ording ht and</td><td>5</td><td>i v</td><td>o 1-' 00'</td><td>speed</td><td>ralisat</td><td>n od tu en tun en ligh e betw</td><td>depen ce betv</td><td>cal dep n turn</td><td>nout si</td><td>nt with</td><td>for ten gers, T</td><td></td></td<>	:	trice points fo by	9	4							- ⁻		2	:	ording ht and	5	i v	o 1-' 00'	speed	ralisat	n od tu en tun en ligh e betw	depen ce betv	cal dep n turn	nout si	nt with	for ten gers, T	
Normalize Normalize 1 1 1 2 1 3 1 4 1 2 1 3 1 4 1 3 1 4 1 3 1 4 1 1 1 1 1 1 <		Name of service point	2							ŠARGAN VITASI	JATAKE	MUKKA GUKA etate dodded	SIALE BUKUEK	is is not equal to the difference of their line km positions	l Metohija are temporarily under the supervision of UNMIK, aco ory D4 lines where the ruling line gradient or resistance differ for the rig	Type of service point 1 Gration	1. Station	 assuing pound Stop A Open line junction and train recording point 	d 11- datum referred to in brackets indicate maximum permitted	er of securing the service point 1. Electro-relay signalling-safety devices for comprehensive cent	 Electro-tenty signaling-safety evertes no competentiars can a licetro-tenty signaling safety devices for partial centralisation 3 Electro-tenty signaling safety devices - key dependance betwe licetro-relay signaling safety devices - key dependance betwe 5 Electroneday spatialisa safety devices the si fechnical dependance 5 Electroneday spatialisa safety devices There is fechnical dependance 1 Electroneday spatialisa safety devices the site of the safety 1 Electroneday spatialisa safety devices the site of the safety 1 Electroneday spatialisa safety devices the site of the safety 1 Electroneday spatialisa safety devices the site of the safety 1 Electroneday spatialisa br/>1 Electroneday spatial	6 Electromechanical interlocking block device. There is technical 7. Mechanical signal point machine. There is technical dependance	 Electromechanical permissive block device. There is no techni 9. Ordinary signal point for semaphore signals. 10. Flactrical diffusers. There is no technical demendance hetwase 	11. Access signals. Tumouts are secured by locking devices with	he service point with side-loading platform, E for the service point	P for permanently manued. U for permanently unmanued and T ervice points open for the acceptance and dispatching of passeng	
New York New York Date of 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 <td< td=""><td></td><td>Shainage</td><td>4</td><td></td><td></td><td></td><td></td><td></td><td></td><td>54+706</td><td>52+262</td><td>/0+140</td><td>106+0/</td><td>vice point</td><td>osovo and line categ(k railway l</td><td></td><td></td><td></td><td>mn 10 and</td><td>7- Manne</td><td></td><td></td><td>, _</td><td></td><td>0-S for th</td><td>1 2- P for st</td><td></td></td<>		Shainage	4							54+706	52+262	/0+140	106+0/	vice point	osovo and line categ(k railway l				mn 10 and	7- Manne			, _		0-S for th	1 2- P for st	
1 Right track Date of 1 1 Right track handover to 1 2 2 Left track transport 1 1 1 3 3 1 1 1 3 3 1 1 1 3 3 1 1 1 3 3 1 1 1 3 3													7	the ser	y of Ka ulway le-trach	Col.6		1	Coh	Col.1					Col.2	Col.2 Col.2	
1) Distance in kn 1 Right track Pablic 1 1 Right track Pablic 2 1 1 1		Distance in km	3								7,556	1,884	08,0	n between	the territor * 2025 Ra }, for doubl												
		Left track	2										1	nce m kr	lines on fil May 1 ns 25-28												
	pandover to	Right track	-) Dista	**) The ***) Uni 'n colum												

	Primary train delay causes (IŽS)
No	Name
1.	Waiting for dispatch
2.	Waiting at the automatic block signal or protective signal
3.	Dispatcher's order
4.	Delay caused by the fault of an infrastructure manager's employee
5.	Entrance/exit to a turn
6.	Traffic on the left track
7.	Speed decrease requested by the infrastructure manager
8.	Delivery of order to the train driver
9.	Unplanned line closure by the infrastructure manager
10.	Level-crossing failure
11.	Failure on the overhead contact line
12.	Extended stay of railway vehicles
13.	Delay caused by restricted-speed running
14.	Rail crack
15.	Deformed track
17.	Technically defective switch
18.	Collision, bumping, derailment, avoided collision of railway vehicles
19.	Failure of signalling-interlocking and telecommunication devices
20.	Extension of the foreseen closure (more than 30 min)

Appendix 7. Overview of primary train delay causes

	Primary train delay causes (railway undertaking)
No	Name
1.	Increased passenger frequency
2.	Waiting for railway undertaking staff
3.	Waiting for locomotive or multiple-unit set
4.	Delay caused by the fault of an railway undertaking's employee
5.	Cleaning of wagon or multiple-unit set requested by the railway undertaking
6.	Brake test
7.	Failure of wagon, traction unit or multiple-unit set
8.	Wagon repair without de-coupling
9.	Decreased train speed due to failure of wagon/multiple-unit set/traction unit
10.	Change of composition requested by the railway undertaking
11.	Intervention of police officers, requested by train staff
13.	Waiting for shunting locomotive
15.	Shift change of railway undertaking's employees



16.	Waiting for train forming
17.	Weighing
18.	Special consignment transport
20.	Stopping for cooling of brake shoes
21.	Delay caused by turnover of the multiple-unit set/traction unit of the same composition
22.	Accident on industrial siding of the transport client
23.	Breakdown of brake system air duct
24.	Train passing by the signal which indicates that the further running is forbidden
25.	Unallowed train passing through the service point where it had to stop

	Primary train delay causes (external influences)
No	Name
1.	State needs
2.	Train accepted with delay by another railway management
3.	Train rejected by another railway management
4.	Waiting for train staff of another railway management
5.	Train incorrectly formed by another railway management
6.	Taking a defective wagon of another railway management out of service
7.	Taking an incorrectly sent wagon of another railway management out of service
8.	Another railway management's employee being late
9.	Natural disasters (landslide, flood, current, snow-drift, avalanche, fire, fog)
10.	Falling out of train
11.	Jumping in or out of train
12.	Holding of the train by police officers
13.	Holding of the train by custom-inspection officers
14.	Emergency brake abuse
15.	Emergency service intervention
16.	Level-crossing device breaking
17.	Train rocking
18.	Theft of equipment or devices owned by the infrastructure



	Secondary train delay causes
No	Name
1.	Waiting for crossing
2.	Waiting for overtaking of a train
3.	Waiting for annunciation
4.	Waiting with the train which is in delay
5.	Extended stay in the station due to waiting for regular passing
6.	Waiting for locomotive or multiple-unit set from turnover
7.	Waiting for railway undertaking's staff from turnover
8.	Delay caused by failure of another train's traction unit
9.	Waiting for train connection (passenger or goods) of another railway management
10.	Abuse of emergency brake on another train
11.	Announced strike of IŽS or RU
12.	Another train accident



Appendix 8. Overview of platforms and arranged surfaces in service points

		km position of the		Ι	Dimensions	3
Service point	Location	beginning and the end	Platform/arranged	Length	Height	Width
2000 F		of platform	surface	(m)	(m)	(m)
1	2	3	4	5	6	7
	1	MAIN LINES	II			
	101 Belgrade Center- Star		er - (Tovarnik)			
	next to 3rd track	0+120-0+00-0+300	platform	420,00	0,55	10,00
	between the 4th and 5th track	0+155-0+00-0+300	platform	455,00	0,55	10,00
BELGRADE CENTER	between the 6th and 7th track	0+155-0+00-0+300	platform	455,00	0,55	10,00
DELORADE CENTER	between the 8th and 9th track	0+120-0+00-0+300	platform	420.00	0,55	10,00
	next to 10th track	0+120-0+00-0+300	platform	420,00	0,55	7,00
	next to 1st track	3+204,17 - 3+679,48	platform	475,00	0,55	5,60
	between the 1st and 2nd	3+204,17 - 3+679,48	•	475,00	0,55	3,86
	track*	5+204,17 5+075,40	platform	475,00	0,55	5,00
NOULDEOGDAD	between the 2nd and 3rd track	3+204,17 - 3+679,48	platform	475,00	0,55	10,46
NOVI BEOGRAD	between the 3rd and 4th	3+204,17 - 3+679,48		475,00	0,55	3,86
	track*		platform			
	between the 4th and 5th track	3+204,17 - 3+679,48	platform	475,00	0,55	10,46
	next to 5th track	3+204,17 - 3+679,48	platform	475,00	0,55	5,60
T X' 1	next to right track	5+104,79 - 5+274,76	platform	110,00	0,55	4,00
Tošin bunar	next to left track	5+104,79 - 5+274,76	platform	110,00	0,55	4,00
	between the 1st and 2nd track	8+276-8+676	platform	400,00	0,55	6,16
	between the 3rd and 4th track	8+276 - 8+676	platform	400,00	0,55	6,16
ZEMUN	between the 6th and 7th track	8+321 - 8+676	platform	355,00	0,55	6,16
	between the 8th and 9 th track	8+321 - 8+676	platform	355,00	0,55	6,16
Altina	next to left track	11+256 - 11+366	platform	110.00	0,55	4,00
7 Intillu	next to right track	10+997 - 11+107	platform	110,00	0,55	4,00
ZEMUNSKO POLJE	between the 1st and 2nd track	12+264 -12+374	platform	110,00	0,55	4,00
	between the 2nd and 3rd track	12+154 -12+374	platform	220,00	,	6,16
	between the 3rd and 4th track	12+134 -12+374	platform	110,00	0,00 0,55 0,00 0,55	4,00
	next to left track	12+204=12+374 13+955-14+065	platform	110,00		4,00
Kamendin	next to right track	13+744 - 13+854	platform	110,00	· · · · · ·	4,00
	next to 1st track	18+884 - 19+104	platform	220,00	0,55	4,00
ΒΑΤΑΙΝΙΟΑ	between the 2nd and 3rd track	18+884 - 19+104	platform	220,00	0,55	6,16
BATAJNICA	next to 6th track	18+884 - 19+104	platform	220,00	0,55	7,41
ΝΟΥΑ ΡΑΖΟΥΑ	between the 4th and 5th track	26+993-27+243 l.n.	platform	250,00	0,55	7,91
novinizovi	next to 1st track	35+015-35+235 l.n.	platform	220,00	0,55	3,00
STARA PAZOVA	between the 5th and 6th track	35+015-35+265 l.n.	platform	250,00	0,55	6,16
	between the 2nd and 3rd track	45+767-45+914	platform	147,00	0,35	1,60
GOLUBINCI	between the 3rd and 4th track	45+767-45+914	platform	147,00	0,35	1,60
	between the 2nd and 3rd track	53+611,93-53+691,91	platform	79,98	0,35	1,60
PUTINCI	between the 3rd and 4th track	53+611,93-53+691,91	platform	79,98	0,35	1,60
	next to right track	59+982,18-60+062,18	platform	80,00	0,55	4,00
BATAJNICA NOVA PAZOVA STARA PAZOVA	next to left track	59+985,29-60+065,29	platform	80,00	0,55	4,00
	between the 2nd and 3rd track	<u>59+985,29-60+065,29</u> 64+733-64+973	platform	240,00	0,35	4,00
RIMA	between the 3rd and 4th track	64+733-64+973	platform	240,00	0,35	1,60
NUMA	between the 4th and 5th track	65+821-64+937	platform	116,00	0,35	1,60
	between the 2nd and 3rd track	73+368-73+518	arranged surface	150,00	0,55	2,00
VOGANJ	between the 3rd and 4th track	73+368-73+518	arranged surface	150,00	0,00	2,00
	between the 2nd and 3rd track	81+563-81+763	platform	200,00	0,00	2,00
SREMSKA MITROVICA	between the 3rd and 4th track	81+563-81+763	platform	200,00	0,35	1,60
Laćarak	between the right and left track	86+109,30-86+159,30	platform	50,00	0,35	1,60
	between the 1nght and 1eft track	94+059-94+159	platform	100,00	0,35	1,60
MARTINCI	between the 3rd and 4th track	94+131-94+141	platform	10,00	0,35	1,60
Kuzmin	between the sitt and 4th track	94+131-94+141 NONE		10,00	0,55	1,00
AUZIIIII	between the 2nd and 3rd track	104+935-104+985	platform	50,00	0,45	1,60
KUKUJEVCI-ERDEVIK	between the 3rd and 4th track	104+990-105+040	platform	50,00	0,45	1,60
Bačinci	next to right track	109+070-109+097	platform	27,00	0,43	1,60
Gibarac	next to right track	109+070-109+097 NONE		27,00	0,35	1,00
Jibarac	between the 1st and 2nd track	116+300-116+490	arranged surface	190,00	0,10	2,50
ŠID	between the 2nd and 3rd track	116+300-116+665	platform.	365,00	0,10	2,50
SID			platform	377,00	0,43	1,60
	between the 3rd and 4th track	116+300-116+677	niattorm	3//101		



		km position of the	Platform/arranged		Dimension	
Service point	Location	beginning and the end	surface	Length	Height	Widt
		of platform		(m)	(m)	(m)
1	2	3	4	5	6	7
	next to 3rd track	0+120-0+00-0+300	platform	420,00	0,55	10,0
	between the 4th and 5th track	0+155-0+00-0+300	platform	455,00	0,55	10,0
BELGRADE CENTER	between the 6th and 7th track	0+155-0+00-0+300	platform	455,00	0,55	10,0
	between the 8th and 9th track	0+120-0+00-0+300	platform	420,00	0,55	10,0
	next to 10th track	0+120-0+00-0+300	platform	420,00	0,55	7,00
	next to 2nd track - right	8+460-8+786	platform	326,00	0,55	6,10
RAKOVICA	between the 3rd and 4th track	8+637-8+868	platform	231,00	0,55	6,10
	between the 5th and 6th track	8+545-8+865	platform	320,00	0,55	6,20
Kneževac	next to right track	10+645-10+758	platform	113,00	0,55	1,55
Kilezevae	next to left track	10+645-10+758	platform	113,00	0,55	1,55
Kijevo	next to right track	11+626-11+731	platform	105,00	0,55	1,55
Rijevo	next to left track	11+713-11+819	platform	106,00	0,55	1,55
	next to 1st track	14+080-14+240	arranged surface	160,00		4,00
RESNIK	between the 1st and 2nd track	14+080-14+240	platform	160,00	0,35	1,55
	between the 3rd and 4th track	13+943-14+238	platform	295,00	0,55	6,20
PINOSAVA		NONE				
Ripanj Kolonija	next to railway line - left	20+080-20+180	platform	100,00	0,35	1,00
_	between the 1st and 2nd track	21+324,00-21+356,40	platform	32,40	0,35	1,00
RIPANJ	between the 2nd and 3rd track	21+265,70-21+361,20	platform	95,50	0,35	1,55
	between the 3rd and 4th track	21+265,70-21+361,20	platform	95,50	0,35	1,55
	between the 1st and 2nd track	24+743,40-24+804,00	platform	60,60		1,00
KLENJE	between the 2nd and 3rd track	24+743,40-24+804,00	platform	60,60		1,00
RIPANJ TUNEL	between the 1st and 2nd track	29+565-29+615	platform	,	,	1,60
	between the 1st and 2nd track	34+695-34+774	platform	,		1,60
RALJA	between the 2nd and 3rd track	34+695-34+774	platform	,	,	1,60
SOPOT KOSMAISKI	between the 2nd and 3rd track	41+454-41+544	platform	,		1,60
	between the 2nd and 3rd track	47+684-47+784	platform	,		1,60
	between the 2nd and 3rd track	53+089-53+190	platform		/	1,60
MLADENOVAC	between the 3rd and 4th track		platform	$\begin{array}{c ccccc} 50,00 & 0,40 \\ \hline 79,00 & 0,40 \\ \hline 79,00 & 0,40 \\ \hline 90,00 & 0,40 \\ \hline 100,00 & 0,40 \\ \hline 101,00 & 0,40 \\ \hline 160,00 & 0,40 \\ \hline 155,00 & 0,40 \\ \hline 149,00 & 0,40 \\ \hline 136,00 & 0,40 \\ \hline 153,00 & 0,40 \\ \hline \end{array}$	1,60	
		53+030-53+190		,	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$,
KOVAČEVAC	between the 1st and 2nd track	59+954-60+109	platform	,	,	1,60
D 1	between the 2nd and 3rd track	59+907-60+056	platform			1,60
Rabrovac	next to railway line - left	62+909-63+045	platform		<i>,</i>	1,60
RALJA SOPOT KOSMAJSKI VLAŠKO POLJE MLADENOVAC	between the 1st and 2nd track	67+497-67+650	platform		/	1,60
	between the 2nd and 3rd track	67+453-67+600	platform	147,00	,	1,60
Ratare	next to railway line - left	70+821-70+931	platform	110,00		1,60
GLIBOVAC	between the 1st and 2nd track	73+941-74+041	platform	100,00		1,50
	between the 2nd and 3rd track	73+978-74+078	platform	100,00		1,50
	between the 1st and 2nd track	78+476-78+586	platform	110,00		1,50
PALANKA	between the 2nd and 3rd track	78+476-78+586	platform	110,00		1,50
	between the 3rd and 4th track	78+476-78+586	platform	110,00	0,50	1,50
MALA PLANA	between the 2nd and 3rd track	85+505-85+605	platform	100,00		1,50
	between the 1st and 2nd track	90+350-90+400	platform	50,00		1,60
Kneževac Kijevo RESNIK PINOSAVA Ripanj Kolonija RIPANJ KLENJE RIPANJ TUNEL RALJA SOPOT KOSMAJSKI VLAŠKO POLJE MLADENOVAC KUSADAK Ratare GLIBOVAC PALANKA MALA PLANA VELIKA PLANA Staro Selo Novo Selo MARKOVAC Lapovo Varoš	between the 2nd and 3rd track	90+289-90+430	platform	141,00	0,40	1,60
V BEINA I LANA	between the 3rd and 4th track	90+370-90+510	platform	140,00	0,40	1,60
	between the 4th and 5th track	90+360-90+464	platform	104,00	0,40	1,60
Store Sale	next to right track	94+008-94+055	platform	47,00	0,40	1,60
Staro Selo	next to left track	94+008-94+055	platform	47,00	0,40	1,60
No 0-1.	next to right track	97+660-97+706	platform	46,00	0,40	1,60
novo Selo	next to left track	97+660-97+706	platform	46,00	0,40	1,60
	between the 2nd and 3rd track	100+400-100+450	platform	50,00	0,40	1,60
MARKOVAC	between the 3rd and 4th track	100+350-100+452	platform	102,00	0,40	1,60
	between the 4th and 5th track	100+350-100+448	platform	98,00	0,40	1,60
T T7 V	next to right track	106+250-106+310	platform	60,00	0,35	1,60
Lapovo Varoš	next to left track	106+250-106+310	platform	60,00	0,35	1,60
	next to right track	108+350-108+400	platform	50,00	0,35	1,60
Lapovo Marshalling Yard	next to left track	108+340-108+390	platform	50,00	0,35	1,60
	next to 1st track	109+460-109+510	platform	50,00	0,35	1,60
LAPOVO	between the 2nd and 3rd track	109+560-109+510	platform	120,00	0,35	1,60
LAFUVU			•			
	between the 3rd and 4th track	109+560-109+680	platform	120,00	0,35	1,60
Brzan	next to right track	114+140-114+190	platform	50,00	0,35	1,60
	next to left track next to right track	114+140-114+190	platform	50,00	0,35	1,60
Miloševo		116+940-116+990	platform	50,00	0,35	1,60



C	Location	km position of the	Platform/arranged		1	
Service point	Location	beginning and the end	surface	Length	Height	Widt
1		of platform	1	· · /	· · ·	(m)
1	2	3	4	-	-	7
	next to left track	116+940-116+990	platform	,		1,60
BAGRDAN	between the 2nd and 3rd track	120+229-120+330	platform	,		1,60
	between 3 rd and 4th track	120+268-120+390	platform			1,60
Lanište	next to right track	126+920-126+970	platform			1,60
	next to left track	126+920-126+970	platform	,		1,60
Bukovče	next to right track	131+229-131+279	platform	,		1,60
	next to left track	131+229-131+279	platform			1,60
	between the 1st and 2nd track	135+192-135+342	platform			1,90
JAGODINA	between the 2nd and 3rd track	135+122-135+364	platform			1,90
	between the 3rd and 4th track	135+182-135+416	platform			1,90
Gilje	next to right track	140+550-140+670	platform			3,00
Shje	next to left track	140+550-140+670	platform			3,00
PARAĆIN	between the 3rd and 4th track	155+081-155+184	platform			1,60
TARACIN	between the 4th and 5th track	155+065-155+166	platform			1,90
Sikirica- Ratari	next to right track	163+560-163+610	platform	50,00	0,35	1,60
Sikiiica- Kataii	next to left track	163+565-163+615	platform	50,00	0,35	1,60
Dranavaa	next to right track	166+605-166+655	platform	50,00	0,35	1,60
Dienovac	next to left track	166+605-166+655	platform	50,00	0,35	1,60
ćićev to	between the 2nd and 3rd track	171+550-171+640	platform	90,00	0,35	1,60
CICEVAC	between 3 rd and 4 th track	171+550-171+640	platform	90,00	0,35	1,60
т	next to right track	173+625-173+674	platform	49,00	0,35	1,60
Lučina	next to left track	173+625-173+674	platform			1,60
	between the 2nd and 3rd track	176+222-176+425	platform			6,40
STALAĆ	between the 4th and 5th track	176+222-176+425	platform			1,60
STILLIO	between the 6th and 7th track	176+270-176+378	platform			5,30
STEVANAC	between the out and 7th track	NONE		100,00	0,20	5,50
	between the 2nd and 3rd track	186+443-186+563	platform	120.00	0.35	1,60
BRALJINA	between the 3rd and 4th track	186+443-186+563	platform			1,60
Cerovo-Ražani	next to railway line - left	190+320-190+370	platform			1,60
	between the 1st and 2nd track	192+150-192+220	platform			1,60
STARO IROBAREVO	between the 2nd and 3rd track	192+130-192+220	platform			1,60
ÐUNIS	between the 3rd and 4th track	194+882-195+003	platform			1,60
STEVANAC BRALJINA Cerovo-Ražanj TARO TRUBAREVO ĐUNIS Vitkovac Donji Ljubeš	next to right track	199+160-199+210	platform			1,60
Vitkovac		199+160-199+210				
	next to left track		platform	,		1,60
Donji Ljubeš	next to right track	201+175-201+225	platform	,		1,60
	next to left track	201+175-201+225	platform	,		1,60
Gornji Ljubeš	next to right track	203+560-203+610	platform		· · · · · ·	1,60
5 5	next to left track	203+560-203+610	platform			1,60
BRALJINA Cerovo-Ražanj STARO TRUBAREVO ĐUNIS Vitkovac Donji Ljubeš Gornji Ljubeš KORMAN Trnjani ADROVAC ALEKSINAC Nozrina	between the 2nd and 3rd track	205+565-205+675	platform			1,60
,	between 3 rd and 4 th track	205+545-205+665	platform			1,60
Trniani	next to right track	208+087-208+186	platform			1,60
- mjum	next to left track	208+087-208+186	platform			1,60
	next to 1st track	210+445-210+530	platform	85,00	0,28	5,00
ADROVAC	between the 1st and 2nd track	210+432-210+521	platform	89,00	(m)(m)5650,000,35101,000,35122,000,3550,000,3550,000,3550,000,3550,000,3550,000,3550,000,35150,000,20242,000,20242,000,20120,000,55103,000,3550,000,3550,000,3550,000,3550,000,3550,000,3590,000,3590,000,3590,000,35203,000,28120,000,35120,000,35120,000,35120,000,35120,000,35121,000,3550,00	1,60
	between the 2nd and 3rd track	210+440-210+562	platform			1,60
ALEVSINAC	between the 2nd and 3rd track	214+067-214+277	platform		0,35	1,60
ALENSINAU	between the 3rd and 4th track	214+067-214+277	platform	210,00	0,35	1,60
Norring	next to right track	217+400-217+500	platform	100,00	0,35	1,60
nozrina	next to left track	217+400-217+500	platform	100,00	0,35	1,60
T≚	next to right track	218+705-218+790	platform			1,60
Lužane	next to left track	218+708-218+785	platform			1,60
т	next to right track	222+062-222+164	platform			1,60
Tešica	next to left track	222+062-222+164	platform			1,60
OPELLĂ	between the 2nd and 3rd track	224+656-224+758	platform			1,60
GREJAČ	between the 3rd and 4th track	224+656-224+708	platform			1,60
a v11	next to right track	228+087-228+155	platform			1,60
Supovački Most	next to left track	228+091-228+159	platform			1,60
Supovacki Wost	next to right track	229+306-229+416	platform			1,60
	ment to right them		platform			1,60
Mezgraja	next to left track	779 + 306 - 779 + 416				1.00
	next to left track	229+306-229+416	· · ·			
Mezgraja Vrtište	next to right track	232+544-232+631	platform	87,00	0,35	1,60
			· · ·	87,00	0,35	1,60 1,60 1,60



		km position of the	Platform/arranged surface	Ι	1	
Service point	Location	beginning and the end		Length	Height	Width
		of platform	~	(m)	(m)	(m)
1	2	3	4	5	6	7
CRVENI KRST	between the 2nd and 3rd track	240+842-240+994	platform	152,00	0,40	1,60
	next to 1st track	243+410-243+763	platform	353,00	0,40	5,80
v	between the 2nd and 3rd track	243+410-243+813	platform	403,00	0,40	8,00
NIŠ	between the 4th and 5th track	243+410-243+771	platform	361,00	0,40	8,00
	between 1b. and 1. track	243+643-243+763	platform	120,00	0,40	5,80
	next to 1a. track	243+660-243+763	platform	103,00	0,40	1,60
MEĐUROVO		NONE				
BELOTINCE	between the 1st and 2nd track	253+906-253+987	platform	81,00	0,40	1,60
Čapljinac	next to railway line - left	255+443-255+493	platform	50,00	0,40	1,60
Malošište	next to railway line - left	257+890-257+940	platform	50,00	0,40	1,60
DOLJEVAC	between the 1st and 2nd track	261+419-261+527	platform	108,00	0,40	1,60
202021110	between the 2nd and 3rd track	261+419-261+526	platform	107,00	0,40	1,60
Kočane	next to railway line - right	263+218-263+263	platform	45,00	0,40	1,10
Trobuie	next to railway line - right	263+274-263+287	platform	13,00	0,40	1,10
Pukovac	next to railway line - right	265+833-265+862	platform	29,00	0,40	1,60
	next to railway line - right	265+870-265+897	platform	27,00	0,40	1,60
BRESTOVAC	between the 2nd and 3rd track	267+906-267+971	platform	65,00	0,40	1,60
Lipovica	next to railway line - left	270+819-270+844	platform	25,00	0,40	1,10
-	next to railway line - left	270+850-270+887	platform	37,00	0,40	1,10
PEČENJEVCE	between the 2nd and 3rd track	275+522-275+596	platform	74,00	0,40	1,60
Živkovo	next to railway line - right	278+820-278+865	platform	45,00	0,40	1,10
Priboj Leskovački	next to railway line - right	280+440-280+480	platform	40,00	0,40	1,30
VINARCI		NONE				
LESKOVAC	between the 1st and 2nd track	287+460-287+679	platform	219,00	0,40	1,60
LESKOVAC	between the 2nd and 3rd track	287+507-287+630	platform	123,00	0,40	1,60
ÐORÐEVO		NONE				
	between the 2nd and 3rd track	301+841-301+886	platform	45,00	0,40	1,60
GRDELICA	between the 3rd and 4th track	301+841-301+886	platform	45,00	0,40	1,60
Palojska Rosulja	next to railway line - left	308+614-308+629	platform	15,00	0,40	1,60
PREDEJANE	between the 1st and 2nd track	312+675-312+750	platform	75,00	0,40	1,60
DŽEP	between the 2nd and 3rd track	319+629-319+710	platform	81,00	0,40	1,60
MOMIN KAMEN	next to railway line - left	322+900-322+930	platform	30,00	0,40	1,60
Šelince		NONE				
VLADIČIN HAN	between the 1st and 2nd track	329+472-329+676	platform	204,00	0,40	1,60
SUVA MORAVA	next to 1st track	334+043-334+095	platform	52,00	0,40	1,60
Lepenički most		NONE		,		, i
Stubal		NONE				
PRIBOJ VRANJSKI		NONE				
VRANJSKA BANJA	between the 1st and 2nd track	347+958-348+080	platform	122,00	0,40	1,60
	between the 1st and 2nd track	354+080-354+260	platform	180,00	0,40	1,60
VRANJE	between the 2nd and 3rd track	354+125-354+242	platform	117,00	0,40	1,60
Neradovac		NONE	plationi	117,00	0,10	1,00
	between the 1st and 2nd track	365+666-365+768	platform	102,00	0,40	1,60
RISTOVAC	between the 2nd and 3rd track	365+666-365+768	platform	102,00	0,40	1,60
BUJANOVAC	between the 1st and 2nd track	373+665-373+720	platform	55,00	0,40	1,60
Letovica	between the 1st and 2nd track	NONE	plationi	35,00	0,40	1,00
BUKAREVAC		NONE				
PREŠEVO	between the 1st and 2nd track	392+256-392+357	platform	101,00	0,40	1,60
TRESEVO	103 (Belgrade Center) - Rako			101,00	0,40	1,00
	next to 2nd track - right	8+460-8+786	platform	326,00	0.55	6,10
DAVOVICA				,	0,55	,
RAKOVICA	between the 3rd and 4th track between the 5th and 6th track	8+637-8+868	platform platform	231,00	0,55	6,10
	between the 5th and 6th track	8+545-8+865	platform	320,00	0,55	6,20
JAJINCI	h	NONE		07.00	0.40	1.00
BELO POTOK	between the 2nd and 3rd track	16+240-16+337	platform	97,00	0,40	1,60
	between the 3rd and 4th track	16+240-16+351	platform	111,00	0,40	1,60
Zuce staj.	next to railway line - right	20+305-20+363	platform	58,00	0,40	1,60
ZUCE	between the 1st and 2nd track	21+180-21+287	platform	107,00	0,40	1,60
VRČIN	between the 1st and 2nd track	24+824-24+932	platform	108,00	0,40	1,60
	between the 2nd and 3rd track	24+824-24+934	platform	110,00	0,40	1,60
Kasapovac	next to railway line - left	27+840-27+938	platform	98,00	0,40	1,60
LIPE	between the 1st and 2nd track	31+208-31+316	platform	108,00	0,40	1,60
MALA IVANČA			platform			



Service point	T di	km position of the	Platform/arranged		Dimensions	
Service point	Location	beginning and the end	surface	Length	Height	Widt
1	2	of platform	4	(m) 5	(m)	(m) 7
1	between the 1st and 2nd track	÷	•	62.00	6	
Drestovi	next to railway line - left	36+863-36+925 39+208-39+305	platform	97,00	0,40 0,40	1,60 1,60
			platform	,	,	
MALI POŽAREVAC	between the 1st and 2nd track	41+250-41+356	platform	,		1,60
Drožoni Šonžin	between the 2nd and 3rd track next to railway line - right	<u>41+250-41+358</u> <u>43+114-43+219</u>	platform platform			1,60 1,60
Drazanj-Sepsin	between the 1st and 2nd track	47+730-47+839	platform			1,60
UMČARI	between the 2nd and 3rd track	47+730-47+839	platform			1,60
Živitovoo	next to railway line - left		platform	,	,	1,60
	2	52+290-52+340		,		
	between the 2nd and 3rd track	55+130-55+229	platform			1,6
	between the 1st and 2nd track	60+558-60+656 66+573-66+605	platform platform	,	,	1,60 1,60
Kalja Shledelevska	next to railway line - left		1	,	,	
	between the 1st and 2nd track	69+030-69+175	platform		<i></i>	1,90
MALA KRSNA	between the 2nd and 3rd track	69+030-69+175	platform			1,90
	between the 3rd and 4th track	69+042-69+184	platform			1,9
<u>01 1 1'</u>	between the 4th and 5th track	69+080-69+230	platform		/	1,90
5	next to railway line - left	71+981-72+015	platform		,	1,60
Osipaonica staj.	next to railway line - left	74+749-74+784	platform	,		1,6
OSIPAONICA	between the 1st and 2nd track	76+168-76+231	platform			1,6
	between the 2nd and 3rd track	76+177-76+229	platform	,		1,6
	next to railway line - right	77+867-77+904	platform	37,00	0,40	1,30
		NONE				
	between the 2nd and 3rd track	82+710-82+812	platform		/	1,6
	next to railway line - left	85+500-85+602	platform	2	,	1,6
KRNJEVO-TRNOVCE	between the 2nd and 3rd track	90+248-90+348	platform	100,00	0,40	1,6
VELIKO ORAŠJE	between the plateau in front of the station building and 2 nd track	94+626,50-94+658,50	platform	32,00	0,40	1,6
	between the 2nd and 3rd track	94+586,50-94+689,50	platform	103,00 0,40 50,00 0,40 141,00 0,40	0,40	1,6
VELIKA PLANA	between the 1st and 2nd track	90+350-90+400	platform			1,6
	between the 2nd and 3rd track	90+289-90+430	platform	141,00	0,40	1,6
VELIKA PLANA	between the 3rd and 4th track	90+370-90+510	platform	140,00		1,6
	between the 4th and 5th track	90+360-90+464	platform	104,00	0,40	1,6
	104 (Jagodina) – Open Lin	e Junction Ćuprija – Ćup	rija – Paraćin			
ÓUDDUA	between the 1st and 2nd track	0+516-0+641	platform	125,00	0,20	1,6
CUPRIJA	between the 2nd and 3rd track	0+516-0+641	platform	125,00	0,30	1,6
ΠΑΠΑĆΙΝΙ	between the 3rd and 4th track	155+081-155+184	platform	103,00	0,35	1,6
PARACIN	between the 4th and 5th track	155+065-155+166	platform	101,00	0,20	1,9
10	5 (Belgrade Center) - Stara Pazo					
	next to 1st track	34+015-35+235 л.н.	platform	103,00 0,40 50,00 0,40 141,00 0,40 141,00 0,40 140,00 0,40 104,00 0,40 125,00 0,20 125,00 0,30 103,00 0,35 101,00 0,20 220,00 0,55 250,00 0,55 400,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 137,00 0,55 405,00 0,55 410,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 0,55 220,00 <td>3,0</td>	3,0	
STAKA PAZOVA	between the 5th and 6th track	35+015-35+265 л.н.	platform	250,00	0,55	6,1
	next to 1 st track	42+577 - 42+977	platform			4,1
INĐIJA	between the 4th and 5th track	42+577 - 42+977	platform	400,00	0,55	7,5
Dražanj-Šepšin UMČARI Živkovac VODANJ KOLARI Ralja Smederevska MALA KRSNA Skobalj Osipaonica staj. OSIPAONICA Lugavčina Saraorci OZOVIK-SARAORCI Miloševac KRNJEVO-TRNOVČE VELIKO ORAŠJE VELIKO ORAŠJE	next to 1st track	53+922 - 54+142	platform			4,0
	next to 4 th track	53+922 - 54+142	platform			4,0
Brestovi MALI POŽAREVAC Dražanj-Šepšin UMČARI Živkovac VODANJ KOLARI Ralja Smederevska MALA KRSNA Skobalj Osipaonica staj. OSIPAONICA Lugavčina Saraorci OZOVIK-SARAORCI Miloševac KNJEVO-TRNOVČE VELIKO ORAŠJE VELIKO ORAŠJE VELIKA PLANA VELIKA PLANA CUPRIJA PARAĆIN PARAĆIN 1NĐIJA BEŠKA INĐIJA BEŠKA INĐIJA BEŠKA REMSKI KARLOVCI PETROVARADIN	between the 1st and 2nd track	65+759 - 65+979	platform	,	,	4,0
	between the 1st and 2nd track	65+759 - 65+979	platform			4,0
	between the 1st and 2nd track	70+603 - 70+823	platform			6,1
PETROVARADIN	between the 5^{th} and 6^{th} track	70+708 - 70+928	platform			6,1
	between the 10th and 11th track	77+077-77+214	platform	,		6,1
	between the 7th and 8th track	76+794-76+919	platform	125.00	0.55	
NOVISAD	next to 1st track	76+809-77+214	platform			8,6
	between the 2nd and 3rd track	76+819-77+247	platform	,		8,6
	between the 4th and 5th track	76+837-78+247	platform			8,6
	next to the 6th track	76+892-77+177	platform		, i i i i i i i i i i i i i i i i i i i	6,0
			pianoriii	200,00	0,55	0,0
	, , , , , , , , , , , , , , , , , , ,	NONE	1.0	000.00	0.55	
KISAC	next to the 1st track left	90+222-90+442	platform	,		4,0
	next to the 4th track right	90+222-90+442	platform			4,0
Stepanovićevo	next to the 1st track right	97+227-97+447	platform		0,55	4,0
1 · -	next to the 4th track left	97+227-97+447	platform	220,00	0,55	4,0
	next to the 1st track right	102+481-102+701	platform	220,00	0,55	4,00



Comvise point	Location	km position of the	Platform/arranged		Dimension	
Service point	Location	beginning and the end of platform	surface	Length	Height	Widt
1	2		4	(m) 5	(m) 6	(m) 7
1	next to the 4th track left	102+664-102+884	platform	220,00	0,55	4,00
	next to the 1st track right	113+500-113+720	platform	220,00	0,55	4,00
VRBAS NOVA	between the 1st and 2nd track	113+410-113+810	platform	400,00	0,55	6,60
VKBAS NOVA	between the 5th and 6th track	113+410-113+810	platform	400,00	0,55	6,60
LOVĆENAC – MALI IĐOŠ	next to the 1st track right	129+386-129+606	platform	220,00	0,55	4,00
LOVCENAC – MALI IDOS	next to the 4th track left	129+386-129+606	platform	220,00	0,55	4,00
	next to the 1st track left	143+406-143+806	platform	400,00	0,55	4,00
BAČKA TOPOLA	next to the 4th track right	143+406-143+806	platform	400,00	0,55	4,00
ŽEDNIK	next to the 1st track right	156+965-157+185	platform	220,00	0,55	4,00
ZEDNIK	next to the 4th track left	156+965-157+185	platform	220,00	0,55	4,00
NAUMOVIĆEVO	next to the 1st track left	166+393-166+613	platform	220,00	0,55	4,00
NAUMOVICEVO				,		
	next to the 4th track right	166+393-166+613	platform	220,00	0,55	4,00
	next to the 1st track left	176+606-176+850	platform	244,00	0,55	3,00
Subotica	between the 2nd and 3rd track	176+450-176+850	platform	400,00	0,55	6,10
Subolicu	between the 4th and 5th track	176+550-176+820	platform	270,00	0,55	6,10
	between the 6th and 7th track	176+605-176+826	platform	221,00	0,55	6,10
	106 NIŠ - DIMITROV	GRAD - state border –(D	ragoman)			
	next to 1st track	243+410-243+763	platform	353,00	0,40	5,80
	between the 2nd and 3rd track	243+410-243+813	platform	403,00	0,40	8,00
NIŠ	between the 4th and 5th track	243+410-243+771	platform	361,00	0,40	8,00
	between 1b and 1 st track	243+643-243+763	platform	120,00	0,40	5,80
	next to 1a. track	243+660-243+763	platform	103,00	0,40	1,6
	next to railway line - left	1+669-1+769	platform	100,00	0,40	1,60
Palilulska rampa	next to railway line - left	1+809-1+875	platform	66,00	0,40	1,60
Vojna Bolnica	hext to failway fine - left	NONE		00,00	0,40	1,00
ĆELE KULA	between the 2nd and 3rd track	5+422-5+502	platform	80,00	0.40	1.60
EI NIŠ	between the 2nd and 5rd track			80,00	0,40	1,00
		NONE		100.00	0.40	1 (1
NIŠKA BANJA	between the 2nd and 3rd track	10+450-10+558	platform	108,00	0,40	1,60
Prosek	next to railway line - right	14+712-14+731	platform	19,00	0,40	1,60
	next to railway line - right	14+740-14+770	platform	30,00	0,40	1,60
SIĆEVO		NONE				
OSTROVICA	between the 1st and 2nd track	22+475-22+529	platform	54,00	0,40	1,6
Majdan Ostrovica		NONE	1 1		<u>г</u> т	
Radov Dol	next to railway line - left	29+494-29+520	platform	26,00	0,40	1,6
DOLAC	between the 2nd and 3rd track	31+640-31+739	platform	79,00	0,40	1,6
Crveni Breg	next to railway line - left	34+262-34+292	platform	30,00	0,40	1,60
CRVENA REKA	between the 2nd and 3rd track	36+393-36+451	platform	58,00	0,40	1,6
Belanovac	next to railway line - left	39+691-39+761	platform	70,00	0,40	1,60
BELA PALANKA	between the 2nd and 3rd track	44+907-44+977	platform	70,00	0,40	1,60
Crkvica		NONE	· - · ·			
ČIFLIK		NONE				
Sinjac		NONE				
Đurđevo polje		NONE				
Crvenčevo		NONE				
STANIČENJE		NONE				
Sopot		NONE				
Sopor	between the 1st and 2nd treak			87.00	0.40	1.60
PIROT	between the 1st and 2nd track between the 2nd and 3rd track	72+901-72+989 72+868-73+021	platform platform	87,00 153,00	0,40 0,40	<u>1,60</u> 1.60
D - ¥4	between the 2nd and 5rd track			155,00	0,40	1,0
Božurat		NONE				
Veliki Jovanovac		NONE				
SUKOVO		NONE		6.00	0.40	1 ~
Činiglavci	next to railway line - left	90+465-90+471	platform	6,00	0,40	1,6
	next to railway line - left	90+485-90+491	platform	6,00	0,40	1,6
Srećkovac		NONE	1 1			
DIMITROVGRAD	next to 14th track	97+126-97+267	platform	141,00	0,40	2,5
	between the 1st and 2nd track	97+316-97+717	platform	401,00	0,40	3,2
107	Belgrade Center- Pančevo Mai	<u>n St Vršac - state bo</u> rde	r - (Stamora Morav	rita)		
	next to 3rd track	0+120-0+00-0+300	platform	420,00	0,55	10,0
	between the 4th and 5th track	0+155-0+00-0+300	platform	455,00	0,55	10,0
BELGRADE CENTER	between the 6th and 7th track	0+155-0+00-0+300	platform	455,00	0,55	10,0
	between the 8th and 9th track	0+120-0+00-0+300	platform	420,00	0,55	10,0
	set the out and out the of	2.223 0.00 0.000	F 1991 0 111		-,	- 0,0



		km position of the		г	Dimensions	3
Service point	Location	beginning and the end	Platform/arranged	Length	Height	Width
•		of platform	surface	(m)	(m)	(m)
1	2	3	4	5	6	7
	between the tracks	1+123-1+215	platform	92,00	0.55	7,00
Karađorđev park	(next to left Banat track)	11120 11210	pinnorm	,00	0,00	7,00
•	between the tracks (next to right Banat track)	1+222-1+314	platform	92,00	0,55	7,00
	between the tracks	2+754,13-2+829,13 (chainage along the left) 2+850,52-2+925,52 (chainage along the right)	central platform	75,00	0,95	18,60
	between the tracks (next to right Banat track)	2+785,52-2+850,52	lateral platform towards the Center	65,00	0,95	3,50
Vukov spomenik	between the tracks (next to right Banat track)	2+925,52-3+010,52	lateral platform towards the bridge	85,00	0,95	3,50
	between the tracks (next to left Banat track)	2+689,13-2+754,13	towards the Center	65,00	0,95	3,50
	between the tracks (next to left Banat track)	2+829,13-2+914,13	towards the bridge	85,00	0,95	3,50
	next to 1st track					4,94
PANČEVAČKI MOST	next to 2nd track	4+694-4+845	•	151,00	0,90	4,94
	next to railway line - right	10+500-10+600		100,00	0,35	1,60
Krnjača most	Between the left and right track	7+003,50-7+223,50	platform	220,00	0,60	7,00
KRNJAČA	next to 4th track	8+165,06-8+385,06	platform	220,00	0,55	3,00
	next to 1st track					3,00
Sebeš	next to left Banat track		•			3,10
	next to right Banat track		+	,	,	3,10 4,00
OVČA	next to 1st track between the 4th and 5th track		•			6,10
	between the 1st and 2nd track		+		220,00 0,60 220,00 0,55 220,00 0,55 10,00 0,60 110,00 0,60 120,00 0,55 10,00 0,60 220,00 0,55 220,00 0,55 220,00 0,55 120,00 0,40 297,00 0,40 50,00 0,40 92,00 0,40 240,00 0,40 240,00 0,40	1,60
PANČEVO MAIN	between the 1st and 2nd track			m 75,00 0,95 m 65,00 0,95 m 85,00 0,95 m 85,00 0,95 m 65,00 0,95 m 65,00 0,95 m 85,00 0,95 m 85,00 0,95 151,00 0,90 151,00 0,90 100,00 0,35 220,00 0,55 220,00 0,55 220,00 0,55 110,00 0,60 120,00 0,40 297,00 0,40 297,00 0,40 240,00 0,40 240,00 0,40 240,00 0,40 264,00 0,40 264,00 0,40 264,00 0,40 264,00 0,40 264,00 0,40 264,00 0,40 264,00 0,40 264,00 0,40	1,60	
STATION	between the 2nd and 3rd track	Ine tracks $2+850,52-2+925,52$ (chainage along the right)Central platform towards the CenterBanat track) $2+785,52-2+850,52$ lateral platform towards the Dridgeform towards the Banat track)the tracks Banat track) $2+925,52-3+010,52$ lateral platform towards the Dridgeform towards the Bridgethe tracks Banat track) $2+689,13-2+754,13$ lateral platform towards the Dridgeform towards the Bridgethe tracks Banat track) $2+829,13-2+914,13$ lateral platform towards the Dridgeform towards the Bridgethe tracks Banat track) $2+829,13-2+914,13$ lateral platform towards the Dridgeform towards the Bridgethe track d track $4+694-4+845$ platformform towards the Bridgethe track d that track $4+694-4+845$ platformform towards the Bridgeay line - right10+500-10+600platformformleft and right ck $7+003,50-7+223,50$ platformformtrack $9+975,05-10+085,05$ platformformlst track $9+975,05-10+085,05$ platformformlst track $12+537,60-12+757,60$ platformformlst track $12+537,60-12+757,60$ platformformlst track $12+937,60-12+757,60$ platformforml and 2nd track $15+913-16+210$ platformforml and 3th track $15+913-16+210$ platformforml and 2nd track $15+93-53+603$ a			1,60	
	between the 3rd and 4th track				75,00 0,95 65,00 0,95 85,00 0,95 65,00 0,95 65,00 0,95 65,00 0,95 151,00 0,90 151,00 0,90 151,00 0,90 100,00 0,35 220,00 0,55 220,00 0,55 220,00 0,55 10,00 0,60 110,00 0,60 120,00 0,40 220,00 0,55 120,00 0,40 297,00 0,40 297,00 0,40 240,00 0,40 240,00 0,40 240,00 0,40 240,00 0,40 240,00 0,40 240,00 0,00 100,00 0,00 100,00 0,00 100,00 0,00 100,00 0,35 100,00 0,35 100,00 0,35 100,00 0,35 100,00 <td>1,60</td>	1,60
	next to 1st track		station plateau		00 0,55 00 0,95 00 0,95 00 0,95 00 0,95 00 0,95 00 0,95 00 0,95 00 0,95 00 0,95 00 0,95 00 0,95 00 0,95 00 0,95 00 0,90 ,00 0,90 ,00 0,55 ,00 0,60 ,00 0,40 ,00 0,40 ,00 0,40 ,00 0,40 ,00 0,40 ,00 0,40 ,00 0,40 ,00 0,40 ,00 0,40 ,00 0,40 ,00 0,40 ,00 0,35 ,00 0,35 ,00 0,35 ,00 0,35	1,60
PANČEVO VAROŠ	between the 1st and 2nd track	18+105-18+345	platform	240,00	0,40	1,60
	between the 2nd and 3rd track	18+100-18+364	platform	264,00	0,40	1,60
BANATSKO NOVO SELO	between the 2nd and 3rd track		v			0,50
VLADIMIROVAC	between the 1st and 2nd track					1,30
	between the 2nd and 3rd track		×			1,30
ALIBUNAR	between the 1st and 2nd track between the 2nd and 3rd track		0		,	1,30 1,30
BANATSKI KARLOVAC	between the 2nd and 3rd track	53+505-53+005	arranged surface	100,00	0,00	1,30
Nikolinci		NONE				
ULJMA	between the 2nd and 3rd track					
Vlajkovac			1.0	05.00	0.40	1 20
VRŠAC	between the 1st and 2nd track between the 2nd and 3rd track				,	1,60 1,60
1					5,10	1,00
	next to 1st track	-			0,55	4,00
RESNIK	between the 1st and 2nd track		U	/		1,55
	between the 3rd and 4th track	13+943-14+238	platform		0,55	6,20
BELA REKA	between the 1st and 2nd track					1,60
Nenadovac	next to railway line - left	12+077-12+127	platform			1,60
BARAJEVO	between the 2nd and 3rd track	15+654-15+764	platform			1,60
Barajevo Centar	next to railway line - left	17+895-18+003	platform			1,60
VELIKI BORAK	between the 1st and 2nd track	23+039-23+151	platform	112,00		1,60
Leskovac Kolubarski STEPOJEVAC	next to railway line - right between the 2nd and 3rd track	27+720-27+770 30+572-30+682	platform platform	50,00 110,00	0,35	1,60 1,60
	between the 2nd and 3rd track	37+150-37+300	platform	150,00	0,35	1,60
VREOCI	between the 3rd and 4th track	37+150-37+300	platform	150,00	0,35	1,60
	serveen nie sie und til taek	57 150 57 1500	Platom	150,00	5,55	1,00



		km position of the		Dimensions			
Service point	Location	beginning and the end	Platform/arranged	Length	Height	Width	
-		of platform	surface	(m)	(m)	(m)	
1	2	3	4	5	6	7	
LAZAREVAC	between the 1st and 2nd track	45+311-45+462	platform	151,00	0,35	1,60	
	between the 2nd and 3rd track	45+311-45+462	platform	151,00	0,35	1,60	
LAJKOVAC	between the 1st and 2nd track	52+547-52+697	platform	150,00	0,40	1,60	
Engite the	between the 2nd and 3rd track	52+527-52+697	platform	170,00	0,35	1,60	
SLOVAC	between the 1st and 2nd track	58+899-59+052	platform	153,00	0,35	1,60	
	between the 2nd and 3rd track	58+899-59+052	platform	153,00	0,35	1,60	
Mlađevo	next to railway line - right	63+958-64+035	platform	77,00	0,35	1,60	
DIVCI	between the 1st and 2nd track	67+043-67+213	platform	170,00	0,35	1,60	
	between the 2nd and 3rd track	67+043-67+213	platform	170,00	0,35	1,60	
Lukavac Kolubarski	next to railway line - right	69+165-69+265	platform	100,00	0,35	1,60	
Iverak	next to railway line - right	72+725-72+825	platform	100,00	0,35	1,60	
VALJEVO	next to 1st track	77+550-77+851	platform	301,00	0,35	5,4	
	between the 2nd and 3rd track	77+562-77+863	platform	301,00	0,35	7,55	
VALJEVSKI GRADAC	next to railway line - right	84+560-84+610	platform	50,00	0,35	1,60	
Leskovice	next to railway line - left	91+605-91+655	platform	50,00	0,35	1,60	
LASTRA	between the 2nd and 3rd track	93+985-94+131	platform	146,00	0,35	1,60	
SAMARI	between the 2nd and 3rd track	103+118-103+168	platform	50,00	0,40	1,60	
Drenovački Kik	next to railway line - right	107+700-107+750	platform	50,00	0,40	1,60	
RAŽANA	between the 3rd and 4th track	111+284-111+430	platform	146,00	0,35	1,60	
KOSJERIĆ	between the 3rd and 4th track	118+748-118+948	platform	200,00	0,40	1,60	
	between the 4th and 5th track	118+748-118+948	platform	200,00	0,40	1,60	
Tubići	next to railway line - left	123+446-123+496	platform	50,00	0,35	1,60	
KALENIĆI	between the 3rd and 4th track	129+772-129+918	platform	146,00	0,35	1,60	
Otanj	next to railway line - right	133+600-133+710	platform	110,00	0,40	1,50	
Glumač	next to railway line - right	135+807-135+863	platform	56,00	0,40	1,60	
POŽEGA	next to 1st track	140+720-140+975	platform	255,00	0,45	10,00	
	between the 2nd and 3rd track	146+675-140+984	platform	309,00	0,45	6,20	
Rasna	next to railway line - right	145+618-145+650	platform	32,00	0,40	1,00	
Rasna UZIĆI Zlakusa	between the 1st and 2nd track	149+125-149+255	platform	129,00	0,40	1,60	
	between the 2nd and 3rd track	149+255-149+389	platform	134,00	0,40	1,60	
	next to railway line - right	151+536-151+566	platform	30,00	0,40	1,60	
Bukovička Rampa	next to railway line - right	154+141-154+161	platform	20,00	0,40	1,60	
SEVOJNO	between the 1st and 2nd track	156+882-157+082	platform	200,00	0,40	1,60	
UŽICE FREIGHT STATION	between the 2nd and 3rd track	161+795-161+995	platform	200,00	0,40	1,60	
	between the 1st and 2nd track	161+813-161+953	platform	140,00	0,40	1,60	
UŽICE	next to 1st track	163+645-163+900	platform	255,00	0,40	3,00	
	between the 2nd and 3rd track	163+626-163+881	platform	255,00	0,60	5,10	
STAPARI	between the 1st and 2nd track	170+590-170+710	platform	120,00	0,40	1,60	
Ristanovića Polje	next to railway line - left	173+412-173+425	platform	13	0,40	1,60	
5	next to railway line - right	173+426-173+464	platform	38	0,40	1,60	
Tripkova	next to railway line - right	176+045-176+095	platform	50	0,40	1,60	
SUŠICA	between the 2nd and 3rd track	178+251-178+371	platform	120,00	0,40	1,60	
	next to 1st track	185+181-185+291	platform	110,00	0,40	5,50	
BRANEŠCI	between the 1st and 2nd track	185+181-185+291	platform	110,00	0,40	1,60	
	between the 2nd and 3rd track	185+181-185+291	platform	110,00	0,40	1,60	
ZLATIBOR	between the 2nd and 3rd track	193+234-193+404	platform	170,00	0,40	1,60	
Ribnica Zlatiborska	next to railway line - left	200+350-200+400	platform	50,00	0,40	1,60	
JABLANICA	between the 3rd and 4th track	204-405-204+550	platform	145,00	0,40	1,60	
Goleš	next to railway line - right	211+590-211+616	platform	26,00	0,40	1,00	
ŚTRPCI	between the 2nd and 3rd track	214-755-214-900	platform	145,00	0,40	1,60	
Rača	next to railway line - right	219+515-219+536	platform	21,00	0,40	1,00	
PRIBOJ	between the 2nd and 3rd track	225+227-225+490	platform	263,00	0,50	5,10	
	between the 6th and 7th track	225+137-225+237	platform	100,00	0,50	3,00	
Poljice	next to railway line - right	228+110-228+190	platform	80,00	0,40	1,60	
Pribojska Banja	next to railway line - right	232+867-232+899	platform	32,00	0,40	1,00	
BISTRICA NA LIMU	between the 2nd and 3rd track	241+208-241+352	platform	144,00	0,40	1,60	
Džurovo	next to railway line - right	246+300-246+328	platform	28,00	0,40	1,00	
PRIJEPOLJE	next to 1st track	252+396-252+705	platform	309,00	0,40	4,60	
	between the 2nd and 3rd track	252+396-252+705	platform	309,00	0,40	7,00	
PRIJEPOLJE FREIGHT	between the 2nd and 3rd track	255+789-255+982	platform	187,00	0,35	1,60	
STATION	between the 3rd and 4th track	255+789-255+982	platform	187,00	0,35	1,60	
Velika Župa	next to railway line - right	259+605-259+624	platform	19,00	0,40	1,00	



		km position of the	Platform/arranged		Dimensions	
Service point	Location	beginning and the end	surface	Length	Height	Width
		of platform		(m)	(m)	(m)
1	2	3	4	5	6	7
LUČICE	between the 2nd and 3rd track	264+581-264+714	platform	133,00	0,35	1,60
BRODAREVO	between the 2nd and 3rd track	273+255-273+404	platform	149,00	0,30	1,60
VRBNICA	between the 1st and 2nd track	285+205-285+255	platform	50,00	0,30	1,60
	between the 2nd and 3rd track	285+112-285+256	platform	144,00	0,30	1,60
109 La	<u>povo - Kraljevo - Lešak - Kosovo</u>		ć - state border - (V	olkovo)		
	between the 2nd and 3rd track	109+560-109+680	platform	120,00	0,35	1,60
LAPOVO	between the 3rd and 4th track	109+560-109+680	platform	120,00	0,35	1,60
	next to 1st track	109+460-109+510	platform	50,00	0,35	1,60
BATOČINA	between the 1st and 2nd track	3+374,70-3+421,90	platform	47,20	0,12	1,30
Gradac	left side	8+243,40-8+292,90	platform	49,50	0,30	1,05
BADNJEVAC	between the 2nd and 3rd track	12+264,50-12+311,50	platform	47,00	0,14	1,80
Resnik Kragujevački		NONE				
Milatovac	right side	18+206,90-18+253,70	platform	46,80	0,33	1,10
Cvetojevac	right side	20+381-422,20	platform	41,20	0,25	1,20
JOVANOVAC	between the 2nd and 3rd track	22+308-22+352	platform	44,00	0,22	1,75
	between the 1st and 2nd track	28+726-28+918,70	platform	192,70	0,24	1,20
KRAGUJEVAC	between the 2nd and 3rd track	28+752-28+907	platform	155,00	0,24	1,80
Zavod	right side	31+280,50-31+288,25	platform	7,75	0,10	0,50
GROŠNICA	between the 1st and 2nd track	34+062,80-34+104,30	platform	41,50	0,22	1,50
DRAGOBRAĆA	between the 1st and 2nd track	39+529-39+565	platform	36,00	0,20	1,20
Vučkovica	right side	44+513-44+538	platform	25,00	0,30	1,20
KNIĆ	between the 1st and 2nd track	47+560-47+607	platform	47,00	0,30	1,40
GRUŽA	between the 1st and 2nd track	53+458-53+505,5	platform	47,50	0,22	1,40
GUBEREVAC	between the 1st and 2nd track	60+567-60+614	platform	47,00	0,20	1,55
Tomića Brdo	right side	64+795-64+822,50	platform	27,50	0,35	1,00
VITKOVAC	between the 1st and 2nd track	66+309-66+353	platform	44,00	0,35	1,00
Milavčići	left side	70+141,80-70+172,80	platform	31,00	0,25	1,20
VITANOVAC	between the 1st and 2nd track	73+904,30-73+948,70	platform	44,40	0,33	1,40
Šumarice	left side		platform		0,22	0,50
		79+111-79+128,4	1	17,40		
Sirča	right side	82+006-82+069	platform	63,00	0,35	1,90
KRALJEVO	between the 1st and 2nd track	84+649-84+733	platform	84,00	0,33	1,60
MATARUŠKA BANJA	between the 2nd and 3rd track between the 2nd and 3rd track	84+649-84+748 93+895-93+940	platform	99,00	0,33	1,60
	left side		platform	45,00	0.20	1,80
Progorelica		97+352-97+386	platform	34,00	0,25	1,40
BOGUTOVAČKA BANJA	between the 1st and 2nd track	100+868-100+919	platform	51,00	0,22	1,80
DOBRE STRANE		NONE		52.00	0.00	1.50
POLUMIR	between the 1st and 2nd track	118+291-118+344	platform	53,00	0,26	1,50
Pusto Polje	left side	123+555-123+589	platform	34,00	0,25	1,00
UŠĆE	between the 1st and 2nd track	127+223-127+281	platform	58,00	0,34	1,50
Lozno	right side	132+832-132+866	platform	34,00	0,22	0,50
JOŠANIČKA BANJA	between the 1st and 2nd track	136+102-136+152	platform	50,00	0,25	1,45
Piskanja	left side	138+842-138+884	platform	42,00	0,21	1,00
BRVENIK	between the 1st and 2nd track	143+481-143+528	platform	47,00	0,32	1,50
Rvati	left side	148+258-148+304	platform	46,00	0,22	1,00
RAŠKA	between the 1st and 2nd track	152+236-152+353	platform	117,00	0,32	1,80
Kaznovići	left side	157+700-157+740	platform	40,00	0,23	1,00
RUDNICA	between the 1st and 2nd track	161+970-162+022	platform	48,00	0,25	1,55
Donje Jarinje		NONE			· · · · ·	
Jerina	next to railway line - left	168+865-168+935	arranged surface	70,00	0,20	1,60
LEŠAK	between the 1st and 2nd track	172+294-172+394	platform	100,00	0,35	1,60
LESAK	between the 2nd and 3rd track	172+294-172+394	platform	100,00	0,35	1,60
Dren		NONE				
LEPOSAVIĆ	between the 1st and 2nd track	182+675-182+775	platform	100,00	0,35	1,60
Pridvorica		NONE				
Sočanica	next to railway line - left	190+000-190+040	platform	40,00	0,35	1,00
IBARSKA SLATINA		NONE	-		I	
Plandište		NONE				
BANJSKA		NONE				
Valač	between the 1st and 2nd track	208+170-208+230	arranged surface	60,00	0,35	1,00
ZVEČAN	next to 1st track	210+900-211+000	platform	100,00	0,35	1,60
Kosovska Mitrovica Sever	next to railway line - left	213+390-213+440	platform	50,00	0,35	1,60
		gojevo - state border - (E)		20,00	5,55	1,00



Location		Platform/arranged			Widt
Location		surface	-	Ű	(m)
2	-	4			7
			5	0	,
between the 1st and 2nd track		platform	30.00	0.30	1,55
			,	,	1,5
between the 2nd and 5rd track		plationi	30,00	0,50	1,57
between the 1st and 2nd track		platform	60.00	0.31	1,61
					1,50
				,	1,50
				/	1,61
					1,5
					1,50
		~ ~			1,50
					1,00
					1,90
between the 2nd and 5rd track		plationi	55,00	0,23	1,7
between the 2nd and 3rd track		platform	50.00	0.30	1.80
between the 2nd and 5rd track		plationi	50,00	0,50	1,00
next to railway line - left		platform	41.00	0.25	1,6
					1,0
		ě			1,60
				,	1,00
				,	1,70
					1,70
			200,00	0,00	
	-				
	NONE				
	NONE				
	NONE				
between the 1st and 2nd track	20+510 - 20+768	platform	258,00	0,35	1,90
between the 2nd and 3rd track	20+543-20+722	platform	179,00	0,35	1,90
between the 3rd and 4th track	20+598-20+722	platform	124,00	0,35	1,60
	20+598-20+722	platform	124,00	0,35	1,60
112 Belgrade Mars	shalling Yard "B" - Ostru	ižnica			
	NONE				
		1 TZ/TZ	1// D ''		
de Marshalling Yard,,A" - Open	line junction "B" - Open	line junction "K/K	I" - Kesnik	<u> </u>	
	NONE				
payt to 1st track	14+080-14+240	arran god surfage	160.00	0.55	4,00
					1,55
					6,20
			295,00	0,55	0,20
		anction "ix/ixi j			
ade Marshalling Vard R" - One		n line junction A"	- (Resnik)		
		junction 3/1	(1100000)		
	NONE				
116 (Belgrade Marshalling Yai	rd,,B") - Open line junctio	on "R" - Rakovica			
next to 2nd track - right	8+460-8+786	platform	326,00	0,55	6,10
between the 3rd and 4th track	8+637-8+868	platform	231,00	0,55	6,10
between the 5th and 6th track	8+545-8+865	platform	320,00	0,55	6,20
117 Belgrade Marshalling Yaı	rd"A" - Open line junctio	n "T" - Rakovica			
	NONE				
<u> </u>		ı			
next to 2nd track - right	8+460-8+786	platform	326,00	0,55	6,10
between the 3rd and 4th track	8+637-8+868	platform	231,00	0,55	6,10
			320,00	0,55	6,20
between the 5th and 6th track	8+545-8+865	platform	520,00	0,55	
			520,00	0,55	
between the 5th and 6th track	d,,B" - Open line junction		520,00		
between the 5th and 6th track	d"B" - Open line junction NONE	"T" - (Rakovica)			
	between the 1st and 2nd track between the 2nd and 3rd track between the 3rd and 4th track between the 4th and 5th track 112 Belgrade Mars de Marshalling Yard,,A" - Open next to 1st track between the 1st and 2nd track between the 3rd and 4th track 114 Ostružnica - Open line ju ade Marshalling Yard,,B" - Open 116 (Belgrade Marshalling Yar next to 2nd track - right between the 3rd and 4th track 117 Belgrade Marshalling Yar	2 3 NONE between the 1st and 2nd track 58+619-58+649 between the 1st and 2nd track 73+619-58+649 NONE between the 1st and 2nd track 73+417-73+477 between the 1st and 2nd track 73+584-73+612 between the 1st and 2nd track 73+584-73+612 between the 2nd and 3rd track 73+417-73+477 between the 2nd and 3rd track 73+84-73+612 between the 2nd and 3rd track 73+84-73+612 between the 2nd and 3rd track 73+584-73+612 between the 2nd and 3rd track 73+584-73+612 between the 2nd and 3rd track 73+584-73+701 between the 2nd and 3rd track 83+340-83+397 between the 2nd and 3rd track 105+138-105+193 NONE NONE next to railway line - left 128+229-128+270 between the 1st and 2nd track 176+360-176+414 between the 1st and 2nd track 176+360-176+414 between the 1st and 2nd track 176+360-176+414 between the 1st and 2nd track 176+335-176+838 between the 1st and 2nd track 176+335-176+573 111 Belgrade Marshalling Yard "A" - Ostružnica NONE NONE NONE NONE NONE NONE between the 1st and 2nd track 20+510 - 20+768 between the 1st and 2nd track 20+598 - 20+722 between the 1st and 2nd track 20+598 - 20+722 between the 1st and 2nd track 20+598 - 20+722 between the 3rd and 4th track 20+598 - 20+722 between the 1st and 2nd track 13+943-14+240 NONE	Location beginning and the end of platform Pratformatranged surface 2 3 4 NONE between the 1st and 2nd track 58+619-58+649 platform between the 1st and 2nd track 73+417-73+477 platform between the 1st and 2nd track 73+584-73+612 arranged surface between the 1st and 2nd track 73+617-73+823 arranged surface between the 2nd and 3rd track 73+584-73+701 arranged surface between the 2nd and 3rd track 73+584-73+701 arranged surface between the 2nd and 3rd track 73+548-73+701 arranged surface between the 2nd and 3rd track 105+138-105+193 platform between the 2nd and 3rd track 105+138-105+193 platform between the 1st and 2nd track 176+432-176+838 arranged surface next to railway line - left 128+229-128+270 platform between the 1st and 2nd track 176+432-176+838 arranged surface between the 1st and 2nd track 176+322-176+838 arranged surface between the 1st and 2nd track 128+320-172 p	Location beginning and the end of platform Platform/arranged surface Length (m) 2 3 4 5 between the 1st and 2nd track 58+619-58+649 platform 30,00 between the 1st and 2nd track 73+417-73+477 platform 60,00 between the 1st and 2nd track 73+584-73-612 arranged surface 28,00 between the 1st and 2nd track 73+417-73+477 platform 60,00 between the 1st and 2nd track 73+417-73+477 platform 60,00 between the 2nd and 3rd track 73+417-73+477 platform 60,00 between the 2nd and 3rd track 73+584-73-710 arranged surface 28,00 between the 2nd and 3rd track 105+138-105+193 platform 55,61 between the 2nd and 3rd track 105+138-105+193 platform 55,00 NONE NONE NONE 177,00 between the 1st and 2nd track 176+30-176+414 arranged surface 54,00 between the 1st and 2nd track 176+322-176+838 arranged surface 16,00 between	Location beginning and the end of platform Platform strate Length (m) Height (m) 2 3 4 5 6 between the 1st and 2nd track 58+619-58+649 platform 30,00 0,30 between the 1st and 2nd track 73+458+73+612 arranged surface 28,00 0,05 between the 1st and 2nd track 73+458+73+612 arranged surface 28,00 0,05 between the 1st and 2nd track 73+458+73+612 arranged surface 28,00 0,05 between the 2nd and 3rd track 73+584-73+701 arranged surface 10,00 0,30 between the 2nd and 3rd track 83+340+83+397 platform 56,70 0,30 between the 2nd and 3rd track 105+138-105+193 platform 50,00 0,30 between the 2nd and 3rd track 115+350-115+440 platform 50,00 0,30 between the 2nd and 3rd track 176+467-176+483 arranged surface 51,00 0,25 between the 2nd and 3rd track 176+467-176+483 arranged surface 130,00 0,25 <tr< td=""></tr<>



		km position of the		T	Dimension	<u> </u>
Service point	Location	beginning and the end	Platform/arranged	Length	Height	Width
I I I I I I I I I I I I I I I I I I I		of platform	surface	(m)	(m)	(m)
1	2	3	4	5	6	7
	between the tracks	1+123-1+215	platform	92,00	0,55	7,00
Karađorđev park	(next to left Banat track)	1+123-1+213	plationin	92,00	0,55	7,00
Haradoraev park	between the tracks	1+222-1+314	platform	92,00	0.55	7,00
	(next to right Banat track)		P	,	.,	.,
		nđija - Golubinci	1.40	120.00	0.40	1.60
INÐIJA	between the 1st and 2nd track between the 2nd and 3rd track	<u>42+840-42+970</u> <u>42+783-42+928</u>	platform platform	130,00 145,00	0,40 0,40	1,60 1,60
	between the 2nd and 3rd track	45+767,00-45+914,00	platform	143,00	0,40	1,60
GOLUBINCI	between the 3rd and 4th track	45+767,00-45+914,00	platform	147,00	0,35	1,60
	122 Novi Sad- Novi Sad Mars			147,00	0,55	1,00
	next to 11th track	77+836-77+950	platform	114,00	0,40	3,00
	between the 11th and 10th track	77+822-77+950	platform	128,00	0,40	3,72
	between the 10th and 1st track	77+835-77+887	platform	52,00	0,40	4,20
NOVI SAD	next to 1st track	77+835-78+250	platform	415,00	0,40	4,20-8,90
	between the 2nd and 4th track	77+843-78+181	platform	338,00	0,40	8,75
	between the 12thand 1st track	78+104-78+250	platform	146,00	0,40	8,90
	between the 14 th and 13 th track	78+104-78+249	platform	145,00	0,40	6,46
NOVI SAD		NONE				
MARSHALLING YARD		NONE				
123 by-pass track	of Mala Krsna station: (Kolari) -			lo28 - (Osij	paonica)	
	124 Open line junction Lapovo					T
Lapovo Varoš	next to right track	106+250-106+310	platform	60,00	0,35	1,60
-	next to left track	106+250-106+310	platform	60,00	0,35	1,60
LAPOVO MARSHALLING YARD		NONE				
	between the 2nd and 3rd track	109+560-109+680	platform	120,00	0.35	1,60
LAPOVO	between the 3 rd and 4 th track	109+560-109+680	platform	120,00	0,35	1,60
	next to 1st track	109+460-109+510	platform	50,00	0,35	1,60
	125 Trupale - Niš	Marshalling Yard - Među		·	· · · · · · · · ·	^
TRUPALE	between the 2nd and 3rd track	234+893-234+994	platform	101,00	0,40	1,60
-	between the 4th and 5th track	234+893-234+994	platform	101,00	0,40	1,60
NIŠ MARSHALLING	next to 1a. track	238+216-238+289	platform	73,00	0,40	2,20
YARD						
MEĐUROVO	10(0)	NONE	•			
CDVENI KDCT	between the 2nd and 3rd track	rst - Niš Marshalling yard		152.00	1.00	0.40
CRVENI KRST NIŠ MARSHALLING	next to 1a. track	240+842-240+994 238+216-238+289	platform platform	152,00 73,00	1,60 0,40	0,40 2,20
YARD	next to 1a. track	230+210-230+209	plation	73,00	0,40	2,20
11110	127 Niš - Open line jun	ction Most - (Niš Marshal	ling Yard)		<u> </u>	L
	next to 1st track	243+410-243+763	platform	353,00	0,40	5,80
	between the 2nd and 3rd track	243+410-243+813	platform	403,00	0,40	8,00
NIŠ	between the 4th and 5th track	243+410-243+771	platform	361,00	0,40	8,00
	between the 1b. and 1st track	243+643-243+763	platform	120,00	0,40	5,80
	next to 1a. track	243+660-243+763	platform	103,00	0,40	1,60
128 Connecting t	rack of Niš station: (Crveni Krst)	- separation switch No3	- separation switch	No4 - (Ćel	e Kula)	
	REGIONA	AL RAILWAY LINES				
		orgoš - state border - (Rös				
	between the 1st and 2nd track	176+360-176+414	arranged surface	54,00	0,05	1,70
	between the 1st and 2nd track	176+414-176+487	platform	73,00	0,25	1,60
SUBOTICA	between the 1st and 2nd track	176+487-176+838	arranged surface	351,00	0,05	1,70
	between the 2nd and 3rd track	176+322-176+838	arranged surface	516,00	0,05	1,70
	between the 3rd and 4th track	176+335-176+573	arranged surface	238,00	0,05	1,70
JAVNA SKLADIŠTA	next to railway line - left	2+275-2+385	platform	110,00	0,55	3,00
PALIĆ	next to 2 nd track (right)	7+575-7+685	platform	110,00	0,55	3,00
	next to 4th track	7+575-7+685	platform	110,00	0,55	8,00
Hajdukovo	next to railway line - right	12+002-12+112	platform	110,00	0,55	3,00
BAČKI VINOGRADI	next to 2 nd track (right)	15+360-15+470	platform	110,00	0,55	3,00
HORGOŠ	next to 2 nd track (right)	23+995-24+105	platform	110,00	0,55	4,00
	next to 5th track	23+995-24+105	platform	110,00	0,55	4,00
	202 Pančevo Main St Zrenj			120	0.40	1,60
	botwoon the let and 2-d to-					
PANČEVO MAIN	between the 1st and 2nd track	15+913-16+033	platform platform	120	0,40	,
PANČEVO MAIN STATION	between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track	<u>15+913-16+033</u> <u>16+090-16+210</u> <u>15+913-16+210</u>	platform platform	120 120 297	0,40 0,40 0,40	1,60 1,60



		km position of the		Ι	Dimension	IS			
Service point	Location	beginning and the end	Platform/arranged	Length	Height	Width			
		of platform	surface	(m)	(m)	(m)			
1	2	3	4	5	6	7			
	between the 3rd and 4th track	15+987-16+137	platform	150	0,40	1,60			
JABUKA		NONE							
KAČAREVO	between the 1st and 2nd track	26+784-26+834	platform	50	1,6	0,35			
CREPAJA		NONE							
DEBELJAČA]	NONE							
KOVAČICA	between the 1st and 2nd track		NONE						
UZDIN		NONE				·			
TOMAŠEVAC	between the 1st and 2nd track	61+920-61+970	platform	50	1,6	0,35			
	between the 2nd and 3rd track	61+920-61+970	platform	50	1,6	0,35			
ORLOVAT STAJALIŠTE	between the 1st and 2nd track	64+025-64+075	platform	50	1,6	0,35			
LUKIĆEVO		NONE							
ZRENJANIN FABRIKA		NONE	1			1			
	next to 1st track	88+705-88+776	platform	71	1,3	0,55			
ZRENJANIN	between the 1st and 2nd track		NONE						
	between the 2nd and 3rd track		NONE						
ELEMIR		NONE							
MELENCI	between the 2nd and 3rd track		NONE						
KUMANE		NONE							
NOVI BEČEJ		NONE							
BANATSKO MILOŠEVO		NONE							
POLJE	· · · · · · · · · · · · · · · · · · ·								
	next to 1st track		NONE						
BANATSKO MILOŠEVO	between the 1st and 2nd track								
	between the 2nd and 3rd track		NONE						
Derić		NONE	1.0	126.00	0.10	2 20 4 40			
KIKINDA	next to 1st track	160+030-160+166	platform	136,00	0,19	3,30-4,40			
BANATSKO VELIKO	between the 1st and 2nd track	160+064-160+190	arranged surface	126,00	0,00	1,50			
SELO		NONE							
	⊥ rad (km 7+041) – Belgrade Duna	v Open line junction Par	nčovočki most TB	AFFIC SI	ISDENDI	70			
203 Beigi aue Doliji G	204 Topčider Putnička (km 4+)			AFFIC SU		2D			
		Miloševo - Senta - Subotic							
	next to 1st track	inosevo - Senta - Suborie							
		NONE							
BANATSKO MILOSEVO									
BANATSKO MILOŠEVO	between the 1st and 2nd track		NONE						
	between the 1st and 2nd track between the 2nd and 3rd track		NONE NONE						
Bočar	between the 1st and 2nd track	NONE	NONE						
Bočar Ester	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track	NONE	NONE NONE NONE						
Bočar	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track	NONE	NONE NONE NONE NONE						
Bočar Ester PADEJ	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track	NONE	NONE NONE NONE NONE NONE						
Bočar Ester	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track	NONE	NONE NONE NONE NONE NONE NONE						
Bočar Ester PADEJ Ostojićevo	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track	NONE	NONE NONE NONE NONE NONE NONE NONE						
Bočar Ester PADEJ	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track	NONE	NONE NONE NONE NONE NONE NONE						
Bočar Ester PADEJ Ostojićevo ČOKA	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 3rd and 4th track		NONE NONE NONE NONE NONE NONE NONE NONE	45.00	0.17	1.90			
Bočar Ester PADEJ Ostojićevo ČOKA SENTA	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track	102+905-102+950	NONE NONE NONE NONE NONE NONE NONE NONE	45,00	0,17	1,90			
Bočar Ester PADEJ Ostojićevo ČOKA SENTA Gornji Breg	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 3rd and 4th track	102+905-102+950 NONE	NONE NONE NONE NONE NONE NONE NONE NONE	45,00	0,17	1,90			
Bočar Ester PADEJ Ostojićevo ČOKA SENTA	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 3rd and 4th track	102+905-102+950 NONE NONE	NONE NONE NONE NONE NONE NONE NONE NONE	45,00	0,17	1,90			
Bočar Ester PADEJ Ostojićevo ČOKA SENTA Gornji Breg Bogaraš	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 3rd and 4th track	102+905-102+950 NONE NONE NONE	NONE NONE NONE NONE NONE NONE NONE NONE	45,00	0,17	1,90			
Bočar Ester PADEJ Ostojićevo ČOKA <u>ŠENTA</u> Gornji Breg Bogaraš Doline	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 3rd and 4th track	102+905-102+950 NONE NONE	NONE NONE NONE NONE NONE NONE NONE NONE	45,00	0,17	1,90			
Bočar Ester PADEJ Ostojićevo ČOKA <u>ČOKA</u> <u>SENTA</u> Gornji Breg Bogaraš Doline OROM	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 3rd and 4th track	102+905-102+950 NONE NONE NONE NONE	NONE NONE NONE NONE NONE NONE NONE NONE	45,00	0,17	1,90			
Bočar Ester PADEJ Ostojićevo ČOKA ŠENTA Gornji Breg Bogaraš Doline OROM Gabrić	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track between the 3rd and 4th track between the 1st and 2nd track	102+905-102+950 NONE NONE NONE NONE NONE NONE	NONE NONE NONE NONE NONE NONE NONE platform	45,00	0,17				
Bočar Ester PADEJ Ostojićevo ČOKA ŠENTA Gornji Breg Bogaraš Doline OROM Gabrić	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track between the 2nd and 3rd track between the 3rd and 4th track	102+905-102+950 NONE NONE NONE NONE NONE 176+360-176+414	NONE NONE NONE NONE NONE NONE NONE platform	54,00	0,05	1,70			
Bočar Ester PADEJ Ostojićevo ČOKA SENTA Gornji Breg Bogaraš Doline OROM Gabrić Bikovo	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 3rd and 3rd track between the 3rd and 4th track between the 1st and 2nd track between the 1st and 2nd track	102+905-102+950 NONE NONE NONE NONE 176+360-176+414 176+414-176+487	NONE NONE NONE NONE NONE NONE NONE platform	54,00 73,00	0,05 0,25	1,70 1,60			
Bočar Ester PADEJ Ostojićevo ČOKA ŠENTA Gornji Breg Bogaraš Doline OROM Gabrić	between the 1st and 2nd track between the 2nd and 3rd track between the 1st and 2nd track between the 2nd and 3rd track between the 3rd and 4th track between the 1st and 2nd track between the 1st and 2nd track	102+905-102+950 NONE NONE NONE NONE NONE 176+360-176+414	NONE NONE NONE NONE NONE NONE NONE platform	54,00	0,05	1,70			

206 Pančevo Varoš - Open line junction 2a - (Јабука)										
	next to 1st track	18+131-18+223	station plateau	92,00	0,40	1,60				
PANČEVO VAROŠ	between the 1st and 2nd track	18+105-18+345	platform	240,00	0,40	1,60				
	between the 2nd and 3rd track	18+100-18+364	platform	264,00	0,40	1,60				
	207 Novi S	ad- Odžaci - Bogojevo								
NOVI SAD	next to 11th track	77+836-77+950	platform	114,00	0,40	3,00				
NOVISAD	between the 11th and 10th track	77+822-77+950	platform	128,00	0,40	3,72				



		km position of the		Г	Dimensior	15
Service point	Location	beginning and the end	Platform/arranged	Length	Height	Width
bervice point	Location	of platform	surface	(m)	(m)	(m)
1	2	3	4	5	6	7
1	between the 10th and 1st track	77+835-77+887	platform	52,00	0,40	4,20
	next to 1st track	77+835-78+250	platform	415,00	0,40	4,20-8,90
	between the 2nd and 4th track	77+843-78+181	platform	338,00	0,40	8,75
	between the 12 th and 1 st track	78+104-78+250	platform	146,00	0,40	8,90
	Between 14 th and 13 th track	78+104-78+249	platform	140,00	0,40	6,46
Veternik	Between 14 and 15 track	NONE	plation	145,00	0,40	0,40
FUTOG		NONE				
PETROVAC - GLOŽAN		NONE				
Bački Maglić		NONE				
GAJDOBRA		NONE				
Parage		NONE				
RATKOVO		NONE				
ODŽACI		NONE				
Odžaci - Kalvarija		NONE				
KARAVUKOVO		NONE				
Bogojevo Selo		NONE				
BOGOJEVO		NONE	× • • • • • • •			
	(NOVI SAD) - Open line junction		nčevi- Orlovat Staja	lište		
RIMSKI ŠANČEVI		NONE				
KAĆ		NONE				
Budisava		NONE				
ŠAJKAŠ		NONE				
Vilovo-Gardinovci		NONE				
Lok		NONE				
TITEL		NONE				
Donji Titel		NONE				
Knićanin		NONE				
PERLEZ		NONE				
FARKAŽDIN		NONE				
ORLOVAT		NONE				
ORLOVAT STAJALIŠTE	between the 1st and 2nd track	64+025-64+075	platform	50,00	1,6	0,35
209 Novi Sad Ma	arshalling yard separation switch	No7 - Novi Sad Lokotere	etna - Open line jun	ction SAJI	LOVO	
NOVI						
SADMARSHALLING		NONE				
YARD						
	210 Orlovat - Ope	n line junction 1a - (Luki	ćevo)			
ORLOVAT		NONE				
211	Ruma - Šabac - Open line junct	<mark>ion Donja Borina - state</mark> b	order - (Zvornik N	ovi)		
	between the 2nd and 3rd track	64+733-64+973	platform	240,00	0,35	1,60
RUMA	between the 3rd and 4th track	64+733-64+973	platform	240,00	0,35	1,60
	between the 4th and 5th track	65+821-64+937	platform	116,00	0,35	1,60
BUÐANOVCI	1 (1 1 1 1 1 1 1	11+324,00-11+355,00	platform	31,00	0,35	1,60
2021110101	between the 1st and 2nd track		plation	01,00		
Nikinci	next to railway line - left	16+657,70-16+688,70	platform	31,00	0,35	1,60
				,		1,60 1,60
Nikinci	next to railway line - left	16+657,70-16+688,70	platform	31,00	0,35	
Nikinci PLATIČEVO Klenak	next to railway line - left between the 1st and 2nd track next to railway line - right	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15	platform platform platform	31,00 30,00 31,00	0,35 0,35 0,35	1,60 1,60
Nikinci PLATIČEVO Klenak ŠABAC	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00	platform platform platform platform	31,00 30,00 31,00 54,00	0,35 0,35 0,35 0,40	1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025	platform platform platform platform platform	31,00 30,00 31,00 54,00 50,00	0,35 0,35 0,35 0,40 0,35	1,60 1,60 1,00
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track	$\begin{array}{r} 16+657,70\text{-}16+688,70\\ 21+293,00\text{-}21+323,00\\ 28+873,15\text{-}28+904,15\\ 32+684,00\text{-}32+738,00\\ 3+975\text{-}4+025\\ 7+713,70\text{-}7+735,70\\ \end{array}$	platform platform platform platform	31,00 30,00 31,00 54,00	0,35 0,35 0,35 0,40	1,60 1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE	platform platform platform platform platform platform	31,00 30,00 31,00 54,00 50,00	0,35 0,35 0,35 0,40 0,35	1,60 1,60 1,00
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE	platform platform platform platform platform platform	31,00 30,00 31,00 54,00 50,00	0,35 0,35 0,35 0,40 0,35	1,60 1,60 1,00
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE	platform platform platform platform platform platform	31,00 30,00 31,00 54,00 50,00	0,35 0,35 0,35 0,40 0,35	1,60 1,60 1,00
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE NONE	platform platform platform platform platform platform	31,00 30,00 31,00 54,00 50,00	0,35 0,35 0,35 0,40 0,35	1,60 1,60 1,00
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE NONE NONE	platform platform platform platform platform platform	31,00 30,00 31,00 54,00 50,00 22,00	0,35 0,35 0,35 0,40 0,35 0,35	1,60 1,60 1,00 1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo LEŠNICA	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE 34+900,00-35+025,00	platform platform platform platform platform platform	31,00 30,00 31,00 54,00 22,00 125,00	0,35 0,35 0,35 0,40 0,35 0,35 2,40	1,60 1,60 1,00 1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo LEŠNICA Jadarska Straža	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE 34+900,00-35+025,00 38+860,00-38+940,00	platform platform platform platform platform platform platform	31,00 30,00 31,00 54,00 50,00 22,00	0,35 0,35 0,35 0,40 0,35 0,35	1,60 1,60 1,00 1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo LEŠNICA Jadarska Straža Lipnica	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE 34+900,00-35+025,00 38+860,00-38+940,00 NONE	platform platform platform platform platform platform platform	31,00 30,00 31,00 54,00 22,00 125,00	0,35 0,35 0,35 0,40 0,35 0,35 2,40	1,60 1,60 1,00 1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo LEŠNICA Jadarska Straža Lipnica LOZNICA	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE 34+900,00-35+025,00 38+860,00-38+940,00 NONE NONE	platform platform platform platform platform platform platform	31,00 30,00 31,00 54,00 22,00 125,00	0,35 0,35 0,35 0,40 0,35 0,35 2,40	1,60 1,60 1,00 1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo LEŠNICA Jadarska Straža Lipnica LOZNICA Loznica Fabrika	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track next to railway line - right	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE 34+900,00-35+025,00 38+860,00-38+940,00 NONE NONE NONE	platform platform platform platform platform platform platform	31,00 30,00 31,00 54,00 22,00 125,00 80,00	0,35 0,35 0,35 0,40 0,35 0,35 2,40 0,35	1,60 1,60 1,00 1,60 0,55 1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo LEŠNICA Jadarska Straža Lipnica LOZNICA Loznica Fabrika KOVILJAČA	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE 34+900,00-35+025,00 38+860,00-38+940,00 NONE NONE S6+170,00-56+213,00	platform platform platform platform platform platform platform	31,00 30,00 31,00 54,00 22,00 125,00	0,35 0,35 0,35 0,40 0,35 0,35 2,40	1,60 1,60 1,00 1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo LEŠNICA Jadarska Straža Lipnica LOZNICA Loznica Fabrika KOVILJAČA Gornja Koviljača	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track next to railway line - right between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE 34+900,00-35+025,00 38+860,00-38+940,00 NONE NONE S6+170,00-56+213,00 NONE	platform platform platform platform platform platform platform platform	31,00 30,00 31,00 54,00 22,00 125,00 80,00 43,00	0,35 0,35 0,35 0,40 0,35 0,35 2,40 0,35 0,35	1,60 1,60 1,00 1,60 0,55 1,60
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo LEŠNICA Jadarska Straža Lipnica LOZNICA Loznica Fabrika KOVILJAČA Gornja Koviljača BRASINA	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track next to railway line - right between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE NONE 34+900,00-35+025,00 38+860,00-38+940,00 NONE S65+170,00-56+213,00 NONE 65+212-65+354	platform platform platform platform platform platform platform platform	31,00 30,00 31,00 54,00 22,00 125,00 80,00 43,00 142,00	0,35 0,35 0,35 0,40 0,35 0,35 2,40 0,35 0,35	1,60 1,60 1,00 1,60 0,55 1,60 1,60 3,20
Nikinci PLATIČEVO Klenak ŠABAC Majur ŠTITAR Dublje Mačvansko PETLOVAČA Ribari PRNJAVOR MAČVANSKI Podrinsko Novo Selo LEŠNICA Jadarska Straža Lipnica LOZNICA Loznica Fabrika KOVILJAČA Gornja Koviljača	next to railway line - left between the 1st and 2nd track next to railway line - right between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track next to railway line - right between the 1st and 2nd track	16+657,70-16+688,70 21+293,00-21+323,00 28+873,15-28+904,15 32+684,00-32+738,00 3+975-4+025 7+713,70-7+735,70 NONE NONE NONE NONE 34+900,00-35+025,00 38+860,00-38+940,00 NONE S65+170,00-56+213,00 NONE 56+170,00-56+213,00 NONE 65+212-65+354 68+650-68+750	platform platform platform platform platform platform platform platform platform	31,00 30,00 31,00 54,00 22,00 125,00 80,00 43,00	0,35 0,35 0,35 0,40 0,35 0,35 2,40 0,35 0,35	1,60 1,60 1,00 1,60 0,55 1,60



		km position of the	Platform/arranged	Γ				
Service point	Location	beginning and the end	surface	Length	Height	Width		
1	2	of platform		(m)	(m)	(m)		
1	2	3	4	5	6	7		
	between the 2nd and 3rd track	<u>ć - Kraljevo - Požega</u> 176+222-176+425	platform	203,00	0,28	6,40		
STALAĆ	between the 2th and 5th track	176+222-176+425	platform	203,00	0,28	6,40		
STALAC	between the 6th and 7th track	176+270-176+378	platform	108,00	0,28	5,30		
Mrzenica	right side	3+868-3+910	platform	42,00	0,28	2,00		
Makrešane		NONE	piunoini	,	0,00	2,00		
DEDINA		NONE						
KRUŠEVAC	between the 2nd and 3rd track	14+451-14+626	platform	175,00	0,35	2,84		
	between the 3 rd and 4 th track	14+490,3-14+610,3	platform	120,00	0,35	1,60		
Čitluk		NONE						
KOŠEVI		NONE						
Globoder STOPANJA		NONE NONE						
Donja Počekovina		NONE						
POČEKOVINA		NONE						
Trstenički Odžaci		NONE						
TRSTENIK	between the 2nd and 3rd track	42+400-42+500	platform	102,00	0,35	1,80		
VRNJAČKA BANJA	between the 2nd and 3rd track	49+136-49+241	platform	105,00	0,35	1,60		
Lipova		NONE						
Tominac		NONE						
PODUNAVCI		NONE						
Vraneši Vrba	NONE NONE							
RATINA		NONE						
Sirča	left side	68+880,70-68+940,40	platform	59,70	0.35	1,60		
	between the 1st and 2nd track	84+641,9-84+774,9	platform	133	0,30	1,60		
KRALJEVO	between the 2nd and 3rd track	84+644,4-84+773	platform	128,6	0,30	1,60		
ADRANI	between the 2nd and 3rd track	78+622,20-78+657,20	platform	35,00	0,35	1,60		
Mrsać	left side	81+513-81+553	platform	40,00	0,33	0,50		
SAMAILA		NONE	1					
Goričani	left side	88+610-88+658	platform	48.00	0.37	1,00		
MRŠINCI	between the 2nd and 3rd track	92+241-92+279	platform	38.00	0.35	1,00		
Kukići ZABLAĆE		NONE NONE						
Baluga		NONE						
Dulugu	left from 1 st track	105+500-105+590	platform	90,00	0,44	6,50		
ČAČAK	between the 1st and 2nd track	105+494-105+628	platform	134,00	0,37	1,60		
	between the 2nd and 3rd track	105+494-105+615	platform	121,00	0,38	1,60		
Trbušani	next to railway line - left	110+240-110+263	platform	23,00	0,40	1,60		
PRIJEVOR	between the 2nd and 3rd track	112+820-113+070	platform	250,00	0,40	1,60		
OVČAR BANJA	next to railway line - right	120+450-120+550	platform	100,00	0,40	1,60		
	between the 1st and 2nd track	120+450-120+652	platform	202,00	0,35	1,60		
Jelen Do	next to railway line - right	127+180-127+230	platform	50,00	0,40	1,60		
DRAGAČEVO	between the 2nd and 3rd track	128+295-128+405	platform	110,00	0,40	1,60		
Gugalj	-	NONE						
Boračko	next to 1st track	<u>NONE</u> 140+720-140+975	platform	255,00	0,45	10,00		
POŽEGA	between the 2nd and 3rd track	140+675-140+984	platform	309,00	0,43	6,20		
214 connecting track	of Kraljevo station: (Mataruška E							
	track of Požega station: (Uzićo) - s					,		
	216 Smederevo – Open line				<i>-</i> /			
SMEDEDEVO	between the 1st and 2nd track	0+000-0+103	platform	103,00	0,40	1,60		
SMEDEREVO	between the 2nd and 3rd track	0+000-0+105	platform	105,00	0,40	1,60		
Godomin	next to railway line - left	3+303-3+350	platform	47,00	0,40	1,60		
RADINAC	next to 1st track	6+650-6+800	platform	150,00	0,50	2,20		
	between the 2nd and 3rd track	6+650-6+800	platform	150,00	0,60	6,20		
Vranovo	next to railway line - left	9+475-9+537	platform	62,00	0,40	1,90		
	between the 1st and 2nd track	69+030-69+175	platform	145,00	0,40	1,90		
MALA KRSNA	between the 2nd and 3rd track between the 3rd and 4th track	<u>69+030-69+175</u> <u>69+042-69+184</u>	platform platform	145,00	0,40	1,9		
	Detween the STU and 4th track	07+042-07+104	pianomi	142,00	0,40	1,90		
	between the 4th and 5th track	69+080-69+230	platform	150,00	0,40	1,90		



		km position of the		Γ	Dimensions	
Service point	Location	beginning and the end	Platform/arranged	Length	Height	Width
I		of platform	surface	(m)	(m)	(m)
1	2	3	4	5	6	7
	between the 1st and 2nd track	69+030-69+175	platform	145,00	0,40	1,90
	between the 2nd and 3rd track	69+030-69+175	platform	145,00	0,40	1,90
MALA KRSNA	between the 3rd and 4th track	69+042-69+184	platform	142,00	0,40	1,90
	between the 4th and 5th track	69+080-69+230	platform	142,00	0,40	1,90
Ljubičevski most	between the 4th and 5th track	09+080-09+230 NONE	plation	130,00	0,40	1,90
· · · · · · · · · · · · · · · · · · ·	between the 1st and 2nd track	87+703-87+826	platform	123,00	0,40	1,80
POŽAREVAC	between the 2nd and 3rd track	87+712-87+816	platform	123,00	0,40	1,60
Inconiémie	next to track - left	89+078-89+094	platform	16,00	0,40	1,00
Jugovićevo Sopot Požarevački			1	,		
BUBUŠINAC-BRATINAC	next to track -right	90+082-90+107	platform	24,00	0,40	1,60
		NONE				
Bare - Kasidol STIG	h stress on the last and 2m d two als	NONE		71.00	0.40	1.0
	between the 1st and 2nd track	102+693-102+764	platform	71,00	0,40	1,60
Majilovac		NONE	1.0	52 .00	0.40	1 (0
SIRAKOVO	between the 1st and 2nd track	109+026-109+079	platform	53,00	0,40	1,60
LJUBINJE	between the 1st and 2nd track	116+381-116+444	platform	63,00	0,40	1,60
Češljeva Bara	next to railway line - left	122+138-122+200	platform	62,00	0,40	1,60
RABROVO-KLENJE	between the 1st and 2nd track	126+007-126+067	platform	60,00	0,40	1,60
Mustapić		NONE				
Mišljenovac		NONE				
ZVIŽD		NONE				
Kučevska Turija		NONE				
KAONA		NONE				
KUČEVO		NONE				
Neresnica		NONE				
Neresnica (tov.)		NONE				
Voluja		NONE				
BRODICA	between the 2nd and 3rd track	164+515-164+576	platform	61,00	0,40	1,60
Bosiljkovac		NONE				
Blagojev Kamen		NONE				
MAJDANPEK	between the 2nd and 3rd track	178+769-178+920	platform	151,00	0,35	1,60
Debeli Lug	next to railway line - left	181+300-181+318	platform platform arranged surface arranged surface	18,00	0,35	1,60
LESKOVO	next to railway line - left between the 2nd and 3rd track	187+660-187+722		62,00 80,00	0,35	1,60
Jasikovo	next to railway line - left				0,09	1,60
Vlaole Selo	next to railway line - right	194+740-194+780			0,20	1,60
		197+163-197+224	platform	61,00	0,35	1,60
	between the 2nd and 3rd track	17/+103-17/+44			0.55	
VLAOLE	between the 2nd and 3rd track next to railway line - right		arranged surface			1.60
VLAOLE Gornjane	between the 2nd and 3rd track next to railway line - right	200+288-200+386	arranged surface	98,00	0,35	,
VLAOLE Gornjane CEROVO	next to railway line - right	200+288-200+386 NONE		98,00	0,35	1,60
VLAOLE Gornjane CEROVO Kriveljski most	next to railway line - right next to railway line - right	200+288-200+386 NONE 207+905-207+995	arranged surface	98,00 90,00	0,35 0,35	1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok	next to railway line - right next to railway line - right next to railway line - left	200+288-200+386 NONE 207+905-207+995 211+873-211+913	arranged surface arranged surface	98,00 90,00 40,00	0,35 0,35 0,35	1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206	arranged surface arranged surface platform	98,00 90,00 40,00 35,00	0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540	arranged surface arranged surface platform platform	98,00 90,00 40,00 35,00 50,00	0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452	arranged surface arranged surface platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00	0,35 0,35 0,35 0,35 0,35 0,35	$ 1,60 \\ 1,60 \\ 1,60 \\ 1,60 \\ 1,60 \\ 8,00 $
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452	arranged surface arranged surface platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 8,00 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375	arranged surface arranged surface platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00	0,35 0,35 0,35 0,35 0,35 0,35	$ 1,60 \\ 1,60 \\ 1,60 \\ 1,60 \\ 1,60 \\ 8,00 $
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE	arranged surface arranged surface platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 8,00 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE NONE	arranged surface arranged surface platform platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738	arranged surface arranged surface platform platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 8,00 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track between the 1st and 2nd track 219 (NIŠ) - Crveni Kr	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE NONE 244+658-244+738 rst - Zaječar – Prahovo Pi	arranged surface arranged surface platform platform platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track between the 1st and 2nd track 219 (NIŠ) - Crveni Kr between the 2nd and 3rd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar – Prahovo Pt 240+842-240+994	arranged surface arranged surface platform platform platform platform platform istanište platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 1st and 2nd track 219 (NIŠ) - Crveni Kr between the 2nd and 3rd track next to railway line - left	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar – Prahovo Pu 240+842-240+994 7+455-7+507	arranged surface arranged surface platform platform platform platform platform istanište platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 52,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track between the 1st and 2nd track 219 (NIŠ) - Crveni Kr between the 2nd and 3rd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar - Prahovo Pu 240+842-240+994 7+455-7+507 12+370-12+395	arranged surface arranged surface platform platform platform platform platform istanište platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 1st and 2nd track 219 (NIŠ) - Crveni Kr between the 2nd and 3rd track next to railway line - left	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar – Prahovo Pi 240+842-240+994 7+455-7+507 12+370-12+395 NONE	arranged surface arranged surface platform platform platform platform platform istanište platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 52,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track 219 (NIŠ) - Crveni Kr between the 2nd and 3rd track next to railway line - left between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar - Prahovo Pu 240+842-240+994 7+455-7+507 12+370-12+395 NONE NONE	arranged surface arranged surface platform platform platform platform platform istanište platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 52,00 25,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,50
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik GRAMADA	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 1st and 2nd track 219 (NIŠ) - Crveni Kr between the 2nd and 3rd track next to railway line - left	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar - Prahovo Pi 240+842-240+994 7+455-7+507 12+370-12+395 NONE NONE 30+232-30+282	arranged surface arranged surface platform platform platform platform platform istanište platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 52,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik GRAMADA Hadžićevo	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track 219 (NIŠ) - Crveni Kr between the 1st and 2nd track next to railway line - left between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 St - Zaječar – Prahovo Pr 240+842-240+994 7+455-7+507 12+370-12+395 NONE NONE 30+232-30+282 NONE	arranged surface arranged surface platform platform platform platform platform istanište platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 52,00 25,00 50,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik GRAMADA Hadžićevo SVRLJIG	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track 219 (NIŠ) - Crveni Kr between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 St - Zaječar – Prahovo Pr 240+842-240+994 7+455-7+507 12+370-12+395 NONE 30+232-30+282 NONE 39+925-40+075	arranged surface arranged surface platform platform platform platform platform platform istanište platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 25,00 25,00 50,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik GRAMADA Hadžićevo SVRLJIG Niševac	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track 219 (NIŠ) - Crveni Kr between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar - Prahovo Pr 240+842-240+994 7+455-7+507 12+370-12+395 NONE 30+232-30+282 NONE 39+925-40+075 46+002-46+018	arranged surface arranged surface platform platform platform platform platform istanište platform platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 25,00 25,00 50,00 150,00 150,00	0,35 0	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik GRAMADA Hadžićevo SVRLJIG Niševac PALILULA	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track 219 (NIŠ) - Crveni Kr between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 St - Zaječar – Prahovo Pr 240+842-240+994 7+455-7+507 12+370-12+395 NONE 30+232-30+282 NONE 39+925-40+075	arranged surface arranged surface platform platform platform platform platform platform istanište platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 25,00 25,00 50,00	0,35 0,35 0,35 0,35 0,35 0,35 0,35 0,35	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik GRAMADA Hadžićevo SVRLJIG Niševac	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track 219 (NIŠ) - Crveni Kr between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar - Prahovo Pr 240+842-240+994 7+455-7+507 12+370-12+395 NONE 30+232-30+282 NONE 39+925-40+075 46+002-46+018	arranged surface arranged surface platform platform platform platform platform istanište platform platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 25,00 25,00 50,00 150,00 150,00	0,35 0	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik GRAMADA Hadžićevo SVRLJIG Niševac PALILULA	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track 219 (NIŠ) - Crveni Kr between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar – Prahovo Pr 240+842-240+994 7+455-7+507 12+370-12+395 NONE 30+232-30+282 NONE 39+925-40+075 46+002-46+018 49+320-49+355	arranged surface arranged surface platform platform platform platform platform istanište platform platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 25,00 25,00 50,00 150,00 150,00	0,35 0	1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,60 1,50
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik GRAMADA Hadžićevo SVRLJIG Niševac PALILULA Svrljiški Miljkovac	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track between the 1st and 2nd track 219 (NIŠ) - Crveni Kr between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar - Prahovo Pr 240+842-240+994 7+455-7+507 12+370-12+395 NONE 30+232-30+282 NONE 39+925-40+075 46+002-46+018 49+320-49+355 NONE	arranged surface arranged surface platform platform platform platform platform platform platform platform platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 25,00 25,00 50,00 150,00 150,00 16,00 35,00	0,35 0	1,60 1,60
VLAOLE Gornjane CEROVO Kriveljski most Kriveljski potok MALI KRIVELJ Brezonik BOR BOR FREIGHT STATION BORSKA SLATINA ZAGRAĐE RGOTINA CRVENI KRST Pantelej MATEJEVAC Gornja Vrežina Jasenovik GRAMADA Hadžićevo SVRLJIG Niševac PALILULA Svrljiški Miljkovac	next to railway line - right next to railway line - right next to railway line - left between the 1st and 2nd track next to railway line - left next to 1st track between the 2nd and 3rd track between the 2nd and 3rd track between the 1st and 2nd track 219 (NIŠ) - Crveni Kr between the 1st and 2nd track next to railway line - left between the 1st and 2nd track between the 1st and 2nd track between the 1st and 2nd track	200+288-200+386 NONE 207+905-207+995 211+873-211+913 215+171-215+206 217+490-217+540 221+369-221+452 221+352-221+452 224+320-224+375 NONE 244+658-244+738 rst - Zaječar - Prahovo Pr 240+842-240+994 7+455-7+507 12+370-12+395 NONE 30+232-30+282 NONE 30+232-30+282 NONE 39+925-40+075 46+002-46+018 49+320-49+355 NONE 60+853-60+903	arranged surface arranged surface platform platform platform platform platform platform platform platform platform platform platform platform	98,00 90,00 40,00 35,00 50,00 83,00 100,00 55,00 80,00 152,00 25,00 25,00 50,00 150,00 150,00 16,00 35,00	0,35 0	1,60 1,60



	<u> </u>	1		г	Dimensions	-		
Service point	Location	km position of the beginning and the end	Platform/arranged	Length	Height	s Width		
Service point	Location	of platform	surface	(m)	(m)	(m)		
1	2	3	4	5	6	7		
Donje Zuniče	next to railway line - right	74+988-75+076	platform	88,00	0.35	1,60		
MINIĆEVO	between the 1st and 2nd track	81+830-81+930	platform	100,00	0,35	1,60		
MINICE VO	between the 2nd and 3rd track	81+930-81+930	platform	45,00	0,35	1,60		
Salažira Daira					0,35	,		
Selačka Reka	next to railway line - right	84+450-84+500	arranged surface	50,00		1,60		
Mali Izvor	next to railway line - right	88+180-88+230	platform	50,00	0,35	1,60		
Vratarnica	between the 1st and 2nd track	96+048-96+098	platform	50,00	0,35	1,60		
GRLJAN	between the 1st and 2nd track	102+955-103+105	platform	150,00	0,35	1,60		
Timok	next to railway line - left	107+320-107+380	arranged surface	60,00	0,35	1,60		
×	between the 1st and 2nd track	111+622-111+820	platform	198,00	0,35	1,60		
ZAJEČAR	between the 2nd and 3rd track	111+662-111+815	platform	153,00	0,35	1,60		
~	between the 3rd and 4th track	111+651-111+803	platform	152,00	0,35	1,60		
VRAŽOGRNAC	between the 1st and 2nd track	118+760-118+910	platform	150,00	0,35	1,60		
TRNAVAC	between the 1st and 2nd track	124+593-124+668	platform	75,00	0,35	1,60		
Čokonjar	next to railway line - left	128+500-128+550	platform	50,00	0,35	1,60		
Sokolovica	next to railway line - right	131+100-131+125	platform	25,00	0,35	1,60		
TABAKOVAC	between the 1st and 2nd track	136+170-136+223	platform	53,00	0,35	1,60		
Tabakovačka reka	next to railway line - right	138+740-138+790	platform	50,00	0,35	1,60		
BRUSNIK	between the 1st and 2nd track	145+616-145+696	platform	80,00	0,35	1,60		
Tamnič	next to railway line - right	148+420-148+480	platform	60,00	0,35	1,60		
Crnomasnica	next to railway line - right	151+323-151+364	platform	41,00	0,35	1,60		
Rajac	next to railway line - right	154+430-154+505	platform	75,00	0,35	1,60		
ROGLJEVO	between the 1st and 2nd track	156+795-156+875	platform	80,00	0,35	1.60		
Veljkovo	between the 1st and 2nd track	between the 1st and 2nd track 156+795-156+875 platform NONE						
Mokranja		NONE						
Kobišnica		NONE						
NEGOTIN	between the 2nd and 3rd track	174+049-174+199	platform	150,00	0,35	1,60		
PRAHOVO	between the 2nd and 3rd track	181+974-182+054	platform	80,00	0,35	1,60		
PRAHOVO PRAHOVO PRISTANIŠTE	between the 2nd and 51d track	NONE	plation	80,00	0,55	1,00		
PRAHOVOPRISTANISTE	220 (Rgotina) - Open line junct		an 1% (Transverse)					
		in line junction "1" - Kurš						
KURŠUMLIJA	221 (Barlovo) - Opc	NONE	uninja					
KUKSUWLIJA		uršumlija - Kastrat						
KURŠUMLIJA		NONE						
Keksewilin	223 Dolievac - Ka	strat – Merdare - Kosovo	Polie					
	between the 1st and 2nd track	261+419-261+527	platform	108	0,40	1,60		
DOLJEVAC	between the 2nd and 3rd track	261+419-261+526	platform	100	0,40	1,60		
Šajinovac	between the 2nd and 51d track	201+419-201+320 NONE	plationin	107	0,40	1,00		
Toplički Badnjevac		NONE						
Jasenica		NONE						
ŽITORAĐA	1 1 1 1 0	NONE	1.0	52.00	0.40	1.60		
Žitorađa Centar	next to railway line - left	10+925-10+977	platform	52,00	0,40	1,60		
Rečica		NONE						
Lukomir		NONE						
Podina		NONE	1		,			
Babin Potok	next to railway line - right	18+726-18+774	platform	48,00	0,40	1,60		
DD OTTENT	· · · · · · · · · · · · · · · · · · ·			113,00	0,40	1,60		
PROKUPLJE	between the 1st and 2nd track	22+257-22+370	platform		,			
Gornja Draganja	· · · · · · · · · · · · · · · · · · ·	24+990-25+027	platform platform	37,00	0,40	1,60		
Gornja Draganja Toplička Mala Plana	between the 1st and 2nd track	24+990-25+027 NONE	1		,	1,60		
Gornja Draganja	between the 1st and 2nd track	24+990-25+027	1		,	1,60		
Gornja Draganja Toplička Mala Plana	between the 1st and 2nd track	24+990-25+027 NONE	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići	between the 1st and 2nd track	24+990-25+027 NONE NONE	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik Barlovo Novoselske Livade	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE NONE NONE	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik Barlovo Novoselske Livade Pepeljevac	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE NONE NONE NONE	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik Barlovo Novoselske Livade Pepeljevac Rasputnica Kastrat	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE NONE NONE NONE NON	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik Barlovo Novoselske Livade Pepeljevac Rasputnica Kastrat Visoka	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE NONE NONE NONE NON	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik Barlovo Novoselske Livade Pepeljevac Rasputnica Kastrat Visoka Ljuša	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE NONE NONE NONE NON	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik Barlovo Novoselske Livade Pepeljevac Rasputnica Kastrat Visoka Ljuša Rudare	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE NONE NONE NONE NON	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik Barlovo Novoselske Livade Pepeljevac Rasputnica Kastrat Visoka Ljuša Rudare Dešiška	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE NONE NONE NONE NON	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik Barlovo Novoselske Livade Pepeljevac Rasputnica Kastrat Visoka Ljuša Rudare Dešiška KOSANIČKA RAČA	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE NONE NONE NONE NON	1		,	1,60		
Gornja Draganja Toplička Mala Plana Bresničići BELOLJIN Toplica Milan Pločnik Barlovo Novoselske Livade Pepeljevac Rasputnica Kastrat Visoka Ljuša Rudare Dešiška	between the 1st and 2nd track	24+990-25+027 NONE NONE NONE NONE NONE NONE NONE NON	1		,			



		km position of the		1	Dimension	s
Service point	Location	beginning and the end	Platform/arranged	Length	Height	Width
Service point	2000000	of platform	surface	(m)	(m)	(m)
1	2	3	4	5	6	7
Vasiljevac		NONE	-		Ű.	,
Merdare		NONE				
	224 Kosovo	Polje - Metohija – Peć**				
		t - Open line junction 1 - (Drenica) **			
	between the 2nd and 3rd track	Vrbas - Sombor		(0.00	0.25	1.40
VRBAS		116+702-116+770,3	platform	68,00	0,35	1,40
	between the 3rd and 4th track between the 2nd and 3rd track	<u>116+702-116+770,3</u> 47+626-47+667	platform platform	68,00 41,00	0,35	1,40
KULA CRVENKA	between the 1st and 2nd track	54+956-54+986	platform	30,00	0,25	1,52 1,56
SIVAC	between the 1st and 2nd track	NONE	plationi	50,00	0,15	1,50
Novi Sivac		NONE				
KLJAJIĆEVO	between the 1st and 2nd track	75+417-75+456	platform	39,00	0,15	1,38
Čonoplja	between the 1st and 2nd track	79+692-79+722	platform	30,00	0,15	1,30
Conopija	between the 1st and 2nd track	73+417-73+477	platform	60,00	0,13	1,51
	between the 1st and 2nd track	73+584-73+612	arranged surface	28,00	0,05	1,01
	between the 1st and 2nd track	73+673-73+823	arranged surface	150,00	0,05	1,50
SOMBOR	between the 1st and 2nd track	73+417-73+477	platform	60,00	0,03	1,50
	between the 2nd and 3rd track	73+584-73+612	arranged surface	28,00	0,05	1,01
	between the 3rd and 4th track	73+584-73+701	arranged surface	117,00	0,05	1,50
	between the 51d and 4th thek	131304 131101	arranged surrace	117,00	0,05	1,50
	LOCAI	RAILWAY LINES				
	301 Subotica - Subotica Fabrika		OUT OF SERVICE			
		ica - Subotica Bolnica	1		1	1
	between the 1st and 2nd track	176+360-176+414	arranged surface	54,00	0,05	1,70
	between the 1st and 2nd track	176+414-176+487	platform	73,00	0,25	1,60
SUBOTICA	between the 1st and 2nd track	176+487-176+838	arranged surface	351,00	0,05	1,70
	between the 2nd and 3rd track	176+322-176+838	arranged surface	516,00	0,05	1,70
	between the 3rd and 4th track	176+335-176+573	arranged surface	238,00	0,05	1,70
		1+042) - Novi Sad Ložion		114.00	0.40	2.00
	next to 11th track	77+836-77+950	platform	114,00	0,40	3,00
	between the 11th and 10th track	77+822-77+950	platform	128,00	0,40	3,72
	between the 10th and 1st track	77+835-77+887	platform	52,00	0,40	4,20
NOVI SAD	next to 1st track	77+835-78+250	platform	415,00	0,40	4,20-8,9
	between the 2nd and 4th track	77+843-78+181	platform	338,00	0,40	8,75
	између 12. и 1. колосека	78+104-78+250	platform	146,00	0,40	8,90
	између 14. и 13. колосека	78+104-78+249	platform	145,00	0,40	6,46
	304 Podbara - Open line jun		tion "2" - (Kać)	· · · ·		
3	05 (Rimski Šančevi) - Open line ju	inction "1" - Open line ju		ra)		
v	306 Rii	mski Šančevi- Bečej				
RIMSKI ŠANČEVI		NONE				
Bački Jarak		NONE				
TEMERIN		NONE				
GOSPOĐINCI		NONE				
ŽABALJ		NONE				
ČURUG		NONE				
Radiza (Iradiáta		NONE				
Bačko Gradište						
Bečej predgrađe		NONE				
	209 (Procine) Open line	NONE	warmile Croad			
Bečej predgrađe BEČEJ	308 (Brasina) - Open line j	NONE junction Donja Borina – Z	Zvornik Grad			
Bečej predgrađe		NONE junction Donja Borina – Z NONE				
Bečej predgrađe BEČEJ	309 Pančevo	NONE junction Donja Borina – Z NONE Varoš - Pančevo Vojlovica	l	92,00	0,40	1,60
Bečej predgrađe BEČEJ		NONE junction Donja Borina – Z NONE Varoš - Pančevo Vojlovica 18+131-18+223	station plateau	92,00 240,00	0,40	,
Bečej predgrađe BEČEJ ZVORNIK GRAD	309 Pančevo next to 1st track	NONE junction Donja Borina – Z NONE Varoš - Pančevo Vojlovica	l	92,00 240,00 264,00	0,40 0,40 0,40	1,60 1,60 1,60
Bečej predgrađe BEČEJ ZVORNIK GRAD	309 Pančevo next to 1st track between the 1st and 2nd track	NONE junction Donja Borina – 7 NONE Varoš - Pančevo Vojlovica 18+131-18+223 18+105-18+345	station plateau platform	240,00	0,40	1,60
Bečej predgrađe BEČEJ ZVORNIK GRAD PANČEVO VAROŠ Pančevo Strelište	309 Pančevo next to 1st track between the 1st and 2nd track between the 2nd and 3rd track	NONE junction Donja Borina – 2 NONE Varoš - Pančevo Vojlovica 18+131-18+223 18+105-18+345 18+100-18+364	station plateau platform platform	240,00 264,00	0,40 0,40	1,60 1,60
Bečej predgrađe BEČEJ ZVORNIK GRAD PANČEVO VAROŠ Pančevo Strelište PANČEVO VOJLOVICA	309 Pančevo next to 1st track between the 1st and 2nd track between the 2nd and 3rd track next to railway line - left between the 3rd and 4th track next to 4th track	NONE junction Donja Borina – Z NONE Varoš - Pančevo Vojlovica 18+131-18+223 18+105-18+345 18+100-18+364 1+290-1+400 2+632-2+852 2+645-2+965	station plateau platform platform platform platform platform	240,00 264,00 110,00 220,00 220,00	$\begin{array}{c} 0,40\\ 0,40\\ 0,40\\ 0,40\\ 0,40\\ 0,40\\ \end{array}$	1,60 1,60 1,60
Bečej predgrađe BEČEJ ZVORNIK GRAD PANČEVO VAROŠ Pančevo Strelište PANČEVO VOJLOVICA	309 Pančevo next to 1st track between the 1st and 2nd track between the 2nd and 3rd track next to railway line - left between the 3rd and 4th track next to 4th track ing track of Senta station: (Čoka)	NONE junction Donja Borina – Z NONE Varoš - Pančevo Vojlovica 18+131-18+223 18+105-18+345 18+100-18+364 1+290-1+400 2+632-2+852 2+645-2+965 - separation switch No22	station plateau platform platform platform platform platform separation switch	240,00 264,00 110,00 220,00 220,00	$\begin{array}{c} 0,40\\ 0,40\\ 0,40\\ 0,40\\ 0,40\\ 0,40\\ \end{array}$	1,60 1,60 1,60 1,60
Bečej predgrađe BEČEJ ZVORNIK GRAD PANČEVO VAROŠ Pančevo Strelište PANČEVO VOJLOVICA	309 Pančevo next to 1st track between the 1st and 2nd track between the 2nd and 3rd track next to railway line - left between the 3rd and 4th track next to 4th track ing track of Senta station: (Čoka) 311 Markovac – Svi	NONE junction Donja Borina – Z NONE Varoš - Pančevo Vojlovica 18+131-18+223 18+105-18+345 18+100-18+364 1+290-1+400 2+632-2+852 2+645-2+965 - separation switch No22 - ilajnac – Despotovac – (Reference)	station plateau platform platform platform platform platform separation switch esavica)	240,00 264,00 110,00 220,00 220,00 No23 - (Or	0,40 0,40 0,40 0,40 0,40 rom)	$ \begin{array}{r} 1,60\\ 1,60\\ 1,60\\ 1,60\\ 1,60\\ 1,60\\ \end{array} $
Bečej predgrađe BEČEJ ZVORNIK GRAD PANČEVO VAROŠ Pančevo Strelište PANČEVO VOJLOVICA	309 Pančevo next to 1st track between the 1st and 2nd track between the 2nd and 3rd track next to railway line - left between the 3rd and 4th track next to 4th track ing track of Senta station: (Čoka)	NONE junction Donja Borina – Z NONE Varoš - Pančevo Vojlovica 18+131-18+223 18+105-18+345 18+100-18+364 1+290-1+400 2+632-2+852 2+645-2+965 - separation switch No22	station plateau platform platform platform platform platform separation switch	240,00 264,00 110,00 220,00 220,00	$\begin{array}{c} 0,40\\ 0,40\\ 0,40\\ 0,40\\ 0,40\\ 0,40\\ \end{array}$	1,60 1,60 1,60 1,60



		km position of the		Ι	Dimension	S				
Service point	Location	beginning and the end	Platform/arranged	Length	Height	Width				
-		of platform	surface	(m)	(m)	(m)				
1	2	3	4	5	6	7				
	between the 4th and 5th track	100+350-100+448	platform	92	0.4	1.6				
	312 M	etohija - Prizren**								
	313 V	′ršac – Bela Crkva								
VRŠAC	between the 1st and 2nd track	82+807,5-82+902,5	platform	95,00	0,40	1,60				
VKSAC	between the 2nd and 3rd track 82+807,5-82+902,5 platform 95,00 0,40									
Potporanj		NONE								
Straža		NONE								
JASENOVO	NONE									
Crvena Crkva	Crvena Crkva NONE									
	between the 1st and 2nd					1.00				
BELA CRKVA	track	119+052-119+082	platform	30,00	0,30	1,60				
	SHU	UNTING LINES								
	401 Vrš	ac - Vršac Vašarište								
VRŠAC	between the 1st and 2nd track	82+807,5-82+902,5	platform	95,00	0,40	1,60				
VRSAC	between the 2nd and 3rd track	82+807,5-87+902,5	platform	95,00	0,40	1,60				
	402 Kikinda – Metano	olsko sirćetni kompleks (k								
KIKINDA	next to 1st track	160+030-160+166	platform	136,00	0,19	3,30-4,40				
KIKINDA	between the 1st and 2nd track	160+064-160+190	arranged surface	126,00	0,00	1,50				
		ka Obala – TRAFFIC SU								
		opovac - TRAFFIC SUSP	PENDED							
~	405 Sur	čin – Jakovo-Bečmen								
SURČIN		NONE								
		ča Nova - state border - (H		100.00	0.40					
ŠID	between the 1st and 2nd track	116+300-116+490	arranged surface	190,00	0,10	2,50				
SID	between the 2nd and 3rd track	116+300-116+665	platform.	365,00	0,45	1,60				
	between the 3rd and 4th track	116+300-116+677	platform	377,00	0,45	1,60				
Adaševci		NONE	1.40	20.00	0.25	1.60				
MOROVIĆ	between the 1st and 2nd track	12+360-12+390	platform	30,00	0,35	1,60				
VIŠNJIĆEVO Bogratnica Boža	between the 1st and 2nd track	19+633-19+655	platform	22,00	0,35	1,60				
Rasputnica Rača SREMSKA RAČA NOVA	between the 1st and 2nd track	NONE 24+169-24+205	nlatform	26.00	0.25	1.60				
<u> σκεμισκά κάζα nuva</u>		Skela - TRAFFIC SUSP	platform	36,00	0,35	1,60				
		ita – Apatin Fabrika								
		ajdobra - TRAFFIC SUS	PENDED							
	TU) Datka i alalika – C	ajuonia - 11/41110 505								

* not intended for handling of passengers ** The lines on the territory of Kosovo and Metohija are temporarily under the supervision of UNMIK, according to the Temporary Agreement between ŽTP Belgrade and UNMIK railways, dated May 31, 2002 (records No 300/2002 - 153 dated May 31, 2002).

Note: In column one halts are marked with small letters and all other service points with capital letters.



Appendix 9. Method for calculation of electricity consumption for train traction

Compensation for calculation of electricity consumption for train traction is determined as follows:

$$Csv/brtkm = \frac{MES.RAČ - TROŠ.INF}{BRTKMter + K * BRTKMput}$$

where:

Csv/brtkm – monthly rate of electric energy spent for train traction, expressed in RSD per gross-tonne km.

MES.RAČ – monthly bill amount for high voltage electric energy issued by electric energy supplier. **TROŠ.INF** – monthly expenses for electric energy for train traction need used by "Infrastruktura

železnice Srbije"

BRTKMter – total (all railway undertakings) monthly freight transport expressed in gross-tonne km.

 \mathbf{K} – coefficient by means of which is taken into consideration that passenger trains consume more electric energy per gross-tonne km than freight trains.

BRTKMput – total (all railway undertakings) monthly passenger transport expressed in gross-tonne km.

The compensation amount per individual RU is calculated by multiplication of monthly rate of electrical energy for train traction with gross-tonne kilometers realized by the respective RU (BRTKMter for freight service, and K* BRTKMput for passenger service):

Ntern = Csv/btkm * BRTKMtern for freight service, i.e Nputn = Csv/btkm * K * BRTKMputn for passenger service,

where:

Ntern – compensation paid by x RU in freight service for the consumption of electrical traction, expressed in RSD.

BRTKMtern – gross-tonne kilometres realized by x RU in freight service in the given month.

Nputn - compensation paid by x RU in passenger service for the consumption of electrical traction, expressed in RSD.

BRTKMputn - gross-tonne kilometres realized by x RU in passenger service in the given month.

The compensation is paid to Infrastructure Manager on a monthly basis, based on the issued bill.

K coefficient values are as follows:

month	Ι	II	III	IV	V	VI	VII	VIII	IX	X	XI	XII
К	2	1,8	1,7	1,5	1,35	1,4	1,4	1,4	1,35	1,5	1,7	1,9



Appendix 10. Railway node boundaries

Node	Border station (service point) of the node	Chainage of the station (service point)	Entry signal from the direction	Railway line	Chainage of mandatory signal	Distance [m]
	Batajnica	19+031 ^P / 20+616 ^T	Nova Pazova	101 Belgrade Center - Stara Pazova - Šid - state border - (Tovarnik)	19+960 ^P / 21+396 ^F	$929 \ ^{P}/780 \ ^{F}$
D	Ovča	12+555 / 12+653	Pančevo Main St.	107 Belgrade Denter - Pančevo Main St Vršac - state border - (Stamora Moravita)	13+550 / 13+647	995
BEOGRAD	Jajinci	10+988	Beli Potok (Mala Krsna)	103 (Belgrade Center) - Rakovica - Jajinci - Mala Krsna - Velika Plana	12+045	1057
BEC	Resnik	14+059	Pinosava (Mladenovac)	102 Belgrade Center - Open line junction "G" - Rakovica - Mladenovac - Lapovo - Niš - Preševo - state border - (Tabanovce)	14+848	789
	Resnik	0+000	Bela Reka (Valjevo)	108 (Belgrade Center) - Resnik - Požega - Vrbnica - state border - (Bijelo Polje)	0+825	825
	Naumovićevo	166+519	Žednik (Vrbas)	105 (Belgrade Center) - Stara Pazova - Novi Sad - Subotica - state border - (Kelebia)	165+640	879
SUBOTICA	Palić	7+658	Bački Vinogradi (Horgoš)	201 Subotica - Horgoš - state border - (Roszke)	8+614	956
UBOJ	Subotica	76+739	Orom (Senta)	205 Banatsko Miloševo - Senta - Subotica	74+990	1751
IS	Subotica Freight St.	75+972	Orom (Senta)	205 Banatsko Miloševo - Senta - Subotica	74+990	982
	Šebešić	123+761	Tavankut (Sombor)	110 Subotica - Bogojevo - state border - (Erdut)	122+915	846
	Novi Sad	77+101	Rumenka (Vrbas)	105 (Belgrade Center) - Stara Pazova - Novi Sad - Subotica - state border - (Kelebia)	78+552	1542
	Sajlovo rasp. i odj.	0+000	Futog (Bogojevo)	207 Novi Sad - Odžaci - Bogojevo	0+280	280
NOVI SAD	Sajlovo rasp. i odj.	0+000	Rimski Šančevi (Orlovat)	208 (Novi Sad) - Open line junction Sajlovo - Rimski Šančevi - Orlovat Stajalište	4+093	1370
NO	Sajlovo rasp. i odj.	0+000	Rumenka (Vrbas)	Sajlovo - Rumenka	1+295 / 1+248	1287
	Petrovaradin	70+870	Sremski Karlovci (Inđija)	105 (Belgrade Center) – Stara Pazova – Novi Sad – Subotica – state border – (Kelebia)	69+870	1000
00	Lapovo Varoš	106+302	Markovac (Velika Plana)	102 Belgrade Center - Open line junction "G" - Rakovica - Mladenovac - Lapovo - Niš - Preševo - state border - (Tabanovce)	105+710	592
LAPOV	Lapovo	109+597	Bagrdan (Stalać)	102 Belgrade Center - Open line junction "G" - Rakovica - Mladenovac - Lapovo - Niš - Preševo - state border - (Tabanovce)	110+540	943
	Batočina	3+405	Badnjevac (Kragujevac)	109 Lapovo - Kraljevo - Lešak - Kosovo Polje - Đeneral Janković - state border - (Volkovo)	4+419	1014
	Trupale	234+939	Grejač (Stalać)	102 Belgrade Center - Open line junction "G" - Rakovica - Mladenovac - Lapovo - Niš - Preševo - state border - (Tabanovce)	233+934	1005
Š	Crveni Krst	0+000	Matejevac (Zaječar)	219 (Niš) - Crveni krst - Zaječar - Prahovo Pristanište	(0+957=3+455) 3+736	1238
NIŠ	Međurovo	249+462	Doljevac	102 Belgrade Center - Open line junction "G" - Rakovica - Mladenovac - Lapovo - Niš - Preševo - state border - (Tabanovce)	250+323	861
	Ćele Kula	5+461	Niška Banja (Pirot)	106 Niš - Dimitrovgrad - state border - (Dragoman)	6+320	859
0/	Pančevo Main St.	16+069	Ovča (Beograd)	107 Belgrade Center - Pančevo Main St Vršac - state border - (Stamora Moravita)	14+878	1191
PANČEVO	Pančevo varoš	18+206	Banatsko Novo Selo (Vršac)	107 Belgrade Center - Pančevo Main St Vršac - state border - (Stamora Moravita)	19+242	1036
PA	Open line junction 2a	17+659	Jabuka (Zrenjanin)	202 Pančevo Main St Zrenjanin - Kikinda - state border - (Jimbolia)	18+160	501

P – passenger traffic (from the direction of Novi Sad) F- freight traffic (mixed, from the direction of Šid)

